

| <b>Link Parameters</b>                         | <b>Units</b> | <b>48K6G7W</b> |
|--|--------------|----------------|
| Uplink frequency                               | GHz          | 12.88          |
| Downlink frequency                             | GHz          | 10.83          |
| User data rate                                 | kbit/s       | 56             |
| Modulation                                     |              | QPSK           |
| Total coding rate                              |              | 0.691          |
| Carrier bandwidth                              | kHz          | 48.6           |
| <b>Uplink:</b>                                 |              |                |
| Nominal E/S e.i.r.p. per carrier               | dBW          | 48.6           |
| Earth station diameter                         | m            | 2.4            |
| Earth station gain                             | dBi          | 48.4           |
| Uplink input power per carrier                 | dBW          | 0.2            |
| Uplink input power density                     | dBW/Hz       | -46.6          |
| Atmospheric loss                               | dB           | 0.2            |
| Free space path loss                           | dB           | 206.4          |
| G/T satellite (-6 dB contour)                  | dB/K         | -1.0           |
| C/N thermal uplink                             | dB           | 22.8           |
| C/I XPOL, ACI, ASI                             | dB           | 24.8           |
| C/(N+I) uplink                                 | dB           | 20.7           |
| <b>Downlink:</b>                               |              |                |
| Satellite e.i.r.p. per carrier (-4 dB contour) | dBW          | 22.3           |
| Atmospheric loss                               | dB           | 0.1            |
| Free space path loss                           | dB           | 204.8          |
| Earth station diameter                         | m            | 1.2            |
| Earth station gain                             | dBi          | 40.8           |
| Noise temperature                              | K            | 120.0          |
| Earth station G/T                              | dB/K         | 20.0           |
| C/N thermal downlink                           | dB           | 19.2           |
| C/I XPOL, ACI, IM, ASI                         | dB           | 12.2           |
| C/(N+I) downlink                               | dB           | 11.4           |
| <b>Overall:</b>                                |              |                |
| C/(N+I) overall                                | dB           | 10.9           |
| C/(N+I) required                               | dB           | 5.7            |
| Margin   | dB           | 5.2            |