



312 File Number: **SATLOA2021121700198**

Filing Description

Question	Response
Description	This is a preliminary constellation of hyperspectral imaging platforms utilizing small satellite space-based technology. It combines advanced space-based sensing with robust data analysis and machine learning methods. HS data is downlinked at Ka-band.

**Satellite
Information**

Question	Response
Select Orbit Type	NGSO
Space Station or Satellite Network Name	GHOST
Estimated Lifetime of Satellite(s) From Date of Launch	5 Years
Will the space station(s) operate on a Common Carrier basis?	No

**Operating
Frequency
Bands (4)**

Nature of service	Description	Frequency Band(s)	Mode Type
Earth Exploration-Satellite Service		25500.0 MHz -27000.0 MHz	Transmit
Earth Exploration-Satellite Service		2025.0 MHz -2110.0 MHz	Receive
Other Satellite Service (please specify)	Intersatellite Service	1615.0 MHz -1617.5 MHz	Transmit
Space Operation Service		400.15 MHz -401.0 MHz	Transmit

**Orbital
Information For
Non-
Geostationary
Satellites**

Question	Response
Total Number of Satellites in the active constellation	6
Orbit Epoch Date	03/21/2022
Celestial Reference Body	Earth

Orbital Plane 1:

Question	Response
Number of Satellites in Plane	2
Inclination Angle	97.5 degrees
Right Ascension of Ascending Node	30.0 degrees
Argument of Perigee	0.0 degrees
Orbital Period	5708.0 seconds
Apogee	525.0 km
Perigee	525.0 km
Active Service Arc Begin Angle with respect to Ascending Node	-90.0 degrees
Active Service Arc End Angle with respect to Ascending Node	90.0 degrees

Mean Anomaly For Each Satellite

Satellite Number	Mean Anomaly (degrees) at the Orbit Epoch Date
1	180.0
2	0.0

Orbital Plane 2:

Question	Response
Number of Satellites in Plane	2
Inclination Angle	97.5 degrees
Right Ascension of Ascending Node	330.0 degrees
Argument of Perigee	0.0 degrees
Orbital Period	5708.0 seconds
Apogee	525.0 km
Perigee	525.0 km
Active Service Arc Begin Angle with respect to Ascending Node	-90.0 degrees
Active Service Arc End Angle with respect to Ascending Node	90.0 degrees

Mean Anomaly For Each Satellite

Satellite Number	Mean Anomaly (degrees) at the Orbit Epoch Date
1	60.0
2	240.0

Orbital Plane 3:

Question	Response
Number of Satellites in Plane	2
Inclination Angle	97.5 degrees
Right Ascension of Ascending Node	0.0 degrees
Argument of Perigee	0.0 degrees
Orbital Period	5708.0 seconds
Apogee	525.0 km
Perigee	525.0 km
Active Service Arc Begin Angle with respect to Ascending Node	-90.0 degrees
Active Service Arc End Angle with respect to Ascending Node	90.0 degrees

Mean Anomaly For Each Satellite

Satellite Number	Mean Anomaly (degrees) at the Orbit Epoch Date
1	300.0
2	120.0

Receiving Beams 1:

Question	Response
Beam ID	SCNT
Receive Beam Frequency	2045.0 MHz -2050.0 MHz
Beam Type	Steerable
Polarization	RHCP
Peak Gain	5.5 dBi
Antenna Pointing Error	0.01 degrees
Antenna Rotational Error	0.05 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
G/T at Max. Gain Point	-22.3 dB/K
Min. Saturation Flux Density	-94.8 dBW/m2
Max. Saturation Flux Density	-93.9 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	NOR, ATA (Svalbard, Norway and Troll, Antarctica)

Receiving Beams 2:

Question	Response
Beam ID	SCMD
Receive Beam Frequency	2054.85 MHz -2055.15 MHz
Beam Type	Steerable
Polarization	RHCP
Peak Gain	5.5 dBi
Antenna Pointing Error	0.01 degrees
Antenna Rotational Error	0.05 degrees

Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
G/T at Max. Gain Point	-20.2 dB/K
Min. Saturation Flux Density	-88.0 dBW/m2
Max. Saturation Flux Density	-76.0 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	NOR (Svalbard and Tromso, Norway)

Receiving
Channels (2)

Channel ID	Channel Bandwidth (MHz)	Center Frequency s (MHz)	Feeder Link, Service Link or TT&C
ACNT	5.0	2047.5	Service Link
ACMD	0.3	2055.0	TT&C

Transmitting
Beams 1:

Question	Response
Beam ID	UTLM
Transmit Beam Frequency	400.48 MHz -400.52 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	0.19 dBi
Antenna Pointing Error	0.0 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
Max. Transmit EIRP Density	-40.8 dBW/Hz
Max. Transmit EIRP	5.21 dBW
Co- or Cross Polar Mode	C
Service Area Description	CA, NOR (Santa Clara, California and Tromso, Norway)

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
* (dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):
4.0 kHz	-142.4	-140.7	-139.1	-137.7	-136.4	-130.2

Transmitting
Beams 2:

Question	Response
Beam ID	LTLM
Transmit Beam Frequency	1615.0 MHz -1617.5 MHz

Beam Type	Fixed
Polarization	LHCP
Peak Gain	4.4 dBi
Antenna Pointing Error	0.01 degrees
Antenna Rotational Error	0.05 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-52.0 dBW/Hz
Max. Transmit EIRP	0.0 dBW
Co- or Cross Polar Mode	C
Service Area Description	GLOBAL. (The beam is nominally directed ZENITH during use and is communicating with a Globalstar satellite).

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²
* BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
4.0 kHz	-169.5	-167.3	-165.3	-163.7	-162.2	-155.5

Transmitting Beams 3:

Question	Response
Beam ID	KaA
Transmit Beam Frequency	25500.0 MHz -25950.0 MHz
Beam Type	Steerable
Polarization	RHCP
Peak Gain	27.4 dBi

Antenna Pointing Error	0.01 degrees
Antenna Rotational Error	0.05 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-52.9 dBW/Hz
Max. Transmit EIRP	33.2 dBW
Co- or Cross Polar Mode	C
Service Area Description	NOR, ATA (Svalbard, Norway and Troll, Antarctica)

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²
* BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
1.0 MHz	-130.5	-128.8	-127.2	-125.8	-124.5	-118.3

Transmitting Beams 4:

Question	Response
Beam ID	KaB
Transmit Beam Frequency	26025.0 MHz -26475.0 MHz
Beam Type	Steerable
Polarization	RHCP
Peak Gain	27.4 dBi
Antenna Pointing Error	0.01 degrees
Antenna Rotational Error	0.05 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees

Max. Transmit EIRP Density	-52.9 dBW/Hz
Max. Transmit EIRP	33.2 dBW
Co- or Cross Polar Mode	C
Service Area Description	NOR, ATA (Svalbard, Norway and Troll, Antarctica)

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
* BW:	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):
1.0 MHz	-130.5	-128.8	-127.2	-125.8	-124.5	-118.3

Transmitting Beams 5:

Question	Response
Beam ID	KaC
Transmit Beam Frequency	26550.0 MHz -27000.0 MHz
Beam Type	Steerable
Polarization	RHCP
Peak Gain	27.4 dBi
Antenna Pointing Error	0.01 degrees
Antenna Rotational Error	0.05 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-52.9 dBW/Hz
Max. Transmit EIRP	33.2 dBW
Co- or Cross Polar Mode	C
Service Area Description	NOR, ATA (Svalbard, Norway and Troll, Antarctica)

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
*	(dbW/m ²	(dbW/m ²	(dbW/m ²	(dbW/m ²	(dbW/m ²	(dbW/m ²
BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
1.0 MHz	-130.5	-128.8	-127.2	-125.8	-124.5	-118.3

Transmitting Beams 6:

Question	Response
Beam ID	KaD
Transmit Beam Frequency	25500.0 MHz -25950.0 MHz
Beam Type	Steerable
Polarization	LHCP
Peak Gain	27.4 dBi
Antenna Pointing Error	0.01 degrees
Antenna Rotational Error	0.05 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-52.9 dBW/Hz
Max. Transmit EIRP	33.2 dBW
Co- or Cross Polar Mode	C
Service Area Description	NOR, ATA (Svalbard, Norway and Troll, Antarctica)

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
*	(dbW/m ²	(dbW/m ²	(dbW/m ²	(dbW/m ²	(dbW/m ²	(dbW/m ²
BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):

1.0 MHz	-130.5	-128.8	-127.2	-125.8	-124.5	-118.3
--------------------	--------	--------	--------	--------	--------	--------

**Transmitting
Beams 7:**

Question	Response
Beam ID	KaE
Transmit Beam Frequency	26025.0 MHz -26475.0 MHz
Beam Type	Steerable
Polarization	LHCP
Peak Gain	27.4 dBi
Antenna Pointing Error	0.01 degrees
Antenna Rotational Error	0.05 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-52.9 dBW/Hz
Max. Transmit EIRP	33.2 dBW
Co- or Cross Polar Mode	C
Service Area Description	NOR, ATA (Svalbard, Norway and Troll, Antarctica)

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
* BW:	(dBW/m² /BW):	(dBW/m² /BW):	(dBW/m² /BW):	(dBW/m² /BW):	(dBW/m² /BW):	(dBW/m² /BW):
1.0 MHz	-130.5	-128.8	-127.2	-125.8	-124.5	-118.3

**Transmitting
Beams 8:**

Question	Response
----------	----------

Beam ID	KaF
Transmit Beam Frequency	26550.0 MHz -27000.0 MHz
Beam Type	Steerable
Polarization	LHCP
Peak Gain	27.4 dBi
Antenna Pointing Error	0.01 degrees
Antenna Rotational Error	0.05 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-52.9 dBW/Hz
Max. Transmit EIRP	33.2 dBW
Co- or Cross Polar Mode	C
Service Area Description	NOR, ATA (Svalbard, Norway and Troll, Antarctica)

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
* BW:	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):
1.0 MHz	-130.5	-128.8	-127.2	-125.8	-124.5	-118.3

Transmitting Beams 9:

Question	Response
Beam ID	KaG
Transmit Beam Frequency	26756.8 MHz -26843.2 MHz
Beam Type	Steerable
Polarization	RHCP

Peak Gain	23.5 dBi
Antenna Pointing Error	0.01 degrees
Antenna Rotational Error	0.05 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-57.4 dBW/Hz
Max. Transmit EIRP	21.2 dBW
Co- or Cross Polar Mode	C
Service Area Description	NOR, ATA (Svalbard, Norway and Troll, Antarctica)

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
* BW:	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):
1.0 MHz	-135.0	-133.3	-131.7	-130.3	-129.0	-122.8

Transmitting Beams 10:

Question	Response
Beam ID	KaH
Transmit Beam Frequency	26756.8 MHz -26843.2 MHz
Beam Type	Steerable
Polarization	LHCP
Peak Gain	23.5 dBi
Antenna Pointing Error	0.01 degrees
Antenna Rotational Error	0.05 degrees
Polarization Switchable	

Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-57.4 dBW/Hz
Max. Transmit EIRP	21.2 dBW
Co- or Cross Polar Mode	C
Service Area Description	NOR, ATA (Svalbard, Norway and Troll, Antarctica)

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²
* BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
1.0 MHz	-135.0	-133.3	-131.7	-130.3	-129.0	-122.8

Transmitting
Channels (10)

Channel ID	Channel Bandwidth (MHz)	Center Frequency s (MHz)	Feeder Link, Service Link or TT&C
CLH	450.0	26775.0	Service Link
BLH	450.0	26250.0	Service Link
ARH	450.0	25725.0	Service Link
ALH	450.0	25725.0	Service Link
LTLM	2.5	1616.25	Service Link
CRH	450.0	26775.0	Service Link
DLH	86.4	26800.0	Service Link
BRH	450.0	26250.0	Service Link
UTLM	0.04	400.5	TT&C
DRH	86.4	26800.0	Service Link

Certification Questions

Question	Response
Are the applicable service area coverage requirements of 25.143(b)(2) (ii) and (iii), or 25.144(a)(3)(i), or 25.145 (c)(1) and (2), or 25.146(i)(1) and (2), or 25.148(c), or 25.225 met?	N/A
Are the applicable frequency tolerances of 25.202(e) and out-of-band emission limits of 25.202(f)(1),(2), and (3) met?	Yes
Are the cessation of emissions requirements of 25.207 met?	Yes
Are the applicable power-flux-density limits of 25.208 met, and is the appropriate technical showing provided within the application?	Yes
For NGSO applications, are the applicable equivalent-power-flux-density limits of 25.208 met, and is the appropriate technical showing provided within the application?	Yes
Are the applicable full-frequency-reuse requirements of 25.210 met?	
If the application is for a 17/24 GHz BSS space station, will it be operated at an offset location with full power and interference protection in accordance with 25.262(b)?	

Attachments

File Name	Beam	Field	Attachment Type	Description
<u>SCMD_Tromso.gxt</u>	SCMD	NGSO Antenna Gain Data	GXT file (*.gxt)	
<u>SCNT_Troll.gxt</u>	SCNT	NGSO Antenna Gain Data	GXT file (*.gxt)	
<u>KaA_KaF_Svalbard.gxt</u>	KaA	NGSO Antenna Gain Data	GXT file (*.gxt)	
<u>KaA_KaF_Troll.gxt</u>	KaA	NGSO Antenna Gain Data	GXT file (*.gxt)	
<u>KaG_KaH_Svalbard.gxt</u>	KaG	NGSO Antenna Gain Data	GXT file (*.gxt)	
<u>KaG_KaH_Troll.gxt</u>	KaG	NGSO Antenna Gain Data	GXT file (*.gxt)	
<u>SCMD_Svalbard.gxt</u>		NGSO Antenna Gain Data	GXT file (*.gxt)	
<u>SCNT_Svalbard.gxt</u>		NGSO Antenna Gain Data	GXT file (*.gxt)	