



312 File Number: **SATLOA2025052300123**

Filing Description

Question	Response
Description	OTTER 24B STRATFI

Satellite
Information

Question	Response
Select Orbit Type	NGSO
Space Station or Satellite Network Name	OTTTER 24B
Estimated Lifetime of Satellite(s) From Date of Launch	10 Years
Will the space station(s) operate on a Common Carrier basis?	No

**Operating
Frequency
Bands (3)**

Nature of service	Description	Frequency Band(s)	Mode Type
Space Research Service		8025.0 MHz -8400.0 MHz	Transmit
Space Research Service		8450.0 MHz -8500.0 MHz	Transmit
Space Research Service		2025.0 MHz -2110.0 MHz	Receive

**Orbital
Information For
Non-
Geostationary
Satellites**

Question	Response
Total Number of Satellites in the active constellation	1
Orbit Epoch Date	01/01/2026
Celestial Reference Body	Earth

Orbital Plane 1:

Question	Response
Number of Satellites in Plane	1
Inclination Angle	0.0 degrees
Right Ascension of Ascending Node	0.0 degrees
Argument of Perigee	0.0 degrees
Orbital Period	86974.0 seconds
Apogee	36050.0 km
Perigee	36050.0 km
Active Service Arc Begin Angle with respect to Ascending Node	-20.0 degrees
Active Service Arc End Angle with respect to Ascending Node	20.0 degrees

Mean Anomaly For Each Satellite

Satellite Number	Mean Anomaly (degrees) at the Orbit Epoch Date
1	0.0

Receiving Beams 1:

Question	Response
Beam ID	SRXL
Receive Beam Frequency	2025.0 MHz -2110.0 MHz
Beam Type	Fixed
Polarization	RHCP
Peak Gain	5.0 dBi
Antenna Pointing Error	0.1 degrees
Antenna Rotational Error	0.1 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
G/T at Max. Gain Point	-24.1 dB/K
Min. Saturation Flux Density	-99.0 dBW/m2
Max. Saturation Flux Density	-98.0 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Global

Receiving Beams 2:

Question	Response
Beam ID	SRXH
Receive Beam Frequency	2025.0 MHz -2110.0 MHz
Beam Type	Steerable
Polarization	RHCP
Peak Gain	10.14 dBi
Antenna Pointing Error	0.1 degrees
Antenna Rotational Error	0.1 degrees

Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
G/T at Max. Gain Point	-16.1 dB/K
Min. Saturation Flux Density	-99.0 dBW/m2
Max. Saturation Flux Density	-98.0 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Global

Receiving
Channels (12)

Channel ID	Channel Bandwidth (MHz)	Center Frequency s (MHz)	Feeder Link, Service Link or TT&C
SRT1	0.2	2027.0	TT&C
SRT2	0.2	2048.5	TT&C
SRT3	0.2	2103.0	TT&C
SRT4	0.01	2027.0	TT&C
SRT5	0.01	2048.5	TT&C
SRT6	0.01	2103.0	TT&C
SRS1	0.2	2027.0	Service Link
SRS2	0.2	2048.5	Service Link
SRS3	0.2	2103.0	Service Link
SRS4	0.01	2027.0	Service Link
SRS5	0.01	2048.5	Service Link
SRS6	0.01	2103.0	Service Link

Transmitting
Beams 1:

Question	Response
Beam ID	XTL2
Transmit Beam Frequency	8450.0 MHz -8500.0 MHz
Beam Type	Fixed
Polarization	RHCP
Peak Gain	7.8 dBi
Antenna Pointing Error	0.1 degrees
Antenna Rotational Error	0.1 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-25.4 dBW/Hz
Max. Transmit EIRP	16.3 dBW
Co- or Cross Polar Mode	C
Service Area Description	Global

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
* (dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):
4.0 kHz	-152.7	-152.6	-152.5	-152.4	-152.3	-151.5

Transmitting
Beams 2:

Question	Response
Beam ID	XTH2
Transmit Beam Frequency	8450.0 MHz -8500.0 MHz

Beam Type	Steerable
Polarization	RHCP
Peak Gain	15.8 dBi
Antenna Pointing Error	0.1 degrees
Antenna Rotational Error	0.1 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-25.2 dBW/Hz
Max. Transmit EIRP	24.67 dBW
Co- or Cross Polar Mode	C
Service Area Description	Global

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²
	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
4.0 kHz	-152.6	-152.5	-152.4	-152.2	-152.1	-151.4

Transmitting Beams 3:

Question	Response
Beam ID	XTH1
Transmit Beam Frequency	8025.0 MHz -8400.0 MHz
Beam Type	Steerable
Polarization	RHCP
Peak Gain	15.8 dBi
Antenna Pointing Error	0.1 degrees

Antenna Rotational Error	0.1 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-25.2 dBW/Hz
Max. Transmit EIRP	24.67 dBW
Co- or Cross Polar Mode	C
Service Area Description	Global

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²
* BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
4.0 kHz	-152.6	-152.5	-152.4	-152.2	-152.1	-151.4

Transmitting Beams 4:

Question	Response
Beam ID	XTL1
Transmit Beam Frequency	8025.0 MHz -8400.0 MHz
Beam Type	Fixed
Polarization	RHCP
Peak Gain	7.8 dBi
Antenna Pointing Error	0.1 degrees
Antenna Rotational Error	0.1 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-25.4 dBW/Hz

Max. Transmit EIRP	16.3 dBW
Co- or Cross Polar Mode	C
Service Area Description	Global

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²
* BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
4.0 kHz	-152.7	-152.6	-152.5	-152.4	-152.3	-151.5

Transmitting
Channels (16)

Channel ID	Channel Bandwidth (MHz)	Center Frequency s (MHz)	Feeder Link, Service Link or TT&C
XS1	2.0	8200.0	Service Link
XS2	0.2	8200.0	Service Link
XS3	0.03	8200.0	Service Link
XS4	0.01	8200.0	Service Link
XS5	2.0	8490.0	Service Link
XS6	0.2	8490.0	Service Link
XS7	0.03	8490.0	Service Link
XS8	0.01	8490.0	Service Link
XT1	2.0	8200.0	TT&C
XT2	0.2	8200.0	TT&C
XT3	0.03	8200.0	TT&C
XT4	0.01	8200.0	TT&C
XT5	2.0	8490.0	TT&C
XT6	0.2	8490.0	TT&C
XT7	0.03	8490.0	TT&C
XT8	0.01	8490.0	TT&C

Certification Questions

Question	Response
Are the applicable service area coverage requirements of 25.143(b)(2) (ii) and (iii), or 25.144(a)(3)(i), or 25.145 (c)(1) and (2), or 25.146(i)(1) and (2), or 25.148(c), or 25.225 met?	N/A
Are the applicable frequency tolerances of 25.202(e) and out-of-band emission limits of 25.202(f)(1),(2), and (3) met?	Yes
Are the cessation of emissions requirements of 25.207 met?	Yes
Are the applicable power-flux-density limits of 25.208 met, and is the appropriate technical showing provided within the application?	
For NGSO applications, are the applicable equivalent-power-flux-density limits of 25.208 met, and is the appropriate technical showing provided within the application?	N/A
Are the applicable full-frequency-reuse requirements of 25.210 met?	
If the application is for a 17/24 GHz BSS space station, will it be operated at an offset location with full power and interference protection in accordance with 25.262(b)?	

Attachments

File Name	Beam	Field	Attachment Type	Description
<u>OTTER_24B_FCC_GIMS.mdb</u>		NGSO Antenna Gain Data	GIMS file (*.mdb)	Antenna Beam Projections for all Relevant Beams with Contours on the Earth's Surface