

File Number: **DRAFT-SAT-LOA-20260527-00216**

Call Sign:

S1. Satellite Information

a. Space Station or Satellite Network Name	b. Orbit Type	c. Estimated Operational Lifetime of Space Station(s) From Date of Launch (yrs)	d. Will the space station(s) operate on a Common Carrier basis?	e. Application Description
Droid.003	Non-Geostationary (NGSO) Small Satellites or Small Spacecraft	5	N/A	Applicant seeks authority to launch and operate one non-geostationary orbit small satellite using the 2025-2110 MHz Earth-to-space and 2200-2290 MHz and 25.5-27 GHz space-to-Earth bands, as well as inter-satellite service, to deliver space research servic

S2. Operating Frequency Bands

a. Type of Service	b. If a. is Other, provide a service description	c. Satellite Frequency Band (MHz)	d. Satellite Frequency (Lower Band Edge) (MHz)	e. Satellite Frequency (Upper Band Edge) (MHz)	f. Direction of Transmission	g. Non Conforming Indicator
EESS		2025 - 2110	2025	2110	Earth-to-Space (Receive)	No
EESS		2200 - 2290	2200	2290	Space-to-Earth (Transmit)	No
ISS		Other	1618.725	1626.5	Space-to-Space (Receive)	Yes
EESS		25500 - 27000	25500	27000	Space-to-Earth (Transmit)	No
ISS		Other	1618.725	1626.5	Space-to-Space (Transmit)	Yes

S3. NGSO Orbital Information

a. Total Number of Simultaneously Operating Satellites in Constellation	b. Total Number of Satellites Deployed During the License Term	c. Orbit Epoch Date	d. Celestial Reference Body	e. If d. is "Other", provide the name of celestial body being referenced	f. Total Number of Orbital Planes
1	1	2027-01-01	Earth		1

g. Orbital Plane Information

(i) Orbital Plane No.	(ii) Number of Satellites in Plane	(iii) Inclination Angle (°)	(iv) Inclination Angle Tolerance (+/- °)	(v) Orbital Period (seconds)	(vi) Apogee (km)	(vii) Apogee Tolerance (+/- km)	(viii) Perigee (km)	(ix) Perigee Tolerance (+/- km)	(x) Argument of Perigee (°)	(xi) Right Ascension of Ascending Node (°)	(xii) Right Ascension of Ascending Node Tolerance (+/- °)	(xiii) Active Service Arc Begin Angle with Respect to Ascending Node (°)	(xiv) Active Service Arc End Angle with Respect to Ascending Node (°)	(xv) Is additional info on the active service arc provided in the application?	(xvi) Satellite Spacing	(xvii) Phase Angle Spacing (°)	(xviii) First Satellite Initial Phase Angle (°)	(xix) Maximum Orbital Eccentricity
1	1	97.4	1	5,689	525	50	525	50	90	257.6	180	-90	90	No	Irregularly			0.01

																-Spaced			
--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	---------	--	--	--

h. Initial Phase Angle Information

(i) Orbital Plane No.	(i) Satellite No.	(ii) Initial Phase Angle (°)
1	1	

S4. Earth-to-Space (Receive) Beams

a. Beam ID:	SRX	n. Beam Peak Flux Density at Command Threshold (dBW/m²):	-100
b. Beam Frequency (Lower Band Edge) (MHz):	2025	o. Peak Isotropic Antenna Gain (dBi):	5.4
c. Beam Frequency (Upper Band Edge) (MHz):	2110	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	RHCP	q. Antenna Pointing Error (°):	
e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	
f. Is this a command beam? (Check box if Yes):	Yes	s. Will a GIMS container file containing all antenna contour data be provided?:	No
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	25.114(c)(4)(vi)(B) (NGSO)
h. Is the beam steerable? (Check box if Yes):	No	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	Yes
j. Maximum G/T (dB/K):	-21.6	w. What information will be provided with the predicted antenna gain contours?:	
k. Minimum G/T (dB/K):			
l. Maximum Saturation Flux Density (dBW/m²):			
m. Minimum Saturation Flux Density (dBW/m²):			

a. Beam ID:	SRX2	n. Beam Peak Flux Density at Command Threshold (dBW/m²):	-100
b. Beam Frequency (Lower Band Edge) (MHz):	2025	o. Peak Isotropic Antenna Gain (dBi):	6.8
c. Beam Frequency (Upper Band Edge) (MHz):	2110	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	RHCP	q. Antenna Pointing Error (°):	
e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	
f. Is this a command beam? (Check box if Yes):	Yes	s. Will a GIMS container file containing all antenna contour data be provided?:	No
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	25.114(c)(4)(vi)(B) (NGSO)
h. Is the beam steerable? (Check box if Yes):	No	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	Yes
j. Maximum G/T (dB/K):	-20.2	w. What information will be provided with the predicted antenna gain contours?:	
k. Minimum G/T (dB/K):			
l. Maximum Saturation Flux Density (dBW/m²):			
m. Minimum Saturation Flux Density (dBW/m²):			

S5. Space-to-Earth (Transmit) Beams

a. Beam ID:	STX	n. Beam Peak Flux Density at Command Threshold (dBW/m²):	
b. Beam Frequency (Lower Band Edge) (MHz):	2200	o. Peak Isotropic Antenna Gain (dBi):	6.1

c. Beam Frequency (Upper Band Edge) (MHz):	2290	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	RHCP	q. Antenna Pointing Error (°):	
e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	
f. Is this a command beam? (Check box if Yes):	No	s. Will a GIMS container file containing all antenna contour data be provided?:	No
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	25.114(c)(4)(vi)(B) (NGSO)
h. Is the beam steerable? (Check box if Yes):	No	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	Yes
j. Maximum Transmit EIRP Density (dBW/Ref BW):	-55	w. What information will be provided with the predicted antenna gain contours?:	
k. Maximum Transmit EIRP (dBW):	5		

y. Max. Power-Flux Densities													
			Angles of Arrival PFD						Geographic Region PFD				
(i) Beam Sub-Frequency (Lower Band Edge) (MHz)	(ii) Beam Sub-Frequency (Upper Band Edge) (MHz)	(iii) Reference Bandwidth (BW)	(iv) 0-2° (dBW/m²/BW)	(v) 2-5° (dBW/m²/BW)	(vi) 5-15° (dBW/m²/BW)	(vii) 15-20° (dBW/m²/BW)	(viii) 20-25° (dBW/m²/BW)	(ix) 25-90° (dBW/m²/BW)	(x) Southeastern Region (dBW/m²/BW)	(xi) Northeastern Region (dBW/m²/BW)	(xii) Western Region (dBW/m²/BW)	(xiii) Other Region (dBW/m²/BW)	(xiv) Energy Dispersal Bandwidth (kHz)
2200	2290	4 kHz	-157.5	-156.4	-153.1	-151.7	-150.4	-144.1					

a. Beam ID:	KTX	n. Beam Peak Flux Density at Command Threshold (dBW/m²):	
b. Beam Frequency (Lower Band Edge) (MHz):	25500	o. Peak Isotropic Antenna Gain (dBi):	33.2
c. Beam Frequency (Upper Band Edge) (MHz):	27000	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	RHCP	q. Antenna Pointing Error (°):	
e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	
f. Is this a command beam? (Check box if Yes):	No	s. Will a GIMS container file containing all antenna contour data be provided?:	Yes
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	25.114(c)(4)(vi)(D) (NGSO)
h. Is the beam steerable? (Check box if Yes):	Yes	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	Yes
j. Maximum Transmit EIRP Density (dBW/Ref BW):	-40	w. What information will be provided with the predicted antenna gain contours?:	
k. Maximum Transmit EIRP (dBW):	38.8		

y. Max. Power-Flux Densities													
			Angles of Arrival PFD						Geographic Region PFD				
(i) Beam Sub-Frequency (Lower Band Edge) (MHz)	(ii) Beam Sub-Frequency (Upper Band Edge) (MHz)	(iii) Reference Bandwidth (BW)	(iv) 0-2° (dBW/m²/BW)	(v) 2-5° (dBW/m²/BW)	(vi) 5-15° (dBW/m²/BW)	(vii) 15-20° (dBW/m²/BW)	(viii) 20-25° (dBW/m²/BW)	(ix) 25-90° (dBW/m²/BW)	(x) Southeastern Region (dBW/m²/BW)	(xi) Northeastern Region (dBW/m²/BW)	(xii) Western Region (dBW/m²/BW)	(xiii) Other Region (dBW/m²/BW)	(xiv) Energy Dispersal Bandwidth (kHz)
25500	27000	1 MHz	-118.6	-117.5	-114.1	-112.7	-111.4	-105.1					

S6. Space-to-Space (Receive) Beams

a. Beam ID:	IRDRX	n. Beam Peak Flux Density at Command Threshold (dBW/m²):	
b. Beam Frequency (Lower Band Edge) (MHz):	1618.725	o. Peak Isotropic Antenna Gain (dBi):	4.5
c. Beam Frequency (Upper Band Edge) (MHz):	1626.5	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	RHCP	q. Antenna Pointing Error (°):	
e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	

f. Is this a command beam? (Check box if Yes):	No	s. Will a GIMS container file containing all antenna contour data be provided?:	No
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	25.114(c)(4)(vi)(B) (NGSO)
h. Is the beam steerable? (Check box if Yes):	No	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	Yes
j. Maximum G/T (dB/K):	-17.3	w. What information will be provided with the predicted antenna gain contours?:	
k. Minimum G/T (dB/K):			
l. Maximum Saturation Flux Density (dBW/m²):			
m. Minimum Saturation Flux Density (dBW/m²):			

S7. Space-to-Space (Transmit) Beams

a. Beam ID:	IRDTX	m. Beam Peak Flux Density at Command Threshold (dBW/m²):	
b. Beam Frequency (Lower Band Edge) (MHz):	1618.725	o. Peak Isotropic Antenna Gain (dBi):	4.5
c. Beam Frequency (Upper Band Edge) (MHz):	1626.5	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	1.5
d. Polarization:	RHCP	q. Antenna Pointing Error (°):	
e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	
f. Is this a command beam? (Check box if Yes):	No	s. Will a GIMS container file containing all antenna contour data be provided?:	No
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	25.114(c)(4)(vi)(B) (NGSO)
h. Is the beam steerable? (Check box if Yes):	No	u. Provide a list of each orbital plane in which this antenna beam is used.:	1
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	Yes
j. Maximum Transmit EIRP Density (dBW/Ref BW):	-40.7	w. What information will be provided with the predicted antenna gain contours?:	
k. Maximum Transmit EIRP (dBW):	5.5		

y. Max. Power-Flux Densities													
			Angles of Arrival PFD						Geographic Region PFD				
(i) Beam Sub-Frequency (Lower Band Edge) (MHz)	(ii) Beam Sub-Frequency (Upper Band Edge) (MHz)	(iii) Reference Bandwidth (BW)	(iv) 0-2° (dBW/m²/BW)	(v) 2-5° (dBW/m²/BW)	(vi) 5-15° (dBW/m²/BW)	(vii) 15-20° (dBW/m²/BW)	(viii) 20-25° (dBW/m²/BW)	(ix) 25-90° (dBW/m²/BW)	(x) Southeastern Region (dBW/m²/BW)	(xi) Northeastern Region (dBW/m²/BW)	(xii) Western Region (dBW/m²/BW)	(xiii) Other Region (dBW/m²/BW)	(xiv) Energy Dispersal Bandwidth (kHz)
		4 kHz	-142.4	-141.3	-137.9	-136.4	-135.2	-128.9					

S8. Attachments

Beam ID	Direction of Transmission	(i) Document Type	(ii) If Document Type is "Other", provide short description	(iii) File Name
IRDRX	Space-to-Space (Receive)	Other	Description of ISL Beam max gain and beamwidth	IRDTX_IRDRX.txt
IRDTX	Space-to-Space (Transmit)	Other	Description of ISL Beam max gain and beamwidth	IRDTX_IRDRX.txt
KTX	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		KTX.zip
SRX	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SRX.zip
SRX2	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SRX2.zip
STX	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		STX_.zip