

General:	Units	Clear Sky	Faded
Emission Designator		250MG7W	250MG7W
Data Rate	Mbit/s	533	533
Modulation		16-APSK	16-APSK
Coding Rate		0.6642	0.6642
Carrier Bandwidth	MHz	250	250
Uplink Frequency	GHz	29.75	29.75
Downlink Frequency	GHz	19.95	19.95
Uplink Elevation Angle	degrees	35	35
Downlink Elevation Angle	degrees	35	35
Uplink:			
Tx E/S Antenna Diameter	m	3.5	3.5
Tx E/S Power to Antenna	W	20.4	512.9
Tx E/S Antenna Gain	dBi	58.9	58.9
Tx E/S EIRP per Carrier	dBW	72	86.0
Tx E/S Antenna Pointing Loss	dB	0.5	0.5
Atmospheric and Rain Losses	dB	0.5	14.5
Free Space Loss	dB	213.6	213.6
G/T (-2dB contour)	dB/K	20	20
C/I - Intra-system	dB	20.8	20.8
Downlink:			
EIRP per Carrier towards Rx E/S (-3dB)	dBW	64	64
Atmospheric and Rain Losses	dB	0.5	4
Free Space Loss	dB	210.1	210.1
Rx E/S Antenna Pointing Loss	dB	0.5	0.5
Rx E/S Antenna Diameter	m	0.74	0.74
Rx E/S Antenna Gain	dBi	42.1	42.1
Rx E/S G/T	dB/K	18.6	16.5
System Noise Temp (LNA+Sky)	K	225	366
C/I - Intra-system	dB	20.1	20.1
End-to-End:			
C/N - Thermal Uplink	dB	22.8	22.8
C/I Up - ASI	dB	19.6	33.6
C/N - Thermal Downlink	dB	16.9	11.3
C/I Down - ASI	dB	17.2	17.2
C/(N+I) - Total Actual	dB	11.3	9.3
C/N - Required	dB	9.3	9.3
Excess Margin	dB	2.0	0.0