

<b>Link Parameters</b>	<b>Units</b>	<b>445KG7W</b>
Uplink frequency	GHz	13.88
Downlink frequency	GHz	11.07
User data rate	kbit/s	512
Modulation		QPSK
Total coding rate		0.691
Carrier bandwidth	kHz	445
<b>Uplink:</b>		
Nominal E/S e.i.r.p. per carrier	dBW	49.7
Earth station diameter	m	4.5
Earth station gain	dBi	54.5
Uplink input power per carrier	dBW	-4.8
Uplink input power density	dBW/Hz	-61.3
Atmospheric loss	dB	0.2
Free space path loss	dB	207.0
G/T satellite (-3dB contour)	dB/K	4.7
C/N thermal uplink	dB	19.3
C/I XPOL, ACI, IM, ASI	dB	19.4
C/(N+I) uplink	dB	16.4
<b>Downlink:</b>		
Satellite e.i.r.p. per carrier (-3dB contour)	dBW	24.6
Atmospheric loss	dB	0.1
Free space path loss	dB	205.0
Earth station diameter	m	1.8
Earth station gain	dBi	44.5
Noise temperature	K	105.0
Earth station G/T	dB/K	24.3
C/N thermal downlink	dB	15.9
C/I XPOL, ACI, IM, ASI	dB	13.5
C/(N+I) downlink	dB	11.5
<b>Overall:</b>		
C/(N+I) overall	dB	10.3
C/(N+I) required	dB	5.7
Margin	dB	4.6