

| Link Parameters | Units | 445KG7W |
|---|--------------|----------------|
| Uplink frequency | GHz | 13.88 |
| Downlink frequency | GHz | 11.07 |
| User data rate | kbit/s | 512 |
| Modulation | | QPSK |
| Total coding rate | | 0.691 |
| Carrier bandwidth | kHz | 445 |
| Uplink: | | |
| Nominal E/S e.i.r.p. per carrier | dBW | 51.6 |
| Earth station diameter | m | 4.5 |
| Earth station gain | dBi | 54.5 |
| Uplink input power per carrier | dBW | -2.9 |
| Uplink input power density | dBW/Hz | -59.4 |
| Atmospheric loss | dB | 0.2 |
| Free space path loss | dB | 207.0 |
| G/T satellite (-3dB contour) | dB/K | 3.9 |
| C/N thermal uplink | dB | 20.4 |
| C/I XPOL, ACI, IM, ASI | dB | 20.4 |
| C/(N+I) uplink | dB | 17.4 |
| Downlink: | | |
| Satellite e.i.r.p. per carrier (-3dB contour) | dBW | 31.5 |
| Atmospheric loss | dB | 0.1 |
| Free space path loss | dB | 205.0 |
| Earth station diameter | m | 1.2 |
| Earth station gain | dBi | 41.0 |
| Noise temperature | K | 105.0 |
| Earth station G/T | dB/K | 20.8 |
| C/N thermal downlink | dB | 19.3 |
| C/I XPOL, ACI, IM, ASI | dB | 15.8 |
| C/(N+I) downlink | dB | 14.2 |
| Overall: | | |
| C/(N+I) overall | dB | 12.5 |
| C/(N+I) required | dB | 5.7 |
| Margin | dB | 6.8 |