

General:	Units	Clear Sky	Faded
Emission Designator		782KG7D	782KG7D
Data Rate	kbit/s	312.5	312.5
Modulation		BPSK	BPSK
Coding Rate		0.5000	0.5000
Carrier Bandwidth	kHz	781.25	781.25
Uplink Frequency	GHz	29.75	29.75
Downlink Frequency	GHz	19.95	19.95
Uplink:			
Tx E/S Antenna Diameter	m	0.67	0.67
Tx E/S Power to Antenna	W	1.7	1.7
Tx E/S Antenna Gain	dBi	44.4	44.4
Tx E/S EIRP per Carrier	dBW	46.7	46.7
Tx E/S Antenna Pointing Loss	dB	0.5	0.5
Atmospheric and Rain Losses	dB	0.5	11.4
Free Space Loss	dB	213.6	213.6
G/T toward Tx E/S	dB/K	18.5	18.5
C/I - Intra-system	dB	15.3	15.3
Downlink:			
EIRP per Carrier towards Rx E/S	dBW	30.1	19.2
Atmospheric and Rain Losses	dB	0.5	14.0
Free Space Loss	dB	209.9	209.9
Rx E/S Antenna Pointing Loss	dB	0.6	0.6
Rx E/S Antenna Diameter	m	7.3	7.3
Rx E/S Antenna Gain	dBi	61.5	61.5
Rx E/S G/T	dB/K	38.0	34.4
System Noise Temp (LNA+Sky)	K	250	517
C/I - Intra-system	dB	13.3	13.3
End-to-End:			
C/N - Thermal Uplink	dB	21.2	10.3
C/I Up - ASI	dB	19.4	8.5
C/N - Thermal Downlink	dB	27.8	-0.2
C/I Down - ASI	dB	28.0	28.0
C/(N+I) - Total Actual	dB	10.1	-1.3
C/N - Required	dB	-1.3	-1.3
Excess Margin	dB	11.4	0.0