# FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS (Technical and Operational Description)

#### S1. GENERAL INFORMATION Complete for all satellite applications.

a. Space Station or Satellite Netwo SATMEX 9	rork Name:	e. Estimated Date of Placement into Service: 8/15/2016		i Will the space station(s) operate on a Common Carrier Basis: N			
b. Construction Commencement D 8/15/2013	Date:	f. Estimated Lifetime of Satellite(s): 15	Years	j. Number of transponders offered on a common carrier basis: 0			
c. Construction Completion Date: 10/1/2015		g. Total Number of Transponders: 2		k. Total Common Carrier Transponder Ban 0	dwidth: MHz		
d1. Est Launch Date Begin: d2. 10/31/2015	2. Est Launch Date End: 12/31/2015	h. Total Transponder Bandwidth (no. transponde 44	rs x Bandwidth) MHz	I. Orbit Type: Mark all boxes that apply:	NGSO		

#### S2. OPERATING FREQUENCY BANDS Identify the frequency range and transmit/receive mode for all frequency bands in which this station will oper Also indicate the nature of service(s) for each frequency band.

	Frequency	Band Limits			f.							
Lower Frequency	(_Hz)	Upper Frequency (	_Hz)	e. T/R Mode	Nature of Service(s): List all that apply to this band							
a. Numeric	b. Unit (K/M/G)	c. Numeric	d. Unit (K/M/G)									
1564.42	М	1586.42	М	Т	Radio Navigation Satellite Service							
1165.45	М	1187.45	М	Т	Radio Navigation Satellite Service							
6628.27	М	6650.27	М	R	Fixed Satellite Service							
6679.42	М	6701.42	М	R	Fixed Satellite Service							
4198	М	4198.4	М	Т	Fixed Satellite Service							
4199.6	М	4200	М	Т	Fixed Satellite Service							

S3. ORBITAL INFORMATION FOR GEOSTATIONARY SATELLITES ONLY:

a. Nominal Orbital Longitude (	Degrees E/W):	b. Alternate Orbital Longitu	ude (Degrees E/W):			c. Reason for orbital location selection:
117 W				Limited availability of orbital positions for the		
Longitudinal Tolerance or E/W	1 0	f. Inclination Excursion or N/S Station-Keeping	Range of orbital are in which a provided (Optional):	•		spacecraft on which this RNSS payload is hosted. Good elevation over North America.
d. Toward West:	0.05 Degrees	Tolerance:		Degrees	E/W	Good elevation over North America.
e. Toward East:	0.05 Degrees	0.05 Degrees	g. Westernmost: h. Easternmost:			
i. Reason for service are s	election (Optional)	:				

Page 2: NGSO Orbits

S4. ORBITAL INFORMATION FOR NON-GEOSTATIONARY SATELLITES ONLY

S4a. Total Number of Satellites in Network or System:

S4b. Total Number of Orbital Planes in Network or System:

S4c. Celestial Reference Body (Earth, Sun, Moon, etc.):

S4d. Orbit Epoch Date:

For each Orbital Plane Provide:

ſ	(e) Orbital	(f) No. of	(g) Inclination	(h) Orbital	(i) Apogee (km)	(j) Perigee (km)	(k) Right Ascension	(I) Argument of	Active Se	e (Degrees)	
	Plane No.	Satellites in	Angle (degrees)	Period			of the Ascending	Perigee	(m) Begin	(n) End Angle	(o) Other
		Plane		(Seconds)			Node (Deg.)	(Degrees)	Angle		

S5. INITIAL SATELLITE PHASE ANGLE For each satellite in each orbital plane, provide the initial phase angle.

nitial
Angle rees)

**NO NGSO DATA FILED** 

Page 3: Service Areas

S6. SERVICE AREA CHARACTERISTICS for each service area provide:

(a) Service Area ID	(b) Type of Associated Station (Earth or Space)	(d) Service Area Description. Provide list of geographic areas (state postal codes or ITU 3-ltr codes), satellites or Figure No. of Service Area Diagram.
GLB	S	All visible areas of the Earth

Page 4: Antenna Beams

(a)	(b)	Isotropic	Antenna	(e)	(f)	(g) Min.	(h) Polar-	(i) Polarization	(j) Service		Transmit				Receive		
Beam	T/R		ain	_ 0	Rotational	Cross-	ization	Alignment Rel.	Area ID	(k) Input	(I) Effective	(m)	· · /	(o) G/T	(p) Min.	Input Atten	uator (dB)
ID	Mode	(c) Peak (dBi)	(d) Edge (dBi)	Error (Degrees)	Error (Degrees)	Polar Iso- lation (dB)	Switch- able?	Equatorial Plane (Degrees)		Losses (dB)	Output Power (W)	Max. EIRP	System Noice	Max. Gain Pt	Saturation Flux Density	(q) Max.	(r) Step
		(UDI)	(UDI)	( -5	( -3,		(Y/N)			(02)			Temp (k)		(dBW/m2)	Value	Size
CGU	R	22.4	16.4	0.1	0	23.3	N		GLB				603	-5.4	-98	15	1
L1GD	Т	17.9	16.2	0.1	0	26	N		GLB	1	72	36.5					
L5GD	Т	17.3	15.8	0.1	0	28	N		GLB	1	71	35.8					
CGD	Т	20.7	16.7	0.1	0	23.3	N		GLB	2	0.12	11.4					

-169.4

-169.2

-168.9

-168.6

-165.4

(a) (b) (c) Co-or (d) GSO e) NGSO Antenna Gain (f) GSO Antenna Max. Power Flux Density (dBW/M2/Hz) Beam Ť/Ŕ Cross Ref. Contour Description Gain Contour Data At Angle of Arrival above horizontal (for emission with highest PFD) ID Mode Polar Orbital (Figure/Table/ Exhibit) (GXT File) (g) 5 Deg (h) 10 Deg (i) 15 Deg (j) 20 Deg (k) 25 Deg Mode ("C" Longitude (Deg. E/W) or" X") CGU.gxt CGU С -117 R L1GD С -117 -165.8 -165.7 -165.4 -165.2 -163.7 L5GD -117 -166.3 -166.1 -165.9 -165.7 -164.4 С

CGD.gxt

CGD

С

-117

S8. ANTENNA BEAM DIAGRAMS For each beam pattern provide the reference to the graphic image and numerical data: Also provide the power flux density levels in each beam that result from the emission with the highest power flux density.

#### Page 5: Beam Diagrams

Page 6: Channels and Transponders

-		(c)		. ,	(f) TTC
(a) Channel No.	nel Bandwidth		(d) Center Frequency (MHz)	(e) Polarization (H, V, L, R)	or Comm Channel (T or C)
C1	22000	R	6639.27	R	С
C5	22000	R	6690.42	R	С
L1	22000	Т	1575.42	R	С
L5	22000	Т	1176.45	R	С
CTLM1	400	Т	4198.2	V	Т
CTLM2	400	Т	4199.8	V	Т

S9. SPACE STATION CHANNELS For each frequency channel provide: S10. SPACE STATION TRANSPONDERS For each transponder provide:

(a)	(b)	Receive	Band	Transmit Band		
Transponder ID	Transponder Gain (dB)	(c) Channel No.	(d) Beam ID	(e) Channel No.	(f) Beam ID	
1		C1	CGU	L1	L1GD	
5		C5	CGU	L5	L5GD	
TLM1				CTLM1	CGD	
TLM2				CTLM2	CGD	

S11. DIGITAL MODULATION PARAMETERS For each digital emission provide:

(a) Digital Mod. ID	(b) Emission Designator	(c) Assigned Bandwidth (kHz)	(d) No. of Phases	(e)Uncoded Data Rate (kbps)	(f) FEC Error Correction Coding Rate	(g) CDMA Processing Gain (dB)	(h) Total C/N Performance Objective (dB)	(i) Single Entry C/I Objective (dB)
D1	22M0X2D	22000	2	0.25	0.5	0	-26	-13.8
D5	22M0X2D	22000	2	0.25	0.5	0	-36	-23.8
DTLM	400KG2D	400	2	10	0.5		12	24.2

Page 7: Digital Modulation

Page 8: Analog Modulation

S12. ANALOG MODULATION PARAMETERS For each analog emission provide:

(a)	(b) Emission	(c)	(d) Signal	(e)		Multi-channe	Multi-channel Telephony (			(k) Video	(I) Video	( )	(n) Total C/N	(-) - 5 -
Analog Mod. ID		Assigned Bandwidth (kHz)	Туре	Channels per Carrier	(f) Ave. Companded Talker Level (dBm0)	(g) Bottom Baseband Freq. (MHz)	(h) Top Baseband Freq. (MHz)	(i) RMS Modulation Index	Standard NTSC, PAL, etc.	Noise- Weighting (dB)	and SCPC/FM Modulation Index	Compander, Preemphasis, and Noise Weighting (dB)	Performance Objective (dB)	Entry C/I Objective (dB)

Page 9: Typical Emissions

S13. TYPICAL EMISSIONS For each planned type of emission provide:

Associated Transponder ID Range		Modulation ID		( )	(f) Carrier	(0)	(h) Energy	Receive Band (Assoc. Transmit Stn)			Transmit Band (This Space Station)			
		(c) Digital (d) A	(d) Analog		Spacing (kHz)	Reference (Table No.)	Dispersal Bandwidth	(i)Assoc. Stn. Max.	Assoc. Station Transmit Power (dBW)		EIRP (dBW)		(n) Max. Power	
(a) Start	(b) End	(Table S11) (Ta	(Table S12)		. ,	-	(kHz)	Antenna	Power	(abvv)			Flux Density (dBW/m2/Hz)	Stn Rec. G/T
								Gain (dBi)	(j) Min.	(k) Max.	(I) Min.	(m) Max.	(0.011/112)	(dB/K)
1	1	D1		1		LB1 (14May14).		59	13	19	32.5	36.5	-163	-20
1	1	D1		1		LB2 (14May14).		57.2	14.8	20.8	32.5	36.5	-163	-20
5	5	D5		1		LB3 (14May14).		59	13	19	32	35.8	-163.7	-20
5	5	D5		1		LB4 (14May14).		57.2	14.8	20.8	32	35.8	-163.7	-20
TLM1	TLM2	DTLM		1		LB5 (14May14).					8.4	11.4	-164.6	36.8
TLM1	TLM2	DTLM		1		LB6 (14May14).					8.4	11.4	-164.6	34.5

Page 10: TT and C

S14. Is the space station(s) controlled and monitored remotely? If Yes, provide the location and telephone number of the TT and C control point(s): #Error

Page 11: Characteristics and Certifications

S15. SPACECRAFT PHYSICAL CHARACTERISTICS:

S15a: Mass of spacecraft without fuel (kg): 1697	Spacecraft Dimensions (meters)	Probability of Survival to End of Life (0.0 - 1.0)
S15b. Mass of fuel and disposables at launch (kg): 264		
S15c. Mass of spacecraft and fuel at launch (kg): 1961	S15f. Length (m): 32	S15i. Payload: 0.93
S15d. Mass of fuel, in orbit, at beginning of life (kg): 100	S15g. Width (m): 7	S15j. Bus: 0.88
S15e. Deployed Area of Solar Array (square meters): 60	S15h. Height (m): 4	S15k. Total: 0.81

#### S16. SPACECRAFT ELECTRICAL CHARACTERISTICS:

Spacecraft Subsystem	Electrical Pov Beginnir	ver (Watts) At ng of Life		ver (Watts) At of Life		
	At Equinox	At Solstice	At Equinox	At Solstice		
Payload (Watts):	<sup>(a):</sup> 8000	<sup>(f):</sup> 8000	<sup>(k):</sup> 7500	<sup>(p):</sup> 7500		
Bus (Watts):	<sup>(b):</sup> 3000	<sup>(g):</sup> 3000	<sup>(I):</sup> 1600	<sup>(q):</sup> 1600		
Total (Watts):	<sup>(c):</sup> 11000	<sup>(h):</sup> 11000	<sup>(m)</sup> 9100	<sup>(r):</sup> 9100		
Solar Array (Watts):	<sup>(d):</sup> 12600	<sup>(i):</sup> 12100	<sup>(n):</sup> 10600	<sup>(s):</sup> 9700		
Depth of Battery Discharge (%):	<sup>(e)</sup> 27 %	<sup>(j)</sup> 27 %	<sup>(0)</sup> 78 %	<sup>(t)</sup> 78 %		

#### S17. CERTIFICATIONS:

a. Are the power flux density limits of § 25.208 met?:	YES	# N	<b>o</b> #	N/A			
b. Are the appropriate service area coverage requirements of § 25.143(b)(ii) and (iii), or § 25.145(c)(1) and (2) met?	YES	# N	<b>o</b> #	N/A			
c. Are the frequency tolerances of § 25.202(e) and the out-of-band emission limits of § 25.202(f)(1), (2) and (3) met? X	YES	N	0	N/A			
In addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the							
Commission's rules, 47 C.F.R § 25.114.							