FCC	312	
Sche	dule	S

FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS (Technical and Operational Description)

Page 1: General, Frequency Bands, and GSO Orbit

S1. GENE	RAL INFOR	MATION C	omplete fo	or all sate	ellite applic	cations
----------	-----------	----------	------------	-------------	---------------	---------

a. Space Station or Satellite N ECHOSTAR-117W	etwork Name:	e. Estimated Date of Placement into Service:		i Will the space station(s) operate on a Common Carrier Basis: N		
b. Construction Commenceme	ent Date:	f. Estimated Lifetime of Satellite(s): 12 j. Number of transponders offered on a common 0				
c. Construction Completion Da	ate:	g. Total Number of Transponders: 64		k. Total Common Carrier Transponder Bandwidth: 0 MHz		
d1. Est Launch Date Begin:	d2. Est Launch Date End:	h. Total Transponder Bandwidth (no. transponde 7360	ers x Bandwidth) MHz	I. Orbit Type: Mark all boxes that apply: X GSO NG	sso	

S2. OPERATING FREQUENCY BANDS Identify the frequency range and transmit/receive mode for all frequency bands in which this station will oper Also indicate the nature of service(s) for each frequency band.

	Frequency	Band Limits							
Lower Frequency (_Hz) Upper Frequence		Upper Frequency (_Hz)	e. T/R Mode	f. Nature of Service(s): List all that apply to this band				
a. Numeric	b. Unit (K/M/G)	c. Numeric	d. Unit (K/M/G)						
28.35	G	28.6	G	R	Fixed Satellite Service				
29.25	G	30.0	G	R	Fixed Satellite Service				
18.3	G	18.8	G	Т	Fixed Satellite Service				
19.7	G	20.2	G	Τ	Fixed Satellite Service				

S3. ORBITAL INFORMATION FOR GEOSTATIONARY SATELLITES ONLY:

a. Nominal Orbital Longitu	ude (Degrees E/W):	b. Alternate Orbital Longito	ude (Degrees E/W):	c. Reason for orbital location selection:
117 W Longitudinal Tolerance or d. Toward West: e. Toward East:	E/W Station-Keeping: 0.05 Degrees 0.05 Degrees	f. Inclination Excursion or N/S Station-Keeping Tolerance: 0.05 Degrees	Range of orbital are in which adequa provided (Optional): g. Westernmost: h. Easternmost:	 This orbital location has been selected because, among other things, it provides high elevation angles to all of North America, which is very important for satellite services to large numbers of small and inexpensive consumer earth stations. The high elevation minimizes the risk of signal blockage due to
i. Reason for service a	are selection (Optional)	:		buildings and foliage, and also minimizes the atmospheric and rain attenuation.

Page 2: NGSO Orbits

FCC Form 312 - Schedule S: (Technical and Operational Description)

S4. ORBITAL INFORMATION FOR NON-GEOSTATIONARY SATELLITES ONLY

S4a. Total Number of Satellites in Network or System:

S4c. Celestial Reference Body (Earth, Sun, Moon, etc.):

S4b. Total Number of Orbital Planes in Network or System: S4d. Orbit Epoch Date:

For each Orbital Plane Provide:

(e) Orbital	(f) No. of	(g) Inclination	(h) Orbital	(i) Apogee (km)	(j) Perigee (km)	(k) Right Ascension	(I) Argument of	Active Se	rvice Arc Rang	e (Degrees)
Plane No.	Satellites in	Angle (degrees)	Period			of the Ascending	Perigee	(m) Begin	(n) End	(o) Other
	Plane		(Seconds)			Node (Deg.)	(Degrees)	Angle	Ångle	,
			((13 111)	7g.c	79.0	

S5. INITIAL SATELLITE PHASE ANGLE For each satellite in each orbital plane, provide the intital phase angle.

(a) Orbital Plane No.	(b) Satellite Number	(c) Initial Phase Angle
		(Degrees)

NO NGSO DATA FILED

FCC Form 312 - Schedule S: (Technical and Operational Description)

S6. SERVICE AREA CHARACTERISTICS for each service area provide:

(a) Service Area ID	(b) Type of Associated Station (Earth or Space)	(d) Service Area Description. Provide list of geographic areas (state postal codes or ITU 3-ltr codes), satellites or Figure No. of Service Area Diagram.
NA	S	CONUS, ALASKA, HAWAII, CANADA, MEXICO

Page 3: Service Areas

Page 4: Antenna Beams

FCC Form 312 - Schedule S: (Technical and Operational Description)

S7. SPACE STATION ANTENNA BEAM CHARACTERISTICS For each antenna beam provide:

(a)	(b)	Isotropic	Antenna	(e)	(f)	(g) Min.	(h) Polar-	(i) Polarization	(j) Service		Transmit				Receive		
Beam	T/R	Ga	ain		Rotational	Cross-	ization	Alignment Rel.	Area ID	(k)	(I) Effective	(m)	(n)	(o) G/T	(p) Min.	Input Attenu	uator (dB)
ID	Mode	(c) i can	(d) Edge	Error		Polar Iso-	Switch-	Equatorial		Input	Output	Max.	System	Max.	Saturation	(q) Max.	(r) Step
		(dBi)	(dBi)	(Degrees)	(Degrees)	lation (dB)		Plane (Degrees)		Losses	Power (W)	EIRP			Flux Density	Value	Size
							(Y/N)			(dB)		(dBW)	Temp (k)	(db/K)	(dBW/m2)		
KAR	R	45.5	41.5	0.12	0.12	30	N		NA				790	16.5	-105	20	1
KARL	R	45.5	41.5	0.12	0.12	30	N		NA				790	16.5	-105	20	1
KAT	Т	45.5	41.5	0.12	0.12	30	N		NA	2	78.9	64.5					
KATL	Т	45.5	41.5	0.12	0.12	30	N		NA	2	78.9	64.5					

FCC Form 312 - Schedule S: (Technical and Operational Description)

S8. ANTENNA BEAM DIAGRAMS For each beam pattern provide the reference to the graphic image and numerical data:
Also provide the power flux density levels in each beam that result from the emission with the highest power flux density.

(a)	(b)	(c) Co-or	· /	(e) NGSO Antenna Gain	\ /			lux Density (dB					
Beam	T/R	Cross	Ref.	Contour Description	ontour Description Gain Contour Data qure/Table/ Exhibit) GAT File)		At Angle of Arrival above horizontal (for emission with highest PFD)						
ID	Mode	Polar Mode ("C"	Orbital Longitude	(Figure/Table/ Exhibit)	(GXT FIIE)	(g) 5 Deg	(h) 10 Deg	(i) 15 Deg	(j) 20 Deg	(k) 25 Deg			
		or" X")	(Deg. E/W)										
KAR	R	С	-117		KARR.gxt								
KARL	R	С	-117		KARL.gxt								
KAT	Т	С	-117		KATR.gxt	-118	-118	-118	-118	-118			
KATL	T	С	-117		KATL.gxt	-118	-118	-118	-118	-118			

Page 5: Beam Diagrams

Page 6: Channels and Transponders

FCC Form 312 - Schedule S: (Technical and Operational Description)

S9. SPACE STATION CHANNELS For each frequency channel provide: S10. SPACE STATION TRANSPONDERS For each transponder provide:

(a) Channel	(B) Assigned Bandwidth	(c) T/R	(d) Center Frequency	(e) Polarization	(f) TTC or Comm
No.	(kHz)	Mode	(MHz)	(H, V, L, R)	Channel
					(T or C)
U001	115000	R	29312.5	L	С
U003	115000	R	29437.5	L	С
U005	115000	R	28412.5	L	С
U007	115000	R	28537.5	L	С
U009	115000	R	29562.5	L	С
U011	115000	R	29687.5	L	С
U013	115000	R	29812.5	L	С
U015	115000	R	29937.5	L	С
U002	115000	R	29312.5	R	С
U004	115000	R	29437.5	R	С
U006	115000	R	28412.5	R	С
U008	115000	R	28537.5	R	С
U010	115000	R	29562.5	R	С
U012	115000	R	29687.5	R	С
U014	115000	R	29812.5	R	С
U016	115000	R	29937.5	R	С
D0001	115000	Т	18362.5	R	С
D0003	115000	Т	18487.5	R	С
D0005	115000	Т	18612.5	R	С
D0007	115000	Т	18737.5	R	С
D0009	115000	Т	19762.5	R	С
D0011	115000	Т	19887.5	R	С
D0013	115000	Т	20012.5	R	С
D0015	115000	Т	20137.5	R	С
D0002	115000	Т	18362.5	L	С
D0004	115000	T	18487.5	L	С
D0006	115000	T	18612.5	L	С
D0008	115000	T	18737.5	L	С
D0010	115000	T	19762.5	L	С
D0012	115000	T	19887.5	L	С

(a)	(b)	Receive	Band	Transm	it Band
Transponder ID	Transponder Gain (dB)	(c) Channel No.	(d) Beam ID	(e) Channel No.	(f) Beam ID
T0001	129.5	U001	KARL	D0001	KATR
T0002	129.5	U003	KARL	D0003	KATR
T0003	129.5	U005	KARL	D0005	KATR
T0004	129.5	U007	KARL	D0007	KATR
T0005	129.5	U009	KARL	D0009	KATR
T0006	129.5	U011	KARL	D0011	KATR
T0007	129.5	U013	KARL	D0013	KATR
T0008	129.5	U015	KARL	D0015	KATR
T0009	129.5	U002	KARR	D0002	KATL
T0010	129.5	U004	KARR	D0004	KATL
T0011	129.5	U006	KARR	D0006	KATL
T0012	129.5	U008	KARR	D0008	KATL
T0013	129.5	U010	KARR	D0010	KATL
T0014	129.5	U012	KARR	D0012	KATL
T0015	129.5	U014	KARR	D0014	KATL
T0016	129.5	U016	KARR	D0016	KATL

D0014	115000	T	20012.5	L	С
D0016	115000	T	20137.5	L	С

Page 7: Digital Modulation

FCC Form 312 - Schedule S: (Technical and Operational Description)

S11. DIGITAL MODULATION PARAMETERS For each digital emission provide:

(a) Digital Mod. ID	(b) Emission Designator	(c) Assigned Bandwidth (kHz)	(d) No. of Phases	(e)Uncoded Data Rate (kbps)	(f) FEC Error Correction Coding Rate	(g) CDMA Processing Gain (dB)	(h) Total C/N Performance Objective (dB)	(i) Single Entry C/I Objective (dB)
D001	51K2G7W	51.2	4	56	0.691		8.4	20.6
D002	102KG7W	102	4	104	0.691		8.4	20.6
D003	500KG7W	500	4	512	0.691		8.4	20.6
D004	2M00G7W	2000	4	2048	0.691		8.4	20.6
D005	6M80G7W	6800	4	6968	0.691		8.4	20.6
D006	115MG7W	115000	4	117760	0.691		8.4	20.6

Page 8: Analog Modulation

FCC Form 312 - Schedule S: (Technical and Operational Description)

S12. ANALOG MODULATION PARAMETERS For each analog emission provide:

(a)	(b) Emission	(c)	(d) Signal	(e)	Multi-channel Telephony			(j) Video	(k) Video	(I) Video	(m) SCPC/FM	(n) Total C/N	(o) Single	
Analo Mod.		Assigned Bandwidth (kHz)	Туре	Channels per Carrier	(f) Ave. Companded Talker Level (dBm0)	(g) Bottom Baseband Freq. (MHz)		(i) RMS Modulation Index	Standard NTSC, PAL, etc.	- 3 - 3	and SCPC/FM Modulation Index	Compander, Preemphasis, and Noise Weighting (dB)	Performance Objective (dB)	Entry C/I Objective (dB)

Page 9: Typical Emissions

FCC Form 312 - Schedule S: (Technical and Operational Description)

S13. TYPICAL EMISSIONS For each planned type of emission provide:

Associated Modulation		lation ID	(e) Carriers	(f) Carrier	(g)Noise Budget	(h) Energy	Receive Band (Assoc. Transmit Stn)			Transmit Band (This Space Station)				
(a) Start	(b) Find (Table (Table S12) Transponder (kH	Spacing (kHz)	(kHz) No.) Bandw		Dispersal Bandwidth (kHz) (i)Assoc. Stn. Max.	Assoc. Station Transmit Power (dBW)		EIRP (dBW)		Power Flux	(o)Assoc. Stn			
(2) 2		511)	S11)				, ,	Antenna Gain (dBi)	(j) Min.	(k) Max.	(I) Min.	(m) Max.	Density (dBW/m2/Hz)	Rec. G/T (dB/K)
T0001	T0016	D001		1790	64	Ka1 LB.doc		43.9	-15.2	-11.2				16.5
T0001	T0016	D002		1000	125	Ka2 LB.doc		43.9	-8.2	-12.2				16.5
T0001	T0016	D003		200	575	Ka3 LB.doc		43.9	-6	-2				16.5
T0001	T0016	D004		50	2300	Ka4 LB.doc		43.9	0	4				16.5
T0001	T0016	D005		16	7187	Ka5 LB.doc		47.7	1.8	5.8				16.5
T0001	T0016	D006		1		Ka6 LB.doc					60.5	64.5	-118	17.5

FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS 242. School U.S. (Technical and Operational Decari

Page 10: TT and C

FCC Form 312 - Schedule S: (Technical and Operational Description)

S14. Is the space station(s) controlled and monitored remotely? If Yes, provide the location and telephone number of the TT and C control point(s): Yes

Remote Control (TT C) Location	n(s):			
S14a: Street Address: 530 Echostar Drive				
S14b. City: S14c. Count			S14d. State/Country	S14e. Zip Code:
Cheyenne	Laramie		WY	82007
S14f. Telephone Number:		S14g. Call Sign of Control Sta	ition (if appropriate):	•
(307) 633-5227				
Remote Control (TT C) Location	n(s):			
S14a: Street Address:				
801 North American Sky Boulav	vard			
S14b. City:	S14c. County:		S14d. State/Country	S14e. Zip Code:
Gilbert	Maricopa		AZ	85233
S14f. Telephone Number:	•	S14g. Call Sign of Control Sta	ation (if appropriate):	
(307) 633-5227				

Characteristics and Certifications FCC Form 312 - Schedule S: (Technical and Operational Description)

Page 11:

S15. SPACECRAFT PHYSICAL CHARACTERISTICS:

S15a: Mass of spacecraft without fuel (kg): 2400	Spacecraft Dimensions (meters)	Probability of Survival to End of Life (0.0 - 1.0)		
S15b. Mass of fuel and disposables at launch (kg): 3400				
S15c. Mass of spacecraft and fuel at launch (kg): 5800	S15f. Length (m): 55	S15i. Payload: 0.85		
S15d. Mass of fuel, in orbit, at beginning of life (kg): 1400	S15g. Width (m):	S15j. Bus: 0.83		
S15e. Deployed Area of Solar Array (square meters): 110	S15h. Height (m): 5	S15k. Total: 0.7055		

S16. SPACECRAFT ELECTRICAL CHARACTERISTICS:

Spacecraft Subsystem		ver (Watts) At ng of Life	Electrical Power (Watts End of Life				
	At Equinox	At Solstice	At Equinox	At Solstice			
Payload (Watts):	^{(a):} 14000	^{(f):} 14000	^{(k):} 14000	^{(p):} 14000			
Bus (Watts):	^{(b):} 1800	^{(g):} 925	^{(l):} 1800	^{(q):} 925			
Total (Watts):	^{(c):} 15800	^{(h):} 14925	^(m) 15800	^{(r):} 14925			
Solar Array (Watts):	^{(d):} 18200	^{(i):} 17400	^{(n):} 16300	^{(s):} 15500			
Depth of Battery Discharge (%):	^(e) 75 %	(j) %	^(o) 75 %	(t) %			

S17. CERTIFICATIONS:

a. Are the power flux density limits of § 25.208 met?:	X YE	S	NO	N/A				
b. Are the appropriate service area coverage requirements of § 25.143(b)(ii) and (iii), or § 25.145(c)(1) and (2) met?	YE	:S	NO	X N/A				
c. Are the frequency tolerances of § 25.202(e) and the out-of-band emission limits of § 25.202(f)(1), (2) and (3) met	? X YE	S	NO	N/A				
In addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the								

Commission's rules, 47 C.F.R § 25.114.