FCC 312 Schedule S

FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS (Technical and Operational Description)

Page 1: General, Frequency Bands, and GSO Orbit

S1. G	SENERAL	INFORMATION	Complete for	all satellite	applications
-------	---------	-------------	--------------	---------------	--------------

a. Space Station or Satellite Ne ECHOSTAR-117W	twork Name:	e. Estimated Date of Placement into Service:	i Will the space station(s) operate on a Common Carrier Basis: N
b. Construction Commencemer	nt Date:	f. Estimated Lifetime of Satellite(s): Years	j. Number of transponders offered on a common carrier basis:
c. Construction Completion Dat	de:	g. Total Number of Transponders:	k. Total Common Carrier Transponder Bandwidth: MHz
d1. Est Launch Date Begin:	d2. Est Launch Date End:	h. Total Transponder Bandwidth (no. transponders x Bandwidth) MHz	I. Orbit Type: Mark all boxes that apply: X GSO NGSO

S2. OPERATING FREQUENCY BANDS Identify the frequency range and transmit/receive mode for all frequency bands in which this station will oper Also indicate the nature of service(s) for each frequency band.

	Frequency	Band Limits						
Lower Frequence	cy (_Hz)	Upper Frequency	' (_Hz)	e. T/R Mode	f. Nature of Service(s): List all that apply to this band			
a. Numeric	b. Unit (K/M/G)	c. Numeric	d. Unit (K/M/G)		()			
14000.5	М	14001.5	М	R	Fixed Satellite Service			
14002.5	M	14003.5	М	R	Fixed Satellite Service			
11705	М	11706	М	Т	Fixed Satellite Service			
29998.5	М	29999.5	М	R	Fixed Satellite Service			
19700.5	М	19701.5	М	Т	Fixed Satellite Service			
20198.5	М	20199.5	М	Т	Fixed Satellite Service			
12197.5	М	12198.5	М	Т	Fixed Satellite Service			

S3. ORBITAL INFORMATION FOR GEOSTATIONARY SATELLITES ONLY:

a. Nominal Orbital Longitude (Degrees	E/W):	b. Alternate C	Orbital Longitu	ude (Degrees E/W):			c. Reason for orbital location selection:
117 W								
Longitudinal Tolerance or E/W	/ Station-		f. Inclination I		Range of orbital are in which	ch adequate serv	ice can be	
d. Toward West:	0.05	Degrees	N/S Station-h Tolerance:	Keeping	provided (Optional):	Degrees	E/W	
e. Toward East:	0.05	Degrees	0.05	Degrees	g. Westernmost: h. Easternmost:			
i. Reason for service are s	selection	(Optional)	•					

Page 2: NGSO Orbits

FCC Form 312 - Schedule S: (Technical and Operational Description)

S4. ORBITAL INFORMATION FOR NON-GEOSTATIONARY SATELLITES ONLY

S4a. Total Number of Satellites in Network or System:

S4c. Celestial Reference Body (Earth, Sun, Moon, etc.):

S4b. Total Number of Orbital Planes in Network or System: S4d. Orbit Epoch Date:

For each Orbital Plane Provide:

(e) Orbital	(f) No. of	(g) Inclination	(h) Orbital	(i) Apogee (km)	(j) Perigee (km)	(k) Right Ascension	(I) Argument of	Active Se	rvice Arc Rang	e (Degrees)
Plane No.	Satellites in	Angle (degrees)	Period			of the Ascending	Perigee	(m) Begin	(n) End	(o) Other
	Plane		(Seconds)			Node (Deg.)	(Degrees)	Angle	Ångle	. ,
			(=====)			(9-)	(5,000)	,g.o	gio	

S5. INITIAL SATELLITE PHASE ANGLE For each satellite in each orbital plane, provide the intital phase angle.

(a) Orbital Plane No.	(b) Satellite Number	(c) Initial Phase Angle
		(Degrees)

NO NGSO DATA FILED

FCC Form 312 - Schedule S: (Technical and Operational Description)

S6. SERVICE AREA CHARACTERISTICS for each service area provide:

(a) Service Area ID	(b) Type of Associated Station (Earth or Space)	(d) Service Area Description. Provide list of geographic areas (state postal codes or ITU 3-ltr codes), satellites or Figure No. of Service Area Diagram.
S	A1	S	Visible Earth

Page 3: Service Areas

Page 4: Antenna Beams

FCC Form 312 - Schedule S: (Technical and Operational Description)

S7. SPACE STATION ANTENNA BEAM CHARACTERISTICS For each antenna beam provide:

(a)	(b)	Isotropic	Antenna	(e)	(f)	(g) Min.	(h) Polar-	(i) Polarization	(j) Service		Transmit				Receive		
Beam	T/R	Ga	ain		Rotational	Cross-	ization	Alignment Rel.	Area ID	(k)	(I) Effective	(m)	(n)	(o) G/T	(p) Min.	Input Attenu	uator (dB)
ID	Mode	(c) i can	(d) Edge	Error		Polar Iso-	Switch-	Equatorial		Input	Output	Max.	System	Max.	Saturation	(q) Max.	(r) Step
		(dBi)	(dBi)	(Degrees)	(Degrees)	lation (dB)	able? (Y/N)	Plane (Degrees)		Losses	Power (W)	EIRP			Flux Density	Value	Size
							, ,			(dB)		(dBW)	Temp (k)	(db/K)	(dBW/m2)		
GBL	R	19.3	16.3	0.15		30	N		SA1				1000	-10.7	-90		
GBLL	T	19.3	16.3	0.15		30	N		SA1	3	2	22.3					
OMN	R	3	-0.5			30	N		SA1					-27	-80		
OMN	Т	3	-0.5			30	N		SA1	3	39.8	16					

Page 5: Beam Diagrams

FCC Form 312 - Schedule S: (Technical and Operational Description)

S8. ANTENNA BEAM DIAGRAMS For each beam pattern provide the reference to the graphic image and numerical data:

Also provide the power flux density levels in each beam that result from the emission with the highest power flux density.

(a)	(b)	(c) Co-or	(d) GSO	(e) NGSO Antenna Gain	(f) GSO Antenna		Max. Power F	lux Density (dB	W/M2/Hz)	
Beam	T/R	Cross	Ref.	Contour Description	Gain Contour Data	At Angle of	Arrival above ho	orizontal (for em	ission with high	hest PFD)
ID	Mode	Polar Mode ("C" or" X")	Orbital Longitude (Deg. E/W)	(Figure/Table/ Exhibit)	(GXT File)	(g) 5 Deg	(h) 10 Deg	(i) 15 Deg	(j) 20 Deg	(k) 25 Deg
GBL	R	С	-117		GBLR.gxt					
GBLL	Т	С	-117		GBLL.gxt	-152	-152	-152	-152	-152

Page 6: Channels and Transponders

FCC Form 312 - Schedule S: (Technical and Operational Description)

S9. SPACE STATION CHANNELS For each frequency channel provide: S10. SPACE STATION TRANSPONDERS For each transponder provide:

(a) Channel No.	(B) Assigned Bandwidth (kHz)	(c) T/R Mode	(d) Center Frequency (MHz)	(e) Polarization (H, V, L, R)	(f) TTC or Comm Channel (T or C)
C1	1000	R	14001	R	Τ
C2	1000	R	14003	R	T
C3	1000	R	29999	R	Т
TM1	1000	Т	11705.5	L	Т
TM2	1000	Т	12198	L	Т
TM3	1000	Т	19701	L	Τ
TM4	1000	T	20199	L	Т

(a)	(b)	Receive	Band	Transmi	t Band
Transponder ID	Transponder Gain (dB)	(c) Channel No.	(d) Beam ID	(e) Channel No.	(f) Beam ID
C001		C1	OMNU		
C002		C2	OMNU		
C003		C3	GBLR		
T001				TM1	OMND
T002				TM2	OMND
T003				TM3	GBLL
T004				TM4	GBLL

Page 7: Digital Modulation

FCC Form 312 - Schedule S: (Technical and Operational Description)

S11. DIGITAL MODULATION PARAMETERS For each digital emission provide:

ĺ	(a) Digital	(b) Emission	(c) Assigned	(d) No. of	(e)Uncoded	(f) FEC Error	(g) CDMA	(h) Total C/N	(i) Single Entry
	Mod. ID	Designator	Bandwidth	Phases	Data Rate	Correction	Processing	Performance	C/I Objective
ı			(kHz)		(kbps)	Coding Rate	Gain (dB)	Objective (dB)	(dB)
ı									

Page 8: Analog Modulation

FCC Form 312 - Schedule S: (Technical and Operational Description)

S12. ANALOG MODULATION PARAMETERS For each analog emission provide:

(a) (b) Emission (c) (d) Signal		(e)	Multi-channel Telephony			(j) Video	(k) Video	(I) Video	(m) SCPC/FM	` '	()			
	Mod. ID Ba	Assigned Bandwidth (kHz)	Туре	Channels per Carrier	Companded	(g) Bottom Baseband Freq. (MHz)	(h) Top Baseband Freq. (MHz)	(i) RMS Modulation Index	Standard NTSC, PAL, etc.		and SCPC/FM Modulation Index	Compander, Preemphasis, and Noise Weighting (dB)	Performance Objective (dB)	Entry C/I Objective (dB)
CMD1	1M00F2D	1000		1									10	22.2
TLM1	1M00G2D	1000		1									9	21.2
CMD2	1M00F2D	1000		1									10	22.2
TLM2	1M00G2D	1000		1									9	21.2

Page 9: Typical Emissions

FCC Form 312 - Schedule S: (Technical and Operational Description)

S13. TYPICAL EMISSIONS For each planned type of emission provide:

Associated Transponder ID Range (a) Start (b) End		Modulation ID		()	(f) Carrier	(g)Noise Budget	(h) Energy	Receive Band (Assoc. Transmit Stn)			Transmit Band (This Space Station)			tion)
		(c) Digital (Table	(d) Analog (Table S12)	per Transponder	Spacing (kHz)	Reference (Table No.)	Dispersal Bandwidth (kHz)	Stn. Max.	Assoc. Station Transmit Power (dBW)		EIRP (dBW)		Power Flux	(o)Assoc. Stn
(4) \$14.1		S11)					()	Antenna Gain (dBi)	(j) Min.	(k) Max.	(I) Min.	(m) Max.		Rec. G/T (dB/K)
C001	C002		CMD1	1		LB1.doc		63.9	19	39.4				-30.5
T001	T002		TLM1	1		LB2.doc					12.5	16	-170	38
C003	C003		CMD2	1		LB3.doc		65	8.3	23.3				-13.7
T003	T004		TLM2	1		LB4.doc					19.3	22.3	-152	37

Page 10: TT and C

FCC Form 312 - Schedule S: (Technical and Operational Description)

S14. Is the space station(s) controlled and monitored remotely? If Yes, provide the location and telephone number of the TT and C control point(s): Yes

Remote Control (TT C) Loca	ition(s):							
S14a: Street Address: 530 Echostar Drive								
S14b. City:	S14c. County:	S14d. State/Country	S14e. Zip Code:					
Cheyenne	Laramie	WY						
S14f. Telephone Number:	S14g. Call Sig	S14g. Call Sign of Control Station (if appropriate):						
Remote Control (TT C) Loca	ition(s):							
S14a: Street Address: 801 North American Sky Bo	ulavard							
S14b. City:	S14c. County:	S14d. State/Country	S14e. Zip Code:					
Gibert	Maricopa	AZ						
S14f. Telephone Number:	S14g. Call Sig	gn of Control Station (if appropriate):	<u> </u>					

FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS FCC Form 312 - Schedule S: (Technical and Operational Description)

Page 11: Characteristics and Certifications

S15. SPACECRAFT PHYSICAL CHARACTERISTICS:

S16. SPACECRAFT ELECTRICAL CHARACTERISTICS:

S17. CERTIFICATIONS:

a. Are the power flux density limits of § 25.208 met?:	X YES	NO	N/A				
b. Are the appropriate service area coverage requirements of § 25.143(b)(ii) and (iii), or § 25.145(c)(1) and (2) me	et? YES	NO	X N/A				
c. Are the frequency tolerances of § 25.202(e) and the out-of-band emission limits of § 25.202(f)(1), (2) and (3) m	et? X YES	NO	N/A				
In addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the							

In addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the Commission's rules, 47 C.F.R § 25.114.