FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS (Technical and Operational Description)

S1. GENERAL INFORMATION Complete for all satellite applications.

a. Space Station or Satellite Network Name: ECHOSTAR-97W	e. Estimated Date of Placement into Service:	i Will the space station(s) operate on a Common Carrier Basis: N
b. Construction Commencement Date:	f. Estimated Lifetime of Satellite(s): Years	j. Number of transponders offered on a common carrier basis:
c. Construction Completion Date:	g. Total Number of Transponders:	k. Total Common Carrier Transponder Bandwidth: MHz
d1. Est Launch Date Begin: d2. Est Launch Date End:	h. Total Transponder Bandwidth (no. transponders x Bandwidth) MHz	I. Orbit Type: Mark all boxes that apply:

S2. OPERATING FREQUENCY BANDS Identify the frequency range and transmit/receive mode for all frequency bands in which this station will oper Also indicate the nature of service(s) for each frequency band.

	Frequency	Band Limits			
Lower Frequency ((_Hz)	Upper Frequency (_Hz)	e. T/R Mode	f. Nature of Service(s): List all that apply to this band
a. Numeric	b. Unit (K/M/G)	c. Numeric	d. Unit (K/M/G)		
14000.5	Μ	14001.5	М	R	Fixed Satellite Service
14002.5	М	14003.5	М	R	Fixed Satellite Service
11705	М	11706	М	Т	Fixed Satellite Service
29998.5	М	29999.5	М	R	Fixed Satellite Service
19700.5	М	19701.5	М	Т	Fixed Satellite Service
20198.5	М	20199.5	М	Т	Fixed Satellite Service
12197.5	М	12198.5	М	Т	Fixed Satellite Service

S3. ORBITAL INFORMATION FOR GEOSTATIONARY SATELLITES ONLY:

a. Nominal Orbital Longitude (97 W	Degrees E/W):	b. Alternate Orbital Longitu	ude (Degrees E/W):			c. Reason for orbital location selection:
Longitudinal Tolerance or E/W d. Toward West: e. Toward East:	/ Station-Keeping: 0.05 Degrees 0.05 Degrees	f. Inclination Excursion or N/S Station-Keeping Tolerance: 0.05 Degrees	Range of orbital are in which provided (Optional): g. Westernmost: h. Easternmost:	n adequate serv <u>Degrees</u>	ice can be <u>E/W</u>	
i. Reason for service are s	election (Optional)	:				

Page 2: NGSO Orbits

S4. ORBITAL INFORMATION FOR NON-GEOSTATIONARY SATELLITES ONLY

S4a. Total Number of Satellites in Network or System:

S4b. Total Number of Orbital Planes in Network or System:

S4c. Celestial Reference Body (Earth, Sun, Moon, etc.):

S4d. Orbit Epoch Date:

For each Orbital Plane Provide:

ſ	(e) Orbital	(f) No. of	(g) Inclination	(h) Orbital	(i) Apogee (km)	(j) Perigee (km)	(k) Right Ascension	(I) Argument of	Active Se	rvice Arc Rang	e (Degrees)
	Plane No.	Satellites in	Angle (degrees)	Period			of the Ascending	Perigee	(m) Begin	(n) End	(o) Other
		Plane		(Seconds)			Node (Deg.)	(Degrees)	Angle	Angle	

S5. INITIAL SATELLITE PHASE ANGLE For each satellite in each orbital plane, provide the intital phase angle.

(a) Orbital	(b) Satellite	(c) Initial
Plane No.	Number	Phase Angle
		(Degrees)

NO NGSO DATA FILED

Page 3: Service Areas

S6. SERVICE AREA CHARACTERISTICS for each service area provide:

(a) Service Area ID	(b) Type of Associated Station (Earth or Space)	(d) Service Area Description. Provide list of geographic areas (state postal codes or ITU 3-ltr codes), satellites or Figure No. of Service Area Diagram.
SA1	S	Visible Earth

Page 4: Antenna Beams

S7. SPACE STATION ANTENNA BEAM CHARACTERISTICS For each antenna beam provide:

(a)	(b)	Isotropic	Antenna	(e)	(f)	(g) Min.	(h) Polar-	(i) Polarization	(j) Service		Transmit				Receive		
Beam	T/R		ain	0	Rotational	Cross-	ization	Alignment Rel.	Area ID	(k)	(I) Effective	(m)		(o) G/T	(p) Min.	Input Atten	uator (dB)
ID	Mode	(c) Peak (dBi)	(d) Edge (dBi)	Error (Degrees)	Error (Degrees)	Polar Iso- lation (dB)	Switch- able? (Y/N)	Equatorial Plane (Degrees)		Input Losses (dB)	Output Power (W)	Max. EIRP (dBW)	System Noice Temp (k)		Saturation Flux Density (dBW/m2)	(q) Max. Value	(r) Step Size
GBL	R	19.3	16.3	0.15		30	Ν		SA1				1000	-10.7	-90		
GBLL	Т	19.3	16.3	0.15		30	N		SA1	3	2	22.3					
OMN	R	3	-0.5			30	N		SA1					-27	-80		
OMN	Т	3	-0.5			30	Ν		SA1	3	39.8	16					

Page 5: Beam Diagrams

S8. ANTENNA BEAM DIAGRAMS For each beam pattern provide the reference to the graphic image and numerical data: Also provide the power flux density levels in each beam that result from the emission with the highest power flux density.

(a)	(b)	(c) Co-or	· · /	(e) NGSO Antenna Gain	(f) GSO Antenna			-lux Density (dB	1	
Beam	T/R	Cross	Ref.	Contour Description	Gain Contour Data	At Angle of	Arrival above ho	orizontal (for em	ission with hig	hest PFD)
ID	Mode	Polar Mode ("C"	Orbital Longitude	(Figure/Table/ Exhibit)	(GXT File)	(g) 5 Deg	(h) 10 Deg	(i) 15 Deg	(j) 20 Deg	(k) 25 Deg
			(Deg. E/W)							
GBL	R	С	-97		GBLR.gxt					
GBLL	Т	С	-97		GBLL.gxt	-128	-128	-128	-128	-128
GBL	R	С	-97		GBLR.gxt					
GBLL	Т	С	-97		GBLL.gxt	-128	-128	-128	-128	-128

Page 6: Channels and Transponders

(a) Channel No.	(B) Assigned Bandwidth (kHz)	(c) T/R Mode	(d) Center Frequency (MHz)	(e) Polarization (H, V, L, R)	(f) TTC or Comm Channel (T or C)
C1	1000	R	14001	R	Т
C2	1000	R	14003	R	Т
C3	1000	R	29999	R	Т
TM1	1000	Т	11705.5	L	Т
TM2	1000	Т	12198	L	Т
TM3	1000	Т	19701	L	Т
TM4	1000	Т	20199	L	Т

S9. SPACE STATION CHANNELS For each frequency channel provide: S10. SPACE STATION TRANSPONDERS For each transponder provide:

(a)	(b)	Receive	Band	Transm	it Band
Transponder ID	Transponder Gain (dB)	(c) Channel No.	(d) Beam ID	(e) Channel No.	(f) Beam ID
C001		C1	OMNU		
C002		C2	OMNU		
C003		C3	GBLR		
T001				TM1	OMND
T002				TM2	OMND
T003				TM3	GBLL
T004				TM4	GBLL

S11. DIGITAL MODULATION PARAMETERS For each digital emission provide:

ſ	(a) Digital Mod. ID	(b) Emission Designator	Bandwidth	(d) No. of Phases	Data Rate	(f) FEC Error Correction Coding Rate	Processing	(h) Total C/N Performance Objective (dB)	C/I Objective
			(kHz)		(kbps)	Coding Rate	Gain (dB)	Objective (dB)	(dB

Page 7: Digital Modulation

Page 8: Analog Modulation

S12. ANALOG MODULATION PARAMETERS For each analog emission provide:

(a)	(b) Emission	(c)	(d) Signal	(e)		Multi-channe	l Telephony		(j) Video	(k) Video	(I) Video	· · /	(n) Total C/N	()
Analog Mod. ID	Designator	Assigned Bandwidth (kHz)	Туре	Channels per Carrier	(f) Ave. Companded Talker Level (dBm0)	(g) Bottom Baseband Freq. (MHz)	(h) Top Baseband Freq. (MHz)	(i) RMS Modulation Index	Standard NTSC, PAL, etc.	Noise- Weighting (dB)	and SCPC/FM Modulation Index	Compander, Preemphasis, and Noise Weighting (dB)	Performance Objective (dB)	Entry C/I Objective (dB)
CMD1	1M00F2D	1000		1									10	22.2
TLM1	1M00G2D	1000		1									9	21.2
CMD2	1M00F2D	1000		1									10	22.2
TLM2	1M00G2D	1000		1									9	21.2

Page 9: Typical Emissions

S13. TYPICAL EMISSIONS For each planned type of emission provide:

Associated Transponder ID Range		Modulation ID		(e) Carriers (f) Carrier per Spacing Transponder (kHz)	(f) Carrier	ng Reference (Table	Bandwidth	Receive Band (Assoc. Transmit Stn)			Trai	nsmit Band	(This Space Stat	nis Space Station)	
					(i)Assoc. Stn. Max.			Assoc. Station Transmit Power (dBW)		EIRP (dBW)		(n) Max. Power Flux	(o)Assoc. Stn		
(a) Start	(b) End	S11)	(,				(kHz)	Antenna Gain (dBi)	(j) Min.	(k) Max.	(I) Min.	(m) Max.	Density (dBW/m2/Hz)	Rec. G/T (dB/K)	
C001	C002		CMD1	1		LB1.doc		63.9	19	39.4				-30.5	
T001	T002		TLM1	1		LB2.doc					12.5	16	-170	38	
C003	C003		CMD2	1		LB3.doc		65	8.3	23.3				-13.7	
T003	T004		TLM2	1		LB4.doc					19.3	22.3	-128	37	

Page 10: TT and C

S14. Is the space station(s) controlled and monitored remotely? If Yes, provide the location and telephone number of the TT and C control point(s): Yes

Remote Control (TT C) Location(s):

S14a: Street Address: 530 Echostar Drive				
S14b. City: Cheyenne	S14c. County: Laramie		S14d. State/Country WY	S14e. Zip Code:
S14f. Telephone Number:		S14g. Call Sign of Control S	tation (if appropriate):	
Remote Control (TT C) Location(s):				
S14a: Street Address: 801 North American Sky Boulavard				

S14b. City: Gibert	S14c. County: Maricopa		S14d. State/Country AZ	S14e. Zip Code:			
S14f. Telephone Number:		S14g. Call Sign of Control Station (if appropriate):					

Page 11: Characteristics and Certifications

S15. SPACECRAFT PHYSICAL CHARACTERISTICS:

S16. SPACECRAFT ELECTRICAL CHARACTERISTICS:

S17. CERTIFICATIONS:

a. Are the power flux density limits of § 25.208 met?:	X	YES		NO		N/A			
b. Are the appropriate service area coverage requirements of § 25.143(b)(ii) and (iii), or § 25.145(c)(1) and (2) m	et?	YES		NO	X	N/A			
c. Are the frequency tolerances of § 25.202(e) and the out-of-band emission limits of § 25.202(f)(1), (2) and (3) n	et? X	YES		NO		N/A			
In addition to the information required in this Form, the space station applicant is required to provide	all the in	formati	ion speci	ified in	Sectio	n 25.114 of the			
Commission's rules, 47 C.F.R § 25.114.									