FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS (Technical and Operational Description)

S1. GENERAL INFORMATION Complete for all satellite applications.

a. Space Station or Satellite Network Name: @CONTACT NGSO	e. Estimated Date of Placement into Service:	i Will the space station(s) operate on a Common Carrier Basis:			
b. Construction Commencement Date:	f. Estimated Lifetime of Satellite(s): Years	j. Number of transponders offered on a common carrier basis:			
c. Construction Completion Date:	g. Total Number of Transponders:	k. Total Common Carrier Transponder Bandwidth: MHz			
d1. Est Launch Date Begin: d2. Est Launch Date End:	h. Total Transponder Bandwidth (no. transponders x Bandwidth) MHz	I. Orbit Type: Mark all boxes that apply:			

S2. OPERATING FREQUENCY BANDS Identify the frequency range and transmit/receive mode for all frequency bands in which this station will oper Also indicate the nature of service(s) for each frequency band.

	Frequency	Band Limits			
Lower Frequency ((_Hz)	Upper Frequency (_Hz)	e. T/R Mode	f. Nature of Service(s): List all that apply to this band
a. Numeric	b. Unit (K/M/G)	c. Numeric	d. Unit (K/M/G)		
29.097	G	29.099	G	R	Telecommand
28.601	G	28.603	G	R	Telecommand
19.297	G	19.299	G	Т	Telemetry
18.801	G	18.803	G	Т	Telemetry

S3. ORBITAL INFORMATION FOR GEOSTATIONARY SATELLITES ONLY:

a. Nominal Orbital Longitude (Degrees E/W): 34 E	b. Alternate Orbital Longitude (Degrees E/W):	c. Reason for orbital location selection:
Longitudinal Tolerance or E/W Station-Keeping: d. Toward West: 0.05 Degrees e. Toward East: 0.05 Degrees	f. Inclination Excursion or N/S Station-Keeping Tolerance: Range of orbital are in which adequate service can be provided (Optional): Degrees E/W g. Westernmost: h. Easternmost:	
i. Reason for service are selection (Option	1):	

Page 2: NGSO Orbits

S4. ORBITAL INFORMATION FOR NON-GEOSTATIONARY SATELLITES ONLY

S4a. Total Number of Satellites in Network or System:

S4b. Total Number of Orbital Planes in Network or System:

S4c. Celestial Reference Body (Earth, Sun, Moon, etc.):

S4d. Orbit Epoch Date:

For each Orbital Plane Provide:

ſ	(e) Orbital	(f) No. of	(g) Inclination	(h) Orbital	(i) Apogee (km)	(j) Perigee (km)	(k) Right Ascension	(I) Argument of	Active Se	rvice Arc Rang	e (Degrees)
	Plane No.	Satellites in	Angle (degrees)	Period			of the Ascending	Perigee	(m) Begin	(n) End	(o) Other
		Plane		(Seconds)			Node (Deg.)	(Degrees)	Angle	Angle	

S5. INITIAL SATELLITE PHASE ANGLE For each satellite in each orbital plane, provide the intital phase angle.

(a) Orbital	(b) Satellite	(c) Initial
Plane No.	Number	Phase Angle
		(Degrees)

NO NGSO DATA FILED

Page 3: Service Areas

S6. SERVICE AREA CHARACTERISTICS for each service area provide:

(a) Service Area ID	(b) Type of Associated Station (Earth or Space)	(d) Service Area Description. Provide list of geographic areas (state postal codes or ITU 3-ltr codes), satellites or Figure No. of Service Area Diagram.
1	S	AAA

Page 4: Antenna Beams

S7. SPACE STATION ANTENNA BEAM CHARACTERISTICS For each antenna beam provide:

(a)	(b)	Isotropic	Antenna	(e)	(f)	(g) Min.	(h) Polar-	(i) Polarization	(j) Service		Transmit				Receive		
Beam	T/R		ain	_ 0	Rotational	Cross-		Alignment Rel.	Area ID	(k)	(I) Effective	(m)		(o) G/T	(p) Min.	Input Atten	uator (dB)
ID	Mode	(c) Peak (dBi)	(d) Edge (dBi)	Error (Degrees)	Error (Degrees)	Polar Iso- lation (dB)	Switch- able? (Y/N)	Equatorial Plane (Degrees)		Input Losses (dB)	Output Power (W)	Max. EIRP (dBW)	System Noice Temp (k)		Saturation Flux Density (dBW/m2)	(q) Max. Value	(r) Step Size
TLM	Т	48	45	0.05		30	N		1	2	0.25	42					
CMD	R	46.5	43.5	0.05		30	N		1				504	19.5	-116.2		
TLM	Т	-3	-3	0.05		30	N		1	3	1	-3					
CMD	R	-2	-2	0.05		30	Ν		1				1154	-32.6	-116.2		

S8. ANTENNA BEAM DIAGRAMS For each beam pattern provide the reference to the graphic image and numerical data: Also provide the power flux density levels in each beam that result from the emission with the highest power flux density.

(a)	(b)	(c) Co-or	(d) GSO	(e) NGSO Antenna Gain	(f) GSO Antenna		Max. Power F	lux Density (dB	W/M2/Hz)	
Beam	T/R	Cross	Ref.	Contour Description	Gain Contour Data	At Angle of A	Arrival above ho	orizontal (for em	ission with high	nest PFD)
ID	Mode	Polar Mode ("C" or" X")	Orbital Longitude (Deg. E/W)	(Figure/Table/ Exhibit)	(GXT File)	(g) 5 Deg	(h) 10 Deg	(i) 15 Deg	(j) 20 Deg	(k) 25 Deg
TLM	Т	С	130	GSO T C.pdf		-120	-119	-118	-118	-118
TLM	Т	Х	130	GSO T X.pdf						
CMD	R	С	130	GSO R C.pdf						
CMD	R	Х	130	GSO R X.pdf						
TLM	Т	С	130	OMNI.pdf						
TLM	Т	Х	130	OMNI.pdf						
CMD	R	С	130	OMNI.pdf						
CMD	R	Х	130	OMNI.pdf						

Page 5: Beam Diagrams

Page 6: Channels and Transponders

(a) Channel No.	(B) Assigned Bandwidth (kHz)	(c) T/R Mode	(d) Center Frequency (MHz)	(e) Polarization (H, V, L, R)	(f) TTC or Comm Channel (T or C)
SOS1	2000	R	29098	R	Т
SOS2	2000	R	28602	R	Т
SOS3	2000	Т	19298	L	Т
SOS4	2000	Т	18802	L	Т

(a) (b) Transponder ID Gain (dB) Receive Band Transmit Band (c) Channel (e) Channel (f) Beam ID (d) Beam No. ID No. SOS1 SOS1 CMD SOS2 SOS2 CMD SOS3 SOS3 TLM SOS4 SOS4 TLM TO1 SOS1 CMDO TO2 CMDO SOS2 TO3 SOS3 TLMO TO4 SOS4 TLMO

S9. SPACE STATION CHANNELS For each frequency channel provide: S10. SPACE STATION TRANSPONDERS For each transponder provide:

S11. DIGITAL MODULATION PARAMETERS For each digital emission provide:

(a) Digital Mod. ID	(b) Emission Designator	(c) Assigned Bandwidth (kHz)	(d) No. of Phases	(e)Uncoded Data Rate (kbps)	(f) FEC Error Correction Coding Rate	(g) CDMA Processing Gain (dB)	(h) Total C/N Performance Objective (dB)	(i) Single Entry C/I Objective (dB)
D1	2M00G7D	2000	2	1000	1		15	27
D2	1M00G7D	1000	2	500	1		15	27

Page 7: Digital Modulation

Page 8: Analog Modulation

S12. ANALOG MODULATION PARAMETERS For each analog emission provide:

(a)						Multi-channel Telephony				(k) Video	(I) Video	(m) SCPC/FM	· /	() 0
Analog Mod. ID	Designator	Assigned Bandwidth (kHz)	Туре	Channels per Carrier	(f) Ave. Companded Talker Level (dBm0)	(g) Bottom Baseband Freq. (MHz)	(h) Top Baseband Freq. (MHz)	(i) RMS Modulation Index	Standard NTSC, PAL, etc.	Noise- Weighting (dB)	and SCPC/FM Modulation Index	Compander, Preemphasis, and Noise Weighting (dB)	Performance Objective (dB)	Entry C/I Objective (dB)
A1	4K00F9D	4	FDM/FM	1									18	27

Page 9: Typical Emissions

S13. TYPICAL EMISSIONS For each planned type of emission provide:

	ciated		ulation ID	(e) Carriers	, , , , , , , , , , , , , , , , , , , ,	(0)	() 0)	Receive Band (Assoc. Transmit Stn)			Transmit Band (This Space Station)			
Transponder ID Range(a) Start(b) End		(c) Digital (d) Analog (Table (Table S12) S11)		per Transponder	Spacing (kHz)	Reference (Table No.)	Dispersal Bandwidth (kHz)	(i)Assoc. Stn. Max.	Assoc. Statio Power		EIRP	(dBW)	(n) Max. Power Flux	(o)Assoc. Stn
. ,		511)					()	Antenna Gain (dBi)	(j) Min.	(k) Max.	(I) Min.	(m) Max.	Density (dBW/m2/Hz)	Rec. G/T (dB/K)
SOS1	SOS2	D2						59	17	17	77	77		
SOS3	SOS4	D1						55.5			42	42		28.9
TO1	TO2		A1					68.9	21.1	21.1	90	90		
TO3	TO4		A1					65.3			-3	-3		39.7

Page 10: TT and C

S14. Is the space station(s) controlled and monitored remotely? If Yes, provide the location and telephone number of the TT and C control point(s): #Error

Page 11: Characteristics and Certifications

S15. SPACECRAFT PHYSICAL CHARACTERISTICS:

S16. SPACECRAFT ELECTRICAL CHARACTERISTICS:

S17. CERTIFICATIONS:

a. Are the power flux density limits of § 25.208 met?:	YES	# NO	# N/A
b. Are the appropriate service area coverage requirements of § 25.143(b)(ii) and (iii), or § 25.145(c)(1) and (2	2) met? YES	# NO	# N/A
c. Are the frequency tolerances of § 25.202(e) and the out-of-band emission limits of § 25.202(f)(1), (2) and ((3) met? YES	# NO	# N/A
In addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the			
Commission's rules, 47 C.F.R § 25.114.			