

**FEDERAL COMMUNICATIONS COMMISSION**  
**SATELLITE SPACE STATION AUTHORIZATIONS**  
**(Technical and Operational Description)**

**S1. GENERAL INFORMATION** Complete for all satellite applications.

a. Space Station or Satellite Network Name: @CONTACT NGSO		e. Estimated Date of Placement into Service:	i. Will the space station(s) operate on a Common Carrier Basis:
b. Construction Commencement Date:		f. Estimated Lifetime of Satellite(s): Years	j. Number of transponders offered on a common carrier basis:
c. Construction Completion Date:		g. Total Number of Transponders:	k. Total Common Carrier Transponder Bandwidth: MHz
d1. Est Launch Date Begin:	d2. Est Launch Date End:	h. Total Transponder Bandwidth (no. transponders x Bandwidth) MHz	i. Orbit Type: Mark all boxes that apply: <input checked="" type="checkbox"/> <b>GSO</b> <input type="checkbox"/> <b>NGSO</b>

**S2. OPERATING FREQUENCY BANDS** Identify the frequency range and transmit/receive mode for all frequency bands in which this station will oper  
Also indicate the nature of service(s) for each frequency band.

Frequency Band Limits				e. T/R Mode	f. Nature of Service(s): List all that apply to this band
Lower Frequency (.Hz)		Upper Frequency (.Hz)			
a. Numeric	b. Unit (K/M/G)	c. Numeric	d. Unit (K/M/G)		
29.097	G	29.099	G	R	Telecommand
28.601	G	28.603	G	R	Telecommand
19.297	G	19.299	G	T	Telemetry
18.801	G	18.803	G	T	Telemetry

**S3. ORBITAL INFORMATION FOR GEOSTATIONARY SATELLITES ONLY:**

a. Nominal Orbital Longitude (Degrees E/W): 83 W		b. Alternate Orbital Longitude (Degrees E/W):		c. Reason for orbital location selection:
Longitudinal Tolerance or E/W Station-Keeping:		f. Inclination Excursion or N/S Station-Keeping Tolerance:	Range of orbital are in which adequate service can be provided (Optional): Degrees      E/W	
d. Toward West:	0.05 Degrees	0.05 Degrees	g. Westernmost:	
e. Toward East:	0.05 Degrees		h. Easternmost:	
i. Reason for service are selection (Optional):				

**FEDERAL COMMUNICATIONS COMMISSION  
SATELLITE SPACE STATION AUTHORIZATIONS  
FCC Form 312 - Schedule S: (Technical and Operational Description)**

**Page 2: NGSO Orbits**

**S4. ORBITAL INFORMATION FOR NON-GEOSTATIONARY SATELLITES ONLY**

S4a. Total Number of Satellites in Network or System:

S4c. Celestial Reference Body (Earth, Sun, Moon, etc.):

S4b. Total Number of Orbital Planes in Network or System:

S4d. Orbit Epoch Date:

For each Orbital Plane Provide:

(e) Orbital Plane No.	(f) No. of Satellites in Plane	(g) Inclination Angle (degrees)	(h) Orbital Period (Seconds)	(i) Apogee (km)	(j) Perigee (km)	(k) Right Ascension of the Ascending Node (Deg.)	(l) Argument of Perigee (Degrees)	Active Service Arc Range (Degrees)		
								(m) Begin Angle	(n) End Angle	(o) Other

**S5. INITIAL SATELLITE PHASE ANGLE** For each satellite in each orbital plane, provide the initial phase angle.

(a) Orbital Plane No.	(b) Satellite Number	(c) Initial Phase Angle (Degrees)
--------------------------	-------------------------	---

**NO NGSO DATA FILED**

**FEDERAL COMMUNICATIONS COMMISSION  
SATELLITE SPACE STATION AUTHORIZATIONS  
FCC Form 312 - Schedule S: (Technical and Operational Description)**

**Page 3: Service Areas**

S6. SERVICE AREA CHARACTERISTICS for each service area provide:

(a) Service Area ID	(b) Type of Associated Station (Earth or Space)	(c) Service Area Diagram File Name (GXT File)	(d) Service Area Description. Provide list of geographic areas (state postal codes or ITU 3-ltr codes), satellites or Figure No. of Service Area Diagram.
1	S		AAA

**FEDERAL COMMUNICATIONS COMMISSION**  
**SATELLITE SPACE STATION AUTHORIZATIONS**  
**FCC Form 312 - Schedule S: (Technical and Operational Description)**

Page 4: Antenna Beams

S7. SPACE STATION ANTENNA BEAM CHARACTERISTICS For each antenna beam provide:

(a) Beam ID	(b) T/R Mode	Isotropic Antenna Gain		(e) Pointing Error (Degrees)	(f) Rotational Error (Degrees)	(g) Min. Cross- Polar Iso- lation (dB)	(h) Polar- ization Switch- able? (Y/N)	(i) Polarization Alignment Rel. Equatorial Plane (Degrees)	(j) Service Area ID	Transmit			Receive			Input Attenuator (dB)	
		(c) Peak (dBi)	(d) Edge (dBi)							(k) Input Losses (dB)	(l) Effective Output Power (W)	(m) Max. EIRP (dBW)	(n) System Noise Temp (K)	(o) G/T Max. Gain Pt. (dB/K)	(p) Min. Saturation Flux Density (dBW/m2)	(q) Max. Value	(r) Step Size
TLM	T	48	45	0.05		30	N		1	2	0.25	42					
CMD	R	46.5	43.5	0.05		30	N		1				504	19.5	-116.2		
TLM	T	-3	-3	0.05		30	N		1	3	1	-3					
CMD	R	-2	-2	0.05		30	N		1				1154	-32.6	-116.2		

**FEDERAL COMMUNICATIONS COMMISSION  
SATELLITE SPACE STATION AUTHORIZATIONS  
FCC Form 312 - Schedule S: (Technical and Operational Description)**

**Page 5: Beam Diagrams**

**S8. ANTENNA BEAM DIAGRAMS** For each beam pattern provide the reference to the graphic image and numerical data:  
Also provide the power flux density levels in each beam that result from the emission with the highest power flux density.

(a) Beam ID	(b) T/R Mode	(c) Co-or Cross Polar Mode ("C" or" X")	(d) GSO Ref. Orbital Longitude (Deg. E/W)	(e) NGSO Antenna Gain Contour Description (Figure/Table/ Exhibit)	(f) GSO Antenna Gain Contour Data (GXT File)	Max. Power Flux Density (dBW/M2/Hz)				
						At Angle of Arrival above horizontal (for emission with highest PFD)				
						(g) 5 Deg	(h) 10 Deg	(i) 15 Deg	(j) 20 Deg	(k) 25 Deg
TLM	T	C	130	GSO T C.pdf		-120	-119	-118	-118	-118
TLM	T	X	130	GSO T X.pdf						
CMD	R	C	130	GSO R C.pdf						
CMD	R	X	130	GSO R X.pdf						
TLM	T	C	130	OMNI.pdf						
TLM	T	X	130	OMNI.pdf						
CMD	R	C	130	OMNI.pdf						
CMD	R	X	130	OMNI.pdf						

**FEDERAL COMMUNICATIONS COMMISSION**  
**SATELLITE SPACE STATION AUTHORIZATIONS**  
**FCC Form 312 - Schedule S: (Technical and Operational Description)**

**Page 6: Channels and Transponders**

S9. SPACE STATION CHANNELS For each frequency channel provide: S10. SPACE STATION TRANSPONDERS For each transponder provide:

(a) Channel No.	(B) Assigned Bandwidth (kHz)	(c) T/R Mode	(d) Center Frequency (MHz)	(e) Polarization (H, V, L, R)	(f) TTC or Comm Channel (T or C)
SOS1	2000	R	29098	R	T
SOS2	2000	R	28602	R	T
SOS3	2000	T	19298	L	T
SOS4	2000	T	18802	L	T

(a) Transponder ID	(b) Transponder Gain (dB)	Receive Band		Transmit Band	
		(c) Channel No.	(d) Beam ID	(e) Channel No.	(f) Beam ID
SOS1		SOS1	CMD		
SOS2		SOS2	CMD		
SOS3				SOS3	TLM
SOS4				SOS4	TLM
TO1		SOS1	CMDO		
TO2		SOS2	CMDO		
TO3				SOS3	TLMO
TO4				SOS4	TLMO

**FEDERAL COMMUNICATIONS COMMISSION**  
**SATELLITE SPACE STATION AUTHORIZATIONS**  
**FCC Form 312 - Schedule S: (Technical and Operational Description)**

Page 7: Digital Modulation

S11. DIGITAL MODULATION PARAMETERS For each digital emission provide:

(a) Digital Mod. ID	(b) Emission Designator	(c) Assigned Bandwidth (kHz)	(d) No. of Phases	(e) Uncoded Data Rate (kbps)	(f) FEC Error Correction Coding Rate	(g) CDMA Processing Gain (dB)	(h) Total C/N Performance Objective (dB)	(i) Single Entry C/I Objective (dB)
D1	2M00G7D	2000	2	1000	1		15	27
D2	1M00G7D	1000	2	500	1		15	27

## Page 8: Analog Modulation

[illegible]



**FEDERAL COMMUNICATIONS COMMISSION**  
**SATELLITE SPACE STATION AUTHORIZATIONS**  
**FCC Form 312 - Schedule S: (Technical and Operational Description)**

**Page 9: Typical Emissions**

S13. TYPICAL EMISSIONS For each planned type of emission provide:

Associated Transponder ID Range		Modulation ID		(e) Carriers per Transponder	(f) Carrier Spacing (kHz)	(g) Noise Budget Reference (Table No.)	(h) Energy Dispersal Bandwidth (kHz)	Receive Band (Assoc. Transmit Stn)			Transmit Band (This Space Station)			
		(c) Digital (Table S11)	(d) Analog (Table S12)					(i) Assoc. Stn. Max. Antenna Gain (dBi)	Assoc. Station Transmit Power (dBW)		EIRP (dBW)		(n) Max. Power Flux Density (dBW/m2/Hz)	(o) Assoc. Stn Rec. G/T (dB/K)
(a) Start	(b) End								(j) Min.	(k) Max.	(l) Min.	(m) Max.		
SOS1	SOS2	D2						59	17	17	77	77		
SOS3	SOS4	D1						55.5			42	42		28.9
TO1	TO2		A1					68.9	21.1	21.1	90	90		
TO3	TO4		A1					65.3			-3	-3		39.7

**FEDERAL COMMUNICATIONS COMMISSION  
SATELLITE SPACE STATION AUTHORIZATIONS  
FCC Form 312 - Schedule S: (Technical and Operational Description)**

**Page 10: TT and C**

S14. Is the space station(s) controlled and monitored remotely? If Yes, provide the location and telephone number of the TT and C control point(s): #Error

**FEDERAL COMMUNICATIONS COMMISSION  
SATELLITE SPACE STATION AUTHORIZATIONS  
FCC Form 312 - Schedule S: (Technical and Operational Description)**

**Page 11:  
Characteristics and  
Certifications**

S15. SPACECRAFT PHYSICAL CHARACTERISTICS:

S16. SPACECRAFT ELECTRICAL CHARACTERISTICS:

S17. CERTIFICATIONS:

a. Are the power flux density limits of § 25.208 met?:	<input type="checkbox"/>	YES	<input type="checkbox"/>	#	NO	<input type="checkbox"/>	#	N/A
b. Are the appropriate service area coverage requirements of § 25.143(b)(ii) and (iii), or § 25.145(c)(1) and (2) met?	<input type="checkbox"/>	YES	<input type="checkbox"/>	#	NO	<input type="checkbox"/>	#	N/A
c. Are the frequency tolerances of § 25.202(e) and the out-of-band emission limits of § 25.202(f)(1), (2) and (3) met?	<input type="checkbox"/>	YES	<input type="checkbox"/>	#	NO	<input type="checkbox"/>	#	N/A
<b>In addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the Commission's rules, 47 C.F.R. § 25.114.</b>								