FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS (Technical and Operational Description)

S1. GENERAL INFORMATION Complete for all satellite applications.

a. Space Station or Satellite Network Name: ORBCOMM USCGDEMO +QL	e. Estimated Date of Placement in	nto Service: N N	isis:
b. Construction Commencement Date:	f. Estimated Lifetime of Satellite(s 5): j. Number of transponders offered on a common carrier bas Years	sis:
c. Construction Completion Date:	g. Total Number of Transponders 3	: k. Total Common Carrier Transponder Bandwidth: MHz	
d1. Est Launch Date Begin: d2. Est Launch Dat	End: h. Total Transponder Bandwidth (5.05	no. transponders x Bandwidth) MHz I. Orbit Type: Mark all boxes that apply: GSO X NGSO	

S2. OPERATING FREQUENCY BANDS Identify the frequency range and transmit/receive mode for all frequency bands in which this station will oper Also indicate the nature of service(s) for each frequency band.

	Frequency	Band Limits			
Lower Frequency	(_Hz)	Upper Frequency	(_Hz)	e. T/R Mode	f. Nature of Service(s): List all that apply to this band
a. Numeric	b. Unit (K/M/G)	c. Numeric	d. Unit (K/M/G)		
137.025	М	137.175	Μ	Т	NVNG MSS
137.000	М	137.025	М	Т	NVNG MSS (Non-voice, non-geostationary mobile satellite service)
137.175	М	137.825	М	Т	NVNG MSS
137.825	М	138.000	М	Т	NVNG MSS
148.000	М	149.900	М	R	NVNG MSS
149.900	М	150.050	М	R	NVNG MSS
161.000	М	161.575	М	R	AIS (USCG Automatic Identification System)
161.575	М	161.625	М	R	AIS
161.625	М	161.775	М	R	AIS
161.775	М	162.0125	М	R	AIS
162.0125	М	163.000	М	R	AIS

S3. ORBITAL INFORMATION FOR GEOSTATIONARY SATELLITES ONLY:

S4. ORBITAL INFORMATION FOR NON-GEOSTATIONARY SATELLITES ONLY

S4a. Total Number of Satellites in Network or System:

S4b. Total Number of Orbital Planes in Network or System:

S4c. Celestial Reference Body (Earth, Sun, Moon, etc.): E

12/31/2007

S4d. Orbit Epoch Date:

For each Orbital Plane Provide:

(e) Orbital Plane No.	(f) No. of Satellites in Plane	(g) Inclination Angle (degrees)	()	(i) Apogee (km)	(j) Perigee (km)	(k) Right Ascension of the Ascending Node (Deg.)	(I) Argument of Perigee (Degrees)	Active Ser (m) Begin Angle	vice Arc Range (n) End Angle	e (Degrees) (o) Other
1	7	48.5	5989	750	750	47	0	0	360	

7

1

S5. INITIAL SATELLITE PHASE ANGLE For each satellite in each orbital plane, provide the intital phase angle.

(a) Orbital Plane No.	(b) Satellite Number	(c) Initial Phase Angle (Degrees)
1	1	0
1	2	51
1	3	102
1	4	153
1	5	204
1	6	255
1	7	306

Page 3: Service Areas

S6. SERVICE AREA CHARACTERISTICS for each service area provide:

(a) Service Area ID	(b) Type of Associated Station (Earth or Space)	(d) Service Area Description. Provide list of geographic areas (state postal codes or ITU 3-ltr codes), satellites or Figure No. of Service Area Diagram.
A	S	Global Coverage

Page 4: Antenna Beams

S7. SPACE STATION ANTENNA BEAM CHARACTERISTICS For each antenna beam provide:

(a)	(b)	Isotropic	Antenna	(e)	(f)	(g) Min.	(h) Polar-	(i) Polarization	(j) Service		Transmit		Receive				
Beam	T/R		ain	_ 0	Rotational	Cross-	ization	Alignment Rel.	Area ID	(k)	(I) Effective	(m)		(o) G/T		Input Atten	uator (dB)
ID	Mode	(c) Peak		Error	Error	Polar Iso- lation (dB)	Switch- able?	Equatorial Plane (Degrees)		Input	Output	Max.	System	Max.	Saturation	(q) Max.	(r) Step
		(dBi)	(dBi)	(Degrees)	(Degrees)		(Y/N)	Fiane (Degrees)		Losses (dB)	Power (W)	EIRP (dBW)	Noice Temp (k)		Flux Density (dBW/m2)	Value	Size
							()			(ub)		(ubw)	Temp (R)	(00/10)	(ubw/mz)		
VHF-	Т	0	-5.2	0	0	18.8	Ν		A	1	22.4	13.5					
VHF-	R	1.5	-9.2	0	0	18.8	Ν		A				680	-26.8			
AIS-	R	0.4	-0.1	0	0	18.8	N		A				680	-27.9			

Page 5: Beam Diagrams

S8. ANTENNA BEAM DIAGRAMS For each beam pattern provide the reference to the graphic image and numerical data: Also provide the power flux density levels in each beam that result from the emission with the highest power flux density.

(a)	(b)	(c) Co-or	(d) GSO	(e) NGSO Antenna Gain	(f) GSO Antenna		Max. Power F	Iux Density (dB	W/M2/Hz)		
Beam	T/R	Cross	Ref.	Contour Description		Gain Contour Data	At Angle of	Arrival above ho	orizontal (for em	ission with hig	hest PFD)
ID	Mode	Polar Mode ("C" or" X")	Orbital Longitude (Deg. E/W)	(Figure/Table/ Exhibit)	(GXT File)	(g) 5 Deg	(h) 10 Deg	(i) 15 Deg	(j) 20 Deg	(k) 25 Deg	
VHF-	Т	С		Attachment A		-126.92	-126.77	-126.52	-126.29	-125.88	
VHF-	R	С		Attachment A							
AIS-	R	С		Attachment A							

Page 6: Channels and Transponders

				1 ,	•
(a) Channel No.	(B) Assigned Bandwidth (kHz)	(c) T/R Mode	(d) Center Frequency (MHz)	(e) Polarization (H, V, L, R)	(f) TTC or Comm Channel (T or C)
VF-T	1000	Т	137.5	R	С
VF-R	2050	R	149.025	R	С
AS-R	2000	R	162	R	С

S9. SPACE STATION CHANNELS For each frequency channel provide: S10. SPACE STATION TRANSPONDERS For each transponder provide:

(a)	(b)	Receive	Band	Transmit Band			
Transponder ID	Transponder Gain (dB)	(c) Channel No.	(d) Beam ID	(e) Channel No.	(f) Beam ID		
V-R		VF-R	VHF-R				
A-R		AS-R	AIS-R				
V-T				VF-T	VHF-T		

S11. DIGITAL MODULATION PARAMETERS For each digital emission provide:

(a) Digital Mod. ID	(b) Emission Designator	(c) Assigned Bandwidth (kHz)	(d) No. of Phases	(e)Uncoded Data Rate (kbps)	(f) FEC Error Correction Coding Rate	(g) CDMA Processing Gain (dB)	(h) Total C/N Performance Objective (dB)	(i) Single Entry C/I Objective (dB)
1	6K72G1D	15	2	4.8			12.3	24.5
3	40K3G1D	50	4	57.6			15.6	27.8
5	10K0F1D	25	2	9.6			15.5	27.7
6	3K36G1D	5	2	2.4			12.3	24.5

Page 7: Digital Modulation

Page 8: Analog Modulation

S12. ANALOG MODULATION PARAMETERS For each analog emission provide:

(a)	(b) Emission	(c)	(d) Signal	(e)	Multi-channe	l Telephony		(j) Video	(k) Video	(I) Video	· · /	(n) Total C/N	() 0
Analog Mod. ID	Designator	Assigned Bandwidth (kHz)	Туре	Channels per Carrier	(g) Bottom Baseband Freq. (MHz)	(h) Top Baseband Freq. (MHz)	(i) RMS Modulation Index	Standard NTSC, PAL, etc.	Noise- Weighting (dB)	and SCPC/FM Modulation Index	Compander, Preemphasis, and Noise Weighting (dB)	Performance Objective (dB)	Entry C/I Objective (dB)

Page 9: Typical Emissions

S13. TYPICAL EMISSIONS For each planned type of emission provide:

	ciated		lation ID	(e) Carriers	.,	(h) Energy	Receive Ba	and (Assoc. Tr	ansmit Stn)	Tra	nsmit Band	(This Space Station)		
Transponder ID Range (a) Start (b) End		(C) Digital (Table	(d) Analog (Table S12)	per Transponder	Spacing (kHz)	Reference (Table No.)	Dispersal Bandwidth (kHz)	(i)Assoc. Stn. Max.	Assoc. Station Transmit Power (dBW)		EIRP	(dBW)	(n) Max. (Power Flux	(o)Assoc. Stn
(a) Start	(0) End	S11)					(KHZ)	Antenna Gain (dBi)	(j) Min.	(k) Max.	(I) Min.	(m) Max.	Density (dBW/m2/Hz)	Rec. G/T (dB/K)
V-T	V-T	1		1		Attach 1					8.3	13.5	-125.8	-32.7
V-T	V-T	3		1		Attach 1					-3.9	1.3	-145.8	-12.6
V-R	V-R	6		13	5	Attach 1		0	7	7				
V-R	V-R	3		1		Attach 1		0	32.7	32.7				
A-R	A-R	5		2	25	Attach 1		0	10.8	10.8				

Page 10: TT and C

S14. Is the space station(s) controlled and monitored remotely? If Yes, provide the location and telephone number of the TT and C control point(s): Yes

Remote Control (TT C) Location(s):

S14a: Street Address: 21700 Atlantic Boulevard						
S14b. City: Dulles	S14c. County: Loudoun		S14d. State/Country VA	S14e. Zip Code: 20166		
S14f. Telephone Number: 703-433-6300	S14g. Call Sign of Control		Control Station (if appropriate):	Station (if appropriate):		
Remote Control (TT C) Locati	on(s):					
S14a: Street Address: 1527 Bray Road						
S14b. City: Arcade	S14c. County: Wyoming		S14d. State/Country NY	S14e. Zip Code: 14009		
		S14g. Call Sign of C E940535	all Sign of Control Station (if appropriate): 535			
Remote Control (TT C) Locati	on(s):					
S14a: Street Address: RT #2 Box 401						
S14b. City: Ocilla	S14c. County: Irwin		S14d. State/Country GA	S14e. Zip Code: 31774		
S14f. Telephone Number:	I	S14g. Call Sign of C E940536	Control Station (if appropriate):			

Remote Control (TT C) Location(s):

S14a: Street Address: State Road 61				
S14b. City: St. Johns	S14c. County: Apache		S14d. State/Country AZ	S14e. Zip Code: 85936
S14f. Telephone Number:		S14g. Call Sign of Control Stat E940537	tion (if appropriate):	

Remote Control (TT C) Location(s):			
S14a: Street Address: 1011 Bager Mountain Rd.				
S14b. City: East Wenatchee	S14c. County: Douglas	S14d. State/Country WA	S14e. Zip Code: 98801	
S14f. Telephone Number:		S14g. Call Sign of Control Station (if appropriate): E940537		

Page 11: Characteristics and Certifications

S15. SPACECRAFT PHYSICAL CHARACTERISTICS:

S15a: Mass of spacecraft without fuel (kg):	Spacecraft Dimensions	Probability of Survival to
110	(meters)	End of Life (0.0 - 1.0)
S15b. Mass of fuel and disposables at launch (kg): 5		
S15c. Mass of spacecraft and fuel at launch (kg):	S15f. Length (m):	S15i. Payload:
115	0.6	0.95
S15d. Mass of fuel, in orbit, at beginning of life (kg):	S15g. Width (m):	S15j. Bus:
5	1.6	0.6
S15e. Deployed Area of Solar Array (square meters):	S15h. Height (m):	S15k. Total:
2	5	0.57

S16. SPACECRAFT ELECTRICAL CHARACTERISTICS:

Spacecraft Subsystem	Electrical Power (Watts) At Beginning of Life		Electrical Power (Watts) At End of Life		
	At Equinox	At Solstice	At Equinox	At Solstice	
Payload (Watts):	^{(a):} 115	^{(f):} 115	^{(k):} 115	^{(p):} 115	
Bus (Watts):	^{(b):} 35	^{(g):} 35	^{(I):} 35	^{(q):} 35	
Total (Watts):	^{(c):} 150	^{(h):} 150	^(m) 150	^{(r):} 150	
Solar Array (Watts):	^{(d):} 400	^{(i):} 358	^{(n):} 368	^{(s):} 330	
Depth of Battery Discharge (%):	^(e) 20 %	^(j) 20 %	⁽⁰⁾ 20 %	^(t) 20 %	

S17. CERTIFICATIONS:

a. Are the power flux density limits of § 25.208 met?:	YES	NO	X N/A		
b. Are the appropriate service area coverage requirements of § 25.143(b)(ii) and (iii), or § 25.145(c)(1) and (2) r	met? YES	NO	X N/A		
c. Are the frequency tolerances of § 25.202(e) and the out-of-band emission limits of § 25.202(f)(1), (2) and (3)	met? X YES	NO	N/A		
In addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the Commission's rules, 47 C.F.R § 25.114.					
Commission 5 Tules, 47 C.F.N. § 25, 114.					