

Representative Return Link Budget

UT Type Carrier Type	Unit	Personal Accessory FDMA
General Parameters		
Gateway elevation angle	deg	42.0
Minimum user elevation angle	deg	20.0
Uplink frequency	GHz	2.020
Downlink frequency	GHz	19.700
Bandwidth/carrier	kHz	8.0
Uplink		
Uplink EIRP	dBW	6.0
Free space loss	dB	190.5
Atmospheric loss	dB	0.1
Uplink propagation margin	dB	16.1
Satellite receive antenna gain (-3 dB contour)	dBi	42.3
Satellite receive system noise temperature	dB-K	27.3
Satellite receive antenna G/T	dB/K	15.0
Uplink C/N _o	dBHz	42.9
Uplink C/I _o Intra-system	dBHz	48.2
Uplink C/I _o External Interference	dBHz	52.9
Downlink		
Satellite EIRP (peak)	dBW	22.1
Free space loss	dB	209.8
Atmospheric loss	dB	0.4
Rain attenuation	dB	10.0
E/S antenna gain	dB	66.5
E/S antenna pointing error	dB	0.3
Nominal system noise temperature	dB-K	23.9
Nominal E/S G/T	dB/K	42.3
System noise temperature degradation in rain	dB	3.1
Rain-degraded system noise temperature	dB-K	27.0
Rain-degraded E/S G/T	dB/K	39.2
Downlink C/No	dBHz	69.4
Downlink C/IM _o	dBHz	64.1
Downlink C/I _o Intra-system	dBHz	60.5
Downlink C/I _o ASI	dBHz	79.3
End-to-End Performance		
End-to-end C/N _o	dBHz	42.9
End-to-end aggregate C/I _o	dBHz	46.7
End-to-end C/IM _o	dBHz	64.1
Total aggregate C/(N _o +I _o +IM _o)	dBHz	41.4
Total aggregate C/(N+I+IM)	dB	2.3
Required C/N	dB	2.3
System Margin	dB	0.0