

Return Link Budget GEN1 AFixed

Return Link: 1.6 GHz up/7 GHz down				
	Inner	Outer		
Uplink Analysis				Units
Frequency	1.6	1.6		GHz
EIRP per user	-12.0	-9.8		dBW
Altitude	1414	1414		km
User elevation angle	70	25		deg
Slant Range	1486	2528		km
Path loss	-160.0	-164.7		dB
Polarization & Tracking loss	-1	-1		dB
S/C Rx Signal Strength	-173.0	-175.5		dB
Satellite antenna gain	13.09	17.78		dBi
Line loss	-2.00	-2.00		dB
User signal at transponder	-161.9	-159.7		dBW
System noise temperature	396.64	396.64		K
Thermal noise density, No	-202.6	-202.6		dBW/Hz
Average user data rate	2400	2400		bps
Uplink Eb/(No)	6.9	9.1		dB
Interference per channel	-142.2	-138.3		dBW
Spreading bandwidth	1.23	1.23		MHz
Interference density, Io	-203.1	-199.2		dBW/Hz
Uplink Eb/(No+Io)	4.1	4.1		dB
Nominal transponder gain	127.4	127.4		dB
Downlink Analysis				
Frequency	6.98	6.98		GHz
TX power per user	-30.4	-28.1		dBW
Transmit line loss	-2.2	-2.2		dB
Satellite antenna gain	7.10	7.10		dBi
EIRP per user	-25.4	-23.2		dBW
GW elevation angle	40	40		deg
Range	1969	1969		km
Free space loss (40 deg GW elev)	-175.2	-175.2		dB
Polarization & tracking loss	-0.1	-0.1		dB
Pointing loss	-1.0	-1.0		dB
RX signal/user/satellite	-201.7	-199.5		dBW
GW antenna gain (incl. line losses)	49.5	49.5		dBi
RX signal at antenna output/user/satellite	-152.2	-150.0		dBW
System noise temperature	127.7	127.7		K
Thermal noise density, No	-207.5	-207.5		dBW/Hz
Interference per channel	-151.40	-151.40		dBW
Spreading bandwidth	1.23	1.23		MHz
1/(10*LOG(spreading bandwidth))	-60.9	-60.9		dB/Hz
Interference Density, Io	-212.3	-212.3		dBW/Hz
Downlink Eb/(No+Io)	20.2	22.5		dB
Coherent Combining gain	1.8	1.8		dB
Overall (up&down) Eb/(No+Io)	5.8	5.8		dB
Required Eb/No w/ power control margin	5.8	5.8		dB
Available margin for propagation effects	16	16		dB