

**FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
(Technical and Operational Description)**

S1. GENERAL INFORMATION Complete for all satellite applications.

a. Space Station or Satellite Network Name: GLOBALSTAR		e. Estimated Date of Placement into Service:		i. Will the space station(s) operate on a Common Carrier Basis: N	
b. Construction Commencement Date:		f. Estimated Lifetime of Satellite(s): 15 Years		j. Number of transponders offered on a common carrier basis:	
c. Construction Completion Date:		g. Total Number of Transponders: 16		k. Total Common Carrier Transponder Bandwidth: MHz	
d1. Est Launch Date Begin: 9/1/2009	d2. Est Launch Date End:	h. Total Transponder Bandwidth (no. transponders x Bandwidth) 16.5 MHz		i. Orbit Type: Mark all boxes that apply: <input type="checkbox"/> GSO <input checked="" type="checkbox"/> NGSO	

S2. OPERATING FREQUENCY BANDS Identify the frequency range and transmit/receive mode for all frequency bands in which this station will oper
Also indicate the nature of service(s) for each frequency band.

Frequency Band Limits				e. T/R Mode	f. Nature of Service(s): List all that apply to this band
Lower Frequency (.Hz)		Upper Frequency (.Hz)			
a. Numeric	b. Unit (K/M/G)	c. Numeric	d. Unit (K/M/G)		
1610	M	1626.5	M	R	Mobile-Satellite Service
2483.5	M	2500	M	T	Mobile-Satellite Service
5091	M	5250	M	R	Feeder Link for Mobile Satellite Service in FSS
6875	M	7055	M	T	Feeder Link for Mobile Satellite Service in FSS

S3. ORBITAL INFORMATION FOR GEOSTATIONARY SATELLITES ONLY:

FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)

S4. ORBITAL INFORMATION FOR NON-GEOSTATIONARY SATELLITES ONLY

S4a. Total Number of Satellites in Network or System: 48 S4c. Celestial Reference Body (Earth, Sun, Moon, etc.): E
 S4b. Total Number of Orbital Planes in Network or System: 8 S4d. Orbit Epoch Date: 12/31/2008

For each Orbital Plane Provide:

(e) Orbital Plane No.	(f) No. of Satellites in Plane	(g) Inclination Angle (degrees)	(h) Orbital Period (Seconds)	(i) Apogee (km)	(j) Perigee (km)	(k) Right Ascension of the Ascending Node (Deg.)	(l) Argument of Perigee (Degrees)	Active Service Arc Range (Degrees)		
								(m) Begin Angle	(n) End Angle	(o) Other
1	6	52	6840	1414	1414	0	90	0	360	
2	6	52	6840	1414	1414	0	90	0	360	
3	6	52	6840	1414	1414	0	90	0	360	
4	6	52	6840	1414	1414	0	90	0	360	
5	6	52	6840	1414	1414	0	90	0	360	
6	6	52	6840	1414	1414	0	90	0	360	
7	6	52	6840	1414	1414	0	90	0	360	
8	6	52	6840	1414	1414	0	90	0	360	

S5. INITIAL SATELLITE PHASE ANGLE For each satellite in each orbital plane, provide the initial phase angle.

(a) Orbital Plane No.	(b) Satellite Number	(c) Initial Phase Angle (Degrees)
1	1	0
1	2	60
1	3	120
1	4	180
1	5	240
1	6	300
2	1	7.5
2	2	67.5
2	3	127.5
2	4	187.5
2	5	247.5
2	6	307.5
3	1	15
3	2	75

3	3	135
3	4	195
3	5	255
3	6	315
4	1	22.5
4	2	82.5
4	3	142.5
4	4	202.5
4	5	262.5
4	6	322.5
5	1	30
5	2	90
5	3	150
5	4	210
5	5	270
5	6	330
6	1	37.5
6	2	97.5
6	3	157.5
6	4	217.5
6	5	277.5
6	6	337.5
7	1	45
7	2	105
7	3	165
7	4	225
7	5	285
7	6	345
8	1	52.5
8	2	112.5
8	3	172.5
8	4	232.5
8	5	292.5
8	6	352.5
7		

**FEDERAL COMMUNICATIONS COMMISSION
 SATELLITE SPACE STATION AUTHORIZATIONS
 FCC Form 312 - Schedule S: (Technical and Operational Description)**

S6. SERVICE AREA CHARACTERISTICS for each service area provide:

(a) Service Area ID	(b) Type of Associated Station (Earth or Space)	(c) Service Area Diagram File Name (GXT File)	(d) Service Area Description. Provide list of geographic areas (state postal codes or ITU 3-ltr codes), satellites or Figure No. of Service Area Diagram.
1	S		Global Coverage between 73N and 73S latitudes

FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)

S7. SPACE STATION ANTENNA BEAM CHARACTERISTICS For each antenna beam provide:

(a) Beam ID	(b) T/R Mode	(e) Isotropic Antenna Gain		(e) Pointing Error (Degrees)	(f) Rotational Error (Degrees)	(g) Min. Cross- Polar Isolation (dB)	(h) Polar- ization Switch- able? (Y/N)	(i) Polarization Alignment Rel. Equatorial Plane (Degrees)	(j) Service Area ID	Transmit			Receive			Input Attenuator (dB)	
		(c) Peak (dBi)	(d) Edge (dBi)							(k) Input Losses (dB)	(l) Effective Output Power (W)	(m) Max. EIRP (dBW)	(n) System Noise Temp (k)	(o) G/T Max. Gain Pt. (db/K)	(p) Min. Saturation Flux Density (dBW/m2)	(q) Max. Value	(r) Step Size
L-16	R	19.09	12.25	0.3		11.6	N		1				397	-6.89			
S-1	T	16.6	12.6	0.3		11	N		1	2.1	74	33.2					
S-2	T	17	13.5	0.3		11	N		1	2.1	74	33.6					
S-3	T	17	13.5	0.3		11	N		1	2.1	74	33.6					
S-4	T	17	13.5	0.3		11	N		1	2.1	74	33.6					
S-5	T	17	13.5	0.3		11	N		1	2.1	74	33.6					
S-6	T	17	13.5	0.3		11	N		1	2.1	74	33.6					
S-7	T	17	13.5	0.3		11	N		1	2.1	74	33.6					
S-8	T	18.9	11.2	0.3		11	N		1	2.1	74	35.5					
S-9	T	18.9	11.2	0.3		11	N		1	2.1	74	35.5					
S-10	T	18.9	11.2	0.3		11	N		1	2.1	74	35.5					
S-11	T	19	11.2	0.3		11	N		1	2.1	74	35.6					
S-12	T	18.9	11.2	0.3		11	N		1	2.1	74	35.5					
S-13	T	18.9	11.2	0.3		11	N		1	2.1	74	35.5					
S-14	T	18.9	11.2	0.3		11	N		1	2.1	74	35.5					
S-15	T	18.9	11.2	0.3		11	N		1	2.1	74	35.5					
S-16	T	18.9	11.2	0.3		11	N		1	2.1	74	35.5					
C-1	R	6.85	2.83	0.3		14.5	N		1				550	-20.55			
C-2	T	6.8	4.3	0.3		12.8	N		1	2.2	18.4	17.3					
L-1	R	13.89	10.52	0.3		11.6	N		1				397	-12.09			
L-2	R	18.91	13.83	0.3		11.6	N		1				397	-7.07			
L-3	R	19.09	12.25	0.3		11.6	N		1				397	-6.89			
L-4	R	18.75	12.9	0.3		11.6	N		1				397	-7.23			
L-5	R	18.95	13.12	0.3		11.6	N		1				397	-7.03			
L-6	R	19.04	13.14	0.3		11.6	N		1				397	-6.94			
L-7	R	18.82	13.16	0.3		11.6	N		1				397	-7.16			
L-8	R	18.89	12.51	0.3		11.6	N		1				397	-7.09			
L-9	R	19	12.6	0.3		11.6	N		1				397	-6.98			
L-10	R	19	12.6	0.3		11.6	N		1				397	-6.98			

L-11	R	18.88	12.51	0.3		11.6	N		1				397	-7.1			
L-12	R	18.82	13.16	0.3		11.6	N		1				397	-7.16			
L-13	R	19.04	13.14	0.3		11.6	N		1				397	-6.94			
L-14	R	18.95	13.12	0.3		11.6	N		1				397	-7.03			
L-15	R	18.75	12.9	0.3		11.6	N		1				397	-7.23			

**FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)**

S8. ANTENNA BEAM DIAGRAMS For each beam pattern provide the reference to the graphic image and numerical data:
Also provide the power flux density levels in each beam that result from the emission with the highest power flux density.

(a) Beam ID	(b) T/R Mode	(c) Co-or Cross Polar Mode ("C" or" X")	(d) GSO Ref. Orbital Longitude (Deg. E/W)	(e) NGSO Antenna Gain Contour Description (Figure/Table/ Exhibit)	(f) GSO Antenna Gain Contour Data (GXT File)	Max. Power Flux Density (dBW/M2/Hz)				
						At Angle of Arrival above horizontal (for emission with highest PFD)				
						(g) 5 Deg	(h) 10 Deg	(i) 15 Deg	(j) 20 Deg	(k) 25 Deg
S-1	T			Exhibit 2		-126	-122.75	-119.5	-116.25	-113
S-2	T			Exhibit 2		-126	-122.75	-119.5	-116.25	-113
S-3	T			Exhibit 2		-126	-122.75	-119.5	-116.25	-113
S-4	T			Exhibit 2		-126	-122.75	-119.5	-116.25	-113
S-5	T			Exhibit 2		-126	-122.75	-119.5	-116.25	-113
S-6	T			Exhibit 2		-126	-122.75	-119.5	-116.25	-113
S-7	T			Exhibit 2		-126	-122.75	-119.5	-116.25	-113
S-8	T			Exhibit 2		-126	-122.75	-119.5	-116.25	-113
S-8	T			Exhibit 2		-126	-122.75	-119.5	-116.25	-113
S-9	T			Exhibit 2		-126	-122.75	-119.5	-116.25	-113
S-10	T			Exhibit 2		-126	-122.75	-119.5	-116.25	-113
S-11	T			Exhibit 2		-126	-122.75	-119.5	-116.25	-113
S-12	T			Exhibit 2		-126	-122.75	-119.5	-116.25	-113
S-13	T			Exhibit 2		-126	-122.75	-119.5	-116.25	-113
S-14	T			Exhibit 2		-126	-122.75	-119.5	-116.25	-113
S-15	T			Exhibit 2		-126	-122.75	-119.5	-116.25	-113
S-16	T			Exhibit 2		-126	-122.75	-119.5	-116.25	-113
C-2	T			Exhibit 3		-134	-131.5	-129	-126.5	-124
L-1	R			Exhibit 1						
L-2	R			Exhibit 1						
L-3	R			Exhibit 1						
L-4	R			Exhibit 1						
L-5	R			Exhibit 1						
L-6	R			Exhibit 1						
L-7	R			Exhibit 1						
L-8	R			Exhibit 1						
L-9	R			Exhibit 1						
L-10	R			Exhibit 1						

L-11	R			Exhibit 1						
L-12	R			Exhibit 1						
L-13	R			Exhibit 1						
L-14	R			Exhibit 1						
L-15	R			Exhibit 1						
L-16	R			Exhibit 1						
C-1	R			Exhibit 3						

**FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)**

S9. SPACE STATION CHANNELS For each frequency channel provide: S10. SPACE STATION TRANSPONDERS For each transponder provide:

(a) Channel No.	(B) Assigned Bandwidth (kHz)	(c) T/R Mode	(d) Center Frequency (MHz)	(e) Polarization (H, V, L, R)	(f) TTC or Comm Channel (T or C)
1	16500	R	1618.25	L	C
2	16500	T	2491.75	L	C
3	1000	R	5091.50	L	T
X1-S	16500	R	5105.21	L	C
Y1-S	16500	R	5105.21	R	C
X2-S	16500	R	5124.59	L	C
Y2-S	16500	R	5124.59	R	C
X3-S	16500	R	5143.97	L	C
Y3-S	16500	R	5143.97	R	C
X4-S	16500	R	5163.35	L	C
Y4-S	16500	R	5163.35	R	C
X5-S	16500	R	5182.73	L	C
Y5-S	16500	R	5182.73	R	C
X6-S	16500	R	5201.11	L	C
Y6-S	16500	R	5201.11	R	C
X7-S	16500	R	5221.49	L	C
Y7-S	16500	R	5221.49	R	C
X8-S	16500	R	5240.87	L	C
Y8-S	16500	R	5240.87	R	C
4	3200	T	6877.50	L	T
X1-L	16500	T	6908.99	L	C
Y1-L	16500	T	6908.99	R	C
X2-L	16500	T	6928.37	L	C
Y2-L	16500	T	6928.37	R	C
X3-L	16500	T	6947.75	L	C
Y3-L	16500	T	6947.75	R	C
X4-L	16500	T	6967.13	L	C
Y4-L	16500	T	6967.13	R	C
X5-L	16500	T	6986.51	L	C
Y5-L	16500	T	6986.51	R	C

(a) Transponder ID	(b) Transponder Gain (dB)	Receive Band		Transmit Band	
		(c) Channel No.	(d) Beam ID	(e) Channel No.	(f) Beam ID
X1-S	122.7	X1-S	C-1	2	S-12
Y1-S	122.7	Y1-S	C-1	2	S-9
X2-S	122.7	X2-S	C-1	2	S-14
Y2-S	122.7	Y2-S	C-1	2	S-11
X3-S	122.7	X3-S	C-1	2	S-16
X4-S	122.7	X4-S	C-1	2	S-10
Y4-S	122.7	Y4-S	C-1	2	S-15
X5-S	122.7	X5-S	C-1	2	S-1
Y5-S	122.7	Y5-S	C-1	2	S-8
X6-S	122.7	X6-S	C-1	2	S-6
Y6-S	122.7	Y6-S	C-1	2	S-3
Y3-S	122.7	Y3-S	C-1	2	S-13
X7-S	122.7	X7-S	C-1	2	S-4
Y7-S	122.7	Y7-S	C-1	2	S-7
X8-S	122.7	X8-S	C-1	2	S-2
Y8-S	122.7	Y8-S	C-1	2	S-5
X1-L	127.4	1	L-8	X1-L	C-2
Y1-L	127.4	1	L-3	Y1-L	C-2
X2-L	127.4	1	L-10	X2-L	C-2
Y2-L	127.4	1	L-15	Y2-L	C-2
X3-L	127.4	1	L-4	X3-L	C-2
Y3-L	127.4	1	L-13	Y3-L	C-2
X4-L	127.4	1	L-6	X4-L	C-2
Y4-L	127.4	1	L-11	Y4-L	C-2
X5-L	127.4	1	L-1	X5-L	C-2
Y5-L	127.4	1	L-5	Y5-L	C-2
X6-L	127.4	1	L-14	X6-L	C-2
Y6-L	127.4	1	L-9	Y6-L	C-2
X7-L	127.4	1	L-2	X7-L	C-2
Y7-L	127.4	1	L-7	Y7-L	C-2

X6-L	16500	T	7005.89	L	C
Y6-L	16500	T	7005.89	R	C
X7-L	16500	T	7025.27	L	C
Y7-L	16500	T	7025.27	R	C
X8-L	16500	T	7044.65	L	C
Y8-L	16500	T	7044.65	R	C

X8-L	127.4	1	L-12	X8-L	C-2
Y8-L	127.4	1	L-16	Y8-L	C-2

FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)

S11. DIGITAL MODULATION PARAMETERS For each digital emission provide:

(a) Digital Mod. ID	(b) Emission Designator	(c) Assigned Bandwidth (kHz)	(d) No. of Phases	(e) Uncoded Data Rate (kbps)	(f) FEC Error Correction Coding Rate	(g) CDMA Processing Gain (dB)	(h) Total C/N Performance Objective (dB)	(i) Single Entry C/I Objective (dB)
1	1M23G7W	1230	4	1230				
2	1M23G2W	1230	4	1230				
3	2M46G7W	2460	4	2460				
4	2M46G2W	2460	4	2460				
5	2M50G2D	2500	4	100				
6	1M23XXX	1230	4	1230				
7	NON	50	1					

FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)

S13. TYPICAL EMISSIONS For each planned type of emission provide:

Associated Transponder ID Range		Modulation ID		(e) Carriers per Transponder	(f) Carrier Spacing (kHz)	(g) Noise Budget Reference (Table No.)	(h) Energy Dispersal Bandwidth (kHz)	Receive Band (Assoc. Transmit Stn)			Transmit Band (This Space Station)			
		(c) Digital (Table S11)	(d) Analog (Table S12)					(i) Assoc. Stn. Max. Antenna Gain (dBi)	Assoc. Station Transmit Power (dBW)		EIRP (dBW)		(n) Max. Power Flux Density (dBW/m ² /Hz)	(o) Assoc. Stn Rec. G/T (dB/K)
(a) Start	(b) End							(j) Min.	(k) Max.	(l) Min.	(m) Max.			
X1-S	Y8-S	1		13	1230	FWD Link Budg		47.6	-20	20.4		68	-113	-28
X1-L	Y8-L	1		13	1230	RTN Link Budg		3	-20	-2		1	-131.5	27.5
X1-S	Y8-S	1		13	1230	FWD Link Budg		47.6	-20	20.4		68	-113	-28
X1-L	Y8-L	1		13	1230	RTN Link Budg		7		1		8	-131.5	27.5
X1-S	Y8-S	1		13	1230	FWD Link Budg		47.6		20.4		68	-113	-28
X1-L	Y8-L	1		13	1230	RTN Link Budg		4		-4		0	-131.5	27.5
X1-S	Y8-S	3		6	2460	FWD Link Budg		47.6		20.4		68	-113	-28
X1-L	Y8-L	3		6	2460	RTN Link Budg		4		-4		0	-131.5	27.5
X1-S	Y8-S	1		13	1230	FWD Link Budg		47.6		20.4		68	-113	-28
X1-L	Y8-L	1		13	1230	RTN Link Budg		4		-4		0	-131.5	27.5
X1-S	Y8-S	3		6	2460	FWD Link Budg		47.6		20.4		68	-113	-28
X1-L	Y8-L	3		6	2460	RTN Link Budg		4		-4		0	-131.5	27.5
X1-S	Y8-S	1		13	1230	FWD Link Budg		47.6		20.4		68	-113	-28
X1-L	Y8-L	1		13	1230	RTN Link Budg		7		1		8	-131.5	27.5
X1-S	Y8-S	3		6	2460	FWD Link Budg		47.6		20.4		68	-113	-28
X1-L	Y8-L	3		6	2460	RTN Link Budg		7		1		8	-131.5	27.5

**FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)**

S14. Is the space station(s) controlled and monitored remotely? If Yes, provide the location and telephone number of the TT and C control point(s): Yes

Remote Control (TT C) Location(s):

S14a: Street Address: Globalstar USA - Clifton TT&C			
S14b. City: Clifton	S14c. County: Bosque	S14d. State/Country TX	S14e. Zip Code: 76634-5084
S14f. Telephone Number: 254-675-4385		S14g. Call Sign of Control Station (if appropriate): E970199	

Remote Control (TT C) Location(s):

S14a: Street Address: Globalstar Monitor & Control Center #2			
S14b. City: El Dorado Hills	S14c. County: El Dorado	S14d. State/Country CA	S14e. Zip Code: 95762-5703
S14f. Telephone Number: 916-605-5414		S14g. Call Sign of Control Station (if appropriate):	

Remote Control (TT C) Location(s):

S14a: Street Address: Globalstar Monitor & Control Center #1			
S14b. City: Milpitas	S14c. County: Santa Clara	S14d. State/Country CA	S14e. Zip Code: 95035-5438
S14f. Telephone Number: 408-933-4600		S14g. Call Sign of Control Station (if appropriate):	

**FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)**

Page 11:
Characteristics and
Certifications

S15. SPACECRAFT PHYSICAL CHARACTERISTICS:

S15a. Mass of spacecraft without fuel (kg): 554.6	Spacecraft Dimensions (meters)	Probability of Survival to End of Life (0.0 - 1.0)
S15b. Mass of fuel and disposables at launch (kg): 160.4		
S15c. Mass of spacecraft and fuel at launch (kg): 715	S15f. Length (m): 3	S15i. Payload: 0.899
S15d. Mass of fuel, in orbit, at beginning of life (kg): 155.97	S15g. Width (m): 2	S15j. Bus: 0.836
S15e. Deployed Area of Solar Array (square meters): 5.19	S15h. Height (m): 1.3	S15k. Total: 0.752

S16. SPACECRAFT ELECTRICAL CHARACTERISTICS:

Spacecraft Subsystem	Electrical Power (Watts) At Beginning of Life		Electrical Power (Watts) At End of Life	
	At Equinox	At Solstice	At Equinox	At Solstice
Payload (Watts):	(a): 1548	(f): 1548	(k): 1538	(p): 1538
Bus (Watts):	(b): 199	(g): 199	(l): 198	(q): 198
Total (Watts):	(c): 1747	(h): 1747	(m): 1736	(r): 1736
Solar Array (Watts):	(d): 2480	(i): 2480	(n): 1660	(s): 1660
Depth of Battery Discharge (%):	(e) 20 %	(j) 20 %	(o) 20 %	(t) 20 %

S17. CERTIFICATIONS:

a. Are the power flux density limits of § 25.208 met?	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO	<input type="checkbox"/> N/A
b. Are the appropriate service area coverage requirements of § 25.143(b)(ii) and (iii), or § 25.145(c)(1) and (2) met?	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO	<input type="checkbox"/> N/A
c. Are the frequency tolerances of § 25.202(e) and the out-of-band emission limits of § 25.202(f)(1), (2) and (3) met?	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO	<input type="checkbox"/> N/A

In addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the Commission's rules, 47 C.F.R § 25.114.