FCC 312	
Schedule	S

FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS (Technical and Operational Description)

Page 1: General, Frequency Bands, and GSO Orbit

S1. GENERAL INFORMATION Complete for all satellite application	S1.	GENERAL	INFORMATION	Complete for a	all satellite	application
--	-----	---------	-------------	----------------	---------------	-------------

a. Space Station or Satellite No USASAT 30A (S2129)	etwork Name:	e. Estimated Date of Placement into Service:		i Will the space station(s) operate on a Common Carrier Basis: N			
b. Construction Commenceme	nt Date:	f. Estimated Lifetime of Satellite(s): 12					
c. Construction Completion Da	te:	g. Total Number of Transponders:		k. Total Common Carrier Transponder Bandwidth:			
		0		0	MHz		
d1. Est Launch Date Begin:	d2. Est Launch Date End:	h. Total Transponder Bandwidth (no. transponde	,	I. Orbit Type: Mark all boxes that apply:			
		0	MHz	GSO X N	IGSO		

S2. OPERATING FREQUENCY BANDS Identify the frequency range and transmit/receive mode for all frequency bands in which this station will oper Also indicate the nature of service(s) for each frequency band.

Frequency Band Limits					f.
Lower Frequency (Lower Frequency (_Hz) Upper Frequency (_Hz)		e. T/R Mode	Nature of Service(s): List all that apply to this band	
a. Numeric	b. Unit (K/M/G)	c. Numeric	d. Unit (K/M/G)		.,,,,
8025	M	8345	M	Т	Earth Exploration Satellite Service

S3. ORBITAL INFORMATION FOR GEOSTATIONARY SATELLITES ONLY:

Page 2: NGSO Orbits

FCC Form 312 - Schedule S: (Technical and Operational Description)

S4. ORBITAL INFORMATION FOR NON-GEOSTATIONARY SATELLITES ONLY

S4a. Total Number of Satellites in Network or System:

1 S4c. Celestial Reference Body (Earth, Sun, Moon, etc.): E

S4b. Total Number of Orbital Planes in Network or System: 1 S4d. Orbit Epoch Date: 10/1/2010

For each Orbital Plane Provide:

(e) Orbital Plane No.	(f) No. of Satellites in Plane	(g) Inclination Angle (degrees)	(/	(i) Apogee (km)	(j) Perigee (km)	(k) Right Ascension of the Ascending Node (Deg.)	(I) Argument of Perigee (Degrees)		rvice Arc Range (n) End Angle	
1	1	97.39	5664	498	481	344.8	90	0	360	

S5. INITIAL SATELLITE PHASE ANGLE For each satellite in each orbital plane, provide the intital phase angle.

(a) Orbital Plane No.	(b) Satellite Number	(c) Initial Phase Angle (Degrees)
1	1	0

FCC Form 312 - Schedule S: (Technical and Operational Description)

S6. SERVICE AREA CHARACTERISTICS for each service area provide:

(a) Service Area	(b) Type of Associated Station (Earth or Space)	(d) Service Area Description. Provide list of geographic areas (state postal codes or ITU 3-ltr codes), satellites or Figure No. of Service Area Diagram.
NA	S	NA

Page 3: Service Areas

Page 4: Antenna Beams

FCC Form 312 - Schedule S: (Technical and Operational Description)

S7. SPACE STATION ANTENNA BEAM CHARACTERISTICS For each antenna beam provide:

(a)	(b)	Isotropic	Antenna	(e)	(f)	(g) Min.	(h) Polar-	(i) Polarization	(j) Service		Transmit				Receive		
Beam	T/R	Ga			Rotational		ization	Alignment Rel.	Area ID	(k) Input	(I) Effective	(m)	(n)	(o) G/T	(p) Min.	Input Attent	uator (dB)
ID	Mode	(c) Peak	(d) Edge	Error	-	Polar Iso-	Switch-	Equatorial		Losses	Output	Max.	System	Max.	Saturation	(q) Max.	(r) Step
		(dBi)	(dBi)	(Degrees)	(Degrees)	lation (dB)		Plane (Degrees)		(dB)	Power (W)	EIRP			Flux Density	Value	Size
							(Y/N)					(dBW)	Temp (k)	(db/K)	(dBW/m2)	7 4.40	0.20
ST3	Т	6	-10	0	0	15	N			8.1	0.8	4.9					
ST4	Т	24.7	23.7	1	0	15	N			3.55	2.65	29					
CMD	R	3	-10	0	0		N						795	-26	-94.9		

FCC Form 312 - Schedule S: (Technical and Operational Description)

S8. ANTENNA BEAM DIAGRAMS For each beam pattern provide the reference to the graphic image and numerical data:

Also provide the power flux density levels in each beam that result from the emission with the highest power flux density.

(a)	(b)	(c) Co-or	(d) GSO	(e) NGSO Antenna Gain	(f) GSO Antenna		Max. Power F	Flux Density (dB	W/M2/Hz)	
Beam	T/R	Cross	Ref.	Contour Description	Gain Contour Data	7 K 7 K gio of 7 K T Car above Tienzer Kar (10) of Tieneelen Titter Ingliet				hest PFD)
ID	Mode	Polar Mode ("C"	Orbital Longitude	(Figure/Table/ Exhibit)	(GXT File)	(g) 5 Deg	(h) 10 Deg	(i) 15 Deg	(j) 20 Deg	(k) 25 Deg
		or" X")	(Deg. E/W)							

Page 5: Beam Diagrams

Page 6: Channels and Transponders

FCC Form 312 - Schedule S: (Technical and Operational Description)

S9. SPACE STATION CHANNELS For each frequency channel provide: S10. SPACE STATION TRANSPONDERS For each transponder provide:

(a) Channel No.	(B) Assigned Bandwidth (kHz)	(c) T/R Mode	(d) Center Frequency (MHz)	(e) Polarization (H, V, L, R)	(f) TTC or Comm Channel (T or C)
ST3	4000	T	8030.0	R	С
ST4	320000	Т	8185.0	R	С
CMD	250	R	2085.6875	R	T

ĺ	(0)	(b)	Receive	Pand	Tronomi	t Pand	
	_ (a)	Transponder Gain (dB)		Dariu	Transmit Band		
	Transponder		(c) Channel	(d) Beam	(e) Channel	(f) Beam ID	
	ID		No.	ID	No.		

Page 7: Digital Modulation

FCC Form 312 - Schedule S: (Technical and Operational Description)

S11. DIGITAL MODULATION PARAMETERS For each digital emission provide:

(a) Digital Mod. ID	(b) Emission Designator	(c) Assigned Bandwidth (kHz)	(d) No. of Phases	(e)Uncoded Data Rate (kbps)	(f) FEC Error Correction Coding Rate	(g) CDMA Processing Gain (dB)	(h) Total C/N Performance Objective (dB)	(i) Single Entry C/I Objective (dB)
ST3	4M00G7D	4000	1	262	0.5	0	22.05	27
ST4	320MG7D	320000	2	256000	0.08	0	20.7	27
CMD	250KXFD	250	1	2	1	0		

Page 8: Analog Modulation

FCC Form 312 - Schedule S: (Technical and Operational Description)

S12. ANALOG MODULATION PARAMETERS For each analog emission provide:

(a)	(b) Emission	(c)	(d) Signal	(e)		Multi-channe	Telephony		(j) Video	(k) Video	(I) Video	(m) SCPC/FM	(n) Total C/N	(o) Single
Analog Mod. II		Assigned Bandwidth (kHz)	21 -	Channels per Carrier	(f) Ave. Companded Talker Level (dBm0)	(g) Bottom Baseband Freq. (MHz)	(h) Top Baseband Freq. (MHz)	(i) RMS Modulation Index	Standard NTSC, PAL, etc.	Noise- Weighting (dB)	and SCPC/FM Modulation Index	Compander, Preemphasis, and Noise Weighting (dB)	Performance Objective (dB)	Entry C/I Objective (dB)

Page 9: Typical Emissions

FCC Form 312 - Schedule S: (Technical and Operational Description)

S13. TYPICAL EMISSIONS For each planned type of emission provide:

Associated				(e) Carriers	()	(g)Noise Budget	(h) Energy	Receive Band (Assoc. Transmit Stn)			Transmit Band (This Space Station)			ion)
Transpo	nder ID Range	(c) Digital	(d) Analog	per Transponder	Spacing (kHz)	Reference (Table No.)	Dispersal Bandwidth	(i)Assoc.	Assoc. Stati		EIRP	(dBW)	(n) Max. Power	(-)
(a) Star	(b) End	nd (Table S11) (Table S12)		·			(kHz)	Stn. Max. Antenna	Power (dBW)				Flux Density (dBW/m2/Hz)	Stn Rec. G/T
					Gain (dBi)	(j) Min.	(k) Max.	(I) Min.	(m) Max.	(0011/11/2/11/2)	(dB/K)			

FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS 212 School of St. (Technical and Operational Descrip

Page 10: TT and C

FCC Form 312 - Schedule S: (Technical and Operational Description)

S14. Is the space station(s) controlled and monitored remotely? If Yes, provide the location and telephone number of the TT and C control point(s): #Error

FEDERAL COMMUNICATIONS COMMISSION **SATELLITE SPACE STATION AUTHORIZATIONS** FCC Form 312 - Schedule S: (Technical and Operational Description)

Page 11: **Characteristics and** Certifications

S15. SPACECRAFT PHYSICAL CHARACTERISTICS:

S15a: Mass of spacecraft without fuel (kg): 952.5	Spacecraft Dimensions (meters)	Probability of Survival to End of Life (0.0 - 1.0)
S15b. Mass of fuel and disposables at launch (kg): 76		
S15c. Mass of spacecraft and fuel at launch (kg): 1028.5	S15f. Length (m): 1.6	S15i. Payload: 0.7981
S15d. Mass of fuel, in orbit, at beginning of life (kg): 76	S15g. Width (m): 1.5	S15j. Bus: 0.9397
S15e. Deployed Area of Solar Array (square meters): 7.7	S15h. Height (m): 2.9	S15k. Total: 0.75

S16. SPACECRAFT ELECTRICAL CHARACTERISTICS:

Spacecraft Subsystem		ver (Watts) At ng of Life	Electrical Power (Watts) At End of Life				
	At Equinox	At Solstice	At Equinox	At Solstice			
Payload (Watts):	^{(a):} 79	^{(f):} 79	^{(k):} 79	^{(p):} 79			
Bus (Watts):	^{(b):} 488	^{(g):} 488	^{(I):} 488	^{(q):} 488			
Total (Watts):	^{(c):} 567	^{(h):} 567	^(m) 567	^{(r):} 567			
Solar Array (Watts):	^{(d):} 721	^{(i):} 721	^{(n):} 721	^{(s):} 721			
Depth of Battery Discharge (%):	^(e) 15 %	^(j) 15 %	^(o) 15 %	^(t) 15 %			

S17. CERTIFICATIONS:

a. Are the power flux density limits of § 25.208 met?:	YES	NO	X N/A					
b. Are the appropriate service area coverage requirements of § 25.143(b)(ii) and (iii), or § 25.145(c)(1) and (2) met?	YES	NO	X N/A					
c. Are the frequency tolerances of § 25.202(e) and the out-of-band emission limits of § 25.202(f)(1), (2) and (3) met?	X YES	NO	N/A					
In addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the								

Commission's rules, 47 C.F.R § 25.114.