

EchoStar 17/24 GHz Link Budget

Link Parameters		Clear Sky (Los Angeles)	Faded D/L (Los Angeles)	Clear Sky (Mexico City)	Faded D/L (Mexico City)
Link Geometry:					
Tx E/S Range to Satellite (Cheyenne)	(km)	38,110	38,110	38,110	38,110
Rx E/S Range to Satellite	(km)	38,362	38,362	36,627	36,627
Uplink:					
Carrier Frequency	(MHz)	25,000	25,000	25,000	25,000
Tx E/S Antenna Diameter	(m)	12.0	12.0	12.0	12.0
Max. Tx E/S Power to Antenna	(W)	5.0	5.0	5.0	5.0
Max. Tx E/S Power Density to Antenna	(dBW/MHz)	-6.6	-6.6	-6.6	-6.6
Tx E/S Antenna Gain	(dB)	68.2	68.2	68.2	68.2
Tx E/S EIRP per Carrier	(dBW)	75.2	75.2	75.2	75.2
Atmospheric and Other Losses	(dB)	0.7	0.7	0.5	0.7
Free Space Loss	(dB)	212.0	212.0	212.0	212.0
Satellite:					
G/T towards Tx E/S	(dB/K)	17.3	17.3	17.3	17.3
EIRP per Carrier towards Rx E/S	(dBW)	52.5	52.5	52.3	52.3
Downlink:					
Carrier Frequency	(MHz)	17,500	17,500	17,500	17,500
Atmospheric and Other Losses	(dB)	0.3	1.7	0.2	1.2
Free Space Loss	(dB)	209.0	209.0	208.6	208.6
Rx E/S Antenna Diameter	(m)	0.45	0.45	0.45	0.45
Rx E/S Antenna Gain	(dB)	36.1	36.1	36.1	36.1
Pointing Error	(dB)	0.5	0.5	0.5	0.5
Rx E/S G/T	(dB/K)	13.1	11.7	13.1	12.0
System (LNA+Sky) Noise Temperature	(K)	200	277	200	258
Total Link:					
Bandwidth	(dB-Hz)	73.6	73.6	73.6	73.6
C/N - Thermal Uplink	(dB)	34.7	34.7	34.9	34.7
C/N - Thermal Downlink	(dB)	10.8	8.0	11.1	9.0
C/I - Aggregate uplink ASI	(dB)	37.5	37.5	37.7	37.5
C/I - Aggregate downlink ASI	(dB)	19.1	19.1	13.3	13.3
C/I - Other Link Degradations	(dB)	22.0	22.0	22.0	22.0
C/(N+I) - Total, Actual	(dB)	9.9	7.5	8.8	7.5
C/(N+I) - Total, Required	(dB)	7.5	7.5	7.5	7.5
Excess Margin	(dB)	2.4	0.0	1.3	0.0
Availability	(%)	N/A	99.72	N/A	99.50
Aggregate Interference Assessment:					
(C/N) - no ASI	(dB)	10.5	7.9	10.8	8.8
Degradation due to aggregate ASI	(dB)	0.6	0.3	1.9	1.3