FCC 312 Schedule S

FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS (Technical and Operational Description)

Page 1: General, Frequency Bands, and GSO Orbit

S1. GENERAL INFORMATION Complete for all satellite application	S1.	GENERAL	INFORMATION	Complete for all	I satellite application
----------------------------------------------------------------	-----	----------------	-------------	------------------	-------------------------

a. Space Station or Satellite No SIRIUS FM-6	etwork Name:	e. Estimated Date of Placement into Service: 3/15/2012		i Will the space station(s) operate on a Common Carrier Basis: N			
b. Construction Commenceme 12/28/2007	nt Date:	f. Estimated Lifetime of Satellite(s): 15	Years	j. Number of transponders offered on a common carrier basis: 0			
c. Construction Completion Da 2/10/2011	ite:	g. Total Number of Transponders: 3		k. Total Common Carrier Transponder Band 0	dwidth: MHz		
d1. Est Launch Date Begin: 10/21/2011	d2. Est Launch Date End: 3/1/2012	h. Total Transponder Bandwidth (no. transponde 12.5	rs x Bandwidth) MHz	I. Orbit Type: Mark all boxes that apply: X GSO I	NGSO		

S2. OPERATING FREQUENCY BANDS Identify the frequency range and transmit/receive mode for all frequency bands in which this station will oper Also indicate the nature of service(s) for each frequency band.

	Frequency	Band Limits			f.
Lower Frequency (_Hz)	Upper Frequency (_Hz)	e. T/R Mode	Nature of Service(s): List all that apply to this band
a. Numeric	b. Unit (K/M/G)	c. Numeric	d. Unit (K/M/G)		., ., .,
2320.0	M	2332.5	M	Т	Satellite Digital Audio Radio Service
7060.0	М	7072.5	М	R	Fixed Satellite Service
7051.5	M	7052.5	M	R	Fixed Satellite Service
7055.5	М	7056.5	М	R	Fixed Satellite Service
2321.35	M	2321.65	M	Т	Satellite Digital Audio Radio Service
2321.85	M	2322.15	M	Т	Satellite Digital Audio Radio Service
2330.35	М	2330.65	М	Т	Satellite Digital Audio Radio Service
2330.85	М	2331.15	М	Τ	Satellite Digital Audio Radio Service

S3. ORBITAL INFORMATION FOR GEOSTATIONARY SATELLITES ONLY:

a. Nominal Orbital Longitude	le (Degrees E/W):	b. Alternate Orbital Longitu	ude (Degrees E/W):			c. Reason for orbital location selection:
116.15 W				The orbital location provides good satellite spatial		
Longitudinal Tolerance or E	1 0		Range of orbital are in which	h adequate serv	rice can be	diversity for the eventual GEO constellation and
d. Toward West: e. Toward East:	0.05 Degrees0.05 Degrees	N/S Station-Keeping Tolerance: 0.05 Degrees	provided (Optional): g. Westernmost: h. Easternmost:	Degrees E/W W W		provides high elevation angles to all of CONUS, which is very important for the link between the satellite and the mobile user terminals in CONUS. The high elevation angle minimizes the risk of signal blockage
i. Reason for service are	e selection (Optional)	:				due to buildings and foliage.

FCC Form 312 - Schedule S: (Technical and Operational Description)

S4. ORBITAL INFORMATION FOR NON-GEOSTATIONARY SATELLITES ONLY

S4a. Total Number of Satellites in Network or System:

S4c. Celestial Reference Body (Earth, Sun, Moon, etc.):

Page 2: NGSO Orbits

S4b. Total Number of Orbital Planes in Network or System: S4d. Orbit Epoch Date:

For each Orbital Plane Provide:

(e) Orbital	(f) No. of	(g) Inclination	(h) Orbital	(i) Apogee (km)	(j) Perigee (km)	(k) Right Ascension	(I) Argument of	Active Se	rvice Arc Rang	e (Degrees)
Plane No.	Satellites in	Angle (degrees)	Period			of the Ascending	Perigee	(m) Begin	(n) End	(o) Other
	Plane		(Seconds)			Node (Deg.)	(Degrees)	Angle	Angle	
			,			` ",	`	3 -	3 -	

S5. INITIAL SATELLITE PHASE ANGLE For each satellite in each orbital plane, provide the intital phase angle.

(a) Orbital	(b) Satellite	(c) Initial
Plane No.	Number	Phase Angle
		(Degrees)

NO NGSO DATA FILED

FCC Form 312 - Schedule S: (Technical and Operational Description)

S6. SERVICE AREA CHARACTERISTICS for each service area provide:

(a) Service Area ID	(b) Type of Associated Station (Earth or Space)	(d) Service Area Description. Provide list of geographic areas (state postal codes or ITU 3-ltr codes), satellites or Figure No. of Service Area Diagram.
SA1S	S	CONUS
SA2X	S	Eastern & Central CONUS

Page 3: Service Areas

Page 4: Antenna Beams

FCC Form 312 - Schedule S: (Technical and Operational Description)

S7. SPACE STATION ANTENNA BEAM CHARACTERISTICS For each antenna beam provide:

(a)	(b)	Isotropic	Antenna	(e)	(f)	(g) Min.	(h) Polar-	(i) Polarization	(j) Service		Transmit				Receive		
Beam	T/R		ain	0	Rotational	Cross-	ization	Alignment Rel.	Area ID	(k) Input	(I) Effective	(m)		(o) G/T	(p) Min.	Input Attenu	uator (dB)
ID	Mode		(d) Edge	Error	Error	Polar Iso-	Switch-	Equatorial		Losses	Output	Max.	System	Max.	Saturation	(q) Max.	(r) Step
		(dBi)	(dBi)	(Degrees)	(Degrees)	iation (db)	able? (Y/N)	Plane (Degrees)		(dB)	Power (W)	EIRP (dBW)	Noice Temp (k)		Flux Density (dBW/m2)	Value	Size
XU1	R	31	30.1	0.18	1	30	N		SA2X				649	2.9	-108	20	0.5
SD1	Т	34.7	26.5	0.18	1	30	N		SA1S	1	1000	71.6					
OMN	R	9	-4	0	1	30	N		SA2X				630	-19			
OMN	Т	9	-4	0	1	30	N		SA1S	6.9	4.1	15.1					
SAT	Т	13.4	12.7	0	1	30	N		SA1S	7	4	19.4					

Page 5: Beam Diagrams

FCC Form 312 - Schedule S: (Technical and Operational Description)

S8. ANTENNA BEAM DIAGRAMS For each beam pattern provide the reference to the graphic image and numerical data:

Also provide the power flux density levels in each beam that result from the emission with the highest power flux density.

(a)	(b)	(c) Co-or	(d) GSO	(e) NGSO Antenna Gain	(f) GSO Antenna		Max. Power F	lux Density (dB	W/M2/Hz)	
Beam	T/R	Cross	Ref.	Contour Description	Gain Contour Data	At Angle of	Arrival above ho	orizontal (for em	ission with higl	hest PFD)
ID	Mode	Polar Mode ("C" or" X")	Orbital Longitude (Deg. E/W)	(Figure/Table/ Exhibit)	(GXT File)	(g) 5 Deg	(h) 10 Deg	(i) 15 Deg	(j) 20 Deg	(k) 25 Deg
XU1	R	С	-116.15		XU1.gxt					
SD1	T	С	-116.15		SD1.gxt	-120.8	-120.8	-120.8	-120.8	-120.8
SAT	Т	С	-116.15		SATM.gxt	-161.2	-161.2	-161.2	-161.2	-161.2

Page 6: Channels and Transponders

FCC Form 312 - Schedule S: (Technical and Operational Description)

S9. SPACE STATION CHANNELS For each frequency channel provide: S10. SPACE STATION TRANSPONDERS For each transponder provide:

(a) Channel No.	(B) Assigned Bandwidth (kHz)	(c) T/R Mode	(d) Center Frequency (MHz)	(e) Polarization (H, V, L, R)	(f) TTC or Comm Channel (T or C)
U001	4500	R	7062.29	R	С
U002	4500	R	7070.21	R	С
D001	4500	Т	2322.29	L	С
D002	4500	Т	2330.21	L	С
CMD1	1000	R	7052.0	L	Т
CMD2	1000	R	7056.0	L	Т
TLM1	300	Т	2321.5	R	Т
TLM2	300	T	2322.0	R	Т
TLM3	300	T	2330.5	R	Т
TLM4	300	Т	2331.0	R	Т
U003	12500	R	7066.25	R	С
D003	12500	Т	2326.25	L	С

(a)	(b)	Receive	Band	Transm	it Band
Transponder ID	Transponder Gain (dB)	(c) Channel No.	(d) Beam ID	(e) Channel No.	(f) Beam ID
BL01	130	U001	XU1	D001	SD1
BL02	130	U002	XU1	D002	SD1
C001		CMD1	OMNX1		
C002		CMD2	OMNX1		
T001				TLM1	OMNS1
T002				TLM2	OMNS1
T003				TLM3	OMNS1
T004				TLM4	OMNS1
T005				TLM1	SATM
T006				TLM2	SATM
T007				TLM3	SATM
T008				TLM4	SATM
BL03	130	U003	XU1	D003	SD1

Page 7: Digital Modulation

FCC Form 312 - Schedule S: (Technical and Operational Description)

S11. DIGITAL MODULATION PARAMETERS For each digital emission provide:

(a) Digital Mod. ID	(b) Emission Designator	(c) Assigned Bandwidth (kHz)	(d) No. of Phases	(e)Uncoded Data Rate (kbps)	(f) FEC Error Correction Coding Rate	(g) CDMA Processing Gain (dB)	(h) Total C/N Performance Objective (dB)	(i) Single Entry C/I Objective (dB)
D1	4M50G7E	4500	4	7517	0.6667		5	
D2	4M50G7E	4500	8	3758	0.3333		5	

Page 8: Analog Modulation

FCC Form 312 - Schedule S: (Technical and Operational Description)

S12. ANALOG MODULATION PARAMETERS For each analog emission provide:

` '	(b) Emission	(c)	(d) Signal	(e)		Multi-channe	Telephony		(j) Video	(k) Video	(I) Video	(m) SCPC/FM	` '	` '
Analog Mod. ID		Assigned Bandwidth (kHz)	Туре	Channels per Carrier	(f) Ave. Companded Talker Level (dBm0)	(g) Bottom Baseband Freq. (MHz)	(h) Top Baseband Freq. (MHz)	(i) RMS Modulation Index	dulation NTSC, Weight		and SCPC/FM Modulation Index	Preemphasis,	Performance Objective (dB)	Entry C/I Objective (dB)
A1	1M00F1D	1000	TC	1									36.2	48.4
A2	300KG1D	300	TM	1									50.1	63.8

Page 9: Typical Emissions

FCC Form 312 - Schedule S: (Technical and Operational Description)

S13. TYPICAL EMISSIONS For each planned type of emission provide:

Associated Transponder ID Range		(c) Digital (d) Analog		(e) Carriers	(f) Carrier	(g)Noise Budget	(h) Energy	Receive Band (Assoc. Transmit Stn)			Transmit Band (This Space Station)				
				per Spacing Transponder (kHz)		Reference (Table No.)	Dispersal Bandwidth	(i)Assoc.	Assoc. Station Transmit Power (dBW)		EIRP	(dBW)	` '	(o)Assoc.	
(a) Start	(b) End	(Table S11)	(Table S12)			,	(kHz)	Stn. Max. Antenna	Power	(aBvv)			Power Flux Density	Stn Rec. G/T	
								Gain (dBi)	(j) Min.	(k) Max.	(I) Min.	(m) Max.	(dBW/m2/Hz)	(dB/K)	
BL01	BL02	D1		1		S-band PRM					63.4	71.6	-120.8	-18.3	
C001	C002		A1	1		X-band CMD		50.5	15.5	24.5	66	75		27.7	
T001	T004		A2	1		S-band TLM					2.1	15.1	-165.5	19.4	
T005	T008		A2	1		S-band TLM					18.7	19.4	-161.2	19.4	

Page 10: TT and C

FCC Form 312 - Schedule S: (Technical and Operational Description)

S14. Is the space station(s) controlled and monitored remotely? If Yes, provide the location and telephone number of the TT and C control point(s): Yes

Remote Control (TT C) Location(s): S14a: Street Address: 24 Vernon Crossing Road S14b. City: S14c. County: S14d. State/Country S14e. Zip Code: Vernon Sussex NJ 07462 S14f. Telephone Number: S14g. Call Sign of Control Station (if appropriate): 973-764-4021 E040363 Remote Control (TT C) Location(s): S14a: Street Address: 24 Vernon Crossing Road S14b. City: S14c. County: S14d. State/Country S14e. Zip Code: Vernon Sussex 07462 S14f. Telephone Number: S14g. Call Sign of Control Station (if appropriate): 973-764-4021 E060276 Remote Control (TT C) Location(s): S14a: Street Address: 2875 Fork Creek Church S14b. City: S14c. County: S14d. State/Country S14e. Zip Code: Ellenwood Clayton GΑ 30294 S14f. Telephone Number: S14g. Call Sign of Control Station (if appropriate): 404-381-2001 E040204

FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS FCC Form 312 - Schedule S: (Technical and Operational Description)

Page 11: Characteristics and Certifications

S15. SPACECRAFT PHYSICAL CHARACTERISTICS:

S15a: Mass of spacecraft without fuel (kg): 2975	Spacecraft Dimensions (meters)	Probability of Survival to End of Life (0.0 - 1.0)
S15b. Mass of fuel and disposables at launch (kg): 3105		
S15c. Mass of spacecraft and fuel at launch (kg): 6080	S15f. Length (m): 32.4	S15i. Payload: 0.9
S15d. Mass of fuel, in orbit, at beginning of life (kg): 733	S15g. Width (m): 18	S15j. Bus: 0.85
S15e. Deployed Area of Solar Array (square meters): 89	S15h. Height (m): 11.1	S15k. Total: 0.76

S16. SPACECRAFT ELECTRICAL CHARACTERISTICS:

Spacecraft Subsystem	Electrical Pov Beginnir	ver (Watts) At ng of Life		ver (Watts) At of Life
	At Equinox	At Solstice	At Equinox	At Solstice
Payload (Watts):	^{(a):} 12978	^{(f):} 12978	^{(k):} 12978	^{(p):} 12978
Bus (Watts):	^{(b):} 3493	^{(g):} 1684	^{(l):} 3493	^{(q):} 1684
Total (Watts):	^{(c):} 16471	^{(h):} 14662	^(m) 16471	^{(r):} 14662
Solar Array (Watts):	^{(d):} 20895	^{(i):} 18499	^{(n):} 18364	^{(s):} 16403
Depth of Battery Discharge (%):	^(e) 55.5 %	^(j) 0 %	^(o) 58.6 %	^(t) 0 %

S17. CERTIFICATIONS:

a. Are the power flux density limits of § 25.208 met?:		YES		NO	Χ	N/A	
b. Are the appropriate service area coverage requirements of § 25.143(b)(ii) and (iii), or § 25.145(c)(1) and (2) met?		YES		NO	X	N/A	
c. Are the frequency tolerances of § 25.202(e) and the out-of-band emission limits of § 25.202(f)(1), (2) and (3) met?)	YES		NO	Χ	N/A	
In addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the							

n addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the Commission's rules, 47 C.F.R § 25.114.