

S1. GENERAL INFORMATION Complete for all satellite applications.

a. Space Station or Satellite Network Name: GALAXY 12		e. Estimated Date of Placement into Service:		i. Will the space station(s) operate on a Common Carrier Basis: N	
b. Construction Commencement Date:		f. Estimated Lifetime of Satellite(s): Years		j. Number of transponders offered on a common carrier basis:	
c. Construction Completion Date:		g. Total Number of Transponders: 24		k. Total Common Carrier Transponder Bandwidth: MHz	
d1. Est Launch Date Begin:	d2. Est Launch Date End:	h. Total Transponder Bandwidth (no. transponders x Bandwidth) 864 MHz		i. Orbit Type: Mark all boxes that apply: <input checked="" type="checkbox"/> GSO <input type="checkbox"/> NGSO	

S2. OPERATING FREQUENCY BANDS Identify the frequency range and transmit/receive mode for all frequency bands in which this station will oper
Also indicate the nature of service(s) for each frequency band.

Frequency Band Limits				e. T/R Mode	f. Nature of Service(s): List all that apply to this band
Lower Frequency (Hz)		Upper Frequency (Hz)			
a. Numeric	b. Unit (K/M/G)	c. Numeric	d. Unit (K/M/G)		
5925	M	6425	M	R	Fixed Satellite Service
3700	M	4200	M	T	Fixed Satellite Service

S3. ORBITAL INFORMATION FOR GEOSTATIONARY SATELLITES ONLY:

a. Nominal Orbital Longitude (Degrees E/W): 129 W		b. Alternate Orbital Longitude (Degrees E/W):		c. Reason for orbital location selection: PROVIDE C-BAND SERVICE TO THE UNITED STATES	
Longitudinal Tolerance or E/W Station-Keeping:		f. Inclination Excursion or N/S Station-Keeping Tolerance:		Range of orbital are in which adequate service can be provided (Optional): Degrees E/W	
d. Toward West:	0.05 Degrees	0.05 Degrees		g. Westernmost:	
e. Toward East:	0.05 Degrees			h. Easternmost:	
i. Reason for service are selection (Optional):					

**FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)**

S4. ORBITAL INFORMATION FOR NON-GEOSTATIONARY SATELLITES ONLY

S4a. Total Number of Satellites in Network or System:

S4c. Celestial Reference Body (Earth, Sun, Moon, etc.):

S4b. Total Number of Orbital Planes in Network or System:

S4d. Orbit Epoch Date:

For each Orbital Plane Provide:

(e) Orbital Plane No.	(f) No. of Satellites in Plane	(g) Inclination Angle (degrees)	(h) Orbital Period (Seconds)	(i) Apogee (km)	(j) Perigee (km)	(k) Right Ascension of the Ascending Node (Deg.)	(l) Argument of Perigee (Degrees)	Active Service Arc Range (Degrees)		
								(m) Begin Angle	(n) End Angle	(o) Other

S5. INITIAL SATELLITE PHASE ANGLE For each satellite in each orbital plane, provide the initial phase angle.

(a) Orbital Plane No.	(b) Satellite Number	(c) Initial Phase Angle (Degrees)

NO NGSO DATA FILED

**FEDERAL COMMUNICATIONS COMMISSION
 SATELLITE SPACE STATION AUTHORIZATIONS
 FCC Form 312 - Schedule S: (Technical and Operational Description)**

S6. SERVICE AREA CHARACTERISTICS for each service area provide:

(a) Service Area ID	(b) Type of Associated Station (Earth or Space)	(c) Service Area Diagram File Name (GXT File)	(d) Service Area Description. Provide list of geographic areas (state postal codes or ITU 3-ltr codes), satellites or Figure No. of Service Area Diagram.
1	S		UNITED STATES
2	S		GLOBAL

FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)

S7. SPACE STATION ANTENNA BEAM CHARACTERISTICS For each antenna beam provide:

(a) Beam ID	(b) T/R Mode	Isotropic Antenna Gain		(e) Pointing Error (Degrees)	(f) Rotational Error (Degrees)	(g) Min. Cross- Polar Iso- lation (dB)	(h) Polar- ization Switch- able? (Y/N)	(i) Polarization Alignment Rel. Equatorial Plane (Degrees)	(j) Service Area ID	Transmit			Receive				
										(k) Input Losses (dB)	(l) Effective Output Power (W)	(m) Max. EIRP (dBW)	(n) System Noise Temp (k)	(o) G/T Max. Gain Pt. (db/K)	(p) Min. Saturation Flux Density (dBW/m2)	Input Attenuator (dB)	
		(q) Max. Value	(r) Step Size														
CHU	R	30.7	26.7	0.12	0.12		Y		01					3.5	-111.5	36	1
CVU	R	30.7	26.7	0.12	0.12		Y		901					3.5	-111.5	36	1
CHD	T	29.5	25.5	0.12	0.12		Y		01			44.2					
CVD	T	29.5	25.5	0.12	0.12		Y		901			44.2					
OMN	R	2.1	0.1	0.12	0.12				2					-25.4	-87.5		
WCA	R	13.1	11.1	0.12	0.12				2					-14.4	-94		
CMD	R	30.7	20.7	0.12	0.12		Y		901					-4.5	-114.7		
OMN	T	2.1	0.1	0.12	0.12				2			5.8					
WCA	T	13.1	11.1	0.12	0.12				2			4.8					
TLMT	T	29.5	19.5	0.12	0.12		Y		01			20					

**FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)**

S8. ANTENNA BEAM DIAGRAMS For each beam pattern provide the reference to the graphic image and numerical data:
Also provide the power flux density levels in each beam that result from the emission with the highest power flux density.

(a) Beam ID	(b) T/R Mode	(c) Co-or Cross Polar Mode ("C" or" X")	(d) GSO Ref. Orbital Longitude (Deg. E/W)	(e) NGSO Antenna Gain Contour Description (Figure/Table/ Exhibit)	(f) GSO Antenna Gain Contour Data (GXT File)	Max. Power Flux Density (dBW/M2/Hz)				
						At Angle of Arrival above horizontal (for emission with highest PFD)				
						(g) 5 Deg	(h) 10 Deg	(i) 15 Deg	(j) 20 Deg	(k) 25 Deg
CHU	R	C	-129		chup.gxt					
CVU	R	C	-129		cvup.gxt					
CHD	T	C	-129		chdn.gxt	-152	-149.5	-148.8	-148.7	-148.6
CVD	T	C	-129		cvdn.gxt	-152	-149.5	-148.8	-148.7	-148.6
OMN	R	C	-129		omnc.gxt					
WCA	R	C	-129		wcac.gxt					
CMD	R	C	-129		cmdc.gxt					
OMN	T	C	-129		omnt.gxt	-175.5	-175.4	-175.2	-175.1	-175
WCA	T	C	-129		wcat.gxt	-176.5	-176.4	-176.2	-176.1	-176
TLMT	T	C	-129		tlmt.gxt	-161.3	-161.2	-161	-160.9	-160.8

FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)

S9. SPACE STATION CHANNELS For each frequency channel provide: S10. SPACE STATION TRANSPONDERS For each transponder provide:

(a) Channel No.	(B) Assigned Bandwidth (kHz)	(c) T/R Mode	(d) Center Frequency (MHz)	(e) Polarization (H, V, L, R)	(f) TTC or Comm Channel (T or C)
CU001	36000	R	5945	V	C
CU003	36000	R	5985	V	C
CU005	36000	R	6025	V	C
CU007	36000	R	6065	V	C
CU009	36000	R	6105	V	C
CU011	36000	R	6145	V	C
CU013	36000	R	6185	V	C
CU015	36000	R	6225	V	C
CU017	36000	R	6265	V	C
CU019	36000	R	6305	V	C
CU021	36000	R	6345	V	C
CU023	36000	R	6385	V	C
CU002	36000	R	5965	H	C
CU004	36000	R	6005	H	C
CU006	36000	R	6045	H	C
CU008	36000	R	6085	H	C
CU010	36000	R	6125	H	C
CU012	36000	R	6165	H	C
CU014	36000	R	6205	H	C
CU016	36000	R	6245	H	C
CU018	36000	R	6285	H	C
CU020	36000	R	6325	H	C
CU022	36000	R	6365	H	C
CU024	36000	R	6405	H	C
CD001	36000	T	3720	H	C
CD003	36000	T	3760	H	C
CD005	36000	T	3800	H	C
CD007	36000	T	3840	H	C
CD009	36000	T	3880	H	C
CD011	36000	T	3920	H	C

(a) Transponder ID	(b) Transponder Gain (dB)	Receive Band		Transmit Band	
		(c) Channel No.	(d) Beam ID	(e) Channel No.	(f) Beam ID
C0001	132.8	CU001	CVUP	CD001	CHDN
C0003	132.8	CU003	CVUP	CD003	CHDN
C0005	132.8	CU005	CVUP	CD005	CHDN
C0007	132.8	CU007	CVUP	CD007	CHDN
C0009	132.8	CU009	CVUP	CD009	CHDN
C0011	132.8	CU011	CVUP	CD011	CHDN
C0013	132.8	CU013	CVUP	CD013	CHDN
C0015	132.8	CU015	CVUP	CD015	CHDN
C0017	132.8	CU017	CVUP	CD017	CHDN
C0019	132.8	CU019	CVUP	CD019	CHDN
C0021	132.8	CU021	CVUP	CD021	CHDN
C0023	132.8	CU023	CVUP	CD023	CHDN
C0002	132.8	CU002	CHUP	CD002	CVDN
C0004	132.8	CU004	CHUP	CD004	CVDN
C0006	132.8	CU006	CHUP	CD006	CVDN
C0008	132.8	CU008	CHUP	CD008	CVDN
C0010	132.8	CU010	CHUP	CD010	CVDN
C0012	132.8	CU012	CHUP	CD012	CVDN
C0014	132.8	CU014	CHUP	CD014	CVDN
C0016	132.8	CU016	CHUP	CD016	CVDN
C0018	132.8	CU018	CHUP	CD018	CVDN
C0020	132.8	CU020	CHUP	CD020	CVDN
C0022	132.8	CU022	CHUP	CD022	CVDN
C0024	132.8	CU024	CHUP	CD024	CVDN

CD013	36000	T	3960	H	C
CD015	36000	T	4000	H	C
CD017	36000	T	4040	H	C
CD019	36000	T	4080	H	C
CD021	36000	T	4120	H	C
CD023	36000	T	4160	H	C
CD002	36000	T	3740	V	C
CD004	36000	T	3780	V	C
CD006	36000	T	3820	V	C
CD008	36000	T	3860	V	C
CD010	36000	T	3900	V	C
CD012	36000	T	3940	V	C
CD014	36000	T	3980	V	C
CD016	36000	T	4020	V	C
CD018	36000	T	4060	V	C
CD020	36000	T	4100	V	C
CD022	36000	T	4140	V	C
CD024	36000	T	4180	V	C
CMD1	1000	R	6424.5	V	T
CMD2	1000	R	6424.5	R	T
CMD3	1000	R	6424.5	R	T
TLM1	500	T	4198	H	T
TLM2	500	T	4199.875	H	T
TLM3	500	T	4198	L	T
TLM4	500	T	4199.875	L	T
TLM5	500	T	4198	L	T
TLM6	500	T	4199.875	L	T

FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)

S11. DIGITAL MODULATION PARAMETERS For each digital emission provide:

(a) Digital Mod. ID	(b) Emission Designator	(c) Assigned Bandwidth (kHz)	(d) No. of Phases	(e) Uncoded Data Rate (kbps)	(f) FEC Error Correction Coding Rate	(g) CDMA Processing Gain (dB)	(h) Total C/N Performance Objective (dB)	(i) Single Entry C/I Objective (dB)
D1	36M0G7W	36000	4	24575	0.5		3.4	12.1
D2	10M3G7W	10300	4	6000	0.5		3.9	11.5
D3	100KG7W	100	4	64	0.5		3	10.6

FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)

Page 8: Analog Modulation

S12. ANALOG MODULATION PARAMETERS For each analog emission provide:

(a) Analog Mod. ID	(b) Emission Designator	(c) Assigned Bandwidth (kHz)	(d) Signal Type	(e) Channels per Carrier	Multi-channel Telephony				(j) Video Standard NTSC, PAL, etc.	(k) Video Noise- Weighting (dB)	(l) Video and SCPC/FM Modulation Index	(m) SCPC/FM Compander, Preemphasis, and Noise Weighting (dB)	(n) Total C/N Performance Objective (dB)	(o) Single Entry C/I Objective (dB)
					(f) Ave. Companded Talker Level (dBm0)	(g) Bottom Baseband Freq. (MHz)	(h) Top Baseband Freq. (MHz)	(i) RMS Modulation Index						
A1	36M0F3F	36000	TV/FM	1					NTSC	12.8	2.6		10	15.6

FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)

S13. TYPICAL EMISSIONS For each planned type of emission provide:

Associated Transponder ID Range (a) Start (b) End		Modulation ID		(e) Carriers per Transponder	(f) Carrier Spacing (kHz)	(g) Noise Budget Reference (Table No.)	(h) Energy Dispersal Bandwidth (kHz)	Receive Band (Assoc. Transmit Stn)			Transmit Band (This Space Station)			
		(c) Digital (Table S11)	(d) Analog (Table S12)					(i) Assoc. Stn. Max. Antenna Gain (dBi)	Assoc. Station Transmit Power (dBW) (j) Min. (k) Max.		EIRP (dBW) (l) Min. (m) Max.		(n) Max. Power Flux Density (dBW/m ² /Hz)	(o) Assoc. Stn Rec. G/T (dB/K)
C0001	C0024		A1	1		G12 Schedule	4000	54.1	20.3	24.3	40.2	44.2	-147.9	23.6
C0001	C0024	D1		1		G12 Schedule		49.4	20	24	40.2	44.2	-156.7	19.2
C0001	C0024	D2		2	10300	G12 Schedule		49.4	13.1	17.1	32.8	36.8	-157.6	19.2
C0001	C0024	D3		269	100	G12 Schedule		49.4	-7.3	-3.3	12.4	16.4	-158.5	19.2

FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)

S14. Is the space station(s) controlled and monitored remotely? If Yes, provide the location and telephone number of the TT and C control point(s): Yes

Remote Control (TT C) Location(s):

S14a: Street Address: 3400 International Drive, N.W.			
S14b. City: Washington	S14c. County:	S14d. State/Country DC	S14e. Zip Code: 20008
S14f. Telephone Number: 202-944-7701		S14g. Call Sign of Control Station (if appropriate):	

**FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)**

**Page 11:
Characteristics and
Certifications**

S15. SPACECRAFT PHYSICAL CHARACTERISTICS:

S16. SPACECRAFT ELECTRICAL CHARACTERISTICS:

S17. CERTIFICATIONS:

a. Are the power flux density limits of § 25.208 met?:	<input checked="" type="checkbox"/>	YES	<input type="checkbox"/>	NO	<input type="checkbox"/>	N/A
b. Are the appropriate service area coverage requirements of § 25.143(b)(ii) and (iii), or § 25.145(c)(1) and (2) met?	<input type="checkbox"/>	YES	<input type="checkbox"/>	NO	<input checked="" type="checkbox"/>	N/A
c. Are the frequency tolerances of § 25.202(e) and the out-of-band emission limits of § 25.202(f)(1), (2) and (3) met?	<input checked="" type="checkbox"/>	YES	<input type="checkbox"/>	NO	<input type="checkbox"/>	N/A
In addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the Commission's rules, 47 C.F.R § 25.114.						