

March 31, 2016

Ms. Marlene H. Dortch  
Secretary  
Federal Communications Commission  
445 12<sup>th</sup> Street, S.W.  
Washington, DC 20554

Re: Further Supplement to Application for Modification of Authority for Intelsat 16  
Call Sign S2750; File No. SAT-MOD-20160201-00009

Dear Ms. Dortch:

Intelsat License LLC (“Intelsat”) hereby further supplements the above referenced application. Specifically, Intelsat has revised Exhibits 1, 2, and 3 of the Engineering Statement to include the Maximum Saturation Flux Density and the Maximum Beam Peak EIRP Density per beam. For the Commission’s convenience, Intelsat attaches herewith a revised Engineering Statement that replaces the prior filed versions.

Please direct any questions to the undersigned at (703) 559-7848.

Sincerely,

*/s/ Susan H. Crandall*

Susan H. Crandall  
Associate General Counsel  
Intelsat Corporation

cc: Kathryn Medley  
Stephen Duall  
Jay Whaley  
Cindy Spiers

# Engineering Statement

---

## 1 Introduction

Intelsat License LLC (“Intelsat”) seeks authority in this application to operate the satellite designated as Intelsat 16 from 58.1° W.L.

The characteristics of the Intelsat 16 spacecraft, as well as its compliance with the various provisions of Part 25 of the Federal Communication Commission’s (“FCC or “Commission”) rules, are provided in the remainder of this Engineering Statement, which updates the gain contours and the operational frequency ranges and beams. In all other respects, the characteristics of Intelsat 16 are the same as those described in SAT-MOD-20150105-00003.

## 2 Spacecraft Overview

Intelsat 16 is an Orbital Star-2 spacecraft that is capable of operating in Ku-band frequencies listed below.

Direction	Frequency
Uplink	13750 – 14500 MHz
	12750 – 13250 MHz
Downlink	10700 – 11450 MHz
	11700 – 12200 MHz

The spacecraft provides the following coverage:

Beam	Coverage
Mexico	Mexico, Central America, the Caribbean, Puerto Rico, U.S.
Mexico 2	Mexico, Central America
Brazil	Eastern Brazil
Global	Global

### 2.1 Spacecraft Characteristics

Intelsat 16 is a three-axis stabilized type spacecraft that has a rectangular outer body structure. Intelsat 16 utilizes two deployable solar array wings and a number of deployable and non-deployable antennas.

The Intelsat 16 spacecraft is composed of the following subsystems:

- Thermal

- Power
- Attitude Control
- Propulsion
- Telemetry, Command and Ranging
- Uplink Power Control
- Communications

These subsystems maintain the correct position and attitude of the spacecraft; ensure that all internal units are maintained within the required temperature range; and ensure that the spacecraft can be commanded and controlled with a high level of reliability from launch to the end of its useful life. The spacecraft design incorporates redundancy in all of the various subsystems in order to avoid single-point failures.

The structural design of Intelsat 16 provides mechanical support for all subsystems. The structure supports the communication antennas, solar arrays, and the thrusters. It also provides a stable platform for preserving the alignment of critical elements of the spacecraft.

## **2.2 Communication Subsystem**

Intelsat 16 provides active communication channels at Ku-band frequencies. The Ku-band payload employs channels having a bandwidth of 36 MHz. The Intelsat 16 frequencies, polarization, and channel plan are provided in the Schedule S.

The coverage contours and performance characteristics of all Intelsat 16 beams are provided in the Schedule S. Exhibits 1 and 2 provide the beam parameters for the Intelsat 16 uplink and downlink beams, respectively.

## **2.3 Telemetry, Command and Ranging Subsystem**

The telemetry, command and ranging (“TC&R”) subsystem provides the following functions:

- 1) Acquisition, processing and transmission of spacecraft telemetry data;
- 2) Reception and retransmission of ground station generated ranging signals; and
- 3) Reception, processing and distribution of telecommands.

The Intelsat 16 command and telemetry channel frequencies are shown in Exhibit 3. The coverage patterns of the command and telemetry beams have gain contours that vary by less than 8 dB across the surface of the Earth and accordingly the gain at 8 dB below the peak falls beyond the edge of the Earth. Therefore, pursuant to Section 25.114(c)(4)(vi)(A) of the FCC’s rules, contours for these beams are not required to be provided and the associated GXT files have not been included in Schedule S. The Intelsat 16 command and telemetry subsystem performance is summarized in Exhibit 3.

## **2.4 Uplink Power Control Subsystem**

Intelsat 16 utilizes two Ku-band channels for uplink power control (“ULPC”), antenna tracking, and ranging. The coverage patterns of the ULPC beam has gain contours that vary by less than 8 dB across the surface of the Earth and accordingly the gain at 8 dB below the peak falls beyond the edge of the Earth. Therefore, pursuant to Section 25.114(c)(4)(vi)(A) of the FCC’s rules, contours for this beam are not required to be provided and the associated GXT file has not been included in Schedule S. The Intelsat 16 ULPC frequencies and subsystem performance are summarized in Exhibit 3.

## **2.5 Satellite Station-Keeping**

The spacecraft will be maintained within 0.05° of its nominal longitudinal position in the east-west direction. Accordingly, it will be in compliance with Section 25.210(j) of the Commission’s rules.

The attitude of the spacecraft will be maintained with accuracy consistent with the achievement of the specified communications performance, after taking into account all error sources (i.e., attitude perturbations, thermal distortions, misalignments, orbital tolerances and thruster perturbations, etc.).

## **3 Services**

Intelsat 16 is a general purpose communications satellite and has been designed to support various services offered within the Intelsat satellite system. Depending upon the needs of the users, the transponders on Intelsat 16 can accommodate television, radio, voice, and data communications. Typical communication services include:

- a) Compressed digital video
- b) High speed digital data
- c) Digital single channel per carrier (“SCPC”) data channels

Emission designators and allocated bandwidths for representative communication carriers are provided in Schedule S.

## **4 Power Flux Density**

The power flux density (“PFD”) limits for space stations operating in the 10950 – 11200 MHz band are contained in Section 25.208 of the Commission’s rules. With respect to the frequency band 10700 - 11450 MHz, there are PFD limits specified in No. 21.16 of the ITU Radio Regulations. Neither the Commission’s rules nor the ITU Radio Regulations specify any PFD

limits for the 11700 – 12200 MHz band applicable to geostationary satellites operating in the fixed satellite service.

The maximum PFD levels for the Intelsat 16 transmissions were calculated for the 10700– 11450 MHz bands. Since the Intelsat 16 telemetry and ULPC carriers are in the 11700 – 12200 MHz band where no PFD limits specified, PFD levels for this band were not calculated. The results are provided in Schedule S and show that the downlink power flux density levels of the Intelsat 16 carriers do not exceed the limits specified in Sections 25.208 of the Commission’s rules or the limits specified in No. 21.16 of the ITU Radio Regulations.

## **5 Emission Compliance**

Section 25.202(e) of the Commission’s rules requires that the carrier frequency of each space station transmitter be maintained within 0.002% of the reference frequency. Intelsat 16 is designed to be compliant with the provisions of this rule.

Intelsat will comply with the provisions of Section 25.202(f) of the Commission’s rules with regard to Intelsat 16 emissions.

## **6 Orbital Location**

Intelsat requests that it be assigned the 58.1° W.L. orbital location for Intelsat 16. The 58.1° W.L. location satisfies Intelsat 16 requirements for optimizing coverage, elevation angles, and service availability. Additionally, the location also ensures that the maximum operational, economic, and public interest benefits will be derived.

## **7 Coordination with Co-frequency Space Stations**

The impact of the Intelsat 16 emissions on adjacent satellites located at 56.1°W.L. and 60.1° W.L. was analyzed. The interference analysis was conducted for a number of representative carriers at Ku-band frequencies. It was assumed that there were hypothetical satellites having the same operating characteristics as Intelsat 16 at the 56.1° W.L. and 60.1° W.L. orbital locations.

For the satellite located at 56.1° W.L., it was assumed that the adjacent satellites were Intelsat 16, located at 58.1° W.L., and a hypothetical satellite having the same operating characteristics as Intelsat 16 located at 54.1° W.L.<sup>1</sup> For the satellite located at 60.1° W.L., it was assumed that the

---

<sup>1</sup> At the time of submission of this application, there are no satellites located at 54.1°W.L. The use of satellites at other locations the interference analysis would be inconsistent with a two-degree orbital separation environment and policy.

adjacent satellites were Intelsat 16, located at 58.1° W.L., and a hypothetical satellite having the same operating characteristics as Intelsat 16 located at 62.1° W.L.<sup>2</sup>

Other assumptions made for the interference analysis were as follows:

- a) In the plane of the geostationary satellite orbit, all transmitting and receiving earth station antennas have off-axis co-polar gains that are compliant with the limits specified in section 25.209(a) of the FCC rules.
- b) All transmitting and receiving earth stations have a cross-polarization isolation value of at least 30 dB within their main beam lobe.
- c) Rain attenuation predictions are derived using Recommendation ITU-R P.618.
- d) Increase in noise temperature of the receiving earth station due to rain is taken into account.
- e) For the cases where the transponder operates in a multi-carrier mode, the effects due to intermodulation interference are taken into account.

All assumptions and the results of the analysis are documented in Exhibits 4 and 5. The Intelsat 16 transmissions will comply with the levels contained in Sections 25.212(c) of the Commission's rules, as applicable, unless higher levels are coordinated with affected adjacent satellite operators within  $\pm 6^\circ$ . In any case, the uplink power density of the Intelsat 16 digital carriers will not exceed the levels specified below:

- |                       |              |
|-----------------------|--------------|
| a) 13750 – 14500 MHz: | -44.8 dBW/Hz |
| b) 12750 – 13250 MHz: | -46.5 dBW/Hz |

The downlink EIRP density of Intelsat 16 digital carriers will not exceed the levels specified below:

- |   |              |
|---|--------------|
| a) 10700 – 10950 and 11200 - 11450 MHz: | -20.1 dBW/Hz |
| b) 10950 – 11200 MHz                    | -22.0 dBW/Hz |
| c) 11700 – 12200:                       | -19.6 dBW/Hz |

## **8 Orbital Debris Mitigation Plan**

Intelsat is proactive in ensuring safe operation and disposal of this and all spacecraft under its control. The four elements of debris mitigation are addressed below.

### **8.1 Spacecraft Hardware Design**

---

<sup>2</sup> At the time of submission of this application, there are no satellites located at 60.1°W.L. The use of satellites at other locations the interference analysis would be inconsistent with a two-degree orbital separation environment and policy.

The spacecraft is designed such that no debris will be released during normal operations. Intelsat has assessed the probability of collision with meteoroids and other small debris (<1 cm diameter) and has taken the following steps to limit the effects of such collisions: (1) critical spacecraft components are located inside the protective body of the spacecraft and properly shielded; and (2) all spacecraft subsystems have redundant components to ensure no single-point failures. The spacecraft does not use any subsystems for end-of-life disposal that are not used for normal operations.

## **8.2 Minimizing Accidental Explosions**

Intelsat has assessed the probability of accidental explosions during and after completion of mission operations. The spacecraft is designed in a manner to minimize the potential for such explosions. Propellant tanks and thrusters are isolated using redundant valves and electrical power systems are shielded in accordance with standard industry practices. Intelsat will ensure the removal of all stored energy on the spacecraft by depleting all propellant tanks, venting all pressurized systems, and turning off all active units.

## **8.3 Safe Flight Profiles**

Intelsat has assessed and limited the probability of the space station becoming a source of debris as a result of collisions with large debris or other operational space stations. Once relocated to 58.1° W.L., Intelsat 16 will not be located at the same orbital location as another satellite or at an orbital location that has an overlapping station-keeping volume with another satellite.

During the relocation of Intelsat 16, Intelsat will take all the necessary steps to coordinate the move with other operators to minimize the risk of collision or interference between Intelsat 16 and any other satellite. Intelsat is not aware of any other FCC licensed system, or any other system applied for and under consideration by the FCC, that will have an overlapping station-keeping volume with Intelsat 16. Intelsat is also not aware of any system with an overlapping station-keeping volume with Intelsat 16 that is the subject of an ITU filing and that is either in orbit or progressing towards launch.

## **8.4 Post Mission Disposal**

At the end of the mission, Intelsat expects to dispose of the spacecraft by moving it to a planned minimum altitude of 300 kilometers above the geostationary arc. This altitude exceeds the minimum altitude established by the Inter-Agency Space Debris Coordination Committee (“IADC”) formula. Intelsat has reserved 6.8 kilograms of fuel for this purpose. The reserved fuel figure was determined by the spacecraft manufacturer and is provided for in the propellant budget. This figure was calculated taking into account the expected mass of the satellite at the end of life and the required delta-velocity to achieve the desired orbit. The fuel gauging uncertainty has been taken into account in these calculations.

In calculating the disposal orbit, Intelsat has used simplifying assumptions as permitted under the Commission's Orbital Debris Report and Order.<sup>3</sup> For reference, the effective area to mass ratio ( $C_r \cdot A/M$ ) of the Intelsat 16 spacecraft is 0.04 m<sup>2</sup>/kg, resulting in a minimum perigee disposal altitude under the IADC formula of at most 280.4 kilometers above the geostationary arc. Accordingly, the Intelsat 16 planned disposal orbit complies with the FCC's rules.

## **9 TC&R Control Earth Stations**

Intelsat will conduct TC&R operations through one or more of the following earth stations: Castle Rock, Colorado and Fillmore, California. Additionally, Intelsat is capable of remotely controlling Intelsat 16 from its facilities in McLean, VA.

---

<sup>3</sup> *Mitigation of Orbital Debris*, Second Report and Order, IB Docket No. 02-54, FCC 04-130 (rel. June 21, 2004).



# Certification Statement

---

I hereby certify that I am a technically qualified person and am familiar with Part 25 of the Commission's rules. The contents of this engineering statement were prepared by me or under my direct supervision and to the best of my knowledge are complete and accurate.

/s/ Candice DeVane

March 31, 2016

---

Candice DeVane

---

Date

Intelsat

Manager, Spectrum Policy

## EXHIBIT 1

### COMMUNICATION SUBSYSTEM UPLINK BEAM PARAMETERS

Beam Name	Ku-Band Linear	Ku-Band Linear	Ku-Band Linear	Ku-Band Linear
<b>Schedule S Beam ID</b>	BHUL	BVUL	MHUL	MVUL
<b>Frequency Band (MHz)</b>	12750-13250 & 13750-14000	12750-13250 & 13750-14000	13750 – 14500	13750 – 14500
<b>Polarization</b>	Horizontal	Vertical	Horizontal	Vertical
<b>Beam Peak Gain (dBi)</b>	38.4	38.4	38.6	38.6
<b>G/T (dB/K)</b>	11.3	11.3	11.5	11.5
<b>Minimum SFD-- (dBW/m<sup>2</sup>)</b>	-108.3	-108.3	-108.5	-108.5
<b>Maximum SFD-- (dBW/m<sup>2</sup>)</b>	-83.2	-83.6	-83.5	-83.5

## EXHIBIT 2

### COMMUNICATION SUBSYSTEM DOWNLINK BEAM PARAMETERS

Beam Name	Ku-Band Linear	Ku-Band Linear	Ku-Band Linear	Ku-Band Linear	Ku-Band Linear
<b>Schedule S Beam ID</b>	BHDL	BVDL	MHDL	MVDL	M2DL
<b>Frequency Band (MHz)</b>	10700 – 11450	10700 – 11450	11700 – 12200	11700 – 12200	11700 – 12200
<b>Polarization</b>	Horizontal	Vertical	Horizontal	Vertical	Vertical
<b>Peak Antenna Gain (dBi)</b>	36.9	36.9	36.6	36.6	39.6
<b>EIRP (dBW)</b>	54.5	54.5	54.2	54.2	57.2
<b>Maximum Beam Peak EIRP Density (dBW/4kHz)</b>	19.4	19.4	19.1	19.1	22.1

### EXHIBIT 3

#### TC&R SUBSYSTEM CHARACTERISTICS

Beam Name	Command Omni	Command Wide Coverage	Command Global	Command Global
Schedule S Beam ID	CMDO	CMDW	CMDH	CMDV
Frequencies (MHz)	13997.5	14499.5	13997.5 & 14499.5	13997.5 & 14499.5
Polarization	LHCP	LHCP	Horizontal	Vertical
Peak Antenna Gain (dBi)	3.0	13.0	20.3	20.3

Beam Name	Telemetry Omni	Telemetry Wide Coverage	Telemetry Global	ULPC	ULPC
Schedule S Beam ID	TLMO	TLMW	TLMH	UPCH	UPCV
Frequencies (MHz)	12198.25 & 12198.75	12198.25 & 12198.75	12198.25 & 12198.75	12119.75	11701.25
Polarization	RHCP	RHCP	Horizontal	Horizontal	Vertical
Peak Antenna Gain (dBi)	3.0	13.0	21.3	21.0	21.0
Maximum Channel EIRP (dBW)	6.4	13.4	13.1	15.6	15.6
Maximum Beam Peak EIRP Density (dBW/4kHz)	-11.6	-4.6	-4.9	10.6	10.6

*Note: RHCP: Right Hand Circular Polarization, LHCP: Left Hand Circular Polarization*

## EXHIBIT 4

### HYPOTHETICAL 56.1°W SATELLITE INTERFERENCE ANALYSIS

<b>UPLINK BEAM INFORMATION</b>				
Uplink Beam Name	Mexico	Mexico	Mexico	Mexico
Uplink Frequency (GHz)	13.75-14.5	13.75-14.5	13.75-14.5	13.75-14.5
Uplink Beam Polarization	Vertical/Horizontal	Vertical/Horizontal	Vertical/Horizontal	Vertical/Horizontal
Uplink Beam Peak G/T (dB/K)	11.5	11.5	11.5	11.5
Uplink Beam Peak SFD (dBW/m2)	-94.3	-88.3	-88.3	-88.3
Uplink Relative Contour Level (dB)	-6.0	-6.0	-6.0	-6.0
<b>DOWNLINK BEAM INFORMATION</b>				
Downlink Beam Name	Mexico	Mexico	Mexico	Mexico
Downlink Frequency (GHz)	11.7-12.2	11.7-12.2	11.7-12.2	11.7-12.2
Downlink Beam Polarization	Horizontal/Vertical	Horizontal/Vertical	Horizontal/Vertical	Horizontal/Vertical
Downlink Beam Peak EIRP (dBW)	54.2	54.2	54.2	54.2
Downlink Relative Contour Level (dB)	-6.0	-6.0	-6.0	-6.0
<b>ADJACENT SATELLITE 1</b>				
Satellite Name	Intelsat 16	Intelsat 16	Intelsat 16	Intelsat 16
Orbital Location	58.1 W	58.1 W	58.1 W	58.1 W
Uplink Power Density (dBW/Hz)	-44.8	-44.8	-44.8	-44.8
Beam Peak Downlink EIRP Density (dBW/Hz)	-19.6	-19.6	-19.6	-19.6
<b>ADJACENT SATELLITE 2</b>				
Satellite Name	Hyp 54.1 W	Hyp 54.1 W	Hyp 54.1 W	Hyp 54.1 W
Orbital Location	54.1 W	54.1 W	54.1 W	54.1 W
Uplink Power Density (dBW/Hz)	-50.0	-50.0	-50.0	-50.0
Beam Peak Downlink EIRP Density (dBW/Hz)	-26.0	-26.0	-26.0	-26.0
<b>CARRIER INFORMATION</b>				
Carrier ID	36M0G7W	8M25G7W	1M54G7W	222KG7W
Carrier Modulation	QPSK	QPSK	QPSK	QPSK
Information Rate(kbps)	36860	8.448	1024	256
Code Rate	3/4x188/203	3/4	1/2	3/4
Occupied Bandwidth(kHz)	26664.7	6111.3	1232.9	170.7
Allocated Bandwidth(kHz)	36000	8250.5	1541.5	239
Minimum C/N, Rain (dB)	7.3	7.3	1.6	4.6
<b>UPLINK EARTH STATION</b>				
Earth Station Diameter (meters)	1.8	2.4	2.4	2.4
Earth Station Gain (dBi)	46.2	48.7	48.7	48.7
<b>DOWNLINK EARTH STATION</b>				
Earth Station Diameter (meters)	1.8	2.4	1.8	1.2
Earth Station Gain (dBi)	44.5	47.0	44.5	40.9
Earth Station G/T (dB/K)	23.3	25.0	23.3	19.8
<b>COMPOSITE LINK PERFORMANCE</b>				
C/N Thermal Uplink (dB)	18.2	23.3	21.2	22.8
Uplink Interference C/I (dB)	29.1	31.4	25.6	27.2
Uplink Adjacent Satellite C/I (dB)	14.3	14.5	12.4	14.0
Intermodulation C/IM (dB)	----	37.9	35.7	39.8
Downlink Thermal C/N (dB)	18.9	16.0	8.7	13.8
Downlink Interference C/I (dB)	28.4	25.0	21.6	22.1
Downlink Adjacent Satellite C/I (dB)	24.0	12.9	4.8	10.0
Subtotal C/N (dB)	11.4	9.2	2.7	7.1
Antenna Mispointing and Other Losses (dB)	0.3	0.3	0.3	0.3
Total C/N (dB)	11.1	8.9	2.4	6.8
Minimum Required C/N (dB)	7.3	7.3	1.6	4.6
<b>CARRIER DENSITY LEVELS</b>				
Uplink Power Density (dBW/Hz)	-55.6	-51.6	-53.6	-52.0
Downlink EIRP Density At Beam Peak (dBW/Hz)	-30.3	-26.1	-28.1	-26.5

<b>UPLINK BEAM INFORMATION</b>				
Uplink Beam Name	Mexico	Mexico	Mexico	Mexico
Uplink Frequency (GHz)	13.75-14.5	13.75-14.5	13.75-14.5	13.75-14.5
Uplink Beam Polarization	Vertical/Horizontal	Vertical/Horizontal	Vertical/Horizontal	Vertical/Horizontal
Uplink Beam Peak G/T (dB/K)	11.5	11.5	11.5	11.5
Uplink Beam Peak SFD (dBW/m2)	-94.3	-88.3	-88.3	-88.3
Uplink Relative Contour Level (dB)	-6.0	-6.0	-6.0	-6.0
<b>DOWNLINK BEAM INFORMATION</b>				
Downlink Beam Name	Mexico 2	Mexico 2	Mexico 2	Mexico 2
Downlink Frequency (GHz)	11.7-12.2	11.7-12.2	11.7-12.2	11.7-12.2
Downlink Beam Polarization	Horizontal/Vertical	Horizontal/Vertical	Horizontal/Vertical	Horizontal/Vertical
Downlink Beam Peak EIRP (dBW)	57.2	57.2	57.2	57.2
Downlink Relative Contour Level (dB)	-6.0	-6.0	-6.0	-6.0
<b>ADJACENT SATELLITE 1</b>				
Satellite Name	Intelsat 16	Intelsat 16	Intelsat 16	Intelsat 16
Orbital Location	58.1 W	58.1 W	58.1 W	58.1 W
Uplink Power Density (dBW/Hz)	-44.8	-44.8	-44.8	-44.8
Beam Peak Downlink EIRP Density (dBW/Hz)	-19.6	-19.6	-19.6	-19.6
<b>ADJACENT SATELLITE 2</b>				
Satellite Name	Hyp 54.1 W	Hyp 54.1 W	Hyp 54.1 W	Hyp 54.1 W
Orbital Location	54.1 W	54.1 W	54.1 W	54.1 W
Uplink Power Density (dBW/Hz)	-50.0	-50.0	-50.0	-50.0
Beam Peak Downlink EIRP Density (dBW/Hz)	-26.0	-26.0	-26.0	-26.0
<b>CARRIER INFORMATION</b>				
Carrier ID	36M0G7W	8M25G7W	1M54G7W	222KG7W
Carrier Modulation	QPSK	QPSK	QPSK	QPSK
Information Rate(kbps)	36860	8.448	1024	256
Code Rate	3/4x188/203	3/4	1/2	3/4
Occupied Bandwidth(kHz)	26664.7	6111.3	1232.9	170.7
Allocated Bandwidth(kHz)	36000	8250.5	1541.5	239
Minimum C/N, Rain (dB)	7.3	7.3	1.6	4.6
<b>UPLINK EARTH STATION</b>				
Earth Station Diameter (meters)	1.8	2.4	2.4	2.4
Earth Station Gain (dBi)	46.2	48.7	48.7	48.7
<b>DOWNLINK EARTH STATION</b>				
Earth Station Diameter (meters)	1.8	2.4	1.8	1.2
Earth Station Gain (dBi)	44.5	47.0	44.5	40.9
Earth Station G/T (dB/K)	23.3	25.0	23.3	19.8
<b>COMPOSITE LINK PERFORMANCE</b>				
C/N Thermal Uplink (dB)	18.2	23.3	21.2	22.8
Uplink Interference C/I (dB)	29.1	31.4	25.6	27.2
Uplink Adjacent Satellite C/I (dB)	14.3	14.5	12.4	14.0
Intermodulation C/IM (dB)	----	37.9	35.7	39.8
Downlink Thermal C/N (dB)	18.9	16.0	8.7	13.8
Downlink Interference C/I (dB)	28.4	25.0	21.6	22.1
Downlink Adjacent Satellite C/I (dB)	24.0	12.9	4.8	10.0
Subtotal C/N (dB)	11.4	9.2	2.7	7.1
Antenna Mispointing and Other Losses (dB)	0.3	0.3	0.3	0.3
Total C/N (dB)	11.1	8.9	2.4	6.8
Minimum Required C/N (dB)	7.3	7.3	1.6	4.6
<b>CARRIER DENSITY LEVELS</b>				
Uplink Power Density (dBW/Hz)	-55.6	-51.6	-53.6	-52.0
Downlink EIRP Density At Beam Peak (dBW/Hz)	-30.3	-26.1	-28.1	-26.5

<b>UPLINK BEAM INFORMATION</b>				
Uplink Beam Name	Brazil	Brazil	Brazil	Brazil
Uplink Frequency (GHz)	12.75-13.25 & 13.75-14.0	12.75-13.25 & 13.75-14.0	12.75-13.25 & 13.75-14.0	12.75-13.25 & 13.75-14.0
Uplink Beam Polarization	Vertical/Horizontal	Vertical/Horizontal	Vertical/Horizontal	Vertical/Horizontal
Uplink Beam Peak G/T (dB/K)	11.3	11.3	11.3	11.3
Uplink Beam Peak SFD (dBW/m2)	-94.3	-88.3	-88.3	-88.3
Uplink Relative Contour Level (dB)	-6.0	-6.0	-6.0	-6.0
<b>DOWNLINK BEAM INFORMATION</b>				
Downlink Beam Name	Brazil	Brazil	Brazil	Brazil
Downlink Frequency (GHz)	10.7 - 11.45	10.7 - 11.45	10.7 - 11.45	10.7 - 11.45
Downlink Beam Polarization	Horizontal/Vertical	Horizontal/Vertical	Horizontal/Vertical	Horizontal/Vertical
Downlink Beam Peak EIRP (dBW)	54.5	54.5	54.5	54.5
Downlink Relative Contour Level (dB)	-6.0	-6.0	-6.0	-6.0
<b>ADJACENT SATELLITE 1</b>				
Satellite Name	Intelsat 16	Intelsat 16	Intelsat 16	Intelsat 16
Orbital Location	58.1 W	58.1 W	58.1 W	58.1 W
Uplink Power Density (dBW/Hz)	-44.8	-44.8	-44.8	-44.8
Beam Peak Downlink EIRP Density (dBW/Hz)	-19.6	-19.6	-19.6	-19.6
<b>ADJACENT SATELLITE 2</b>				
Satellite Name	Hyp 54.1 W	Hyp 54.1 W	Hyp 54.1 W	Hyp 54.1 W
Orbital Location	54.1 W	54.1 W	54.1 W	54.1 W
Uplink Power Density (dBW/Hz)	-50.0	-50.0	-50.0	-50.0
Beam Peak Downlink EIRP Density (dBW/Hz)	-26.0	-26.0	-26.0	-26.0
<b>CARRIER INFORMATION</b>				
Carrier ID	36M0G7W	8M25G7W	1M54G7W	222KG7W
Carrier Modulation	QPSK	QPSK	QPSK	QPSK
Information Rate(kbps)	36860	8.448	1024	256
Code Rate	3/4x188/203	3/4	1/2	3/4
Occupied Bandwidth(kHz)	26664.7	6111.3	1232.9	170.7
Allocated Bandwidth(kHz)	36000	8250.5	1541.5	239
Minimum C/N, Rain (dB)	7.3	7.3	1.6	4.6
<b>UPLINK EARTH STATION</b>				
Earth Station Diameter (meters)	1.8	2.4	2.4	2.4
Earth Station Gain (dBi)	46.2	48.7	48.7	48.7
<b>DOWNLINK EARTH STATION</b>				
Earth Station Diameter (meters)	1.8	2.4	1.8	1.2
Earth Station Gain (dBi)	44.5	47.0	44.5	40.9
Earth Station G/T (dB/K)	23.3	25.0	23.3	19.8
<b>COMPOSITE LINK PERFORMANCE</b>				
C/N Thermal Uplink (dB)	18.2	23.3	21.2	22.8
Uplink Interference C/I (dB)	29.1	31.4	25.6	27.2
Uplink Adjacent Satellite C/I (dB)	14.3	14.5	12.4	14.0
Intermodulation C/I (dB)	----	37.9	35.7	39.8
Downlink Thermal C/N (dB)	18.9	16.0	8.7	13.8
Downlink Interference C/I (dB)	28.4	25.0	21.6	22.1
Downlink Adjacent Satellite C/I (dB)	24.0	12.9	4.8	10.0
Subtotal C/N (dB)	11.4	9.2	2.7	7.1
Antenna Mispointing and Other Losses (dB)	0.3	0.3	0.3	0.3
Total C/N (dB)	11.1	8.9	2.4	6.8
Minimum Required C/N (dB)	7.3	7.3	1.6	4.6
<b>CARRIER DENSITY LEVELS</b>				
Uplink Power Density (dBW/Hz)	-55.6	-51.6	-53.6	-52.0
Downlink EIRP Density At Beam Peak (dBW/Hz)	-30.3	-26.1	-28.1	-26.5

## EXHIBIT 5

### HYPOTHETICAL 60.1°W SATELLITE INTERFERENCE ANALYSIS

<b>UPLINK BEAM INFORMATION</b>				
Uplink Beam Name	Mexico	Mexico	Mexico	Mexico
Uplink Frequency (GHz)	13.75-14.5	13.75-14.5	13.75-14.5	13.75-14.5
Uplink Beam Polarization	Vertical/Horizontal	Vertical/Horizontal	Vertical/Horizontal	Vertical/Horizontal
Uplink Beam Peak G/T (dB/K)	11.5	11.5	11.5	11.5
Uplink Beam Peak SFD (dBW/m2)	-94.3	-88.3	-88.3	-88.3
Uplink Relative Contour Level (dB)	-6.0	-6.0	-6.0	-6.0
<b>DOWNLINK BEAM INFORMATION</b>				
Downlink Beam Name	Mexico	Mexico	Mexico	Mexico
Downlink Frequency (GHz)	11.7-12.2	11.7-12.2	11.7-12.2	11.7-12.2
Downlink Beam Polarization	Horizontal/Vertical	Horizontal/Vertical	Horizontal/Vertical	Horizontal/Vertical
Downlink Beam Peak EIRP (dBW)	54.2	54.2	54.2	54.2
Downlink Relative Contour Level (dB)	-6.0	-6.0	-6.0	-6.0
<b>ADJACENT SATELLITE 1</b>				
Satellite Name	Intelsat 16	Intelsat 16	Intelsat 16	Intelsat 16
Orbital Location	58.1 W	58.1 W	58.1 W	58.1 W
Uplink Power Density (dBW/Hz)	-44.8	-44.8	-44.8	-44.8
Beam Peak Downlink EIRP Density (dBW/Hz)	-19.6	-19.6	-19.6	-19.6
<b>ADJACENT SATELLITE 2</b>				
Satellite Name	Hyp 62.1 W	Hyp 62.1 W	Hyp 62.1 W	Hyp 62.1 W
Orbital Location	62.1 W	62.1 W	62.1 W	62.1 W
Uplink Power Density (dBW/Hz)	-50.0	-50.0	-50.0	-50.0
Beam Peak Downlink EIRP Density (dBW/Hz)	-26.0	-26.0	-26.0	-26.0
<b>CARRIER INFORMATION</b>				
Carrier ID	36M0G7W	8M25G7W	1M54G7W	222KG7W
Carrier Modulation	QPSK	QPSK	QPSK	QPSK
Information Rate(kbps)	36860	8.448	1024	256
Code Rate	3/4x188/203	3/4	1/2	3/4
Occupied Bandwidth(kHz)	26664.7	6111.3	1232.9	170.7
Allocated Bandwidth(kHz)	36000	8250.5	1541.5	239
Minimum C/N, Rain (dB)	7.3	7.3	1.6	4.6
<b>UPLINK EARTH STATION</b>				
Earth Station Diameter (meters)	1.8	2.4	2.4	2.4
Earth Station Gain (dBi)	46.2	48.7	48.7	48.7
<b>DOWNLINK EARTH STATION</b>				
Earth Station Diameter (meters)	1.8	2.4	1.8	1.2
Earth Station Gain (dBi)	44.5	47.0	44.5	40.9
Earth Station G/T (dB/K)	23.3	25.0	23.3	19.8
<b>COMPOSITE LINK PERFORMANCE</b>				
C/N Thermal Uplink (dB)	18.2	23.3	21.2	22.8
Uplink Interference C/I (dB)	29.1	31.4	25.6	27.2
Uplink Adjacent Satellite C/I (dB)	14.3	14.5	12.4	14.0
Intermodulation C/IM (dB)	----	37.9	35.7	39.8
Downlink Thermal C/N (dB)	18.9	16.0	8.7	13.8
Downlink Interference C/I (dB)	28.4	25.0	21.6	22.1
Downlink Adjacent Satellite C/I (dB)	24.0	12.9	4.8	10.0
Subtotal C/N (dB)	11.4	9.2	2.7	7.1
Antenna Mispointing and Other Losses (dB)	0.3	0.3	0.3	0.3
Total C/N (dB)	11.1	8.9	2.4	6.8
Minimum Required C/N (dB)	7.3	7.3	1.6	4.6
<b>CARRIER DENSITY LEVELS</b>				
Uplink Power Density (dBW/Hz)	-55.6	-51.6	-53.6	-52.0
Downlink EIRP Density At Beam Peak (dBW/Hz)	-30.3	-26.1	-28.1	-26.5

<b>UPLINK BEAM INFORMATION</b>				
Uplink Beam Name	Mexico	Mexico	Mexico	Mexico
Uplink Frequency (GHz)	13.75-14.5	13.75-14.5	13.75-14.5	13.75-14.5
Uplink Beam Polarization	Vertical/Horizontal	Vertical/Horizontal	Vertical/Horizontal	Vertical/Horizontal
Uplink Beam Peak G/T (dB/K)	11.5	11.5	11.5	11.5
Uplink Beam Peak SFD (dBW/m2)	-94.3	-88.3	-88.3	-88.3
Uplink Relative Contour Level (dB)	-6.0	-6.0	-6.0	-6.0
<b>DOWNLINK BEAM INFORMATION</b>				
Downlink Beam Name	Mexico 2	Mexico 2	Mexico 2	Mexico 2
Downlink Frequency (GHz)	11.7-12.2	11.7-12.2	11.7-12.2	11.7-12.2
Downlink Beam Polarization	Horizontal/Vertical	Horizontal/Vertical	Horizontal/Vertical	Horizontal/Vertical
Downlink Beam Peak EIRP (dBW)	57.2	57.2	57.2	57.2
Downlink Relative Contour Level (dB)	-6.0	-6.0	-6.0	-6.0
<b>ADJACENT SATELLITE 1</b>				
Satellite Name	Intelsat 16	Intelsat 16	Intelsat 16	Intelsat 16
Orbital Location	58.1 W	58.1 W	58.1 W	58.1 W
Uplink Power Density (dBW/Hz)	-44.8	-44.8	-44.8	-44.8
Beam Peak Downlink EIRP Density (dBW/Hz)	-19.6	-19.6	-19.6	-19.6
<b>ADJACENT SATELLITE 2</b>				
Satellite Name	Hyp 62.1 W	Hyp 62.1 W	Hyp 62.1 W	Hyp 62.1 W
Orbital Location	62.1 W	62.1 W	62.1 W	62.1 W
Uplink Power Density (dBW/Hz)	-50.0	-50.0	-50.0	-50.0
Beam Peak Downlink EIRP Density (dBW/Hz)	-26.0	-26.0	-26.0	-26.0
<b>CARRIER INFORMATION</b>				
Carrier ID	36M0G7W	8M25G7W	1M54G7W	222KG7W
Carrier Modulation	QPSK	QPSK	QPSK	QPSK
Information Rate(kbps)	36860	8.448	1024	256
Code Rate	3/4x188/203	3/4	1/2	3/4
Occupied Bandwidth(kHz)	26664.7	6111.3	1232.9	170.7
Allocated Bandwidth(kHz)	36000	8250.5	1541.5	239
Minimum C/N, Rain (dB)	7.3	7.3	1.6	4.6
<b>UPLINK EARTH STATION</b>				
Earth Station Diameter (meters)	1.8	2.4	2.4	2.4
Earth Station Gain (dBi)	46.2	48.7	48.7	48.7
<b>DOWNLINK EARTH STATION</b>				
Earth Station Diameter (meters)	1.8	2.4	1.8	1.2
Earth Station Gain (dBi)	44.5	47.0	44.5	40.9
Earth Station G/T (dB/K)	23.3	25.0	23.3	19.8
<b>COMPOSITE LINK PERFORMANCE</b>				
C/N Thermal Uplink (dB)	18.2	23.3	21.2	22.8
Uplink Interference C/I (dB)	29.1	31.4	25.6	27.2
Uplink Adjacent Satellite C/I (dB)	14.3	14.5	12.4	14.0
Intermodulation C/IM (dB)	----	37.9	35.7	39.8
Downlink Thermal C/N (dB)	18.9	16.0	8.7	13.8
Downlink Interference C/I (dB)	28.4	25.0	21.6	22.1
Downlink Adjacent Satellite C/I (dB)	24.0	12.9	4.8	10.0
Subtotal C/N (dB)	11.4	9.2	2.7	7.1
Antenna Mispointing and Other Losses (dB)	0.3	0.3	0.3	0.3
Total C/N (dB)	11.1	8.9	2.4	6.8
Minimum Required C/N (dB)	7.3	7.3	1.6	4.6
<b>CARRIER DENSITY LEVELS</b>				
Uplink Power Density (dBW/Hz)	-55.6	-51.6	-53.6	-52.0
Downlink EIRP Density At Beam Peak (dBW/Hz)	-30.3	-26.1	-28.1	-26.5



<b>UPLINK BEAM INFORMATION</b>				
Uplink Beam Name	Brazil	Brazil	Brazil	Brazil
Uplink Frequency (GHz)	12.75-13.25 & 13.75-14.0	12.75-13.25 & 13.75-14.0	12.75-13.25 & 13.75-14.0	12.75-13.25 & 13.75-14.0
Uplink Beam Polarization	Vertical/Horizontal	Vertical/Horizontal	Vertical/Horizontal	Vertical/Horizontal
Uplink Beam Peak G/T (dB/K)	11.3	11.3	11.3	11.3
Uplink Beam Peak SFD (dBW/m2)	-94.3	-88.3	-88.3	-88.3
Uplink Relative Contour Level (dB)	-6.0	-6.0	-6.0	-6.0
<b>DOWNLINK BEAM INFORMATION</b>				
Downlink Beam Name	Brazil	Brazil	Brazil	Brazil
Downlink Frequency (GHz)	10.7 - 11.45	10.7 - 11.45	10.7 - 11.45	10.7 - 11.45
Downlink Beam Polarization	Horizontal/Vertical	Horizontal/Vertical	Horizontal/Vertical	Horizontal/Vertical
Downlink Beam Peak EIRP (dBW)	54.5	54.5	54.5	54.5
Downlink Relative Contour Level (dB)	-6.0	-6.0	-6.0	-6.0
<b>ADJACENT SATELLITE 1</b>				
Satellite Name	Intelsat 16	Intelsat 16	Intelsat 16	Intelsat 16
Orbital Location	58.1 W	58.1 W	58.1 W	58.1 W
Uplink Power Density (dBW/Hz)	-44.8	-44.8	-44.8	-44.8
Beam Peak Downlink EIRP Density (dBW/Hz)	-19.6	-19.6	-19.6	-19.6
<b>ADJACENT SATELLITE 2</b>				
Satellite Name	Hyp 62.1 W	Hyp 62.1 W	Hyp 62.1 W	Hyp 62.1 W
Orbital Location	62.1 W	62.1 W	62.1 W	62.1 W
Uplink Power Density (dBW/Hz)	-50.0	-50.0	-50.0	-50.0
Beam Peak Downlink EIRP Density (dBW/Hz)	-26.0	-26.0	-26.0	-26.0
<b>CARRIER INFORMATION</b>				
Carrier ID	36M0G7W	8M25G7W	1M54G7W	222KG7W
Carrier Modulation	QPSK	QPSK	QPSK	QPSK
Information Rate(kbps)	36860	8.448	1024	256
Code Rate	3/4x188/203	3/4	1/2	3/4
Occupied Bandwidth(kHz)	26664.7	6111.3	1232.9	170.7
Allocated Bandwidth(kHz)	36000	8250.5	1541.5	239
Minimum C/N, Rain (dB)	7.3	7.3	1.6	4.6
<b>UPLINK EARTH STATION</b>				
Earth Station Diameter (meters)	1.8	2.4	2.4	2.4
Earth Station Gain (dBi)	46.2	48.7	48.7	48.7
<b>DOWNLINK EARTH STATION</b>				
Earth Station Diameter (meters)	1.8	2.4	1.8	1.2
Earth Station Gain (dBi)	44.5	47.0	44.5	40.9
Earth Station G/T (dB/K)	23.3	25.0	23.3	19.8
<b>COMPOSITE LINK PERFORMANCE</b>				
C/N Thermal Uplink (dB)	18.2	23.3	21.2	22.8
Uplink Interference C/I (dB)	29.1	31.4	25.6	27.2
Uplink Adjacent Satellite C/I (dB)	14.3	14.5	12.4	14.0
Intermodulation C/I (dB)	----	37.9	35.7	39.8
Downlink Thermal C/N (dB)	18.9	16.0	8.7	13.8
Downlink Interference C/I (dB)	28.4	25.0	21.6	22.1
Downlink Adjacent Satellite C/I (dB)	24.0	12.9	4.8	10.0
Subtotal C/N (dB)	11.4	9.2	2.7	7.1
Antenna Mispointing and Other Losses (dB)	0.3	0.3	0.3	0.3
Total C/N (dB)	11.1	8.9	2.4	6.8
Minimum Required C/N (dB)	7.3	7.3	1.6	4.6
<b>CARRIER DENSITY LEVELS</b>				
Uplink Power Density (dBW/Hz)	-55.6	-51.6	-53.6	-52.0
Downlink EIRP Density At Beam Peak (dBW/Hz)	-30.3	-26.1	-28.1	-26.5