



312 File Number: **SATMOD2017030100024**

---

## Filing Description

Question	Response
Description	This Schedule S is submitted in support of the modification application of SES Americom, Inc. seeking authority for the re-orientation of the Ka-band transponders on AMC-15 at 105.05 W.L.

---

**Satellite  
Information**

Question	Response
Select Orbit Type	GSO
Space Station or Satellite Network Name	AMC-15
Estimated Lifetime of Satellite(s) From Date of Launch	15 Years
Will the space station(s) operate on a Common Carrier basis?	No

## Operating Frequency Bands (9)

Nature of service	Description	Frequency Band (s)	Mode Type
Fixed-Satellite Service		11700.0 MHz -12200.0 MHz	Transmit
Fixed-Satellite Service		14000.0 MHz -14500.0 MHz	Receive
Fixed-Satellite Service		19700.0 MHz -20200.0 MHz	Transmit
Fixed-Satellite Service		29500.0 MHz -30000.0 MHz	Receive
Fixed-Satellite Service		28400.0 MHz -28600.0 MHz	Receive
Direct-to-Home in the Fixed-Satellite Service		19700.0 MHz -20200.0 MHz	Transmit
Direct-to-Home in the Fixed-Satellite Service		18580.0 MHz -18800.0 MHz	Transmit
Fixed-Satellite Service		18580.0 MHz -18800.0 MHz	Transmit
Direct-to-Home in the Fixed-Satellite Service		11700.0 MHz -12200.0 MHz	Transmit

## Orbital Information For Geostationary Satellites

Section	Question	Response
<b>Orbital Longitude Information</b>	Orbital Longitude	105.0 degrees
	Hemisphere of Orbital Longitude	W
<b>Longitudinal Tolerance or East /West Station-Keeping</b>	Toward West	0.05 degrees
	Toward East	0.05 degrees
<b>Inclination Excursion or North /South Station-Keeping Tolerance</b>	Inclination Excursion or North /South Station-Keeping Tolerance	0.05 degrees
<b>Antenna Axis Attitude Accuracy</b>	Roll	0.11 degrees
	Pitch	0.09 degrees
	Yaw	0.0 degrees

## Receiving Beams 1:

Question	Response
Beam ID	KURV
Receive Beam Frequency	14000.0 MHz -14500.0 MHz
Beam Type	Fixed
Polarization	V
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
G/T at Max. Gain Point	6.06 dB/K
Min. Saturation Flux Density	-99.06 dBW/m2
Max. Saturation Flux Density	-81.06 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Continental United States, Alaska, Hawaii, Caribbean, Mexico

## Receiving Beams 2:

Question	Response
Beam ID	TC1
Receive Beam Frequency	14001.1 MHz -14001.9 MHz
Beam Type	Fixed
Polarization	V
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees

Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
G/T at Max. Gain Point	0.0 dB/K
Min. Saturation Flux Density	-1.0 dBW/m2
Max. Saturation Flux Density	0.0 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Continental United States, Alaska, Hawaii, Caribbean, Mexico

**Receiving Beams 3:**

Question	Response
Beam ID	KURH
Receive Beam Frequency	14000.0 MHz -14500.0 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	33.3 dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
G/T at Max. Gain Point	5.98 dB/K
Min. Saturation Flux Density	-98.98 dBW/m2
Max. Saturation Flux Density	-80.98 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Continental United States, Alaska, Hawaii, Caribbean, Mexico

## Receiving Beams 4:

Question	Response
Beam ID	1AU
Receive Beam Frequency	28400.0 MHz -28600.0 MHz
Beam Type	Spot
Polarization	LHCP
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
G/T at Max. Gain Point	17.34 dB/K
Min. Saturation Flux Density	-116.8 dBW/m2
Max. Saturation Flux Density	-93.96 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Continental United States, Caribbean, Mexico, Central America

## Receiving Beams 5:

Question	Response
Beam ID	2AU
Receive Beam Frequency	29500.0 MHz -30000.0 MHz
Beam Type	Spot
Polarization	LHCP
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	

---

Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
G/T at Max. Gain Point	17.34 dB/K
Min. Saturation Flux Density	-116.8 dBW/m <sup>2</sup>
Max. Saturation Flux Density	-93.96 dBW/m <sup>2</sup>
Co- or Cross Polar Mode	C
Service Area Description	Continental United States, Caribbean, Mexico, Central America

---



## Receiving Channels (37)

Channel ID	Channel Bandwidth (MHz)	Center Frequency s (MHz)	Feeder Link, Service Link or TT&C
KU11	36.0	14220.0	Service Link
Ka6	125.0	29687.5	Service Link
Ka8	125.0	29812.5	Service Link
Ka9	125.0	29812.5	Service Link
Ka1	125.0	28500.5	Service Link
Ka2	125.0	28500.5	Service Link
Ka7	125.0	29687.5	Service Link
KU23	36.0	14460.0	Service Link
KU21	36.0	14420.0	Service Link
KU20	36.0	14400.0	Service Link
KU15	36.0	14300.0	Service Link
KU16	36.0	14320.0	Service Link
KU14	36.0	14280.0	Service Link
KU13	36.0	14260.0	Service Link
KU12	36.0	14240.0	Service Link
KU10	36.0	14200.0	Service Link
KU1	36.0	14020.0	Service Link
KU22	36.0	14400.0	Service Link
KU2	36.0	14040.0	Service Link
KU19	36.0	14380.0	Service Link
KU18	36.0	14360.0	Service Link
KU17	36.0	14340.0	Service Link
TC1	0.8	14001.5	TT&C
KU9	36.0	14180.0	Service Link

<b>KU8</b>	36.0	14160.0	Service Link
<b>Ka3</b>	125.0	29562.5	Service Link
<b>Ka4</b>	125.0	29562.5	Service Link
<b>KU7</b>	36.0	14140.0	Service Link
<b>KU6</b>	36.0	14120.0	Service Link
<b>KU5</b>	36.0	14100.0	Service Link
<b>KU4</b>	36.0	14080.0	Service Link
<b>KU3</b>	36.0	14060.0	Service Link
<b>Ka10</b>	125.0	29812.5	Service Link
<b>Ka5</b>	125.0	29562.5	Service Link
<b>Ka11</b>	125.0	29937.5	Service Link
<b>Ka12</b>	125.0	29937.5	Service Link
<b>KU24</b>	36.0	14480.0	Service Link

## Transmitting Beams 1:

Question	Response
Beam ID	KUTH
Transmit Beam Frequency	11700.0 MHz -12200.0 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
Max. Transmit EIRP Density	-23.65 dBW/Hz
Max. Transmit EIRP	51.91 dBW
Co- or Cross Polar Mode	C
Service Area Description	Continental United States, Alaska, Hawaii, Caribbean, Mexico

### Max. Power Flux Density

Information not provided.

## Transmitting Beams 2:

Question	Response
Beam ID	TM1
Transmit Beam Frequency	11701.675 MHz -11702.325 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees

Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
Max. Transmit EIRP Density	-42.53 dBW/Hz
Max. Transmit EIRP	15.6 dBW
Co- or Cross Polar Mode	C
Service Area Description	Continental United States, Mexico, Caribbean, Central America

### Max. Power Flux Density

Information not provided.

### Transmitting Beams 3:

Question	Response
Beam ID	TM2
Transmit Beam Frequency	12197.675 MHz -12198.325 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
Max. Transmit EIRP Density	-42.43 dBW/Hz
Max. Transmit EIRP	15.7 dBW
Co- or Cross Polar Mode	C
Service Area Description	Continental United States, Mexico, Caribbean, Central America

### Max. Power Flux Density

Information not provided.

## Transmitting Beams 4:

Question	Response
Beam ID	TM3
Transmit Beam Frequency	18581.675 MHz -18582.325 MHz
Beam Type	Fixed
Polarization	RHCP
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-42.43 dBW/Hz
Max. Transmit EIRP	15.7 dBW
Co- or Cross Polar Mode	C
Service Area Description	Continental United States, Mexico, Caribbean, Central America

## Max. Power Flux Density

	* 0° - 5° (dBW/m <sup>2</sup> ) /BW:	* 5° - 10° (dBW/m <sup>2</sup> ) /BW:	* 10° - 15° (dBW/m <sup>2</sup> ) /BW:	* 15° - 20° (dBW/m <sup>2</sup> ) /BW:	* 20° - 25° (dBW/m <sup>2</sup> ) /BW:	* 25° - 90° (dBW/m <sup>2</sup> ) /BW:
<b>1.0 MHz</b>	-143.7	-143.7	-143.7	-143.7	-143.7	-143.7

## Transmitting Beams 5:

Question	Response
Beam ID	KUTV
Transmit Beam Frequency	11700.0 MHz -12200.0 MHz

Beam Type	Fixed
Polarization	V
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
Max. Transmit EIRP Density	-22.84 dBW/Hz
Max. Transmit EIRP	52.72 dBW
Co- or Cross Polar Mode	C
Service Area Description	Continental United States, Alaska, Hawaii, Caribbean, Mexico

### Max. Power Flux Density

Information not provided.

### Transmitting Beams 6:

Question	Response
Beam ID	1BD
Transmit Beam Frequency	18580.0 MHz -18800.0 MHz
Beam Type	Spot
Polarization	RHCP
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-19.22 dBW/Hz

Max. Transmit EIRP	61.74 dBW
Co- or Cross Polar Mode	C
Service Area Description	Continental United States, Caribbean, Mexico, Central America

### Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
	(dBW/m <sup>2</sup>	(dBW/m <sup>2</sup>	(dBW/m <sup>2</sup>	(dBW/m <sup>2</sup>	(dBW/m <sup>2</sup>	(dBW/m <sup>2</sup>
*	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
<b>1.0 MHz</b>	-141.7	-141.6	-141.5	-140.0	-132.8	-120.5

### Transmitting Beams 7:

Question	Response
Beam ID	2BD
Transmit Beam Frequency	19700.0 MHz -20200.0 MHz
Beam Type	Spot
Polarization	RHCP
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-19.22 dBW/Hz
Max. Transmit EIRP	61.74 dBW
Co- or Cross Polar Mode	C
Service Area Description	Continental United States, Caribbean, Mexico, Central America

## Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
*	(dBW/m <sup>2</sup> )	(dBW/m <sup>2</sup> )	(dBW/m <sup>2</sup> )	(dBW/m <sup>2</sup> )	(dBW/m <sup>2</sup> )	(dBW/m <sup>2</sup> )
BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
<b>1.0</b> <b>MHz</b>	-141.7	-141.6	-141.5	-140.0	-132.8	-120.5

---



## Transmitting Channels (39)

Channel ID	Channel Bandwidth (MHz)	Center Frequency s (MHz)	Feeder Link, Service Link or TT&C
KU13	36.0	11960.0	Service Link
KU12	36.0	11940.0	Service Link
KU11	36.0	11920.0	Service Link
TM2	0.65	12198.0	TT&C
KU2	36.0	11740.0	Service Link
TM3	0.65	18582.0	TT&C
KU8	36.0	11860.0	Service Link
KU7	36.0	11840.0	Service Link
Ka6	125.0	19887.5	Service Link
Ka7	125.0	19887.5	Service Link
Ka11	125.0	20137.5	Service Link
KU23	36.0	12160.0	Service Link
KU22	36.0	12140.0	Service Link
KU19	36.0	12080.0	Service Link
KU5	36.0	11800.0	Service Link
KU4	36.0	11780.0	Service Link
KU3	36.0	11760.0	Service Link
TM1	0.65	11702.0	TT&C
KU21	36.0	12120.0	Service Link
KU20	36.0	12100.0	Service Link
KU6	36.0	11820.0	Service Link
KU14	36.0	11980.0	Service Link
Ka3	125.0	19762.5	Service Link
Ka4	125.0	19762.5	Service Link

<b>Ka1</b>	125.0	18700.5	Service Link
<b>Ka2</b>	125.0	18700.5	Service Link
<b>KU10</b>	36.0	11900.0	Service Link
<b>KU9</b>	36.0	11880.0	Service Link
<b>Ka12</b>	125.0	20137.5	Service Link
<b>Ka8</b>	125.0	20012.5	Service Link
<b>Ka9</b>	125.0	20012.5	Service Link
<b>KU18</b>	36.0	12060.0	Service Link
<b>KU1</b>	36.0	11720.0	Service Link
<b>KU17</b>	36.0	12040.0	Service Link
<b>KU16</b>	36.0	12020.0	Service Link
<b>KU15</b>	36.0	12000.0	Service Link
<b>KU24</b>	36.0	12180.0	Service Link
<b>Ka10</b>	125.0	20012.5	Service Link
<b>Ka5</b>	125.0	19762.5	Service Link

## Certification Questions

Question	Response
<p>Are the applicable service area coverage requirements of 25.143(b)(2) (ii) and (iii), or 25.144(a)(3)(i), or 25.145 (c)(1) and (2), or 25.146(i)(1) and (2), or 25.148(c), or 25.225 met?</p>	<p>N/A</p>
<p>Are the applicable frequency tolerances of 25.202(e) and out-of-band emission limits of 25.202(f)(1),(2), and (3) met?</p>	<p>Yes</p>
<p>Are the cessation of emissions requirements of 25.207 met?</p>	<p>Yes</p>
<p>Are the applicable power-flux-density limits of 25.208 met, and is the appropriate technical showing provided within the application?</p>	<p>Yes</p>
<p>For NGSO applications, are the applicable equivalent-power-flux-density limits of 25.208 met, and is the appropriate technical showing provided within the application?</p>	<p>N/A</p>
<p>Are the applicable full-frequency-reuse requirements of 25.210 met?</p>	<p>Yes</p>
<p>If the application is for a 17/24 GHz BSS space station, will it be operated at an offset location with full power and interference protection in accordance with 25.262(b)?</p>	

## Attachments

File Name	Beam	Field	Attachment Type	Description
<a href="#"><u>Beam-1BD.gxt</u></a>	1BD	GSO Antenna Gain Contour Data	GXT file (*.gxt)	
<a href="#"><u>KURH.gxt</u></a>	KURH	GSO Antenna Gain Contour Data	GXT file (*.gxt)	
<a href="#"><u>KURV.gxt</u></a>	KURV	GSO Antenna Gain Contour Data	GXT file (*.gxt)	
<a href="#"><u>KUTH.gxt</u></a>	KUTH	GSO Antenna Gain Contour Data	GXT file (*.gxt)	
<a href="#"><u>KUTV.gxt</u></a>	KUTV	GSO Antenna Gain Contour Data	GXT file (*.gxt)	
<a href="#"><u>Beam-4C U.gxt</u></a>	2AU	GSO Antenna Gain Contour Data	GXT file (*.gxt)	
<a href="#"><u>Beam-1AU.gxt</u></a>	1AU	GSO Antenna Gain Contour Data	GXT file (*.gxt)	
<a href="#"><u>Beam-3AD.gxt</u></a>	2BD	GSO Antenna Gain Contour Data	GXT file (*.gxt)	