



312 File Number: **SATMOD2020041300033**

Filing Description

Question	Response
Description	This Schedule S is submitted in support of the application of SES Americom, Inc. and Alascom, Inc. seeking an extension of the license term for AMC-8/Aurora III and Commission authority to relocate the satellite to 135 W.L.

**Satellite
Information**

Question	Response
Select Orbit Type	GSO
Space Station or Satellite Network Name	AMC-8
Estimated Lifetime of Satellite(s) From Date of Launch	27 Years
Will the space station(s) operate on a Common Carrier basis?	No

Operating Frequency Bands (2)

Nature of service	Description	Frequency Band(s)	Mode Type
Fixed-Satellite Service		5925.0 MHz -6425.0 MHz	Receive
Fixed-Satellite Service		3700.0 MHz -4200.0 MHz	Transmit

Orbital Information For Geostationary Satellites

Section	Question	Response
Orbital Longitude Information	Orbital Longitude	135.0 degrees
	Hemisphere of Orbital Longitude	W
Longitudinal Tolerance or East /West Station-Keeping	Toward West	0.05 degrees
	Toward East	0.05 degrees
Inclination Excursion or North /South Station-Keeping Tolerance	Inclination Excursion or North /South Station-Keeping Tolerance	5.5 degrees
Antenna Axis Attitude Accuracy	Roll	0.14 degrees
	Pitch	0.11 degrees
	Yaw	0.33 degrees

Receiving Beams 1:

Question	Response
Beam ID	CMD
Receive Beam Frequency	6422.5 MHz -6424.5 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	No
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
G/T at Max. Gain Point	-12.6 dB/K
Min. Saturation Flux Density	-95.0 dBW/m2
Max. Saturation Flux Density	-92.0 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Visible Earth

Receiving Beams 2:

Question	Response
Beam ID	CRV
Receive Beam Frequency	5925.0 MHz -6425.0 MHz
Beam Type	Fixed
Polarization	V
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees

Polarization Switchable	Yes
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
G/T at Max. Gain Point	2.7 dB/K
Min. Saturation Flux Density	-98.9 dBW/m2
Max. Saturation Flux Density	-76.7 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	North America, Caribbean, Central America and parts of the Pacific Ocean

Receiving Beams 3:

Question	Response
Beam ID	CRH
Receive Beam Frequency	5925.0 MHz -6425.0 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	Yes
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
G/T at Max. Gain Point	4.0 dB/K
Min. Saturation Flux Density	-100.0 dBW/m2
Max. Saturation Flux Density	-77.9 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	North America, Caribbean, Central America and parts of the Pacific Ocean

Receiving Beams 4:

Question	Response
Beam ID	ARV
Receive Beam Frequency	5925.0 MHz -6425.0 MHz
Beam Type	Fixed
Polarization	V
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	Yes
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
G/T at Max. Gain Point	5.3 dB/K
Min. Saturation Flux Density	-101.2 dBW/m ²
Max. Saturation Flux Density	-79.6 dBW/m ²
Co- or Cross Polar Mode	C
Service Area Description	Western North America and parts of the Pacific Ocean

Receiving Beams 5:

Question	Response
Beam ID	ARH
Receive Beam Frequency	5925.0 MHz -6425.0 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	Yes

Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
G/T at Max. Gain Point	7.0 dB/K
Min. Saturation Flux Density	-103.0 dBW/m ²
Max. Saturation Flux Density	-81.1 dBW/m ²
Co- or Cross Polar Mode	C
Service Area Description	Western North America and parts of the Pacific Ocean

Receiving Channels (25)

Channel ID	Channel Bandwidth (MHz)	Center Frequency s (MHz)	Feeder Link, Service Link or TT&C
C20	36.0	6325.0	Service Link
C10	36.0	6125.0	Service Link
C11	36.0	6145.0	Service Link
C21	36.0	6345.0	Service Link
C22	36.0	6365.0	Service Link
C23	36.0	6385.0	Service Link
C9	36.0	6105.0	Service Link
C4	36.0	6005.0	Service Link
C5	36.0	6025.0	Service Link
C6	36.0	6045.0	Service Link
C1	36.0	5945.0	Service Link
C3	36.0	5985.0	Service Link
C24	36.0	6405.0	Service Link
C18	36.0	6285.0	Service Link
C17	36.0	6265.0	Service Link
C16	36.0	6245.0	Service Link
C15	36.0	6225.0	Service Link
C14	36.0	6205.0	Service Link
C13	36.0	6185.0	Service Link
C12	36.0	6165.0	Service Link
TC1	1.2	6423.5	TT&C
C7	36.0	6065.0	Service Link
C8	36.0	6085.0	Service Link
C19	36.0	6305.0	Service Link

C2

36.0

5965.0

Service Link

Transmitting Beams 1:

Question	Response
Beam ID	CTM
Transmit Beam Frequency	3700.0 MHz -4200.0 MHz
Beam Type	Fixed
Polarization	V
Peak Gain	dBi
Antenna Pointing Error	0.0 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	No
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
Max. Transmit EIRP Density	-36.6 dBW/Hz
Max. Transmit EIRP	21.51 dBW
Co- or Cross Polar Mode	C
Service Area Description	Horn Antenna for emergency operations telemetry

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
*	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²
BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
4.0 kHz	-163.9	-163.7	-163.6	-163.5	-163.4	-162.6

Transmitting Beams 2:

Question	Response
Beam ID	CTH
Transmit Beam Frequency	3700.0 MHz -4200.0 MHz

Beam Type	Fixed
Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	Yes
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
Max. Transmit EIRP Density	-30.5 dBW/Hz
Max. Transmit EIRP	43.72 dBW
Co- or Cross Polar Mode	C
Service Area Description	North America, Caribbean, Central America and parts of the Pacific Ocean

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
* (dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):
4.0 kHz	-157.8	-157.6	-157.5	-157.4	-157.3	-156.5

Transmitting Beams 3:

Question	Response
Beam ID	CTV
Transmit Beam Frequency	3700.0 MHz -4200.0 MHz
Beam Type	Fixed
Polarization	V
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees

Antenna Rotational Error	0.0 degrees
Polarization Switchable	Yes
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
Max. Transmit EIRP Density	-30.9 dBW/Hz
Max. Transmit EIRP	43.31 dBW
Co- or Cross Polar Mode	C
Service Area Description	North America, Caribbean, Central America and parts of the Pacific Ocean

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
*	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²
BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
4.0 kHz	-158.2	-158.0	-157.9	-157.8	-157.7	-156.9

Transmitting Beams 4:

Question	Response
Beam ID	ATH
Transmit Beam Frequency	3700.0 MHz -4200.0 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	Yes
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
Max. Transmit EIRP Density	-28.5 dBW/Hz

Max. Transmit EIRP	45.77 dBW
Co- or Cross Polar Mode	C
Service Area Description	Western North America and parts of the Pacific Ocean

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
*	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²
BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
4.0 kHz	-155.8	-155.6	-155.5	-155.4	-155.3	-154.5

Transmitting Beams 5:

Question	Response
Beam ID	ATV
Transmit Beam Frequency	3700.0 MHz -4200.0 MHz
Beam Type	Fixed
Polarization	V
Peak Gain	dBi
Antenna Pointing Error	0.15 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	Yes
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
Max. Transmit EIRP Density	-28.5 dBW/Hz
Max. Transmit EIRP	45.7 dBW
Co- or Cross Polar Mode	C
Service Area Description	Western North America and parts of the Pacific Ocean

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
*	(dbW/m ²)	(dbW/m ²)	(dbW/m ²)	(dbW/m ²)	(dbW/m ²)	(dbW/m ²)
BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
4.0 kHz	-155.8	-155.6	-155.5	-155.4	-155.3	-154.5

Transmitting Channels (27)

Channel ID	Channel Bandwidth (MHz)	Center Frequency s (MHz)	Feeder Link, Service Link or TT&C
C15	36.0	4000.0	Service Link
C16	36.0	4020.0	Service Link
C21	36.0	4120.0	Service Link
C24	36.0	4180.0	Service Link
C22	36.0	4140.0	Service Link
C12	36.0	3940.0	Service Link
C14	36.0	3980.0	Service Link
C20	36.0	4100.0	Service Link
C10	36.0	3900.0	Service Link
C11	36.0	3920.0	Service Link
C5	36.0	3800.0	Service Link
C1	36.0	3720.0	Service Link
C3	36.0	3760.0	Service Link
C23	36.0	4160.0	Service Link
C8	36.0	3860.0	Service Link
C6	36.0	3820.0	Service Link
TMV	0.65	3700.5	TT&C
C7	36.0	3840.0	Service Link
C17	36.0	4040.0	Service Link
C18	36.0	4060.0	Service Link
C4	36.0	3780.0	Service Link
TMH	0.65	3700.5	TT&C
C2	36.0	3740.0	Service Link
TM2	0.65	4199.5	TT&C

C9	36.0	3880.0	Service Link
C13	36.0	3960.0	Service Link
C19	36.0	4080.0	Service Link

Certification Questions

Question	Response
<p>Are the applicable service area coverage requirements of 25.143(b)(2) (ii) and (iii), or 25.144(a)(3)(i), or 25.145 (c)(1) and (2), or 25.146(i)(1) and (2), or 25.148(c), or 25.225 met?</p>	<p>N/A</p>
<p>Are the applicable frequency tolerances of 25.202(e) and out-of-band emission limits of 25.202(f)(1),(2), and (3) met?</p>	<p>Yes</p>
<p>Are the cessation of emissions requirements of 25.207 met?</p>	<p>Yes</p>
<p>Are the applicable power-flux-density limits of 25.208 met, and is the appropriate technical showing provided within the application?</p>	<p>Yes</p>
<p>For NGSO applications, are the applicable equivalent-power-flux-density limits of 25.208 met, and is the appropriate technical showing provided within the application?</p>	<p>N/A</p>
<p>Are the applicable full-frequency-reuse requirements of 25.210 met?</p>	<p>Yes</p>
<p>If the application is for a 17/24 GHz BSS space station, will it be operated at an offset location with full power and interference protection in accordance with 25.262(b)?</p>	

Attachments

File Name	Beam	Field	Attachment Type	Description
CTH.gxt	CTH	GSO Antenna Gain Contour Data	GXT file (*.gxt)	
CRV.gxt	CRV	GSO Antenna Gain Contour Data	GXT file (*.gxt)	
CRH.gxt	CRH	GSO Antenna Gain Contour Data	GXT file (*.gxt)	
ATV.gxt	ATV	GSO Antenna Gain Contour Data	GXT file (*.gxt)	
ARV.gxt	ARV	GSO Antenna Gain Contour Data	GXT file (*.gxt)	
ARH.gxt	ARH	GSO Antenna Gain Contour Data	GXT file (*.gxt)	
CTV.gxt	CTV	GSO Antenna Gain Contour Data	GXT file (*.gxt)	
ATH.gxt	ATH	GSO Antenna Gain Contour Data	GXT file (*.gxt)	