

#### 312 File Number: SATMOD2021050600060

Question	Response
Description	Modification to S2129 non-GSO satellite space station license orbit planes

## Satellite Information

Question	Response
Select Orbit Type	NGSO
Space Station or Satellite Network Name	USASAT-30A
Estimated Lifetime of Satellite(s) From Date of Launch	10 Years
Will the space station(s) operate on a Common Carrier basis?	No

# Operating Frequency Bands (2)

Nature of service	Description	Frequency Band(s)	Mode Type
Earth Exploration-Satellite Service		8025.0 MHz -8400.0 MHz	Transmit
Earth Exploration-Satellite Service		2025.0 MHz -2110.0 MHz	Receive

Orbital Information For	Question	Response
Non-	Total Number of Satellites in the active constellation	12
Geostationary Satellites	Orbit Epoch Date	03/01/2021
	Celestrial Reference Body	Earth

### Orbital Plane 1:

Question	Response
Number of Satellites in Plane	1
Inclination Angle	45.0 degrees
Right Ascension of Ascending Node	338.687 degrees
Argument of Perigee	0.0 degrees
Orbital Period	5698.0 seconds
Apogee	450.0 km
Perigee	450.0 km
Active Service Arc Begin Angle with respect to Ascending Node	0.0 degrees
Active Service Arc End Angle with respect to Ascending Node	0.0 degrees

### Mean Anomaly For Each Satellite

Satellite Number	Mean Anomaly (degrees) at the Orbit Epoch Date
1	0.0

### Orbital Plane 2:

Question	Response
Number of Satellites in Plane	1
Inclination Angle	45.0 degrees
Right Ascension of Ascending Node	158.687 degrees
Argument of Perigee	0.0 degrees
Orbital Period	5698.0 seconds
Apogee	450.0 km
Perigee	450.0 km
Active Service Arc Begin Angle with respect to Ascending Node	0.0 degrees

Satellite Number	Mean Anomaly (degrees) at the Orbit Epoch Date
1	0.0

### **Orbital Plane 3:**

Question	Response
Number of Satellites in Plane	1
Inclination Angle	45.0 degrees
Right Ascension of Ascending Node	68.687 degrees
Argument of Perigee	0.0 degrees
Orbital Period	5698.0 seconds
Apogee	450.0 km
Perigee	450.0 km
Active Service Arc Begin Angle with respect to Ascending Node	0.0 degrees
Active Service Arc End Angle with respect to Ascending Node	0.0 degrees

Satellite Number	Mean Anomaly (degrees) at the Orbit Epoch Date
1	0.0

Question	Response
Number of Satellites in Plane	1
Inclination Angle	45.0 degrees
Right Ascension of Ascending Node	248.687 degrees
Argument of Perigee	0.0 degrees

Orbital Period	5698.0 seconds
Apogee	450.0 km
Perigee	450.0 km
Active Service Arc Begin Angle with respect to Ascending Node	0.0 degrees
Active Service Arc End Angle with respect to Ascending Node	0.0 degrees

Satellite Number	Mean Anomaly (degrees) at the Orbit Epoch Date
1	0.0

## Orbital Plane 5:

Question	Response
Number of Satellites in Plane	2
Inclination Angle	97.214 degrees
Right Ascension of Ascending Node	136.187 degrees
Argument of Perigee	0.0 degrees
Orbital Period	6013.0 seconds
Apogee	450.0 km
Perigee	450.0 km
Active Service Arc Begin Angle with respect to Ascending Node	0.0 degrees
Active Service Arc End Angle with respect to Ascending Node	0.0 degrees

Satellite Number	Mean Anomaly (degrees) at the Orbit Epoch Date
1	0.0
2	180.0

## **Orbital Plane 6:**

Question	Response
Number of Satellites in Plane	1
Inclination Angle	57.0 degrees
Right Ascension of Ascending Node	338.687 degrees
Argument of Perigee	0.0 degrees
Orbital Period	5698.0 seconds
Apogee	450.0 km
Perigee	450.0 km
Active Service Arc Begin Angle with respect to Ascending Node	0.0 degrees
Active Service Arc End Angle with respect to Ascending Node	0.0 degrees

Satellite Number	Mean Anomaly (degrees) at the Orbit Epoch Date
1	0.0

Orbital Plane 7:	Question	Response
	Number of Satellites in Plane	1
	Inclination Angle	57.0 degrees
	Right Ascension of Ascending Node	68.687 degrees
	Argument of Perigee	0.0 degrees
	Orbital Period	5698.0 seconds
	Apogee	450.0 km
	Perigee	450.0 km
	Active Service Arc Begin Angle with respect to Ascending Node	0.0 degrees

Satellite Number	Mean Anomaly (degrees) at the Orbit Epoch Date
1	0.0

**Orbital Plane 8:** 

Question	Response
Number of Satellites in Plane	1
Inclination Angle	57.0 degrees
Right Ascension of Ascending Node	158.687 degrees
Argument of Perigee	0.0 degrees
Orbital Period	5698.0 seconds
Apogee	450.0 km
Perigee	450.0 km
Active Service Arc Begin Angle with respect to Ascending Node	0.0 degrees
Active Service Arc End Angle with respect to Ascending Node	0.0 degrees

#### Mean Anomaly For Each Satellite

Satellite Number	Mean Anomaly (degrees) at the Orbit Epoch Date
1	0.0

### **Orbital Plane 9:**

Question	Response
Number of Satellites in Plane	1
Inclination Angle	57.0 degrees
Right Ascension of Ascending Node	248.687 degrees

Argument of Perigee	0.0 degrees
Orbital Period	5698.0 seconds
Apogee	450.0 km
Perigee	450.0 km
Active Service Arc Begin Angle with respect to Ascending Node	0.0 degrees
Active Service Arc End Angle with respect to Ascending Node	0.0 degrees

Satellite Number	Mean Anomaly (degrees) at the Orbit Epoch Date
1	0.0

Orbital Plane 10:	Question	Response
	Number of Satellites in Plane	2
	Inclination Angle	97.788 degrees
	Right Ascension of Ascending Node	136.187 degrees
	Argument of Perigee	0.0 degrees
	Orbital Period	6013.0 seconds
	Apogee	600.0 km
	Perigee	600.0 km
	Active Service Arc Begin Angle with respect to Ascending Node	0.0 degrees
	Active Service Arc End Angle with respect to Ascending Node	0.0 degrees

Satellite Number	Mean Anomaly (degrees) at the Orbit Epoch Date
1	90.0

270.0

2

## Receiving Beams 1:

Question	Response
Beam ID	CMD
Receive Beam Frequency	2085.02 MHz -2086.35 MHz
Beam Type	Steerable
Polarization	RHCP
Peak Gain	0.0 dBi
Antenna Pointing Error	0.25 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
G/T at Max. Gain Point	-28.1 dB/K
Min. Saturation Flux Density	-104.3 dBW/m2
Max. Saturation Flux Density	-87.3 dBW/m2
Co- or Cross Polar Mode	С
Service Area Description	Earth coverage for uplink commanding

# Receiving Channels (1)

Channel ID	Channel Bandwidth (MHz)	Center Frequency s (MHz)	Feeder Link, Service Link or TT&C
CMD	1.32	2085.6875	TT&C

## Transmitting Beams 1:

Question	Response
Beam ID	NB
Transmit Beam Frequency	8379.68 MHz -8380.32 MHz
Beam Type	Steerable
Polarization	RHCP
Peak Gain	0.0 dBi
Antenna Pointing Error	0.25 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-51.9 dBW/Hz
Max. Transmit EIRP	0.0 dBW
Co- or Cross Polar Mode	С
Service Area Description	Earth coverage for downlink of spacecraft health and status telemetry to earth station

## Max. Power Flux Density

* BW:	* 0° - 5° (dbW/m² /BW):	* 5° - 10° (dbW/m² /BW):	* 10° - 15° (dbW/m <sup>2</sup> /BW):	* 15° - 20° (dbW/m <sup>2</sup> /BW):	* 20° - 25° (dbW/m <sup>2</sup> /BW):	* 25° - 90° (dbW/m <sup>2</sup> /BW):
4.0 kHz	-154.2	-151.5	-149.9	-148.0	-146.6	-140.1

## Transmitting Beams 2:

Question	Response
Beam ID	WB
Transmit Beam Frequency	8025.0 MHz -8400.0 MHz

Beam Type	Steerable
Polarization	RHCP
Peak Gain	24.5 dBi
Antenna Pointing Error	0.25 degrees
Antenna Rotational Error	0.0 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-51.8 dBW/Hz
Max. Transmit EIRP	31.1 dBW
Co- or Cross Polar Mode	С
Service Area Description	Steerable beam to point at earth station for downlinking image data

## Max. Power Flux Density

* BW:	* 0° - 5° (dbW/m <sup>2</sup> /BW):	(dbW/m <sup>2</sup>	15°	•	* 20° - 25° (dbW/m <sup>2</sup> /BW):	* 25° - 90° (dbW/m <sup>2</sup> /BW):
4.0 kHz	-154.2	-151.5	-149.5	-147.9	-146.5	-140.1

# Transmitting Channels (3)

Channel ID	Channel Bandwidth (MHz)	Center Frequency s (MHz)	Feeder Link, Service Link or TT&C
NB2	0.037	8380.0	TT&C
WB	150.0	8185.0	TT&C
NB1	0.625	8380.0	TT&C

Certification Questions	Question	Response
	Are the applicable service area coverage requirements of 25.143(b)(2) (ii) and (iii), or 25.144(a)(3)(i), or 25.145 (c)(1) and (2), or 25.146(i)(1) and (2), or 25.148(c), or 25.225 met?	N/A
	Are the applicable frequency tolerances of 25.202(e) and out-of- band emission limits of 25.202(f)(1),(2), and (3) met?	Yes
	Are the cessation of emissions requirements of 25.207 met?	Yes
	Are the applicable power-flux-density limits of 25.208 met, and is the appropriate technical showing provided within the application?	Yes
	For NGSO applications, are the applicable equivalent-power-flux- density limits of 25.208 met, and is the appropriate technical showing provided within the application?	Yes
	Are the applicable full-frequency-reuse requirements of 25.210 met?	Yes
	If the application is for a 17/24 GHz BSS space station, will it be operated at an offset location with full power and interference protection in accordance with 25.262(b)?	

## Attachments

File Name	Beam	Field	Attachment Type	Descriptic
<u>WVL-</u> Wideband antenna gain pattern.pdf	WB	NGSO Antenna Gain Data	PDF file (*. pdf)	Wideband downlink antenna gain patter
<u>WVL-</u> <u>Command antenna gain pattern.</u> pdf	CMD	NGSO Antenna Gain Data	PDF file (*. pdf)	Command uplink antenna gain patter
<u>WVL-</u> <u>Narrownband antenna gain pattern.</u> <u>pdf</u>	NB	NGSO Antenna Gain Data	PDF file (*. pdf)	Narrowbar downlink antenna gain patter