



312 File Number: **SATMOD2023030800050**

Filing Description

Question	Response
Description	Intelsat 5 move to 166.15 E.L.

Satellite
Information

Question	Response
Select Orbit Type	GSO
Space Station or Satellite Network Name	Intelsat 5
Estimated Lifetime of Satellite(s) From Date of Launch	20 Years
Will the space station(s) operate on a Common Carrier basis?	No

**Operating
Frequency
Bands (7)**

Nature of service	Description	Frequency Band(s)	Mode Type
Fixed-Satellite Service		14000.0 MHz -14500.0 MHz	Receive
Fixed-Satellite Service		11200.0 MHz -11450.0 MHz	Transmit
Fixed-Satellite Service		10700.0 MHz -10950.0 MHz	Transmit
Fixed-Satellite Service		12750.0 MHz -14500.0 MHz	Receive
Fixed-Satellite Service		11450.0 MHz -11700.0 MHz	Transmit
Fixed-Satellite Service		3700.0 MHz -4200.0 MHz	Transmit
Fixed-Satellite Service		5925.0 MHz -6425.0 MHz	Receive

**Orbital
Information For
Geostationary
Satellites**

Section	Question	Response
Orbital Longitude Information	Orbital Longitude	166.0 degrees
	Hemisphere of Orbital Longitude	E
Longitudinal Tolerance or East /West Station-Keeping	Toward West	0.05 degrees
	Toward East	0.05 degrees
Inclination Excursion or North /South Station-Keeping Tolerance	Inclination Excursion or North /South Station-Keeping Tolerance	7.4 degrees
Antenna Axis Attitude Accuracy	Roll	0.1 degrees
	Pitch	0.1 degrees
	Yaw	0.1 degrees

Receiving Beams 1:

Question	Response
Beam ID	PKHU
Receive Beam Frequency	14000.0 MHz -14250.0 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
G/T at Max. Gain Point	-12.0 dB/K
Min. Saturation Flux Density	-91.9 dBW/m2
Max. Saturation Flux Density	-76.9 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Asia Pacific, Canada, Alaska and Western United States

Receiving Beams 2:

Question	Response
Beam ID	PCVU
Receive Beam Frequency	5925.0 MHz -6425.0 MHz
Beam Type	Fixed
Polarization	V
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees

Polarization Switchable	No
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
G/T at Max. Gain Point	0.2 dB/K
Min. Saturation Flux Density	-96.2 dBW/m2
Max. Saturation Flux Density	-81.2 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Asia Pacific, Canada, Alaska and Western United States

Receiving Beams 3:

Question	Response
Beam ID	PCHU
Receive Beam Frequency	5925.0 MHz -6425.0 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	No
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
G/T at Max. Gain Point	0.6 dB/K
Min. Saturation Flux Density	-96.6 dBW/m2
Max. Saturation Flux Density	-81.6 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Asia Pacific, Canada, Alaska and Western United States

Receiving Beams 4:

Question	Response
Beam ID	CMDP
Receive Beam Frequency	13998.5 MHz -13999.5 MHz
Beam Type	Fixed
Polarization	RHCP
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
G/T at Max. Gain Point	-25.3 dB/K
Min. Saturation Flux Density	-92.5 dBW/m2
Max. Saturation Flux Density	-77.5 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Command Global Coverage

Receiving Beams 5:

Question	Response
Beam ID	CMDG
Receive Beam Frequency	14497.5 MHz -14498.5 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees

**Receiving
Beams 6:**

Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
G/T at Max. Gain Point	-12.6 dB/K
Min. Saturation Flux Density	-104.8 dBW/m2
Max. Saturation Flux Density	-89.8 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Command Global Coverage

Question	Response
Beam ID	CMDB
Receive Beam Frequency	14497.5 MHz -14498.5 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
G/T at Max. Gain Point	-12.6 dB/K
Min. Saturation Flux Density	-104.8 dBW/m2
Max. Saturation Flux Density	-89.8 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Command Global Coverage

Receiving Beams 7:

Question	Response
Beam ID	NPVU
Receive Beam Frequency	12750.0 MHz -13250.0 MHz
Beam Type	Fixed
Polarization	V
Peak Gain	30.38 dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.03 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
G/T at Max. Gain Point	4.6 dB/K
Min. Saturation Flux Density	-93.6 dBW/m2
Max. Saturation Flux Density	-78.6 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Asia Pacific, Canada, Alaska and Western United States

Receiving Beams 8:

Question	Response
Beam ID	P1HU
Receive Beam Frequency	12750.0 MHz -13250.0 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	28.26 dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	

Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
G/T at Max. Gain Point	2.9 dB/K
Min. Saturation Flux Density	-91.9 dBW/m2
Max. Saturation Flux Density	-76.9 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Asia Pacific, Canada, Alaska and Western United States

Receiving Channels (32)

Channel ID	Channel Bandwidth (MHz)	Center Frequency s (MHz)	Feeder Link, Service Link or TT&C
CU03	36.0	6025.0	Service Link
CU02	36.0	5985.0	Service Link
CU01	36.0	5945.0	Service Link
CMD2	1.0	14498.0	TT&C
CMD1	1.0	13999.0	TT&C
CU06	36.0	6145.0	Service Link
CU07	36.0	6185.0	Service Link
KU17	36.0	13190.0	Service Link
KU16	36.0	13149.0	Service Link
KU15	36.0	13108.0	Service Link
KU14	36.0	13067.0	Service Link
KU13	36.0	13026.0	Service Link
KU12	36.0	12979.0	Service Link
KU11	36.0	12937.0	Service Link
KU10	36.0	12895.0	Service Link
KU09	36.0	12853.0	Service Link
KU08	36.0	12811.0	Service Link
KU06	36.0	14224.0	Service Link
KU05	36.0	14183.0	Service Link
KU04	36.0	14142.0	Service Link
KU03	36.0	14101.0	Service Link
KU02	36.0	14060.0	Service Link
KU01	36.0	14019.0	Service Link
CU12	36.0	6385.0	Service Link

CU11	36.0	6345.0	Service Link
CU10	36.0	6305.0	Service Link
CU09	36.0	6265.0	Service Link
CU08	36.0	6225.0	Service Link
CU04	36.0	6065.0	Service Link
CU05	36.0	6105.0	Service Link
KU18	36.0	13231.0	Service Link
KU07	36.0	12769.0	Service Link

Transmitting
Beams 1:

Question	Response
Beam ID	SKVD
Transmit Beam Frequency	11450.0 MHz -11700.0 MHz
Beam Type	Steerable
Polarization	V
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
Max. Transmit EIRP Density	-27.0 dBW/Hz
Max. Transmit EIRP	48.6 dBW
Co- or Cross Polar Mode	C
Service Area Description	Steerable Pacific & Hawaii

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
* (dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):
4.0 kHz	-150.2	-150.1	-150.0	-149.9	-149.8	-149.0

Transmitting
Beams 2:

Question	Response
Beam ID	UPCR
Transmit Beam Frequency	11453.987 MHz -11454.013 MHz

Beam Type	Fixed
Polarization	RHCP
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-45.59 dBW/Hz
Max. Transmit EIRP	11.4 dBW
Co- or Cross Polar Mode	C
Service Area Description	Uplink Power Control Global

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²
	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
4.0 kHz	-159.8	-159.7	-159.6	-159.5	-159.4	-159.4

Transmitting Beams 3:

Question	Response
Beam ID	UPCL
Transmit Beam Frequency	11453.987 MHz -11454.013 MHz
Beam Type	Fixed
Polarization	LHCP
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees

Antenna Rotational Error	0.34 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-45.59 dBW/Hz
Max. Transmit EIRP	11.4 dBW
Co- or Cross Polar Mode	C
Service Area Description	Uplink Power Control Global

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²
* BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
4.0 kHz	-163.2	-163.1	-163.0	-162.9	-162.8	-162.8

Transmitting Beams 4:

Question	Response
Beam ID	TLMP
Transmit Beam Frequency	11450.75 MHz -11452.25 MHz
Beam Type	Fixed
Polarization	RHCP
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	45.0 degrees
Max. Transmit EIRP Density	-46.79 dBW/Hz

Max. Transmit EIRP	10.2 dBW
Co- or Cross Polar Mode	C
Service Area Description	Telemetry Global

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²
* BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
4.0 kHz	-174.0	-173.9	-173.8	-173.7	-173.6	-173.6

Transmitting Beams 5:

Question	Response
Beam ID	TLMG
Transmit Beam Frequency	11450.75 MHz -11452.25 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
Max. Transmit EIRP Density	-47.79 dBW/Hz
Max. Transmit EIRP	9.2 dBW
Co- or Cross Polar Mode	C
Service Area Description	Telemetry Global

Max. Power Flux Density

**Transmitting
Beams 6:**

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
* BW:	(dbW/m ² /BW):	(dbW/m ² /BW):	(dbW/m ² /BW):	(dbW/m ² /BW):	(dbW/m ² /BW):	(dbW/m ² /BW):
4.0 kHz	-175.0	-174.9	-174.8	-174.7	-174.6	-173.8

Question	Response
Beam ID	TLMB
Transmit Beam Frequency	11450.75 MHz -11452.25 MHz
Beam Type	Fixed
Polarization	V
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
Max. Transmit EIRP Density	-47.99 dBW/Hz
Max. Transmit EIRP	9.0 dBW
Co- or Cross Polar Mode	C
Service Area Description	Telemetry Global

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
* BW:	(dbW/m ² /BW):	(dbW/m ² /BW):	(dbW/m ² /BW):	(dbW/m ² /BW):	(dbW/m ² /BW):	(dbW/m ² /BW):
4.0 kHz	-175.2	-175.1	-175.0	-174.9	-174.8	-174.8

Transmitting
Beams 7:

Question	Response
Beam ID	PCVD
Transmit Beam Frequency	3700.0 MHz -4200.0 MHz
Beam Type	Fixed
Polarization	V
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	No
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
Max. Transmit EIRP Density	-34.6 dBW/Hz
Max. Transmit EIRP	41.0 dBW
Co- or Cross Polar Mode	C
Service Area Description	Asia Pacific and Western United States

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²
* BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
4.0 kHz	-161.8	-161.7	-161.6	-161.5	-161.4	-160.6

Transmitting
Beams 8:

Question	Response
Beam ID	PCHD
Transmit Beam Frequency	3700.0 MHz -4200.0 MHz

Beam Type	Fixed
Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	No
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
Max. Transmit EIRP Density	-34.0 dBW/Hz
Max. Transmit EIRP	41.6 dBW
Co- or Cross Polar Mode	C
Service Area Description	Asia Pacific and Western United States

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
* BW:	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):
4.0 kHz	-161.2	-161.1	-161.0	-160.9	-160.8	-160.0

Transmitting Beams 9:

Question	Response
Beam ID	CKHD
Transmit Beam Frequency	11200.0 MHz -11450.0 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	34.85 dBi
Antenna Pointing Error	0.19 degrees

Antenna Rotational Error	0.34 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
Max. Transmit EIRP Density	-23.0 dBW/Hz
Max. Transmit EIRP	52.6 dBW
Co- or Cross Polar Mode	C
Service Area Description	CKHD has 2 freq China, Japan & Northeast Asia

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²
* BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
4.0 kHz	-150.2	-150.1	-150.0	-149.9	-149.8	-149.0

Transmitting Beams 10:

Question	Response
Beam ID	C1HD
Transmit Beam Frequency	10700.0 MHz -10950.0 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	34.85 dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
Max. Transmit EIRP Density	-23.0 dBW/Hz

Max. Transmit EIRP	52.6 dBW
Co- or Cross Polar Mode	C
Service Area Description	CKHD has 2 freq China, Japan & Northeast Asia

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²
* BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
4.0 kHz	-150.2	-150.1	-150.0	-149.9	-149.8	-149.0

Transmitting Beams 11:

Question	Response
Beam ID	JKVD
Transmit Beam Frequency	11200.0 MHz -11450.0 MHz
Beam Type	Fixed
Polarization	V
Peak Gain	33.28 dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
Max. Transmit EIRP Density	-23.0 dBW/Hz
Max. Transmit EIRP	52.6 dBW
Co- or Cross Polar Mode	C
Service Area Description	J beam Japan, Northeast Asia

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
*	(dbW/m ²	(dbW/m ²	(dbW/m ²	(dbW/m ²	(dbW/m ²	(dbW/m ²
BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
4.0 kHz	-148.8	-148.7	-148.6	-148.5	-148.4	-147.6

**Transmitting
Channels (32)**

Channel ID	Channel Bandwidth (MHz)	Center Frequency s (MHz)	Feeder Link, Service Link or TT&C
KD02	36.0	11517.0	Service Link
KD03	36.0	11558.0	Service Link
KD04	36.0	11599.0	Service Link
KD05	36.0	11640.0	Service Link
KD06	36.0	11681.0	Service Link
UPC1	0.025	11454.0	TT&C
KD07	36.0	10727.0	Service Link
KD09	36.0	10768.0	Service Link
KD10	36.0	10809.0	Service Link
KD11	36.0	10891.0	Service Link
KD12	36.0	10932.0	Service Link
CD09	36.0	4040.0	Service Link
CD03	36.0	3800.0	Service Link
CD02	36.0	3760.0	Service Link
CD01	36.0	3720.0	Service Link
KD01	36.0	11476.0	Service Link
CD10	36.0	4080.0	Service Link
CD11	36.0	4120.0	Service Link
CD12	36.0	4160.0	Service Link
TLM1	0.5	11451.0	TT&C
TLM2	0.5	11452.0	TT&C
KD18	36.0	11429.0	Service Link
KD17	36.0	11387.0	Service Link
KD16	36.0	11345.0	Service Link

KD15	36.0	11303.0	Service Link
KD14	36.0	11261.0	Service Link
KD13	36.0	11219.0	Service Link
CD04	36.0	3840.0	Service Link
CD05	36.0	3880.0	Service Link
CD06	36.0	3920.0	Service Link
CD07	36.0	3960.0	Service Link
CD08	36.0	4000.0	Service Link

Certification Questions

Question	Response
Are the applicable service area coverage requirements of 25.143(b)(2) (ii) and (iii), or 25.144(a)(3)(i), or 25.145 (c)(1) and (2), or 25.146(i)(1) and (2), or 25.148(c), or 25.225 met?	N/A
Are the applicable frequency tolerances of 25.202(e) and out-of-band emission limits of 25.202(f)(1),(2), and (3) met?	Yes
Are the cessation of emissions requirements of 25.207 met?	Yes
Are the applicable power-flux-density limits of 25.208 met, and is the appropriate technical showing provided within the application?	Yes
For NGSO applications, are the applicable equivalent-power-flux-density limits of 25.208 met, and is the appropriate technical showing provided within the application?	N/A
Are the applicable full-frequency-reuse requirements of 25.210 met?	Yes
If the application is for a 17/24 GHz BSS space station, will it be operated at an offset location with full power and interference protection in accordance with 25.262(b)?	

Attachments

File Name	Beam	Field	Attachment Type	Description
IS-5.mdb		GSO Antenna Gain Contour Data	GIMS file (*.mdb)	