

S1. GENERAL INFORMATION Complete for all satellite applications.

a. Space Station or Satellite Network Name: AMC-18		e. Estimated Date of Placement into Service: 1/1/2007		i. Will the space station(s) operate on a Common Carrier Basis: N	
b. Construction Commencement Date: 8/1/2001		f. Estimated Lifetime of Satellite(s): 21.5 Years		j. Number of transponders offered on a common carrier basis: 0	
c. Construction Completion Date: 11/1/2006		g. Total Number of Transponders: 24		k. Total Common Carrier Transponder Bandwidth: 0 MHz	
d1. Est Launch Date Begin: 11/1/2006	d2. Est Launch Date End: 11/30/2006	h. Total Transponder Bandwidth (no. transponders x Bandwidth) 864 MHz		i. Orbit Type: Mark all boxes that apply: <input checked="" type="checkbox"/> GSO <input type="checkbox"/> NGSO	

S2. OPERATING FREQUENCY BANDS Identify the frequency range and transmit/receive mode for all frequency bands in which this station will oper
Also indicate the nature of service(s) for each frequency band.

Frequency Band Limits				e. T/R Mode	f. Nature of Service(s): List all that apply to this band
Lower Frequency (.Hz)		Upper Frequency (.Hz)			
a. Numeric	b. Unit (K/M/G)	c. Numeric	d. Unit (K/M/G)		
3700	M	4200	M	T	Fixed Satellite Service
3700	M	4200	M	T	
5925	M	6425	M	R	Fixed Satellite Service
5925	M	6425	M	R	

S3. ORBITAL INFORMATION FOR GEOSTATIONARY SATELLITES ONLY:

a. Nominal Orbital Longitude (Degrees E/W): 104.95 W		b. Alternate Orbital Longitude (Degrees E/W):		c. Reason for orbital location selection: Availability of C-band spectrum at 105W (nominal).			
Longitudinal Tolerance or E/W Station-Keeping:		f. Inclination Excursion or N/S Station-Keeping Tolerance:				Range of orbital are in which adequate service can be provided (Optional):	
d. Toward West:	0.05 Degrees	e. Toward East:				0.05 Degrees	g. Westernmost: W h. Easternmost: W
i. Reason for service are selection (Optional):							

**FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)**

S4. ORBITAL INFORMATION FOR NON-GEOSTATIONARY SATELLITES ONLY

S4a. Total Number of Satellites in Network or System:

S4c. Celestial Reference Body (Earth, Sun, Moon, etc.):

S4b. Total Number of Orbital Planes in Network or System:

S4d. Orbit Epoch Date:

For each Orbital Plane Provide:

(e) Orbital Plane No.	(f) No. of Satellites in Plane	(g) Inclination Angle (degrees)	(h) Orbital Period (Seconds)	(i) Apogee (km)	(j) Perigee (km)	(k) Right Ascension of the Ascending Node (Deg.)	(l) Argument of Perigee (Degrees)	Active Service Arc Range (Degrees)		
								(m) Begin Angle	(n) End Angle	(o) Other

S5. INITIAL SATELLITE PHASE ANGLE For each satellite in each orbital plane, provide the initial phase angle.

(a) Orbital Plane No.	(b) Satellite Number	(c) Initial Phase Angle (Degrees)

NO NGSO DATA FILED

**FEDERAL COMMUNICATIONS COMMISSION
 SATELLITE SPACE STATION AUTHORIZATIONS
 FCC Form 312 - Schedule S: (Technical and Operational Description)**

S6. SERVICE AREA CHARACTERISTICS for each service area provide:

(a) Service Area ID	(b) Type of Associated Station (Earth or Space)	(c) Service Area Diagram File Name (GXT File)	(d) Service Area Description. Provide list of geographic areas (state postal codes or ITU 3-ltr codes), satellites or Figure No. of Service Area Diagram.
CNA	E		-7 dB gain contour of beams CUH and CUV for the uplink; -8 dB gain contour of beams CDH and CDV for the do

FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)

S7. SPACE STATION ANTENNA BEAM CHARACTERISTICS For each antenna beam provide:

(a) Beam ID	(b) T/R Mode	Isotropic Antenna Gain		(e) Pointing Error (Degrees)	(f) Rotational Error (Degrees)	(g) Min. Cross- Polar Iso- lation (dB)	(h) Polar- ization Switch- able? (Y/N)	(i) Polarization Alignment Rel. Equatorial Plane (Degrees)	(j) Service Area ID	Transmit			Receive			Input Attenuator (dB)	
										(k) Input Losses (dB)	(l) Effective Output Power (W)	(m) Max. EIRP (dBW)	(n) System Noise Temp (k)	(o) G/T Max. Gain Pt. (db/K)	(p) Min. Saturation Flux Density (dBW/m2)	(q) Max. Value	(r) Step Size
		(c) Peak (dBi)	(d) Edge (dBi)														
CDH	T	30.24	22.24	0.15	0	31.3	Y	0	CNA	1.65	12.56	41.23					
CDV	T	30.51	22.51	0.15	0	30.6	Y	90	CNA	1.68	12.56	41.5					
CUH	R	31.74	23.74	0.15	0	33.8	Y	0	CNA				583	4.01	-96.01	18	1
CUV	R	31.61	23.61	0.15	0	32.6	Y	90	CNA				593	3.96	-95.96	18	1
TC	R	10	8	0.15	0		Y		CNA				585	-17			

**FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)**

S8. ANTENNA BEAM DIAGRAMS For each beam pattern provide the reference to the graphic image and numerical data:
Also provide the power flux density levels in each beam that result from the emission with the highest power flux density.

(a) Beam ID	(b) T/R Mode	(c) Co-or Cross Polar Mode ("C" or" X")	(d) GSO Ref. Orbital Longitude (Deg. E/W)	(e) NGSO Antenna Gain Contour Description (Figure/Table/ Exhibit)	(f) GSO Antenna Gain Contour Data (GXT File)	Max. Power Flux Density (dBW/M2/Hz)				
						At Angle of Arrival above horizontal (for emission with highest PFD)				
						(g) 5 Deg	(h) 10 Deg	(i) 15 Deg	(j) 20 Deg	(k) 25 Deg
CDH	T	C	-104.95		ch12_CDH.gxt	-153	-152	-151	-150	-149
CDV	T	C	-104.95		ch13_CDV.gxt	-153	-152	-151	-150	-149
CUH	R	C	-104.95		ch13_CUH.gxt					
CUV	R	C	-104.95		ch12_CUV.gxt					
CDH	T	X	-104.95		ch12_CDH_X.gxt					
CDV	T	X	-104.95		ch13_CDV_X.gxt					
CUH	R	X	-104.95		ch13_CUH_X.gxt					
CUV	R	X	-104.95		ch12_CUV_X.gxt					
TC	R	C	-104.95		_command_rx_anten					

**FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)**

S9. SPACE STATION CHANNELS For each frequency channel provide: S10. SPACE STATION TRANSPONDERS For each transponder provide:

(a) Channel No.	(B) Assigned Bandwidth (kHz)	(c) T/R Mode	(d) Center Frequency (MHz)	(e) Polarization (H, V, L, R)	(f) TTC or Comm Channel (T or C)
CD001	36000	T	3720	V	C
CD003	36000	T	3760	V	C
CD005	36000	T	3800	V	C
CD007	36000	T	3840	V	C
CD009	36000	T	3880	V	C
CD011	36000	T	3920	V	C
CD013	36000	T	3960	V	C
CD015	36000	T	4000	V	C
CD017	36000	T	4040	V	C
CD019	36000	T	4080	V	C
CD021	36000	T	4120	V	C
CD023	36000	T	4160	V	C
CD002	36000	T	3740	H	C
CD004	36000	T	3780	H	C
CD006	36000	T	3820	H	C
CD008	36000	T	3860	H	C
CD010	36000	T	3900	H	C
CD012	36000	T	3940	H	C
CD014	36000	T	3980	H	C
CD016	36000	T	4020	H	C
CD018	36000	T	4060	H	C
CD020	36000	T	4100	H	C
CD022	36000	T	4140	H	C
CD024	36000	T	4180	H	C
CU001	36000	R	5945	H	C
CU003	36000	R	5985	H	C
CU005	36000	R	6025	H	C
CU007	36000	R	6065	H	C
CU009	36000	R	6105	H	C
CU011	36000	R	6145	H	C

(a) Transponder ID	(b) Transponder Gain (dB)	Receive Band		Transmit Band	
		(c) Channel No.	(d) Beam ID	(e) Channel No.	(f) Beam ID
C0001	112	CU001	CUH	CD001	CDV
C0003	112	CU003	CUH	CD003	CDV
C0005	112	CU005	CUH	CD005	CDV
C0007	112	CU007	CUH	CD007	CDV
C0009	112	CU009	CUH	CD009	CDV
C0011	112	CU011	CUH	CD011	CDV
C0013	112	CU013	CUH	CD013	CDV
C0015	112	CU015	CUH	CD015	CDV
C0017	112	CU017	CUH	CD017	CDV
C0019	112	CU019	CUH	CD019	CDV
C0021	112	CU021	CUH	CD021	CDV
C0023	112	CU023	CUH	CD023	CDV
C0002	112	CU002	CUV	CD002	CDH
C0004	112	CU004	CUV	CD004	CDH
C0006	112	CU006	CUV	CD006	CDH
C0008	112	CU008	CUV	CD008	CDH
C0010	112	CU010	CUV	CD010	CDH
C0012	112	CU012	CUV	CD012	CDH
C0014	112	CU014	CUV	CD014	CDH
C0016	112	CU016	CUV	CD016	CDH
C0018	112	CU018	CUV	CD018	CDH
C0020	112	CU020	CUV	CD020	CDH
C0022	112	CU022	CUV	CD022	CDH
C0024	112	CU024	CUV	CD024	CDH
TC001		TC	TC		
TM001				TM1	CDH
TM002				TM2	CDV

CU013	36000	R	6185	H	C
CU015	36000	R	6225	H	C
CU017	36000	R	6265	H	C
CU019	36000	R	6305	H	C
CU021	36000	R	6345	H	C
CU023	36000	R	6385	H	C
CU002	36000	R	5965	V	C
CU004	36000	R	6005	V	C
CU006	36000	R	6045	V	C
CU008	36000	R	6085	V	C
CU010	36000	R	6125	V	C
CU012	36000	R	6165	V	C
CU014	36000	R	6205	V	C
CU016	36000	R	6245	V	C
CU018	36000	R	6285	V	C
CU020	36000	R	6325	V	C
CU022	36000	R	6365	V	C
CU024	36000	R	6405	V	C
TC	800	R	6423.5	H	T
TM1	300	T	3700.5	H	T
TM2	300	T	4199.5	V	T

FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)

S11. DIGITAL MODULATION PARAMETERS For each digital emission provide:

(a) Digital Mod. ID	(b) Emission Designator	(c) Assigned Bandwidth (kHz)	(d) No. of Phases	(e) Uncoded Data Rate (kbps)	(f) FEC Error Correction Coding Rate	(g) CDMA Processing Gain (dB)	(h) Total C/N Performance Objective (dB)	(i) Single Entry C/I Objective (dB)
A	36M0G7W	36000	4	40000	0.691		6.8	19
B	6M95G1W	6950	4	8000	0.691		6.8	19
C	36M0G7W	36000	8	60000	0.614		9.9	22.1
D	100KG1W	100	4	56	0.691		6.8	19
E	1M35G7W	1350	4	1544	0.691		6.8	19

FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)

S13. TYPICAL EMISSIONS For each planned type of emission provide:

Associated Transponder ID Range (a) Start (b) End		Modulation ID		(e) Carriers per Transponder	(f) Carrier Spacing (kHz)	(g) Noise Budget Reference (Table No.)	(h) Energy Dispersal Bandwidth (kHz)	Receive Band (Assoc. Transmit Stn)			Transmit Band (This Space Station)			
		(c) Digital (Table S11)	(d) Analog (Table S12)					(i) Assoc. Stn. Max. Antenna Gain (dBi)	Assoc. Station Transmit Power (dBW) (j) Min. (k) Max.		EIRP (dBW) (l) Min. (m) Max.		(n) Max. Power Flux Density (dBW/m ² /Hz)	(o) Assoc. Stn Rec. G/T (dB/K)
C0001	C0024	A		1		7, 8		53.8	14	32	31.1	41.2	-159.7	22.3
C0001	C0024	B		5	6950	7, 8		53.8	-1.5	16.5	22.1	34.1	-159.9	23.7
C0001	C0024	C		1		9, 10		53.8	14	32	32.3	41.2	-160.2	29.8
C0001	C0024	D		360	100	11, 12		47.8	-14.5	3.5	3.8	15.6	-156.7	22.3
C0001	C0024	E		26	1350	11, 12		47.8	0.7	18.7	17.6	26.9	-159.8	22.3
C0001	C0024		F	1		13, 14	2800	53.2	14.6	32.6	35.3	41.2	-149.6	23.7
TC001	TC001		G	1		15		54.4	10	15				
TM001	TM002		H	1		15					10	14	-167.3	33.2

**FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)**

S14. Is the space station(s) controlled and monitored remotely? If Yes, provide the location and telephone number of the TT and C control point(s): Yes

Remote Control (TT C) Location(s):

S14a: Street Address: Woodbine TT&C			
S14b. City: Mt. Airy	S14c. County:	S14d. State/Country MD	S14e. Zip Code: 21771
S14f. Telephone Number: 410-549-4300		S14g. Call Sign of Control Station (if appropriate): E7169	

Remote Control (TT C) Location(s):

S14a: Street Address: Vernon Valley Spacecraft Ops			
S14b. City: Sussex	S14c. County:	S14d. State/Country NJ	S14e. Zip Code: 07461
S14f. Telephone Number: 973-823-6000		S14g. Call Sign of Control Station (if appropriate): WB81	

Remote Control (TT C) Location(s):

S14a: Street Address: Suite 9A, Leanse Place			
S14b. City: Gibraltar	S14c. County: Gibraltar	S14d. State/Country	S14e. Zip Code:
S14f. Telephone Number: 011-350-77025		S14g. Call Sign of Control Station (if appropriate):	

Remote Control (TT C) Location(s):

S14a: Street Address:			
S14b. City:	S14c. County:	S14d. State/Country	S14e. Zip Code:
S14f. Telephone Number:		S14g. Call Sign of Control Station (if appropriate):	

**FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)**

Page 11:
Characteristics and
Certifications

S15. SPACECRAFT PHYSICAL CHARACTERISTICS:

S15a. Mass of spacecraft without fuel (kg): 918	Spacecraft Dimensions (meters)	Probability of Survival to End of Life (0.0 - 1.0)
S15b. Mass of fuel and disposables at launch (kg): 1163		
S15c. Mass of spacecraft and fuel at launch (kg): 2081	S15f. Length (m): 14.65	S15i. Payload: 0.92
S15d. Mass of fuel, in orbit, at beginning of life (kg): 360.41	S15g. Width (m): 1.82	S15j. Bus: 0.86
S15e. Deployed Area of Solar Array (square meters): 23.99	S15h. Height (m): 3.79	S15k. Total: 0.79

S16. SPACECRAFT ELECTRICAL CHARACTERISTICS:

Spacecraft Subsystem	Electrical Power (Watts) At Beginning of Life		Electrical Power (Watts) At End of Life	
	At Equinox	At Solstice	At Equinox	At Solstice
Payload (Watts):	(a): 1516	(f): 1516	(k): 1516	(p): 1516
Bus (Watts):	(b): 924	(g): 574	(l): 924	(q): 574
Total (Watts):	(c): 2440	(h): 2090	(m): 2440	(r): 2090
Solar Array (Watts):	(d): 3592	(i): 3044	(n): 2797	(s): 2483
Depth of Battery Discharge (%):	(e) 58 %	(j) %	(o) 58 %	(t) %

S17. CERTIFICATIONS:

a. Are the power flux density limits of § 25.208 met?	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO	<input type="checkbox"/> N/A
b. Are the appropriate service area coverage requirements of § 25.143(b)(ii) and (iii), or § 25.145(c)(1) and (2) met?	<input type="checkbox"/> YES	<input type="checkbox"/> NO	<input checked="" type="checkbox"/> N/A
c. Are the frequency tolerances of § 25.202(e) and the out-of-band emission limits of § 25.202(f)(1), (2) and (3) met?	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO	<input type="checkbox"/> N/A

In addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the Commission's rules, 47 C.F.R § 25.114.