FCC	31	2	
Sche	dul	е	S

FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS (Technical and Operational Description)

Page 1: General, Frequency Bands, and GSO Orbit

a. Space Station or Satellite No MARISAT-F2	etwork Name:	e. Estimated Date of Placement into Service: 1/1/1977	i Will the space station(s) operate on a Common Carrier Basis: N
b. Construction Commenceme	nt Date:	f. Estimated Lifetime of Satellite(s): 5 Years	j. Number of transponders offered on a common carrier basis:
c. Construction Completion Da	te:	g. Total Number of Transponders: 2	k. Total Common Carrier Transponder Bandwidth: MHz
d1. Est Launch Date Begin: 10/14/1976	d2. Est Launch Date End:	h. Total Transponder Bandwidth (no. transponders x Ba 0.048 MHz	, , , , , , , , , , , , , , , , , , , ,

S2. OPERATING FREQUENCY BANDS Identify the frequency range and transmit/receive mode for all frequency bands in which this station will oper Also indicate the nature of service(s) for each frequency band.

	Frequency	Band Limits						
Lower Frequency (_Hz) Upper Fr		Upper Frequency (Upper Frequency (_Hz)		f. Nature of Service(s): List all that apply to this band			
a. Numeric	b. Unit (K/M/G)	c. Numeric	d. Unit (K/M/G)					
254.138	М	254.162	M	Т	Military SATCOM			
257.538	М	257.562	М	Т	Military SATCOM			
307.738	М	307.762	М	R	Military SATCOM			
311.138	М	311.162	M	R	Military SATCOM			

S3. ORBITAL INFORMATION FOR GEOSTATIONARY SATELLITES ONLY:

a. Nominal Orbital Longitu 33.9 W	E/W):	b. Alternate 0	Orbital Longitu	ude (Degrees E/W):		c. Reason for orbital location selection: MARISAT-F2 is currently authorized to operate at 33.9			
Longitudinal Tolerance or d. Toward West: e. Toward East:	E/W Station- 0.1 0.1	Keeping: Degrees Degrees	f. Inclination I N/S Station-A Tolerance:		Range of orbital are in whi provided (Optional): g. Westernmost: h. Easternmost:	ich adequate serv <u>Degrees</u>	vice can be <u>E/W</u>	W in the C & L Bands.	
i. Reason for service a	re selection	n (Optional)	:						

Page 2: NGSO Orbits

FCC Form 312 - Schedule S: (Technical and Operational Description)

S4. ORBITAL INFORMATION FOR NON-GEOSTATIONARY SATELLITES ONLY

S4a. Total Number of Satellites in Network or System:

S4c. Celestial Reference Body (Earth, Sun, Moon, etc.):

S4b. Total Number of Orbital Planes in Network or System: S4d. Orbit Epoch Date:

For each Orbital Plane Provide:

(e) Orbital	(f) No. of	(g) Inclination	(h) Orbital	(i) Apogee (km)	(j) Perigee (km)	(k) Right Ascension	(I) Argument of	Active Service Arc Range (De		e (Degrees)
Plane No.	Satellites in	Angle (degrees)	Period			of the Ascending	Perigee	(m) Begin	(n) End	(o) Other
	Plane		(Seconds)			Node (Deg.)	(Degrees)	Angle	Ångle	,
			((13 111)	7g.c	79.0	

S5. INITIAL SATELLITE PHASE ANGLE For each satellite in each orbital plane, provide the intital phase angle.

(a) Orbital Plane No.	(b) Satellite Number	(c) Initial Phase Angle
		(Degrees)

NO NGSO DATA FILED

FCC Form 312 - Schedule S: (Technical and Operational Description)

S6. SERVICE AREA CHARACTERISTICS for each service area provide:

(a) Service Area ID	(b) Type of Associated Station (Earth or Space)	(d) Service Area Description. Provide list of geographic areas (state postal codes or ITU 3-ltr codes), satellites or Figure No. of Service Area Diagram.
AOR-T	Е	Atlantic Ocean Region
AOR-R	Е	Atlantic Ocean Region

Page 3: Service Areas

Page 4: Antenna Beams

FCC Form 312 - Schedule S: (Technical and Operational Description)

S7. SPACE STATION ANTENNA BEAM CHARACTERISTICS For each antenna beam provide:

(a)	(b)	Isotropic	Antenna	(e)	(f)	(g) Min.	(h) Polar-	(i) Polarization	(j) Service		Transmit				Receive		
Beam	T/R		ain	Pointing	Rotational	Cross-	ization	Alignment Rel.	Area ID	(k)	(I) Effective	(m)	(n)	(o) G/T	(p) Min.	Input Attenu	uator (dB)
ID	Mode	(c) Peak	(d) Edge	Error		Polar Iso-	Switch-	Equatorial		Input	Output	Max.	System	Max.	Saturation	(g) Max.	(r) Step
		(dBi)	(dBi)	(Degrees)	(Degrees)	lation (dB)		Plane (Degrees)		Losses	Power (W)	EIRP			Flux Density	Value	Size
							(Y/N)			(dB)		(dBW)	Temp (k)	(db/K)	(dBW/m2)	Value	0.20
AOR-	Т	14	13	0.65	0.65		N		AOR-T	1.5	18	23					
AOR-	R	15.4	14.4	0.65	0.65		N		AOR-R				31	-18	-151		

Page 5: Beam Diagrams

FCC Form 312 - Schedule S: (Technical and Operational Description)

S8. ANTENNA BEAM DIAGRAMS For each beam pattern provide the reference to the graphic image and numerical data:
Also provide the power flux density levels in each beam that result from the emission with the highest power flux density.

(a)	(b)	(c) Co-or	(d) GSO	(e) NGSO Antenna Gain									
Beam	T/R	Cross	Ref.	Contour Description	Gain Contour Data At Angle of Arrival above horizontal (for emission with highest								
ID	Mode	Polar Mode ("C" or" X")	Orbital Longitude (Deg. E/W)	(Figure/Table/ Exhibit)	(GXT File)	(g) 5 Deg	(h) 10 Deg	(i) 15 Deg	(j) 20 Deg	(k) 25 Deg			
AOR-	T	С	-33.9	MARISAT.pdf		-148	-148	-148	-148	-148			
AOR-	R	С	-33.9	MARISAT.pdf									

Page 6: Channels and Transponders

FCC Form 312 - Schedule S: (Technical and Operational Description)

S9. SPACE STATION CHANNELS For each frequency channel provide:

(B) Assigned Bandwidth (c) T/R (d) Center Frequency (MHz) (e) Polarization (f) TTC or Comm Channel (kHz) Mode (H, V, L, R) Channel No. (T or C) 307.75 A-T 24 T В-Т 24 T 311.15 24 R A-R 254.15

257.55

24 R

B-R

S10. SPACE STATION TRANSPONDERS For	or each transponder provide:

(a)	(b)	Receive	Band	Transmit Band		
Transponder ID	Transponder Gain (dB)	(c) Channel No.	(d) Beam ID	(e) Channel No.	(f) Beam ID	
Α	170	A-R	AOR-R	A-T	AOR-T	
В	170	B-R	AOR-R	B-T	AOR-T	

Page 7: Digital Modulation

FCC Form 312 - Schedule S: (Technical and Operational Description)

S11. DIGITAL MODULATION PARAMETERS For each digital emission provide:

ſ	(a) Digital	(b) Emission	(c) Assigned	(d) No. of	(e)Uncoded	(f) FEC Error	(g) CDMA	(h) Total C/N	(i) Single Entry
ı	Mod. ID	Designator	Bandwidth	Phases	Data Rate	Correction	Processing	Performance	C/I Objective
ı			(kHz)		(kbps)	Coding Rate	Gain (dB)	Objective (dB)	(dB)
П									

Page 8: Analog Modulation

FCC Form 312 - Schedule S: (Technical and Operational Description)

S12. ANALOG MODULATION PARAMETERS For each analog emission provide:

(a)	(b) Emission	(c)	(d) Signal	(e)	Multi-channel Telephony			(j) Video	(k) Video	(I) Video	(m) SCPC/FM	(n) Total C/N	(o) Single	
Analo Mod.		Assigned Bandwidth (kHz)	Туре	Channels per Carrier	(f) Ave. Companded Talker Level (dBm0)	(g) Bottom Baseband Freq. (MHz)		(i) RMS Modulation Index	Standard NTSC, PAL, etc.	- 3 - 3	and SCPC/FM Modulation Index	Compander, Preemphasis, and Noise Weighting (dB)	Performance Objective (dB)	Entry C/I Objective (dB)

Page 9: Typical Emissions

FCC Form 312 - Schedule S: (Technical and Operational Description)

S13. TYPICAL EMISSIONS For each planned type of emission provide:

	ciated			(e) Carriers	()	(3)	() - 3)	Receive Ba	and (Assoc. T	ransmit Stn)	Transmit Band (This Space Station			tion)
(a) Start	er ID Range (b) End	(c) Digital (Table S11)	(d) Analog (Table S12)	per Transponder	Spacing (kHz)	Reference (Table No.)	Dispersal Bandwidth (kHz)	(i)Assoc. Stn. Max.	Assoc. Stati Power		EIRP	(dBW)	Power Flux	(o)Assoc. Stn Rec. G/T
		511)					, ,	Antenna Gain (dBi)	(j) Min.	(k) Max.	(I) Min.	(m) Max.	Density (dBW/m2/Hz)	(dB/K)

FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS 212. School Like St. (Technical and Operational Property)

FCC Form 312 - Schedule S: (Technical and Operational Description)

S14. Is the space station(s) controlled and monitored remotely? If Yes, provide the location and telephone number of the TT and C control point(s): Yes

Remote Control (TT C) Location(s):

S14a: Street Address: 22000				
S14b. City: Clarksburg	S14c. County: Montgomery		S14d. State/Country MD	S14e. Zip Code: 20871
S14f. Telephone Number: 301-428-1501	S14g. Call Sign of Control Stat E000355	tion (if appropriate):		

Page 10: TT and C

FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS FCC Form 312 - Schedule S: (Technical and Operational Description)

Page 11: Characteristics and Certifications

S15. SPACECRAFT PHYSICAL CHARACTERISTICS:

S15a: Mass of spacecraft without fuel (kg): 306.356	Spacecraft Dimensions (meters)	Probability of Survival to End of Life (0.0 - 1.0)
S15b. Mass of fuel and disposables at launch (kg): 655.441		
S15c. Mass of spacecraft and fuel at launch (kg): 392.942	S15f. Length (m): 2.159	S15i. Payload: 1
S15d. Mass of fuel, in orbit, at beginning of life (kg): 328.841	S15g. Width (m): 2.159	S15j. Bus: 1
S15e. Deployed Area of Solar Array (square meters):	S15h. Height (m): 3.81	S15k. Total: 1

S16. SPACECRAFT ELECTRICAL CHARACTERISTICS:

Spacecraft Subsystem		ver (Watts) At ng of Life	Electrical Power (Watts) At End of Life						
	At Equinox	At Solstice	At Equinox	At Solstice					
Payload (Watts):	(a):	(f):	(k):	(p):					
Bus (Watts):	(b):	(g):	(I):	(q):					
Total (Watts):	(c):	(h):	(m)	^{(r):} 202					
Solar Array (Watts):	^{(d):} 409	^{(i):} 380	^{(n):} 348	^{(s):} 312					
Depth of Battery Discharge (%):	(e) %	(j) %	(o) %	^(t) 10 %					

S17. CERTIFICATIONS:

a. Are the power flux density limits of § 25.208 met?:		YES		NO	X	N/A	
b. Are the appropriate service area coverage requirements of § 25.143(b)(ii) and (iii), or § 25.145(c)(1) and (2) met?		YES		NO	Χ	N/A	
c. Are the frequency tolerances of § 25.202(e) and the out-of-band emission limits of § 25.202(f)(1), (2) and (3) met	?	YES		NO	X	N/A	
In addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the							

n addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the Commission's rules, 47 C.F.R § 25.114.