

<b>General</b>	Unit	
User terminal type	-	INM-M (Med. Gain)
Modulation ID / Designator	-	20K0G1X
Data rate (kbps)	(kbps)	1.5
Coding rate	-	0.5
Modulation	-	BPSK
Carrier bandwidth	(kHz)	3.75
Allocated bandwidth	(kHz)	20
<b>Uplink</b>		
Frequency	(GHz)	1.6
User terminal EIRP towards satellite	(dBW)	21.0
User terminal tx gain	(dBi)	14.0
Uplink power	(dBW)	7.0
Uplink p.s.d averaged in 4 kHz	(dBW/4kHz)	7.0
Path loss	(dB)	188.8
Mean Atmospheric loss	(dB)	0.1
Satellite G/T	(dB/K)	-10.0
Adjacent Channel Interference	(dB)	0.2
Up-path C/No	(dBHz)	50.5
<b>Downlink</b>		
Frequency	(GHz)	3.6
Satellite EIRP	(dBW)	-17.4
Path loss	(dB)	195.7
Mean Atmospheric loss	(dB)	0.4
Antenna diameter	m	19.0
Earth station G/T	(dB/K)	35.6
Random Loss	(dB)	1.0
Down-path C/No	(dBHz)	49.7
<b>Total</b>		
Mean satellite C/IMo	(dBHz)	51.1
Co-Channel Interference	(dBHz)	75.4
Other system interference allocation	(dB)	1.0
Mean Overall C/No	(dBHz)	44.6
Mean Overall C/N	(dB)	8.9
<b>Margin</b>		
C/N objective	(dB)	1.7
C/N margin	(dB)	7.2