

General	Unit	
User terminal type	-	AERO-I P-048
Modulation ID / Designator	-	5K00G1D
Data rate (kbps)	(kbps)	4.8
Coding rate	-	0.5
Modulation	-	A-QPSK
Carrier bandwidth	(kHz)	3
Allocated bandwidth	(kHz)	5
Uplink		
Frequency	(GHz)	1.6
User terminal EIRP towards satellite	(dBW)	15.9
User terminal tx gain	(dBi)	6.0
Uplink power	(dBW)	9.9
Uplink p.s.d averaged in 4 kHz	(dBW/4kHz)	9.9
Path loss	(dB)	188.8
Mean Atmospheric loss	(dB)	0.1
Satellite G/T	(dB/K)	-10.0
Adjacent Channel Interference	(dB)	0.2
Up-path C/No	(dBHz)	45.4
Downlink		
Frequency	(GHz)	3.6
Satellite EIRP	(dBW)	-10.2
Path loss	(dB)	195.7
Mean Atmospheric loss	(dB)	0.4
Antenna diameter	m	19.0
Earth station G/T	(dB/K)	35.6
Random Loss	(dB)	1.0
Down-path C/No	(dBHz)	56.9
Total		
Mean satellite C/IMo	(dBHz)	58.3
Co-Channel Interference	(dBHz)	75.4
Other system interference allocation	(dB)	1.0
Mean Overall C/No	(dBHz)	43.9
Mean Overall C/N	(dB)	9.1
Margin		
C/N objective	(dB)	4.7
C/N margin	(dB)	4.4