

| General | | |
|--------------------------------------|------------|----------|
| User terminal type | Unit | FLEET-55 |
| Modulation ID / Designator | - | 45K0G7D |
| Data rate (kbps) | (kbps) | 64 |
| Coding rate | - | 0.5 |
| Modulation | - | 16 QAM |
| Carrier bandwidth | (kHz) | 40 |
| Allocated bandwidth | (kHz) | 45 |
| Uplink | | |
| Frequency | (GHz) | 1.6 |
| User terminal EIRP towards satellite | (dBW) | 27.6 |
| User terminal tx gain | (dBi) | 17.0 |
| Uplink power | (dBW) | 10.6 |
| Uplink p.s.d averaged in 4 kHz | (dBW/4kHz) | 0.6 |
| Path loss | (dB) | 188.8 |
| Mean Atmospheric loss | (dB) | 0.1 |
| Satellite G/T | (dB/K) | 2.2 |
| Adjacent Channel Interference | (dB) | 0.2 |
| Up-path C/No | (dBHz) | 69.3 |
| Downlink | | |
| Frequency | (GHz) | 3.6 |
| Satellite EIRP | (dBW) | 1.2 |
| Path loss | (dB) | 195.7 |
| Mean Atmospheric loss | (dB) | 0.4 |
| Earth station G/T | (dB/K) | 35.6 |
| Random Loss | (dB) | 1.0 |
| Down-path C/No | (dBHz) | 68.3 |
| Total | | |
| Mean satellite C/IMo | (dBHz) | 69.7 |
| Co-Channel Interference | (dBHz) | 75.4 |
| Other system interference allocation | (dB) | 1.0 |
| Mean Overall C/No | (dBHz) | 63.0 |
| Mean Overall C/N | (dB) | 17.0 |
| Margin | | |
| C/N objective | (dB) | 7.7 |
| C/N margin | (dB) | 9.3 |