

**LB6 – LINK BUDGETS - EVDOF**

<b>Table A-3: EVDO Forward Data Link Budget</b>		
<b>Satellite and Earth Station Information</b>		
Uplink name	Las Vegas (6.3 m)	Las Vegas (9.3 m)
Satellite longitude (degrees) (- = West)	-111.1	-111.1
Downlink elevation angle (degrees)	36.10	36.10
<b>Carrier Information</b>		
Frequency reuse pattern	4	4
Beam pitch (deg)	0.25	0.25
CDMA carrier bandwidth (MHz)	1.25	1.25
Information rate (including overhead) (kbps)	964	965
Modulation	QPSK	QPSK
FEC code rate	0.5	0.5
Required total C/N with margin (dB)	1.51	1.51
<b>Uplink</b>		
Uplink frequency (GHz)	12.88	12.88
Uplink EIRP (on-axis) (dBW)	51.93	55.13
Uplink atmospheric loss (dB)	0.11	0.11
Rain availability (%)	99.99	99.99
Uplink rain fade (dB)	3.37	3.37
Uplink free space path loss (dB)	206.05	206.05
Transponder G/T (dBi/K)	15.06	15.06
Uplink C/N (dB)	26.22	29.41
C/I adj channel (dB)	16.13	16.12
C/I depolarization (dB)	25.23	25.23
Composite uplink C/I (dB)	15.62	15.62
<b>Satellite Transponder</b>		
Power control tolerance (dB)-per user	0.50	0.50
Power control tolerance (dB)-per uplink	1.00	1.00
Per carrier output backoff (dB)	27.47	27.47
Expected C/IM in digital carrier bandwidth at satellite (dB)	12.50	12.50
<b>Downlink</b>		
Downlink frequency (GHz)	2.19	2.19
Satellite EIRP per carrier (dBW)	75.10	75.10
Downlink free space path loss (dB)	190.87	190.87
Downlink atmospheric loss (dB)	0.06	0.06
Shadowing + fading (dB)	3.00	3.00
Earth station on-axis G/T (with downlink rain fade) (dBi/K)	-28.00	-28.00
Polarization loss (dB)	3.00	3.00
Downlink C/N (dB)	18.94	18.93
Expected composite downlink C/I (dB)	2.16	2.16
<b>Overall Performance Summary</b>		
Computed uplink or system margin (dB)	0.00	0.00
Downlink margin (dB)	0.01	0.20

**Table A-4: EVDO Forward Voice Link Budget**

<b>Table A-4: EVDO Forward Voice Link Budget</b>		
<b>Satellite and Earth Station Information</b>		
Uplink name	Las Vegas (6.3 m)	Las Vegas (9.3 m)
Satellite longitude (degrees) (- = West)	-111.1	-111.1
Downlink elevation Angle (degrees)	36.10	36.10
<b>Carrier Information</b>		
Frequency reuse pattern	4	4
Beam pitch (deg)	0.25	0.25
Number of beams	280	280
Number of CDMA carriers per beam	2	2
Number of users per carrier	1	1
CDMA carrier bandwidth (MHz)	1.25	1.25
Information rate (including overhead) (kbps)	304.56	304.56
Activity factor	0.4	0.4
Voice rate (including overhead) (kbps)	5.64	5.64
Number of voice channels per beam	270.00	270.00
Modulation	QPSK	QPSK
FEC code rate	0.2	0.2
Required total C/N with margin (dB)	-3.53	-3.53
<b>Uplink</b>		
Uplink frequency (GHz)	12.88	12.88
Uplink EIRP (on-axis) (dBW)	48.92	52.12
Uplink atmospheric loss (dB)	0.11	0.11
Rain availability (%)	99.99	99.99
Uplink rain fade (dB)	3.37	3.37
Uplink free space path loss (dB)	206.05	206.05
Transponder G/T (dBi/K)	15.06	15.06
Uplink C/N (dB)	24.23	27.43
C/I adj-channel (dB)	21.13	21.13
C/I depolarization (dB)	25.23	25.23
Composite uplink C/I (dB)	19.70	19.70
<b>Satellite Transponder</b>		
Power control tolerance (dB)-per user	0.50	0.50
Power control tolerance (dB)-per uplink	1.00	1.00
Per carrier output backoff (dB)	30.48	30.48
Expected C/IM in digital carrier bandwidth at satellite (dB)	12.50	12.50
<b>Downlink</b>		
Downlink frequency (GHz)	2.19	2.19
Satellite EIRP per carrier (dBW)	52.86	52.86
Downlink free space path loss (dB)	190.87	190.87
Downlink atmospheric loss (dB)	0.06	0.06
Shadowing + fading (dB)	3.00	3.00
Earth station on-axis G/T (with downlink rain fade) (dBi/K)	-28.00	-28.00
Polarization loss (dB)	3.00	3.00
Downlink C/N (dB)	-2.28	-2.28
Expected composite downlink C/I (dB)	3.19	3.19
<b>Overall Performance Summary</b>		
Computed uplink or system margin (dB)	0.02	0.03
Downlink margin (dB)	0.03	0.04