FCC	312	
Sche	dule	S

FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS (Technical and Operational Description)

Page 1: General, Frequency Bands, and GSO Orbit

a. Space Station or Satellite N INMARSAT-3 F3	etwork Name:	e. Estimated Date of Placement into Service: 1/25/1997	i Will the space station(s) operate on a Common Carrier Basis:		
b. Construction Commenceme	nt Date:	f. Estimated Lifetime of Satellite(s): 13 Years	j. Number of transponders offered on a common carrier basis:		
c. Construction Completion Da	te:	g. Total Number of Transponders: 4	k. Total Common Carrier Transponder Bandwidth: 0 MHz		
d1. Est Launch Date Begin:	d2. Est Launch Date End:	h. Total Transponder Bandwidth (no. transponders x Bandwidth) 68 MHz	I. Orbit Type: Mark all boxes that apply: X GSO NGSO		

S2. OPERATING FREQUENCY BANDS Identify the frequency range and transmit/receive mode for all frequency bands in which this station will oper Also indicate the nature of service(s) for each frequency band.

	Frequency	Band Limits						
Lower Frequency (_Hz) Upper Frequency (_Hz)		_Hz)	e. T/R Mode	f. Nature of Service(s): List all that apply to this band				
a. Numeric	b. Unit (K/M/G)	c. Numeric	d. Unit (K/M/G)					
1525	М	1559	M	Т	Mobile-Satellite Service			
1626.5	М	1660.5	М	R	Mobile-Satellite Service			
6425	М	6454	М	R	Feeder Link for Mobile Satellite Service in FSS			
3600	М	3629	M	Т	Feeder Link for Mobile Satellite Service in FSS			

S3. ORBITAL INFORMATION FOR GEOSTATIONARY SATELLITES ONLY:

a. Nominal Orbital Longitude (Degrees E/W): 178.1 E			b. Alternate Orbital Longitude (Degrees E/W):				c. Reason for orbital location selection: Inmarsat is authorized by the United Kingdom to	
Longitudinal Tolerance or E d. Toward West: e. Toward East:	E/W Station 0.1 0.1	-Keeping: Degrees Degrees	f. Inclination N/S Station-P Tolerance: 2.7		Range of orbital are in wh provided (Optional): g. Westernmost: h. Easternmost:	hich adequate serv <u>Degrees</u>	vice can be <u>E/W</u>	operate the Inmarsat-3 F3 satellite at 178.1 E.L.
i. Reason for service ar	e selectio	n (Optional)	:					

Page 2: NGSO Orbits

FCC Form 312 - Schedule S: (Technical and Operational Description)

S4. ORBITAL INFORMATION FOR NON-GEOSTATIONARY SATELLITES ONLY

S4a. Total Number of Satellites in Network or System:

S4c. Celestial Reference Body (Earth, Sun, Moon, etc.):

S4b. Total Number of Orbital Planes in Network or System: S4d. Orbit Epoch Date:

For each Orbital Plane Provide:

(e) Orbital	(f) No. of	(g) Inclination	(h) Orbital	(i) Apogee (km)	(j) Perigee (km)	(k) Right Ascension	(I) Argument of	Active Se	rvice Arc Rang	e (Degrees)
Plane No.	Satellites in	Angle (degrees)	Period			of the Ascending	Perigee	(m) Begin	(n) End	(o) Other
	Plane		(Seconds)			Node (Deg.)	(Degrees)	Angle	Ångle	,
			((13 111)	7g.c	79.0	

S5. INITIAL SATELLITE PHASE ANGLE For each satellite in each orbital plane, provide the intital phase angle.

(a) Orbital Plane No.	(b) Satellite Number	(c) Initial Phase Angle
		(Degrees)

NO NGSO DATA FILED

FCC Form 312 - Schedule S: (Technical and Operational Description)

S6. SERVICE AREA CHARACTERISTICS for each service area provide:

	(a) Service Area ID	(b) Type of Associated Station (Earth or Space)	(d) Service Area Description. Provide list of geographic areas (state postal codes or ITU 3-ltr codes), satellites or Figure No. of Service Area Diagram.
Ī	GLOBAL	S	All visible areas of the Earth.

Page 3: Service Areas

Page 4: Antenna Beams

FCC Form 312 - Schedule S: (Technical and Operational Description)

S7. SPACE STATION ANTENNA BEAM CHARACTERISTICS For each antenna beam provide:

(a)	(b)	Isotropic	Antenna	(e)	(f)	(g) Min.	(h) Polar-	(i) Polarization	(j) Service		Transmit				Receive		
Beam	T/R	Ga	ain	0	Rotational	Cross-	ization	Alignment Rel.	Area ID	(k)	(I) Effective	(m)	(n)	(o) G/T	(p) Min.	Input Attenu	uator (dB)
ID	Mode	(c) Peak (dBi)	(d) Edge (dBi)	Error (Degrees)	Error (Degrees)	Polar Iso- lation (dB)		Equatorial Plane (Degrees)		Input Losses	Output Power (W)	Max. EIRP			Saturation Flux Density	(q) Max. Value	(r) Step Size
							(Y/N)			(dB)		(dBW)	Temp (k)	(db/K)	(dBW/m2)	Value	OIZO
CGU	R	20.5	16.5	0.1	0.1	30	Ν		GLOBAL				891	-9	-98	24	2
CGU	R	20.5	16.5	0.1	0.1	30	Ν		GLOBAL				891	-9	-98	24	2
CGD	T	20	16.5	0.1	0.1	30	Ν		GLOBAL	3.3	10.5	30.5					
CGD	T	20	16.5	0.1	0.1	30	Ν		GLOBAL	3.3	10.5	30.5					
LGU	R	18.5	16	0.1	0.1		Ν		GLOBAL				562	-9	-109	23	2
LGD	Т	19.5	17	0.1	0.1	·	N		GLOBAL	4.1	159	41.5			·	·	

FCC Form 312 - Schedule S: (Technical and Operational Description)

S8. ANTENNA BEAM DIAGRAMS For each beam pattern provide the reference to the graphic image and numerical data:
Also provide the power flux density levels in each beam that result from the emission with the highest power flux density.

(a)	(b)	(c) Co-or	(d) GSO	(e) NGSO Antenna Gain	(f) GSO Antenna		Max. Power F	lux Density (dB	W/M2/Hz)		
Beam	T/R	Cross	Ref.	Contour Description	Gain Contour Data	At Angle of	Arrival above ho	orizontal (for em	nission with highest PFD)		
ID	Mode	Polar Mode ("C"	Orbital Longitude	(Figure/Table/ Exhibit)	(GXT File)	(g) 5 Deg	(h) 10 Deg	(i) 15 Deg	(j) 20 Deg	(k) 25 Deg	
		or" X")	(Deg. E/W)								
CGU	R	С	178.1		CGUR.GXT						
CGU	R	С	178.1		CGUL.GXT						
CGD	Т	С	178.1		CGDR.GXT	-180.2	-180	-179.8	-179.5	-179.2	
CGD	Т	С	178.1		CGDL.GXT	-180.2	-180	-179.8	-179.5	-179.2	
LGU	R	С	178.1		LGUR.GXT						
LGD	Т	С	178.1		LGDR.GXT						

Page 5: Beam Diagrams

Page 6: Channels and Transponders

FCC Form 312 - Schedule S: (Technical and Operational Description)

S9. SPACE STATION CHANNELS For each frequency channel provide: S10. SPACE STATION TRANSPONDERS For each transponder provide:

(a) Channel No.	(B) Assigned Bandwidth (kHz)	(c) T/R Mode	(d) Center Frequency (MHz)	(e) Polarization (H, V, L, R)	(f) TTC or Comm Channel (T or C)
CUR	29000	R	6439.5	R	С
CUL	29000	R	6439.5	L	С
CDR	29000	Т	3614.5	R	С
CDL	29000	Т	3614.5	L	С
LUR	34000	R	1643.5	R	С
LDR	34000	T	1542	R	С

(a)	(b)	Receive	Band	Transmit Band		
Transponder ID	Transponder Gain (dB)	(c) Channel No.	(d) Beam ID	(e) Channel No.	(f) Beam ID	
FL1	137	CUR	CGUR	LDR	LGDR	
FL2	137	CUL	CGUL	LDR	LGDR	
RL1	127	LUR	LGUR	CDR	CGDR	
RL2	127	LUR	LGUR	CDL	CGDL	

Page 7: Digital Modulation

FCC Form 312 - Schedule S: (Technical and Operational Description)

S11. DIGITAL MODULATION PARAMETERS For each digital emission provide:

(a) Digital Mod. ID	(b) Emission Designator	(c) Assigned Bandwidth (kHz)	(d) No. of Phases	(e)Uncoded Data Rate (kbps)	(f) FEC Error Correction Coding Rate	Processing	(h) Total C/N Performance Objective (dB)	(i) Single Entry C/I Objective (dB)
D1	5K00G1D	5000	2	0.3	0.5		3.5	15.7

Page 8: Analog Modulation

FCC Form 312 - Schedule S: (Technical and Operational Description)

S12. ANALOG MODULATION PARAMETERS For each analog emission provide:

(a)	(b) Emission	(c)	(d) Signal	(e)	Multi-channel Telephony			(j) Video	(k) Video	(I) Video	(m) SCPC/FM	(n) Total C/N	(o) Single	
Analo Mod.		Assigned Bandwidth (kHz)	Туре	Channels per Carrier	(f) Ave. Companded Talker Level (dBm0)	(g) Bottom Baseband Freq. (MHz)		(i) RMS Modulation Index	Standard NTSC, PAL, etc.	- 3 - 3	and SCPC/FM Modulation Index	Compander, Preemphasis, and Noise Weighting (dB)	Performance Objective (dB)	Entry C/I Objective (dB)

Page 9: Typical Emissions

FCC Form 312 - Schedule S: (Technical and Operational Description)

S13. TYPICAL EMISSIONS For each planned type of emission provide:

Assoc			lation ID	(-)	` '	(g)Noise Budget	(h) Energy	Receive Ba	and (Assoc. Ti	ransmit Stn)	Trai	nsmit Band	(This Space Stat	tion)
(a) Start	er ID Range (b) End	(C) Digital (Table	(d) Analog (Table S12)	per Transponder	Spacing (kHz)	Reference (Table No.)	Dispersal Bandwidth (kHz)	(i)Assoc. Stn. Max. Antenna	Assoc. Static Power		EIRP	(dBW)	Power Flux	(o)Assoc. Stn Rec. G/T
		S11)		, ,	Gain (dBi)	(j) Min.	(k) Max.	(I) Min.	(m) Max.	(dBW/m2/Hz) (dB/K)				
FL1	FL2	D1		83	10000	FL INM-C LB.d		54	1.5	7.1	19.8	24.3		-23
RL1	RL2	D1		2900	10000	RL INM-C LB.d		54	10.5	16	-24.7	-13.4	-175.5	30.7

Page 10: TT and C

FCC Form 312 - Schedule S: (Technical and Operational Description)

S14. Is the space station(s) controlled and monitored remotely? If Yes, provide the location and telephone number of the TT and C control point(s): #Error

Remote Control (TT C) Locatio S14a: Street Address: Beijing Inmarsat TTC Station	n(s):							
S14b. City: Beijing	S14c. County:		S14d. State/Country	S14e. Zip Code: 102206				
\$14f. Telephone Number: +86 10 6202 7169	•		S14g. Call Sign of Control Station (if appropriate):					
Remote Control (TT C) Locatio	n(s):							
S14a: Street Address: Stazione del Fucino								
S14b. City: Ortucchio AQ	S14c. County: Avezzano		S14d. State/Country	S14e. Zip Code: 67050				
S14f. Telephone Number: +39 0863 550597	•		S14g. Call Sign of Control Station (if appropriate):					
Remote Control (TT C) Locatio	n(s):							
S14a: Street Address: 8801 Youbou Road								
S14b. City: Lake Cowichan	S14c. County: BC		S14d. State/Country	S14e. Zip Code: V0R 2G0				
S14f. Telephone Number: +1 250-749-6646	•	S14g. Call Sign	of Control Station (if appropriate):	•				

FEDERAL COMMUNICATIONS COMMISSION **SATELLITE SPACE STATION AUTHORIZATIONS** FCC Form 312 - Schedule S: (Technical and Operational Description)

Page 11: Characteristics and Certifications

S15. SPACECRAFT PHYSICAL CHARACTERISTICS:

S15a: Mass of spacecraft without fuel (kg): 865	Spacecraft Dimensions (meters)	Probability of Survival to End of Life (0.0 - 1.0)
S15b. Mass of fuel and disposables at launch (kg): 1175		
S15c. Mass of spacecraft and fuel at launch (kg): 2040	S15f. Length (m): 3.15	S15i. Payload: 0.72
S15d. Mass of fuel, in orbit, at beginning of life (kg): 283	S15g. Width (m): 20.67	S15j. Bus: 0.9
S15e. Deployed Area of Solar Array (square meters): 30.5	S15h. Height (m): 2.31	S15k. Total: 0.65

S16. SPACECRAFT ELECTRICAL CHARACTERISTICS:

Spacecraft Subsystem		ver (Watts) At ng of Life	Electrical Power (Watts) and of Life				
	At Equinox	At Solstice	At Equinox	At Solstice			
Payload (Watts):	^{(a):} 2099	^{(f):} 2132	^{(k):} 2099	^{(p):} 2132			
Bus (Watts):	^{(b):} 717	^{(g):} 478	^{(l):} 717	^{(q):} 478			
Total (Watts):	^{(c):} 2816	^{(h):} 2610	^(m) 2816	^{(r):} 2610			
Solar Array (Watts):	^{(d):} 3700	^{(i):} 3250	^{(n):} 3105	^{(s):} 2832			
Depth of Battery Discharge (%):	^(e) 70 %	^(j) 0 %	⁽⁰⁾ 70 %	^(t) 0 %			

S17. CERTIFICATIONS:

a. Are the power flux density limits of § 25.208 met?:	XY	ES	NO	N/A				
b. Are the appropriate service area coverage requirements of § 25.143(b)(ii) and (iii), or § 25.145(c)(1) and (2) met?	Y	ES	NO	X N/A				
c. Are the frequency tolerances of § 25.202(e) and the out-of-band emission limits of § 25.202(f)(1), (2) and (3) met	XY	ES	NO	N/A				
In addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the								

Commission's rules, 47 C.F.R § 25.114.