

General		
User terminal type	Unit	INM-B
	-	
Modulation ID / Designator	-	100KG1X
Data rate (kbps)	(kbps)	64
Coding rate	-	0.5
Modulation	-	O-QPSK
Carrier bandwidth	(kHz)	80
Allocated bandwidth	(kHz)	100
Uplink		
Frequency	(GHz)	1.6
User terminal EIRP towards satellite	(dBW)	33.0
User terminal tx gain	(dBi)	21.0
Uplink power	(dBW)	12.0
Uplink p.s.d averaged in 4 kHz	(dBW/4kHz)	-1.0
Path loss	(dB)	188.8
Mean Atmospheric loss	(dB)	0.1
Satellite G/T	(dB/K)	-10.0
Adjacent Channel Interference	(dB)	0.2
Up-path C/No	(dBHz)	62.5
Downlink		
Frequency	(GHz)	3.6
Satellite EIRP	(dBW)	-1.4
Path loss	(dB)	195.7
Mean Atmospheric loss	(dB)	0.4
Antenna diameter	m	19.0
Earth station G/T	(dB/K)	35.6
Random Loss	(dB)	1.0
Down-path C/No	(dBHz)	65.7
Total		
Mean satellite C/IMo	(dBHz)	67.1
Co-Channel Interference	(dBHz)	75.4
Other system interference allocation	(dB)	1.0
Mean Overall C/No	(dBHz)	58.8
Mean Overall C/N	(dB)	9.7
Margin		
C/N objective	(dB)	5.0
C/N margin	(dB)	4.7