

FREQUENCY COORDINATION AND INTERFERENCE ANALYSIS REPORT

Prepared for
Global Crossing Americas Solutions, Inc
ALTONA, USVI
E080123
Satellite Earth Station

Prepared By:
COMSEARCH
19700 Janelia Farm Boulevard
Ashburn, VA 20147
January 16, 2016

TABLE OF CONTENTS

1. CONCLUSIONS	3
2. SUMMARY OF RESULTS	4
3. SUPPLEMENTAL SHOWING	5
4. EARTH STATION COORDINATION DATA.....	6
5. CERTIFICATION.....	10

1. CONCLUSIONS

An interference study considering all existing, proposed and prior coordinated microwave facilities within the coordination contours of the proposed earth station demonstrates that this site will operate satisfactorily with the common carrier microwave environment. Further, there will be no restrictions of its operation due to interference considerations.

2. SUMMARY OF RESULTS

A number of great circle interference cases were identified during the interference study of the proposed earth station. Each of the cases, which exceeded the interference objective on a line-of-sight basis, was profiled and the propagation losses estimated using NBS TN101 (Revised) techniques. The losses were found to be sufficient to reduce the signal levels to acceptable magnitudes in every case.

3. SUPPLEMENTAL SHOWING

Pursuant to Part 25.203(c) of the FCC Rules and Regulations, the satellite earth station proposed in this application was coordinated by Comsearch using computer techniques and in accordance with Part 25 of the FCC Rules and Regulations.

Coordination data for this earth station was sent to the below listed carriers with a letter dated 01/12/2016.

Company

AT&T Mobility Puerto Rico
AT&T Mobility Virgin Islands, Inc.
Aeronet Wireless Broadband Corp.
Broadband Telecommunications Network
Broadband VI, LLC
Choice Communications, LLC (VI)
EVERTEC, INC
Iniciativa Tecnologica Centro Oriental
Neptuno Media
PR Wireless, Inc.
PREPA Networks, LLC.
Puerto Rico Commonwealth
Puerto Rico Electric Power Authority
Puerto Rico Telephone Company, Inc.
Sprintcom, Inc
Sprintcom, Inc. Puerto Rico
Surge Communications LLC
System Development Integration, LLC
T-Mobile Puerto Rico LLC
UNIVERSITY OF THE VIRGIN ISLANDS
Virgin Islands Telephone Corporation

4. EARTH STATION COORDINATION DATA

This section presents the data pertinent to frequency coordination of the proposed earth station that was circulated to all carriers within its coordination contours.

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Date: 01/16/2016
Job Number: 160112COMSGE06

Administrative Information

Status ENGINEER PROPOSAL
Call Sign E080123
Licensee Code GLOAME
Licensee Name Global Crossing Americas Solutions, Inc

Site Information

ALTONA, VI
Venue Name
Latitude (NAD 83) 18° 20' 19.3" N
Longitude (NAD 83) 64° 56' 49.9" W
Climate Zone C
Rain Zone 1
Ground Elevation (AMSL) 15.0 m / 49.2 ft

Link Information

Satellite Type Geostationary
Mode TR - Transmit-Receive
Modulation Digital
Satellite Arc 45° W to 56° West Longitude
Azimuth Range 130.9° to 153.4°
Corresponding Elevation Angles 58.6° / 66.2°
Antenna Centerline (AGL) 9.45 m / 31.0 ft

Antenna Information

		Receive - FCC32		Transmit - FCC32	
Manufacturer		Prodelin		Prodelin	
Model		1251		1251	
Gain / Diameter		38.0 dBi / 2.4 m		42.0 dBi / 2.4 m	
3-dB / 15-dB Beamwidth		2.30° / 4.60°		1.50° / 3.00°	
Max Available RF Power	(dBW/4 kHz) (dBW/MHz)			-17.6 6.4	
Maximum EIRP	(dBW/4 kHz) (dBW/MHz)			24.4 48.4	
Interference Objectives:	Long Term	-156.0 dBW/MHz	20%	-154.0 dBW/4 kHz	20%
	Short Term	-146.0 dBW/MHz	0.01%	-131.0 dBW/4 kHz	0.0025%

Frequency Information

	Receive 4.0 GHz	Transmit 6.1 GHz
Emission / Frequency Range (MHz)	115KG7D - 8M45G7D / 3700.0 - 4200.0	115KG7D - 1M15G7D / 5925.0 - 6425.0
Max Great Circle Coordination Distance	710.9 km / 441.7 mi	200.9 km / 124.8 mi
Precipitation Scatter Contour Radius	100.0 km / 62.1 mi	100.0 km / 62.1 mi

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Coordination Values

ALTONA, VI

Licensee Name Global Crossing Americas Solutions, Inc
Latitude (NAD 83) 18° 20' 19.3" N
Longitude (NAD 83) 64° 56' 49.9" W
Ground Elevation (AMSL) 15.0 m / 49.2 ft
Antenna Centerline (AGL) 9.45 m / 31.0 ft
Antenna Model Prodelin 2.4 meter
Antenna Mode Receive 4.0 GHz Transmit 6.1 GHz
Interference Objectives: Long Term -156.0 dBW/MHz 20% -154.0 dBW/4 kHz 20%
Short Term -146.0 dBW/MHz 0.01% -131.0 dBW/4 kHz 0.0025%
Max Available RF Power -17.6 (dBW/4 kHz)

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 4.0 GHz		Transmit 6.1 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	13.08	117.30	-10.00	100.00	-10.00	100.00
5	13.52	114.46	-10.00	100.00	-10.00	100.00
10	14.04	111.46	-10.00	100.00	-10.00	100.00
15	13.55	107.97	-10.00	100.00	-10.00	100.00
20	12.35	104.29	-10.00	100.00	-10.00	100.00
25	10.79	100.61	-10.00	100.00	-10.00	100.00
30	9.43	97.11	-10.00	100.00	-10.00	100.00
35	9.43	93.87	-10.00	100.00	-10.00	100.00
40	6.94	90.57	-10.00	127.48	-10.00	100.00
45	6.51	87.50	-10.00	132.17	-10.00	100.00
50	5.92	84.52	-10.00	139.48	-10.00	100.00
55	5.66	81.58	-10.00	145.39	-10.00	100.00
60	4.18	79.05	-10.00	170.88	-10.00	100.00
65	4.33	76.24	-10.00	169.04	-10.00	100.00
70	5.36	73.11	-10.00	152.46	-10.00	100.00
75	5.36	70.43	-10.00	152.42	-10.00	100.00
80	5.36	67.86	-10.00	152.43	-10.00	100.00
85	2.42	67.25	-10.00	251.76	-10.00	100.00
90	2.09	65.39	-10.00	275.97	-10.00	100.00
95	1.08	64.26	-10.00	378.14	-10.00	100.00
100	1.90	61.94	-10.00	292.05	-10.00	100.00
105	3.80	58.81	-10.00	180.71	-10.00	100.00
110	2.34	58.80	-10.00	257.64	-10.00	100.00
115	1.46	58.60	-10.00	334.66	-10.00	100.00
120	1.31	58.00	-10.00	351.14	-10.00	100.00
125	1.99	56.86	-10.00	283.67	-10.00	100.00
130	1.92	56.74	-10.00	290.60	-10.00	100.00
135	1.53	57.21	-10.00	326.38	-10.00	100.00
140	0.89	58.21	-10.00	415.15	-10.00	100.00
145	0.00	59.69	-10.00	710.92	-10.00	200.95
150	0.00	60.55	-10.00	710.92	-10.00	200.95
155	0.00	61.64	-10.00	710.92	-10.00	200.95
160	0.00	62.95	-10.00	710.92	-10.00	200.95
165	0.91	63.76	-10.00	410.18	-10.00	100.00
170	1.66	64.98	-10.00	315.67	-10.00	100.00
175	2.30	65.81	-10.00	259.96	-10.00	100.00
180	1.87	67.18	-10.00	295.45	-10.00	100.00
185	1.10	68.95	-10.00	375.64	-10.00	100.00

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Coordination Values


ALTONA, VI

Licensee Name Global Crossing Americas Solutions, Inc
Latitude (NAD 83) 18° 20' 19.3" N
Longitude (NAD 83) 64° 56' 49.9" W
Ground Elevation (AMSL) 15.0 m / 49.2 ft
Antenna Centerline (AGL) 9.45 m / 31.0 ft
Antenna Model Prodelin 2.4 meter
Antenna Mode Receive 4.0 GHz Transmit 6.1 GHz
Interference Objectives: Long Term -156.0 dBW/MHz 20% -154.0 dBW/4 kHz 20%
Short Term -146.0 dBW/MHz 0.01% -131.0 dBW/4 kHz 0.0025%
Max Available RF Power -17.6 (dBW/4 kHz)

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 4.0 GHz		Transmit 6.1 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
190	1.60	69.82	-10.00	319.35	-10.00	100.00
195	0.68	71.91	-10.00	465.69	-10.00	113.64
200	1.07	73.17	-10.00	378.86	-10.00	100.00
205	0.00	75.45	-10.00	710.92	-10.00	200.95
210	0.00	77.14	-10.00	710.92	-10.00	200.95
215	0.00	78.91	-10.00	710.92	-10.00	200.95
220	0.90	80.42	-10.00	411.16	-10.00	100.00
225	1.06	82.35	-10.00	380.55	-10.00	100.00
230	2.19	84.16	-10.00	268.62	-10.00	100.00
235	0.89	86.49	-10.00	414.87	-10.00	100.00
240	1.33	88.55	-10.00	349.02	-10.00	100.00
245	2.46	90.70	-10.00	248.76	-10.00	100.00
250	1.97	92.86	-10.00	285.87	-10.00	100.00
255	0.88	94.82	-10.00	416.26	-10.00	100.00
260	1.37	96.98	-10.00	344.35	-10.00	100.00
265	1.56	99.08	-10.00	323.49	-10.00	100.00
270	3.86	102.01	-10.00	178.37	-10.00	100.00
275	4.59	104.44	-10.00	165.79	-10.00	100.00
280	4.28	106.31	-10.00	169.60	-10.00	100.00
285	4.86	108.59	-10.00	162.69	-10.00	100.00
290	5.85	111.09	-10.00	141.04	-10.00	100.00
295	6.74	113.49	-10.00	129.63	-10.00	100.00
300	6.75	115.14	-10.00	129.49	-10.00	100.00
305	7.31	117.06	-10.00	123.48	-10.00	100.00
310	8.44	119.35	-10.00	109.55	-10.00	100.00
315	8.65	120.64	-10.00	105.87	-10.00	100.00
320	10.17	122.96	-10.00	100.00	-10.00	100.00
325	10.97	124.38	-10.00	100.00	-10.00	100.00
330	11.66	125.42	-10.00	100.00	-10.00	100.00
335	12.35	126.18	-10.00	100.00	-10.00	100.00
340	11.44	125.02	-10.00	100.00	-10.00	100.00
345	11.17	124.04	-10.00	100.00	-10.00	100.00
350	12.13	122.29	-10.00	100.00	-10.00	100.00
355	12.75	120.00	-10.00	100.00	-10.00	100.00

5. CERTIFICATION

I HEREBY CERTIFY THAT I AM THE TECHNICALLY QUALIFIED PERSON RESPONSIBLE FOR THE PREPARATION OF THE FREQUENCY COORDINATION DATA CONTAINED IN THIS APPLICATION, THAT I AM FAMILIAR WITH PARTS 101 AND 25 OF THE FCC RULES AND REGULATIONS, THAT I HAVE EITHER PREPARED OR REVIEWED THE FREQUENCY COORDINATION DATA SUBMITTED WITH THIS APPLICATION, AND THAT IT IS COMPLETE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

BY: 

Gary K. Edwards
Senior Manager
COMSEARCH
19700 Janelia Farm Boulevard
Ashburn, VA 20147

DATED: January 16, 2016