# Ka-Band Earth Station – Taos, NM Frequency Coordination Report 28 GHz



Prepared on Behalf of HUGHES NETWORK SYSTEMS LIMITED

January 9, 2019





## **Table of Contents**

1.	Summary of Results	- 1 -
2.	28 GHz Common Carrier and LTTS Coordination	- 1 -
3.	28 GHz UMFUS Coordination	- 2 -
4.	Earth Station Coordination Data	- 3 -
5.	Contact Information	- 7 -



### 1. Summary of Results

On behalf of HUGHES NETWORK SYSTEMS LIMITED, Comsearch performed a coordination notice for all existing and proposed terrestrial licenses within the coordination contours of their proposed Ka-Band earth station in Taos, NM, which will transmit at 28 GHz<sup>1</sup>. Prior-notification letters were sent to the licensees and a copy of the notification data is provided in section four of this report. The earth station coordination was finalized on January 4, 2019.

No objections were received from any of the incumbent 28 GHz licensees. Our notification to the UMFUS incumbents was performed under the assumption that the earth station would be operating on a secondary basis to UMFUS L1 & L2 Block operations and a contact at Hughes Network Systems Limited has been provided in case any concerns may arise in the future.

#### 2. 28 GHz Common Carrier and LTTS Coordination

In accordance with FCC Rules and Regulations, the Ka-Band earth station in Taos, NM was priorcoordinated by Comsearch. A notification letter and datasheets for this earth station were sent to the following 28 GHz common carrier fixed microwave licensees. These licensees are authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis or local basis.

Licensee	Authorized Geographic Area
Frontier Southwest Incorporated	Nationwide

A notification letter and datasheets for the Ka-Band earth station in Taos, NM were also sent to the following 28 GHz local television transmission licensee. This licensee is authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis.

Licensee	Authorized Geographic Area
Information Super Station, LLC	Continental US

No objections were received from the common carrier or local television transmission service incumbents.

<sup>&</sup>lt;sup>1</sup> The proposed earth station will operate in the 27.5 – 28.6 GHz portion of the Ka-Band.



#### **3.** 28 GHz UMFUS Coordination

A Notification letter was sent to the following 28 GHz UMFUS licensees. The proposed earth station will operate on frequencies that overlap Channel L1 & L2 of the UMFUS service. The total frequency allocation for Channels L1 & L2 of the UMFUS spectrum appears below.

Channel:	L1	27.500 - 27.925 GHz
	L2	27.925 - 28.350 GHz

Licensee	Channel	Area of Operation
Verizon	L1, L2	County Based

No objections were received from the UMFUS incumbents.



### 4. Earth Station Coordination Data

This section presents the data pertinent to the proposed Ka-Band earth station in Taos, NM. This data was circulated to all incumbent licensees in the shared 28 GHz frequency ranges.



Licensee Code HUN		E1701 HUNE HUGH				
Latitude (NAD 83)36° 2Longitude (NAD 83)105°Climate ZoneARain Zone2			<b>DS, NM</b> 23' 16.0" N ' 35' 16.5" W 1.62 m / 6927.9 ft			
Link Information Satellite Type Mode Modulation Satellite Arc Azimuth Range Corresponding Elevati Antenna Centerline (A	on Angles	TO - T Digital 95.2° \ 162.8° 46.4° /	N to 95.2° West Longitude to 162.8°			
Antenna Informatio Manufacturer Model Gain / Diameter 3-dB / 15-dB Beamwid			Transmit SED 10.0M 67.1 dBi / 10.0 m 0.08° / 0.16°			
Max Available RF Power	(dBW/4 kH (dBW/MH:		-35.0 -11.0			
Maximum EIRP	(dBW/4 kł (dBW/MH:		32.1 56.1			
Interference Objectives:	Long Term Short Term		-151.0 dBW/4 kHz 20% -128.0 dBW/4 kHz 0.0025%			
Frequency Information Emission / Frequency Range (MHz)			Transmit 28.0 GHz 450MG7W - 470MG7W / 27500.0 - 28600.0			
Max Great Circle Coordination Distance Precipitation Scatter Contour Radius			100.0 km / 62.1 mi 100.0 km / 62.1 mi			



Coordination Values	TAOS, NM
Licensee Name	HUGHES NETWORK SYSTEMS LIMITED
Latitude (NAD 83)	36° 23' 16.0" N
Longitude (NAD 83)	105° 35' 16.5" W
Ground Elevation (AMSL)	2111.62 m / 6927.9 ft
Antenna Centerline (AGL)	5.49 m / 18.0 ft
Antenna Mode	Transmit 28.0 GHz
Interference Objectives: Long Ten	
Short Ter	
Max Available RF Power	-35.0 (dBW/4 kHz)

		Transmit 28.0 GHz			
	Horizon	Antenna	Horizon	Coordination	
Azimuth (°)	Elevation (°)	Discrimination (°)	Gain (dBi)	Distance (km)	
0	0.49	131.70	-10.00	100.00	
5	0.53	130.18	-10.00	100.00	
10	0.54	128.31	-10.00	100.00	
15	0.55	126.15	-10.00	100.00	
20	0.51	123.71	-10.00	100.00	
25	0.55	121.10	-10.00	100.00	
30	0.67	118.35	-10.00	100.00	
35	0.67	115.36	-10.00	100.00	
40	0.60	112.22	-10.00	100.00	
45	0.84	109.09	-10.00	100.00	
50	1.80	106.05	-10.00	100.00	
55	3.02	102.87	-10.00	100.00	
60	3.24	99.33	-10.00	100.00	
65	3.90	95.77	-10.00	100.00	
70	4.27	92.10	-10.00	100.00	
75	4.97	88.37	-10.00	100.00	
80	4.92	84.63	-10.00	100.00	
85	4.51	80.97	-10.00	100.00	
90	4.33	77.33	-10.00	100.00	
95	3.84	73.85	-10.00	100.00	
100	3.63	70.41	-10.00	100.00	
105	4.49	66.64	-10.00	100.00	
110	5.19	62.95	-10.00	100.00	
115	5.64	59.42	-10.00	100.00	
120	5.62	56.25	-10.00	100.00	
125	5.77	53.15	-10.00	100.00	
130	6.23	50.03	-10.00	100.00	
135	5.88	47.73	-9.97	100.00	
140	4.80	46.40	-9.66	100.00	
145	4.24	45.09	-9.35	100.00	
150	4.21	43.71	-9.01	100.00	
155	3.65	43.29	-8.91	100.00	
160	3.62	42.82	-8.79	100.00	
165	3.34	43.07	-8.85	100.00	
170	2.51	44.32	-9.17	100.00	
175	1.77	45.89	-9.54	100.00	
180	1.30	47.56	-9.93	100.00	
185	2.08	48.47	-10.00	100.00	

Comsearch Proprietary



Coordination Values		TAOS, NM			
Licensee Nan	ne	HUGHES NETWORK SYSTEMS LIMITED			
Latitude (NAD	83)	36° 23' 16.0" N			
Longitude (NA		105° 35' 16.5" W			
Ground Eleva		2111.62 m / 6927.9 ft	t		
Antenna Cent	erline (AGL)	5.49 m / 18.0 ft			
Antenna Mod		Transmit 28.0	GHz		
Interference C	bjectives: Long Te	erm -151.0 dBW/4	kHz 20%		
	Short T			6	
Max Available	RF Power	-35.0 (dBW/4	kHz)		
			Transm	nit 28.0 GHz	
	Horizon	Antenna	Horizon	Coordination	
Azimuth (°)	Elevation (°)	Discrimination (°)	Gain (dBi)	Distance (km)	

	Horizon	Antenna	Horizon	Coordination
Azimuth (°)	Elevation (°)	Discrimination (°)	Gain (dBi)	Distance (km)
190	2.11	50.42	-10.00	100.00
195	0.66	53.77	-10.00	100.00
200	0.60	56.23	-10.00	100.00
205	0.62	58.85	-10.00	100.00
210	0.55	61.72	-10.00	100.00
215	0.41	64.76	-10.00	100.00
220	0.36	67.88	-10.00	100.00
225	0.30	71.10	-10.00	100.00
230	0.00	74.47	-10.00	100.00
235	0.00	77.80	-10.00	100.00
240	0.00	81.19	-10.00	100.00
245	0.00	84.60	-10.00	100.00
250	0.00	88.05	-10.00	100.00
255	0.00	91.50	-10.00	100.00
260	0.00	94,94	-10.00	100.00
265	0.00	98.36	-10.00	100.00
270	0.00	101.75	-10.00	100.00
275	0.00	105.09	-10.00	100.00
280	0.00	108.37	-10.00	100.00
285	0.00	111.55	-10.00	100.00
290	0.00	114.64	-10.00	100.00
295	0.00	117.60	-10.00	100.00
300	0.00	120.40	-10.00	100.00
305	0.00	123.02	-10.00	100.00
310	0.00	125.44	-10.00	100.00
315	0.00	127.60	-10.00	100.00
320	0.22	129.68	-10.00	100.00
325	0.27	131.31	-10.00	100.00
330	0.31	132.58	-10.00	100.00
335	0.42	133.54	-10.00	100.00
340	0.39	133.95	-10.00	100.00
345	0.39	133.99	-10.00	100.00
350	0.45	133.65	-10.00	100.00
355	0.48	132.88	-10.00	100.00



### 5. Contact Information

For questions or information regarding the 28 GHz Frequency Coordination Report, please contact:

Contact person:	Dennis Jimeno
Title:	Engineer III, Telecommunications
Company:	Comsearch
Address:	19700 Janelia Farm Blvd., Ashburn, VA 20147
Telephone:	703-726-5858
Fax:	703-726-5599
Email:	DJimeno@Comsearch.com
Web site:	www.comsearch.com