

Ka-Band Earth Station – Lindon, UT

Frequency Coordination Report

28 GHz



Prepared on Behalf of
HUGHES NETWORK
SYSTEMS LIMITED

January 9, 2019



COMSEARCH
A CommScope Company

Table of Contents

1. Summary of Results	- 1 -
2. 28 GHz Common Carrier and LTTS Coordination	- 1 -
3. 28 GHz UMFUS Coordination	- 2 -
4. Earth Station Coordination Data	- 3 -
5. Contact Information	- 7 -



1. Summary of Results

On behalf of HUGHES NETWORK SYSTEMS LIMITED, Comsearch performed a coordination notice for all existing and proposed terrestrial licenses within the coordination contours of their proposed Ka-Band earth station in Lindon, UT, which will transmit at 28 GHz¹. Prior-notification letters were sent to the licensees and a copy of the notification data is provided in section four of this report. The earth station coordination was finalized on January 4, 2019.

No objections were received from any of the incumbent 28 GHz licensees. Our notification to the UMFUS incumbents was performed under the assumption that the earth station would be operating on a secondary basis to UMFUS L1 & L2 Block operations and a contact at Hughes Network Systems Limited has been provided in case any concerns may arise in the future.

2. 28 GHz Common Carrier and LTTS Coordination

In accordance with FCC Rules and Regulations, the Ka-Band earth station in Lindon, UT was prior-coordinated by Comsearch. A notification letter and datasheets for this earth station were sent to the following 28 GHz common carrier fixed microwave licensees. These licensees are authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis or local basis.

Licensee	Authorized Geographic Area
Frontier Southwest Incorporated	Nationwide

A notification letter and datasheets for the Ka-Band earth station in Lindon, UT were also sent to the following 28 GHz local television transmission licensee. This licensee is authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis.

Licensee	Authorized Geographic Area
Information Super Station, LLC	Continental US

No objections were received from the common carrier or local television transmission service incumbents.

¹ The proposed earth station will operate in the 27.5 – 28.6 GHz portion of the Ka-Band.

3. 28 GHz UMFUS Coordination

A Notification letter was sent to the following 28 GHz UMFUS licensees. The proposed earth station will operate on frequencies that overlap Channel L1 & L2 of the UMFUS service. The total frequency allocation for Channels L1 & L2 of the UMFUS spectrum appears below.

Channel: **L1** 27.500 - 27.925 GHz
 L2 27.925 - 28.350 GHz

Licensee	Channel	Area of Operation
Verizon	L1, L2	County Based
Vivint Wireless	L1, L2	County Based

No objections were received from the UMFUS incumbents.



4. Earth Station Coordination Data

This section presents the data pertinent to the proposed Ka-Band earth station in Lindon, UT. This data was circulated to all incumbent licensees in the shared 28 GHz frequency ranges.

Administrative Information

Call Sign E170165
 Licensee Code HUNESY
 Licensee Name HUGHES NETWORK SYSTEMS LIMITED

Site Information

LINDON, UT
 Latitude (NAD 83) 40° 19' 58.1" N
 Longitude (NAD 83) 111° 43' 50.2" W
 Climate Zone A
 Rain Zone 5
 Ground Elevation (AMSL) 1398.37 m / 4587.8 ft

Link Information

Satellite Type Geostationary
 Mode TO - Transmit-Only
 Modulation Digital
 Satellite Arc 95.2° W to 95.2° West Longitude
 Azimuth Range 155.4° to 155.4°
 Corresponding Elevation Angles 40.3° / 40.3°
 Antenna Centerline (AGL) 5.49 m / 18.0 ft

Antenna Information

Transmit - FCC32
 Manufacturer General Dynamics
 Model 9.2 Meter
 Gain / Diameter 66.1 dBi / 9.2 m
 3-dB / 15-dB Beamwidth 0.08° / 0.16°

Max Available RF Power (dBW/4 kHz) -35.0
 (dBW/MHz) -11.0

Maximum EIRP (dBW/4 kHz) 31.1
 (dBW/MHz) 55.1

Interference Objectives: Long Term -151.0 dBW/4 kHz 20%
 Short Term -128.0 dBW/4 kHz 0.0025%

Frequency Information

Transmit 28.0 GHz
 Emission / Frequency Range (MHz) 450MG7W - 470MG7W / 27500.0 - 28600.0

Max Great Circle Coordination Distance 100.0 km / 62.1 mi
 Precipitation Scatter Contour Radius 100.0 km / 62.1 mi



HUGHES NETWORK SYSTEMS LIMITED
Ka-Band Earth Station – Lindon, UT
Frequency Coordination Report
28 GHz

Coordination Values	LINDON, UT
Licensee Name	HUGHES NETWORK SYSTEMS LIMITED
Latitude (NAD 83)	40° 19' 58.1" N
Longitude (NAD 83)	111° 43' 50.2" W
Ground Elevation (AMSL)	1398.37 m / 4587.8 ft
Antenna Centerline (AGL)	5.49 m / 18.0 ft
Antenna Mode	Transmit 28.0 GHz
Interference Objectives: Long Term	-151.0 dBW/4 kHz 20%
Short Term	-128.0 dBW/4 kHz 0.0025%
Max Available RF Power	-35.0 (dBW/4 kHz)

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Transmit 28.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)
0	3.77	136.90	-10.00	100.00
5	5.46	135.49	-10.00	100.00
10	8.11	134.11	-10.00	100.00
15	8.59	130.92	-10.00	100.00
20	7.74	126.84	-10.00	100.00
25	6.33	122.48	-10.00	100.00
30	7.52	119.11	-10.00	100.00
35	7.67	115.19	-10.00	100.00
40	7.75	111.16	-10.00	100.00
45	8.47	107.19	-10.00	100.00
50	8.56	103.02	-10.00	100.00
55	10.27	98.96	-10.00	100.00
60	10.09	94.64	-10.00	100.00
65	7.58	90.31	-10.00	100.00
70	7.25	86.12	-10.00	100.00
75	5.98	82.06	-10.00	100.00
80	5.79	77.99	-10.00	100.00
85	4.86	74.12	-10.00	100.00
90	3.96	70.39	-10.00	100.00
95	3.21	66.78	-10.00	100.00
100	2.41	63.37	-10.00	100.00
105	2.34	59.82	-10.00	100.00
110	2.21	56.45	-10.00	100.00
115	2.11	53.23	-10.00	100.00
120	2.09	50.18	-10.00	100.00
125	2.09	47.34	-9.88	100.00
130	2.05	44.83	-9.29	100.00
135	1.96	42.69	-8.76	100.00
140	1.72	41.11	-8.35	100.00
145	1.52	39.96	-8.04	100.00
150	1.19	39.45	-7.90	100.00
155	1.07	39.27	-7.85	100.00
160	0.93	39.63	-7.95	100.00
165	0.61	40.68	-8.24	100.00
170	0.33	42.17	-8.62	100.00
175	0.00	44.11	-9.11	100.00
180	0.00	46.14	-9.60	100.00
185	0.00	48.50	-10.00	100.00



HUGHES NETWORK SYSTEMS LIMITED
Ka-Band Earth Station – Lindon, UT
Frequency Coordination Report
28 GHz

Coordination Values	LINDON, UT
Licensee Name	HUGHES NETWORK SYSTEMS LIMITED
Latitude (NAD 83)	40° 19' 58.1" N
Longitude (NAD 83)	111° 43' 50.2" W
Ground Elevation (AMSL)	1398.37 m / 4587.8 ft
Antenna Centerline (AGL)	5.49 m / 18.0 ft
Antenna Mode	Transmit 28.0 GHz
Interference Objectives: Long Term	-151.0 dBW/4 kHz 20%
Short Term	-128.0 dBW/4 kHz 0.0025%
Max Available RF Power	-35.0 (dBW/4 kHz)

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Transmit 28.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)
190	0.00	51.15	-10.00	100.00
195	0.00	54.05	-10.00	100.00
200	0.00	57.15	-10.00	100.00
205	0.00	60.41	-10.00	100.00
210	0.00	63.82	-10.00	100.00
215	0.00	67.33	-10.00	100.00
220	0.00	70.94	-10.00	100.00
225	0.00	74.61	-10.00	100.00
230	0.00	78.34	-10.00	100.00
235	0.00	82.11	-10.00	100.00
240	0.00	85.91	-10.00	100.00
245	0.00	89.72	-10.00	100.00
250	0.00	93.53	-10.00	100.00
255	0.00	97.33	-10.00	100.00
260	0.00	101.10	-10.00	100.00
265	0.00	104.84	-10.00	100.00
270	0.00	108.52	-10.00	100.00
275	0.00	112.14	-10.00	100.00
280	0.00	115.67	-10.00	100.00
285	0.00	119.09	-10.00	100.00
290	0.00	122.38	-10.00	100.00
295	0.00	125.51	-10.00	100.00
300	0.00	128.43	-10.00	100.00
305	0.00	131.12	-10.00	100.00
310	0.00	133.53	-10.00	100.00
315	0.00	135.61	-10.00	100.00
320	0.00	137.31	-10.00	100.00
325	0.00	138.58	-10.00	100.00
330	0.32	139.69	-10.00	100.00
335	0.36	140.02	-10.00	100.00
340	0.38	139.83	-10.00	100.00
345	0.42	139.13	-10.00	100.00
350	0.66	138.13	-10.00	100.00
355	1.84	137.49	-10.00	100.00



5. Contact Information

For questions or information regarding the 28 GHz Frequency Coordination Report, please contact:

Contact person:	Dennis Jimeno
Title:	Engineer III, Telecommunications
Company:	Comsearch
Address:	19700 Janelia Farm Blvd., Ashburn, VA 20147
Telephone:	703-726-5858
Fax:	703-726-5599
Email:	DJimeno@Comsearch.com
Web site:	www.comsearch.com