



July 11, 2019

*By Electronic Filing*

Jose P. Albuquerque  
Chief, Satellite Division, International Bureau  
Federal Communications Commission  
445 12<sup>th</sup> St., SW  
Washington, D.C. 20554

Re: HNS Licensee Sub, LLC  
IBFS File Nos. SES-AMD-20190221-00282 through SES-AMD-20190221-00285, SES-AMD-20190221-00288; SES-AMD-20190221-00293 through SES-AMD-20190221-00299; SES-AMD-20190221-00302 through SES-AMD-20190221-00305; SES-AMD-20190221-00307 through SES-AMD-20190221-00310  
Call Signs: E170151 through E170170

Dear Mr. Albuquerque:

HNS License Sub, LLC (“HNS”) submits this supplemental letter to clarify that prior coordination notification letters were sent to existing and proposed terrestrial 28 GHz licensees without any stated assumption regarding secondary earth station operations. Accordingly, the attached Comsearch coordination reports have been revised to delete reference to any assumption of secondary operations.

Further, as requested by Commission staff, Comsearch sent the following additional notice to existing and proposed terrestrial 28 GHz licensees: “Pursuant to Section 101.103(d)(2)(ix) of the Commission’s Rules, you are being notified that the associated applications for the coordination reports referenced above and previously forwarded in December 2018 are being amended to clarify that, in the frequency band 27.5-28.35 GHz, the applicant is seeking an authorization pursuant to Section 25.136(a)(4) of the Commission’s Rules. No response is required.”

Please contact the undersigned with any further questions.

Sincerely,

/s/ Kimberly M. Baum  
Kimberly M. Baum  
Vice President, Regulatory Affairs

Attachments

cc: Karl Kensinger  
Kerry Murray  
Stephen Duall  
Kathryn Medley  
Paul Blais

# Ka-Band Earth Station – Lindon, UT

## Frequency Coordination Report

28 GHz



Prepared on Behalf of  
HUGHES NETWORK  
SYSTEMS LIMITED

January 9, 2019



**COMSEARCH**  
A CommScope Company

## **Table of Contents**

|   |              |
|---|--------------|
| <b>1. Summary of Results</b>                          | <b>- 1 -</b> |
| <b>2. 28 GHz Common Carrier and LTTS Coordination</b> | <b>- 1 -</b> |
| <b>3. 28 GHz UMFUS Coordination</b>                   | <b>- 2 -</b> |
| <b>4. Earth Station Coordination Data</b>             | <b>- 3 -</b> |
| <b>5. Contact Information</b>                         | <b>- 7 -</b> |



## 1. Summary of Results

On behalf of HUGHES NETWORK SYSTEMS LIMITED, Comsearch performed a coordination notice under Section 25.136(a)(4) of the FCC’s rules for all existing and proposed terrestrial licenses within the coordination contours of their proposed Ka-Band earth station in Lindon, UT, which will transmit at 28 GHz<sup>1</sup>. Prior-notification letters were sent to the licensees and a copy of the notification data is provided in section four of this report. The earth station coordination was finalized on January 4, 2019.

No objections were received from any of the incumbent 28 GHz licensees.

## 2. 28 GHz Common Carrier and LTTS Coordination

In accordance with FCC Rules and Regulations, the Ka-Band earth station in Lindon, UT was prior-coordinated by Comsearch. A notification letter and datasheets for this earth station were sent to the following 28 GHz common carrier fixed microwave licensees. These licensees are authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis or local basis.

| Licensee                        | Authorized Geographic Area |
|---------------------------------|----------------------------|
| Frontier Southwest Incorporated | Nationwide                 |

A notification letter and datasheets for the Ka-Band earth station in Lindon, UT were also sent to the following 28 GHz local television transmission licensee. This licensee is authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis.

| Licensee                       | Authorized Geographic Area |
|--------------------------------|----------------------------|
| Information Super Station, LLC | Continental US             |

No objections were received from the common carrier or local television transmission service incumbents.

<sup>1</sup> The proposed earth station will operate in the 27.5 – 28.6 GHz portion of the Ka-Band.

### 3. 28 GHz UMFUS Coordination

A Notification letter was sent to the following 28 GHz UMFUS licensees. The proposed earth station will operate on frequencies that overlap Channel L1 & L2 of the UMFUS service. The total frequency allocation for Channels L1 & L2 of the UMFUS spectrum appears below.

**Channel:**    **L1**    27.500 - 27.925 GHz  
                   **L2**    27.925 - 28.350 GHz

| Licensee        | Channel | Area of Operation |
|-----------------|---------|-------------------|
| Verizon         | L1, L2  | County Based      |
| Vivint Wireless | L1, L2  | County Based      |

No objections were received from the UMFUS incumbents.



## **4. Earth Station Coordination Data**

This section presents the data pertinent to the proposed Ka-Band earth station in Lindon, UT. This data was circulated to all incumbent licensees in the shared 28 GHz frequency ranges.

**Administrative Information**

Call Sign E170165  
 Licensee Code HUNESY  
 Licensee Name HUGHES NETWORK SYSTEMS LIMITED

**Site Information**

**LINDON, UT**  
 Latitude (NAD 83) 40° 19' 58.1" N  
 Longitude (NAD 83) 111° 43' 50.2" W  
 Climate Zone A  
 Rain Zone 5  
 Ground Elevation (AMSL) 1398.37 m / 4587.8 ft

**Link Information**

Satellite Type Geostationary  
 Mode TO - Transmit-Only  
 Modulation Digital  
 Satellite Arc 95.2° W to 95.2° West Longitude  
 Azimuth Range 155.4° to 155.4°  
 Corresponding Elevation Angles 40.3° / 40.3°  
 Antenna Centerline (AGL) 5.49 m / 18.0 ft

**Antenna Information**

**Transmit - FCC32**  
 Manufacturer General Dynamics  
 Model 9.2 Meter  
 Gain / Diameter 66.1 dBi / 9.2 m  
 3-dB / 15-dB Beamwidth 0.08° / 0.16°

Max Available RF Power (dBW/4 kHz) -35.0  
 (dBW/MHz) -11.0

Maximum EIRP (dBW/4 kHz) 31.1  
 (dBW/MHz) 55.1

Interference Objectives: Long Term -151.0 dBW/4 kHz 20%  
 Short Term -128.0 dBW/4 kHz 0.0025%

**Frequency Information**

**Transmit 28.0 GHz**  
 Emission / Frequency Range (MHz) 450MG7W - 470MG7W / 27500.0 - 28600.0

Max Great Circle Coordination Distance 100.0 km / 62.1 mi  
 Precipitation Scatter Contour Radius 100.0 km / 62.1 mi



**HUGHES NETWORK SYSTEMS LIMITED**  
**Ka-Band Earth Station – Lindon, UT**  
**Frequency Coordination Report**  
**28 GHz**

|                                    |                                |
|------------------------------------|--------------------------------|
| <b>Coordination Values</b>         | <b>LINDON, UT</b>              |
| Licensee Name                      | HUGHES NETWORK SYSTEMS LIMITED |
| Latitude (NAD 83)                  | 40° 19' 58.1" N                |
| Longitude (NAD 83)                 | 111° 43' 50.2" W               |
| Ground Elevation (AMSL)            | 1398.37 m / 4587.8 ft          |
| Antenna Centerline (AGL)           | 5.49 m / 18.0 ft               |
| Antenna Mode                       | Transmit 28.0 GHz              |
| Interference Objectives: Long Term | -151.0 dBW/4 kHz 20%           |
| Short Term                         | -128.0 dBW/4 kHz 0.0025%       |
| Max Available RF Power             | -35.0 (dBW/4 kHz)              |

| Azimuth (°) | Horizon Elevation (°) | Antenna Discrimination (°) | Transmit 28.0 GHz  |                            |
|-------------|-----------------------|----------------------------|--------------------|----------------------------|
|             |                       |                            | Horizon Gain (dBi) | Coordination Distance (km) |
| 0           | 3.77                  | 136.90                     | -10.00             | 100.00                     |
| 5           | 5.46                  | 135.49                     | -10.00             | 100.00                     |
| 10          | 8.11                  | 134.11                     | -10.00             | 100.00                     |
| 15          | 8.59                  | 130.92                     | -10.00             | 100.00                     |
| 20          | 7.74                  | 126.84                     | -10.00             | 100.00                     |
| 25          | 6.33                  | 122.48                     | -10.00             | 100.00                     |
| 30          | 7.52                  | 119.11                     | -10.00             | 100.00                     |
| 35          | 7.67                  | 115.19                     | -10.00             | 100.00                     |
| 40          | 7.75                  | 111.16                     | -10.00             | 100.00                     |
| 45          | 8.47                  | 107.19                     | -10.00             | 100.00                     |
| 50          | 8.56                  | 103.02                     | -10.00             | 100.00                     |
| 55          | 10.27                 | 98.96                      | -10.00             | 100.00                     |
| 60          | 10.09                 | 94.64                      | -10.00             | 100.00                     |
| 65          | 7.58                  | 90.31                      | -10.00             | 100.00                     |
| 70          | 7.25                  | 86.12                      | -10.00             | 100.00                     |
| 75          | 5.98                  | 82.06                      | -10.00             | 100.00                     |
| 80          | 5.79                  | 77.99                      | -10.00             | 100.00                     |
| 85          | 4.86                  | 74.12                      | -10.00             | 100.00                     |
| 90          | 3.96                  | 70.39                      | -10.00             | 100.00                     |
| 95          | 3.21                  | 66.78                      | -10.00             | 100.00                     |
| 100         | 2.41                  | 63.37                      | -10.00             | 100.00                     |
| 105         | 2.34                  | 59.82                      | -10.00             | 100.00                     |
| 110         | 2.21                  | 56.45                      | -10.00             | 100.00                     |
| 115         | 2.11                  | 53.23                      | -10.00             | 100.00                     |
| 120         | 2.09                  | 50.18                      | -10.00             | 100.00                     |
| 125         | 2.09                  | 47.34                      | -9.88              | 100.00                     |
| 130         | 2.05                  | 44.83                      | -9.29              | 100.00                     |
| 135         | 1.96                  | 42.69                      | -8.76              | 100.00                     |
| 140         | 1.72                  | 41.11                      | -8.35              | 100.00                     |
| 145         | 1.52                  | 39.96                      | -8.04              | 100.00                     |
| 150         | 1.19                  | 39.45                      | -7.90              | 100.00                     |
| 155         | 1.07                  | 39.27                      | -7.85              | 100.00                     |
| 160         | 0.93                  | 39.63                      | -7.95              | 100.00                     |
| 165         | 0.61                  | 40.68                      | -8.24              | 100.00                     |
| 170         | 0.33                  | 42.17                      | -8.62              | 100.00                     |
| 175         | 0.00                  | 44.11                      | -9.11              | 100.00                     |
| 180         | 0.00                  | 46.14                      | -9.60              | 100.00                     |
| 185         | 0.00                  | 48.50                      | -10.00             | 100.00                     |





**HUGHES NETWORK SYSTEMS LIMITED**  
**Ka-Band Earth Station – Lindon, UT**  
**Frequency Coordination Report**  
**28 GHz**

|                                    |                                |
|------------------------------------|--------------------------------|
| <b>Coordination Values</b>         | <b>LINDON, UT</b>              |
| Licensee Name                      | HUGHES NETWORK SYSTEMS LIMITED |
| Latitude (NAD 83)                  | 40° 19' 58.1" N                |
| Longitude (NAD 83)                 | 111° 43' 50.2" W               |
| Ground Elevation (AMSL)            | 1398.37 m / 4587.8 ft          |
| Antenna Centerline (AGL)           | 5.49 m / 18.0 ft               |
| Antenna Mode                       | Transmit 28.0 GHz              |
| Interference Objectives: Long Term | -151.0 dBW/4 kHz 20%           |
| Short Term                         | -128.0 dBW/4 kHz 0.0025%       |
| Max Available RF Power             | -35.0 (dBW/4 kHz)              |

| Azimuth (°) | Horizon Elevation (°) | Antenna Discrimination (°) | Transmit 28.0 GHz  |                            |
|-------------|-----------------------|----------------------------|--------------------|----------------------------|
|             |                       |                            | Horizon Gain (dBi) | Coordination Distance (km) |
| 190         | 0.00                  | 51.15                      | -10.00             | 100.00                     |
| 195         | 0.00                  | 54.05                      | -10.00             | 100.00                     |
| 200         | 0.00                  | 57.15                      | -10.00             | 100.00                     |
| 205         | 0.00                  | 60.41                      | -10.00             | 100.00                     |
| 210         | 0.00                  | 63.82                      | -10.00             | 100.00                     |
| 215         | 0.00                  | 67.33                      | -10.00             | 100.00                     |
| 220         | 0.00                  | 70.94                      | -10.00             | 100.00                     |
| 225         | 0.00                  | 74.61                      | -10.00             | 100.00                     |
| 230         | 0.00                  | 78.34                      | -10.00             | 100.00                     |
| 235         | 0.00                  | 82.11                      | -10.00             | 100.00                     |
| 240         | 0.00                  | 85.91                      | -10.00             | 100.00                     |
| 245         | 0.00                  | 89.72                      | -10.00             | 100.00                     |
| 250         | 0.00                  | 93.53                      | -10.00             | 100.00                     |
| 255         | 0.00                  | 97.33                      | -10.00             | 100.00                     |
| 260         | 0.00                  | 101.10                     | -10.00             | 100.00                     |
| 265         | 0.00                  | 104.84                     | -10.00             | 100.00                     |
| 270         | 0.00                  | 108.52                     | -10.00             | 100.00                     |
| 275         | 0.00                  | 112.14                     | -10.00             | 100.00                     |
| 280         | 0.00                  | 115.67                     | -10.00             | 100.00                     |
| 285         | 0.00                  | 119.09                     | -10.00             | 100.00                     |
| 290         | 0.00                  | 122.38                     | -10.00             | 100.00                     |
| 295         | 0.00                  | 125.51                     | -10.00             | 100.00                     |
| 300         | 0.00                  | 128.43                     | -10.00             | 100.00                     |
| 305         | 0.00                  | 131.12                     | -10.00             | 100.00                     |
| 310         | 0.00                  | 133.53                     | -10.00             | 100.00                     |
| 315         | 0.00                  | 135.61                     | -10.00             | 100.00                     |
| 320         | 0.00                  | 137.31                     | -10.00             | 100.00                     |
| 325         | 0.00                  | 138.58                     | -10.00             | 100.00                     |
| 330         | 0.32                  | 139.69                     | -10.00             | 100.00                     |
| 335         | 0.36                  | 140.02                     | -10.00             | 100.00                     |
| 340         | 0.38                  | 139.83                     | -10.00             | 100.00                     |
| 345         | 0.42                  | 139.13                     | -10.00             | 100.00                     |
| 350         | 0.66                  | 138.13                     | -10.00             | 100.00                     |
| 355         | 1.84                  | 137.49                     | -10.00             | 100.00                     |



## **5. Contact Information**

For questions or information regarding the 28 GHz Frequency Coordination Report, please contact:

|                 |   |
|-----------------|---|
| Contact person: | Dennis Jimeno                               |
| Title:          | Engineer III, Telecommunications            |
| Company:        | Comsearch                                   |
| Address:        | 19700 Janelia Farm Blvd., Ashburn, VA 20147 |
| Telephone:      | 703-726-5858                                |
| Fax:            | 703-726-5599                                |
| Email:          | DJimeno@Comsearch.com                       |
| Web site:       | www.comsearch.com                           |