Ka-Band Earth Station – Simi Valley, CA Frequency Coordination Report 28 GHz



Prepared on Behalf of HUGHES NETWORK SYSTEMS LIMITED

January 9, 2019





Table of Contents

| 1. | Summary of Results | - 1 - |
|----|---|-------|
| 2. | 28 GHz Common Carrier and LTTS Coordination | - 1 - |
| 3. | 28 GHz UMFUS Coordination | - 2 - |
| 4. | Earth Station Coordination Data | - 3 - |
| 5. | Contact Information | - 7 - |
| | | |



1. Summary of Results

On behalf of HUGHES NETWORK SYSTEMS LIMITED, Comsearch performed a coordination notice for all existing and proposed terrestrial licenses within the coordination contours of their proposed Ka-Band earth station in Simi Valley, CA, which will transmit at 28 GHz¹. Priornotification letters were sent to the licensees and a copy of the notification data is provided in section four of this report. The earth station coordination was finalized on January 4, 2019.

No objections were received from any of the incumbent 28 GHz licensees. Our notification to the UMFUS incumbents was performed under the assumption that the earth station would be operating on a secondary basis to UMFUS L1 & L2 Block operations and a contact at Hughes Network Systems Limited has been provided in case any concerns may arise in the future.

2. 28 GHz Common Carrier and LTTS Coordination

In accordance with FCC Rules and Regulations, the Ka-Band earth station in Simi Valley, CA was prior-coordinated by Comsearch. A notification letter and datasheets for this earth station were sent to the following 28 GHz common carrier fixed microwave licensees. These licensees are authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis or local basis.

| Licensee | Authorized Geographic Area |
|---------------------------------|----------------------------|
| AT&T | CA, NV |
| Crosslink Networks | CA |
| Frontier Southwest Incorporated | Nationwide |

A notification letter and datasheets for the Ka-Band earth station in Simi Valley, CA were also sent to the following 28 GHz local television transmission licensee. This licensee is authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis.

| Licensee | Authorized Geographic Area |
|--------------------------------|----------------------------|
| Information Super Station, LLC | Continental US |

No objections were received from the common carrier or local television transmission service incumbents.

¹ The proposed earth station will operate in the 27.5 – 28.6 GHz portion of the Ka-Band.



3. 28 GHz UMFUS Coordination

A Notification letter was sent to the following 28 GHz UMFUS licensees. The proposed earth station will operate on frequencies that overlap Channel L1 & L2 of the UMFUS service. The total frequency allocation for Channels L1 & L2 of the UMFUS spectrum appears below.

| Channel: | L1 | 27.500 - 27.925 GHz |
|----------|----|---------------------|
| | L2 | 27.925 - 28.350 GHz |

| Licensee | Channel | Area of Operation |
|--------------------|---------|-------------------|
| T-Mobile | L1, L2 | County Based |
| TPx Communications | L1, L2 | County Based |
| Verizon | L1, L2 | County Based |

No objections were received from the UMFUS incumbents.



4. Earth Station Coordination Data

This section presents the data pertinent to the proposed Ka-Band earth station in Simi Valley, CA. This data was circulated to all incumbent licensees in the shared 28 GHz frequency ranges.



| Administrative Information Call Sign Licensee Code Licensee Name | | E170163 HUNESY HUGHES NETWORK SYSTEMS LIMITED | | |
|--|----------------------------------|--|--|--|
| Latitude (NAD 83)34° 1Longitude (NAD 83)118°Climate ZoneARain Zone4 | | II VALLEY, CA 16' 9.8" N ° 42' 12.8" W .44 m / 962.7 ft | | |
| Link Information Satellite Type Mode Modulation Satellite Arc Azimuth Range Corresponding Elevati Antenna Centerline (A | on Angles | Geostationary FO - Transmit-Only Digital 95.2° W to 95.2° West Longitude 142.3° to 142.3° 12.9° / 42.9° 5.49 m / 18.0 ft | | |
| Antenna Informatio Manufacturer Model Gain / Diameter 3-dB / 15-dB Beamwid | | Transmit General Dynamics 9.2 Meter 66.1 dBi / 9.2 m 0.08° / 0.16° | | |
| Max Available RF Power | (dBW/4 kH: (dBW/MHz) | | | |
| Maximum EIRP | (dBW/4 kH: (dBW/MHz) | | | |
| Interference Objectives: | Long Term Short Term | -151.0 dBW/4 kHz 20% -128.0 dBW/4 kHz 0.0025% | | |
| Frequency Information Emission / Frequency Range (MHz) | | Transmit 28.0 GHz 450MG7W - 470MG7W / 27500.0 - 28600.0 | | |
| Max Great Circle Coordinal Precipitation Scatter Conto | a state that a state and the set | 100.0 km / 62.1 mi 100.0 km / 62.1 mi | | |



| Coordination Values Licensee Name Latitude (NAD 83) Longitude (NAD 83) Ground Elevation (AMSL) Antenna Centerline (AGL) Antenna Mode Interference Objectives: Long T Short T Max Available RF Power | | | | | |
|--|---------------|--------------------|------------|---------------|--|
| | | | Transm | nit 28.0 GHz | |
| | Horizon | Antenna | Horizon | Coordination | |
| Azimuth (°) | Elevation (°) | Discrimination (°) | Gain (dBi) | Distance (km) | |
| 0 | 2.58 | 127.11 | -10.00 | 100.00 | |
| 5 | 3.06 | 124.36 | -10.00 | 100.00 | |
| 10 | 2.35 | 120.76 | -10.00 | 100.00 | |
| 15 | 2.92 | 117.68 | -10.00 | 100.00 | |
| 20 | 2.77 | 114.12 | -10.00 | 100.00 | |
| 25 | 3.21 | 110.68 | -10.00 | 100.00 | |
| 30 | 2.50 | 106.81 | -10.00 | 100.00 | |
| 35 | 3.14 | 103.23 | -10.00 | 100.00 | |
| 40 | 4.18 | 99.58 | -10.00 | 100.00 | |
| 45 | | | -10.00 | 100.00 | |
| | 3.81 | 95.68 | | | |
| 50 | 4.07 | 91.81 | -10.00 | 100.00 | |
| 55 | 4.33 | 87.91 | -10.00 | 100.00 | |
| 60 | 4.79 | 83.97 | -10.00 | 100.00 | |
| 65 | 4.62 | 80.08 | -10.00 | 100.00 | |
| 70 | 5.72 | 76.00 | -10.00 | 100.00 | |
| 75 | 6.63 | 71.89 | -10.00 | 100.00 | |
| 80 | 7.70 | 67.70 | -10.00 | 100.00 | |
| 85 | 8.87 | 63.43 | -10.00 | 100.00 | |
| 90 | 9.51 | 59.32 | -10.00 | 100.00 | |
| 95 | 9.66 | 55.47 | -10.00 | 100.00 | |
| 100 | 11.74 | 50.76 | -10.00 | 100.00 | |
| 105 | 12.73 | 46.57 | -9.70 | 100.00 | |
| 110 | 12.96 | 42.93 | -8.82 | 100.00 | |
| 115 | 12.55 | 39.96 | -8.04 | 100.00 | |
| 120 | 11.87 | 37.58 | -7.37 | 100.00 | |
| 125 | 10.72 | 36.11 | -6.94 | 100.00 | |
| 130 | 11.04 | 33.94 | -6.27 | 100.00 | |
| 135 | 10.83 | 32.83 | -5.91 | 100.00 | |
| 140 | 10.07 | 32.92 | -5.94 | 100.00 | |
| 145 | 11.18 | 31.84 | -5.57 | 100.00 | |
| 150 | 11.14 | 32.60 | -5.83 | 100.00 | |
| 155 | 9.91 | 35.10 | -6.63 | 100.00 | |
| 160 | 9.07 | 37.69 | -7.40 | 100.00 | |
| 165 | 8.20 | 40.67 | -8.23 | 100.00 | |
| 170 | 8.30 | 43.22 | -8.89 | 100.00 | |
| 175 | 9.36 | 45.46 | -9.44 | 100.00 | |
| 180 | 10.41 | 48.13 | -10.00 | 100.00 | |
| 195 | 11.47 | 51.10 | 10.00 | 100.00 | |

Comsearch Proprietary

11.47

185

-10.00

51.16

100.00



100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

| Coordination Values Licensee Name Latitude (NAD 83) Longitude (NAD 83) Ground Elevation (AMSL) Antenna Centerline (AGL) Antenna Mode Interference Objectives: Long Te Short T Max Available RF Power | | | | | |
|---|---------------|--------------------|------------|---------------|--|
| | | | Transm | nit 28.0 GHz | |
| | Horizon | Antenna | Horizon | Coordination | |
| Azimuth (°) | Elevation (°) | Discrimination (°) | Gain (dBi) | Distance (km) | |
| 190 | 11.09 | 55.10 | -10.00 | 100.00 | |
| 195 | 11.76 | 58.75 | -10.00 | 100.00 | |
| 200 | 11.09 | 62.98 | -10.00 | 100.00 | |
| 205 | 9.72 | 67.41 | -10.00 | 100.00 | |
| 210 | 8.68 | 71.70 | -10.00 | 100.00 | |
| 215 | 7.90 | 75.89 | -10.00 | 100.00 | |
| 220 | 6.43 | 80.12 | -10.00 | 100.00 | |
| 225 | 5.91 | 84.16 | -10.00 | 100.00 | |
| 230 | 5.33 | 88.16 | -10.00 | 100.00 | |
| 235 | 3.74 | 92.08 | -10.00 | 100.00 | |
| 240 | 2.30 | 95.82 | -10.00 | 100.00 | |
| 245 | 1.41 | 99.46 | -10.00 | 100.00 | |
| 250 | 0.47 | 102.95 | -10.00 | 100.00 | |
| 255 | 0.00 | 106.40 | -10.00 | 100.00 | |
| 260 | 0.00 | 109.89 | -10.00 | 100.00 | |
| 265 | 0.00 | 113.29 | -10.00 | 100.00 | |
| 270 | 0.00 | 116.59 | -10.00 | 100.00 | |
| 275 | 0.00 | 119.76 | -10.00 | 100.00 | |
| 280 | 0.00 | 122.78 | -10.00 | 100.00 | |
| 285 | 0.21 | 125.76 | -10.00 | 100.00 | |
| 290 | 0.36 | 128.50 | -10.00 | 100.00 | |

295

300

305

310

315

320

325

330

335

340

345

350

355

0.81

1.06

0.94

1.37

1.71

2.35

3.08

3.00

2.73

2.66

2.08

2.31

2.75

131.23

133.55

135.21

136.98

138.26

139.38

140.09

139.47

138.19

136.65

134.27

132.24

130.03



5. Contact Information

For questions or information regarding the 28 GHz Frequency Coordination Report, please contact:

| Contact person: | Dennis Jimeno |
|-----------------|---|
| Title: | Engineer III, Telecommunications |
| Company: | Comsearch |
| Address: | 19700 Janelia Farm Blvd., Ashburn, VA 20147 |
| Telephone: | 703-726-5858 |
| Fax: | 703-726-5599 |
| Email: | DJimeno@Comsearch.com |
| Web site: | www.comsearch.com |