Ka-Band Earth Station – Billings, MT Frequency Coordination Report 28 GHz



Prepared on Behalf of HUGHES NETWORK SYSTEMS LIMITED

January 9, 2019





Table of Contents

1.	Summary of Results	-1-
2.	28 GHz Common Carrier and LTTS Coordination	- 1 -
3.	28 GHz UMFUS Coordination	- 2 -
4.	Earth Station Coordination Data	- 3 -
5.	Contact Information	-7-



1. Summary of Results

On behalf of HUGHES NETWORK SYSTEMS LIMITED, Comsearch performed a coordination notice for all existing and proposed terrestrial licenses within the coordination contours of their proposed Ka-Band earth station in Billings, MT, which will transmit at 28 GHz¹. Prior-notification letters were sent to the licensees and a copy of the notification data is provided in section four of this report. The earth station coordination was finalized on January 4, 2019.

No objections were received from any of the incumbent 28 GHz licensees. Our notification to the UMFUS incumbents was performed under the assumption that the earth station would be operating on a secondary basis to UMFUS L1 & L2 Block operations and a contact at Hughes Network Systems Limited has been provided in case any concerns may arise in the future.

2. 28 GHz Common Carrier and LTTS Coordination

In accordance with FCC Rules and Regulations, the Ka-Band earth station in Billings, MT was prior-coordinated by Comsearch. A notification letter and datasheets for this earth station were sent to the following 28 GHz common carrier fixed microwave licensees. These licensees are authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis or local basis.

Licensee		Authorized Geographic Area	
	Frontier Southwest Incorporated	Nationwide	

A notification letter and datasheets for the Ka-Band earth station in Billings, MT were also sent to the following 28 GHz local television transmission licensee. This licensee is authorized to operate temporary fixed operations from 27.5 - 29.5 GHz on a nationwide basis.

Licensee	Authorized Geographic Area
Information Super Station, LLC	Continental US

No objections were received from the common carrier or local television transmission service incumbents.

¹ The proposed earth station will operate in the 27.5 – 28.6 GHz portion of the Ka-Band.

3. 28 GHz UMFUS Coordination

A Notification letter was sent to the following 28 GHz UMFUS licensees. The proposed earth station will operate on frequencies that overlap Channel L1 & L2 of the UMFUS service. The total frequency allocation for Channels L1 & L2 of the UMFUS spectrum appears below.

Channel: L1 27.500 - 27.925 GHz

L2 27.925 - 28.350 GHz

Licensee	Channel	Market	Market Name
No Licensees Identified	-	-	-

There were no UMFUS incumbents identified in the Billings, MT area.

4. Earth Station Coordination Data

This section presents the data pertinent to the proposed Ka-Band earth station in Billings, MT. This data was circulated to all incumbent licensees in the shared 28 GHz frequency ranges.



Administrative Information

Call Sign E170158 Licensee Code HUNESY

Licensee Name HUGHES NETWORK SYSTEMS LIMITED

Site Information BILLINGS, MT

Latitude (NAD 83) 45° 46' 7.3" N Longitude (NAD 83) 108° 32' 29.0" W

Climate Zone A Rain Zone 5

Ground Elevation (AMSL) 962.06 m / 3156.4 ft

Link Information

Satellite Type Geostationary
Mode TO - Transmit-Only

Modulation Digital

Satellite Arc 95.2° W to 95.2° West Longitude

Azimuth Range 161.7° to 161.7°
Corresponding Elevation Angles 35.7° / 35.7°
Antenna Centerline (AGL) 5.49 m / 18.0 ft

Antenna Information Transmit

Manufacturer SED Model 10.0M

Gain / Diameter 67.1 dBi / 10.0 m 3-dB / 15-dB Beamwidth 0.08° / 0.16°

Max Available RF Power (dBW/4 kHz) -35.0

(dBW/MHz) -11.0

Maximum EIRP (dBW/4 kHz) 32.1

(dBW/MHz) 56.1

Interference Objectives: Long Term -151.0 dBW/4 kHz 20%

Short Term -128.0 dBW/4 kHz 0.0025%

Frequency Information Transmit 28.0 GHz

Emission / Frequency Range (MHz) 450MG7W - 470MG7W / 27500.0 - 28600.0

Max Great Circle Coordination Distance 100.0 km / 62.1 mi Precipitation Scatter Contour Radius 100.0 km / 62.1 mi

Coordination Values BILLINGS, MT

Licensee Name HUGHES NETWORK SYSTEMS LIMITED

Latitude (NAD 83) 45° 46' 7.3" N Longitude (NAD 83) 108° 32' 29.0" W Ground Elevation (AMSL) 962.06 m / 3156.4 ft Antenna Centerline (AGL) 5.49 m / 18.0 ft

Antenna Mode Transmit 28.0 GHz
Interference Objectives: Long Term -151.0 dBW/4 kHz 20%

Short Term -128.0 dBW/4 kHz 0.0025%

Max Available RF Power -35.0 (dBW/4 kHz)

Trongmil	20.0	CLIE
Transmit	. Z0.U	GHZ

	Charles	Nationale	Harismit 28.0 GHZ		
	Horizon	Antenna	Horizon	Coordination	
Azimuth (°)	Elevation (°)	Discrimination (°)	Gain (dBi)	Distance (km)	
0	1.90	142.09	-10.00	100.00	
5	1.83	139.70	-10.00	100.00	
10	1.73	136.91	-10.00	100.00	
15	1.62	133.81	-10.00	100.00	
20	1.56	130.50	-10.00	100.00	
25	1.47	126.99	-10.00	100.00	
30	1.42	123.34	-10.00	100.00	
35	1.33	119.55	-10.00	100.00	
40	1.15	115.64	-10.00	100.00	
45	0.93	111.65	-10.00	100.00	
50	0.91	107.67	-10.00	100.00	
55	0.00	103.49	-10.00	100.00	
60	0.00	99.47	-10.00	100.00	
65	0.00	95.43	-10.00	100.00	
70	0.48	91.38	-10.00	100.00	
75	0.72	87.29	-10.00	100.00	
80	1.32	83.15	-10.00	100.00	
85	1.43	79.03	-10.00	100.00	
90	1.24	74.99	-10.00	100.00	
95	1.34	70.93	-10.00	100.00	
100	1.32	66.96	-10.00	100.00	
105	0.95	63.17	-10.00	100.00	
110	0.56	59.54	-10.00	100.00	
115	0.66	55.83	-10.00	100.00	
120	0.70	52.28	-10.00	100.00	
125	0.90	48.81	-10.00	100.00	
130	0.81	45.73	-9.50	100.00	
135	1.13	42.62	-8.74	100.00	
140	1.17	40.04	-8.06	100.00	
145	1.69	37.43	-7.33	100.00	
150	1.42	35.98	-6.90	100.00	
155	1.28	34.97	-6.59	100.00	
160	0.84	34.88	-6.57	100.00	
165	0.78	35.05	-6.62	100.00	
170	0.88	35.66	-6.81	100.00	
175	0.90	36.95	-7.19	100.00	
180	0.88	38.79	-7.72	100.00	
185	0.88	41.06	-8.34	100.00	

Coordination Values BILLINGS, MT

Licensee Name HUGHES NETWORK SYSTEMS LIMITED

Latitude (NAD 83) 45° 46' 7.3" N Longitude (NAD 83) 108° 32' 29.0" W Ground Elevation (AMSL) 962.06 m / 3156.4 ft Antenna Centerline (AGL) 5.49 m / 18.0 ft

Antenna Mode Transmit 28.0 GHz
Interference Objectives: Long Term Short Term -128.0 dBW/4 kHz 0.0025%

Max Available RF Power -35.0 (dBW/4 kHz)

- 0.0 - 0.0		- Contract 1
Transmi	10 11	(2147
Transmi	1 ZO.U	1/11/12

	Transmit 28.0 GHz				
	Horizon	Antenna	Horizon	Coordination	
Azimuth (°)	Elevation (°)	Discrimination (°)	Gain (dBi)	Distance (km)	
190	0.97	43.64	-9.00	100.00	
195	0.76	46.75	-9.74	100.00	
200	0.50	50.11	-10.00	100.00	
205	0.62	53.45	-10.00	100.00	
210	0.00	57.30	-10.00	100.00	
215	0.00	60.97	-10.00	100.00	
220	0.00	64.74	-10.00	100.00	
225	0.00	68.60	-10.00	100.00	
230	0.00	72.53	-10.00	100.00	
235	0.00	76.51	-10.00	100.00	
240	0.00	80.53	-10.00	100.00	
245	0.26	84.55	-10.00	100.00	
250	0.30	88.62	-10.00	100.00	
255	0.32	92.70	-10.00	100.00	
260	0.36	96.77	-10.00	100.00	
265	0.39	100.83	-10.00	100.00	
270	0.44	104.87	-10.00	100.00	
275	0.44	108.85	-10.00	100.00	
280	0.46	112.79	-10.00	100.00	
285	0.48	116.66	-10.00	100.00	
290	0.52	120.45	-10.00	100.00	
295	0.53	124.11	-10.00	100.00	
300	1.30	128.04	-10.00	100.00	
305	1.52	131.57	-10.00	100.00	
310	1.64	134.83	-10.00	100.00	
315	1.67	137.78	-10.00	100.00	
320	1.72	140.41	-10.00	100.00	
325	1.90	142.76	-10.00	100.00	
330	1.89	144.46	-10.00	100.00	
335	1.83	145.56	-10.00	100.00	
340	1.93	146.21	-10.00	100.00	
345	1.98	146.15	-10.00	100.00	
350	1.96	145.38	-10.00	100.00	
355	1.95	144.02	-10.00	100.00	

5. Contact Information

For questions or information regarding the 28 GHz Frequency Coordination Report, please contact:

Contact person: Dennis Jimeno

Title: Engineer III, Telecommunications

Company: Comsearch

Address: 19700 Janelia Farm Blvd., Ashburn, VA 20147

Telephone: 703-726-5858 Fax: 703-726-5599

Email: DJimeno@Comsearch.com

Web site: www.comsearch.com