FCC 312	FEDERAL COMMUNICATIONS COMMISSION	Page 1: General,
Schedule S	SATELLITE SPACE STATION AUTHORIZATIONS	Frequency Bands,
	(Technical and Operational Description)	and GSO Orbit

S1. GENERAL INFORMATION Complete for all satellite applications.

Space Station or Satellite Non PROBA-V	etwork Name:	e. Estimated Date of Placement into Service 11/7/2013	e:	i Will the space station(s) operate on a N	Common Carrier Basis:		
b. Construction Commenceme	ent Date:	f. Estimated Lifetime of Satellite(s):		j. Number of transponders offered on a	common carrier basis:		
1/1/2011		5	Years	0			
c. Construction Completion Da	ate:	g. Total Number of Transponders:		k. Total Common Carrier Transponder Bandwidth:			
6/1/2012		1		0 MHz			
d1. Est Launch Date Begin:	d2. Est Launch Date End:	h. Total Transponder Bandwidth (no. transp	onders x Bandwidth)	Orbit Type: Mark all boxes that apply:			
5/7/2013	5/7/2013	0	MHz	GSO X	NGSO		

S2. OPERATING FREQUENCY BANDS Identify the frequency range and transmit/receive mode for all frequency bands in which this station will opera Also indicate the nature of service(s) for each frequency band.

	Frequency Band Limits Upper Frequency (_Hz) Upper Frequency (_Hz) D. Unit C. Numeric d. Unit (K/M/G) (K/M/G) Unit (K/M/G) U				f.
Lower Frequency (e. T/R Mode	Nature of Service(s): List all that apply to this band	
a. Numeric				117	
8040.0	, ,		Т	Earth Exploration Satellite Service	

S3. ORBITAL INFORMATION FOR GEOSTATIONARY SATELLITES ONLY:

FCC Form 312 - Schedule S: (Technical and Operational Description)

S4. ORBITAL INFORMATION FOR NON-GEOSTATIONARY SATELLITES ONLY

S4a. Total Number of Satellites in Network or System:

1 S4c. Celestial Reference Body (Earth, Sun, Moon, etc.): E

S4b. Total Number of Orbital Planes in Network or System:

1 S4d. Orbit Epoch Date: 9/8/2014

For each Orbital Plane Provide:

(e) Orbital	(f) No. of	(g) Inclination	(h) Orbital	(i) Apogee (km)	(j) Perigee (km)	(k) Right Ascension of	0		rvice Arc Rang	e (Degrees)
Plane No.	Satellites in	Angle (degrees)	Period			the Ascending Node	0	(m) Begin	(n) End Angle	(o) Other
	Plane		(Seconds)			(Deg.)	(Degrees)	Angle		
-			-							
1	1	98.7	6072	826	818	330.1	74.9			

S5. INITIAL SATELLITE PHASE ANGLE For each satellite in each orbital plane, provide the intital phase angle.

(a) Orbital Plane No.	(b) Satellite Number	(c) Initial Phase Angle (Degrees)
1		0

Page 2: NGSO Orbits

FCC Form 312 - Schedule S: (Technical and Operational Description)

S6. SERVICE AREA CHARACTERISTICS for each service area provide:

(a) Service Area ID	(b) Type of Associated Station (Earth or Space)		(d) Service Area Description. Provide list of geographic areas (state postal codes or ITU 3-ltr codes), satellites or Figure No. of Service Area Diagram.
1	E	None	Entire planet science gatthering

Page 3: Service Areas

Page 4: Antenna Beams

FCC Form 312 - Schedule S: (Technical and Operational Description)

S7. SPACE STATION ANTENNA BEAM CHARACTERISTICS For each antenna beam provide:

(a)	(b)	Isotropic	Antenna	(e)	(f)	(g) Min.	(h) Polar-	(i) Polarization	(j) Service		Transmit				Receive		
Beam		Ga	ain	Pointing	Rotational	Cross-		Alignment Rel.	Area ID	(k) Input	(I) Effective	(m)	(n)	(o) G/T	(p) Min.	Input Attenu	uator (dB)
ID	Mode	(c) Peak	(d) Edge	Error	Error	Polar Iso-	Switch-	Equatorial		Losses	Output	Max.	System	Max.	Saturation	(q) Max.	(r) Step
		(dBi)	(dBi)	(Degrees)	(Degrees)	lation (dB)		Plane (Degrees)		(dB)	Power (W)	EIRP			Flux Density	Value	Size
							(Y/N)					(dBW)	Temp (k)	(db/K)	(dBW/m2)	Value	CIZO
WBD	Т	3	-1	1	0	13	N	0	1	1	10	13					

Page 5: Beam Diagrams

FCC Form 312 - Schedule S: (Technical and Operational Description)

S8. ANTENNA BEAM DIAGRAMS For each beam pattern provide the reference to the graphic image and numerical data:

Also provide the power flux density levels in each beam that result from the emission with the highest power flux density.

(a) Beam	(b) T/R	(c) Co-or Cross	(d) GSO Ref. Orbital	(e) NGSO Antenna Gain Contour Description	(f) GSO Antenna Gain Contour Data (GXT File)		Max. Power F Arrival above ho	Flux Density (dB		nest PFD)
ID	Mode	Polar	Longitude (Deg. E/W)	(Figure/Table/ Exhibit)	Johnson Data (G/11 1 110)	(g) 5 Deg	(h) 10 Deg	(i) 15 Deg	(j) 20 Deg	(k) 25 Deg
WBD	Т	J. 117		′ antenna pattern Exhil	None	-160.2	-160.2	-160.2	-160.2	-160.2

Page 6: Channels and Transponders

FCC Form 312 - Schedule S: (Technical and Operational Description)

S9. SPACE STATION CHANNELS For each frequency channel provide: S10. SPACE STATION TRANSPONDERS For each transponder provide:

(a) Channel No.	(B) Assigned Bandwidth (kHz)	(c) T/R Mode	(d) Center Frequency (MHz)	(e) Polarization (H, V, L, R)	(f) TTC or Comm Channel (T or C)
WBD	100000	Т	8090.0	R	Т

	(a) ransponder ID	(b)	Receive	Band	Transmi	t Band
Tra	nsponder ID	Transponder Gain (dB)	(c) Channel No.	(d) Beam ID	(e) Channel No.	(f) Beam ID
Α1	.1		WBD	WBD	WBD	WBD

Page 7: Digital Modulation

FCC Form 312 - Schedule S: (Technical and Operational Description)

S11. DIGITAL MODULATION PARAMETERS For each digital emission provide:

	(a) Digital Mod. ID	(b) Emission Designator	(c) Assigned Bandwidth (kHz)	(d) No. of Phases	(e)Uncoded Data Rate (kbps)	(f) FEC Error Correction Coding Rate	Processing	(h) Total C/N Performance Objective (dB)	(i) Single Entry C/I Objective (dB)
١	WBD	100MG2D	100000	4	84448	1	0	0	0

Page 8: Analog Modulation

FCC Form 312 - Schedule S: (Technical and Operational Description)

S12. ANALOG MODULATION PARAMETERS For each analog emission provide:

(a)	(b) Emission	(c)	(d) Signal	(e)		Multi-channe	Telephony		(j) Video	(k) Video	(I) Video	(m) SCPC/FM	(n) Total C/N	(o) Single
Analog Mod. II		Assigned Bandwidth (kHz)	21 -	Channels per Carrier	(f) Ave. Companded Talker Level (dBm0)	(g) Bottom Baseband Freq. (MHz)	(h) Top Baseband Freq. (MHz)	(i) RMS Modulation Index	Standard NTSC, PAL, etc.	Noise- Weighting (dB)	and SCPC/FM Modulation Index	Compander, Preemphasis, and Noise Weighting (dB)	Performance Objective (dB)	Entry C/I Objective (dB)

Page 9: Typical Emissions

FCC Form 312 - Schedule S: (Technical and Operational Description)

S13. TYPICAL EMISSIONS For each planned type of emission provide:

_	Assoc				(1)	(f) Carrier	(g)Noise Budget	(h) Energy	Receive Band (Assoc. Transmit Stn)			Tra	nsmit Band	(This Space Station)	
Transponder ID Range (a) Start (b) End		(c) Digital	(d) Analog (Table S12)	per Transponder	Spacing (kHz)	Reference (Table No.)	Dispersal Bandwidth (kHz)	(i)Assoc. Stn. Max.	Assoc. Station Transmit Power (dBW)		EIRP (dBW)			Stn Rec.	
. ,		, ,						,	Antenna Gain (dBi)	(j) Min.	(k) Max.	(I) Min.	(m) Max.	(dBW/m2/Hz)	G/T (dB/K)
A1		A1	WBD									9	13	-160.2	37.7

FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS 212 School of St. (Technical and Operational Descrip

Page 10: TT and C

FCC Form 312 - Schedule S: (Technical and Operational Description)

S14. Is the space station(s) controlled and monitored remotely? If Yes, provide the location and telephone number of the TT and C control point(s): No

FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS FCC Form 312 - Schedule S: (Technical and Operational Description)

Page 11: Characteristics and Certifications

S15. SPACECRAFT PHYSICAL CHARACTERISTICS:

S15a: Mass of spacecraft without fuel (kg): 138	Spacecraft Dimensions (meters)	Probability of Survival to End of Life (0.0 - 1.0)			
S15b. Mass of fuel and disposables at launch (kg): 0					
S15c. Mass of spacecraft and fuel at launch (kg): 138	S15f. Length (m): 0.8	S15i. Payload: 0.9			
S15d. Mass of fuel, in orbit, at beginning of life (kg): 0	S15g. Width (m): 0.8	S15j. Bus: 0.9			
S15e. Deployed Area of Solar Array (square meters): 1.9	S15h. Height (m):	S15k. Total: 0.9			

S16. SPACECRAFT ELECTRICAL CHARACTERISTICS:

Spacecraft Subsystem		ver (Watts) At ng of Life	Electrical Power (Watts) At End of Life					
	At Equinox	At Solstice	At Equinox	At Solstice				
Payload (Watts):	^{(a):} 30	^{(f):} 30	^{(k):} 30	^{(p):} 30				
Bus (Watts):	^{(b):} 48	^{(g):} 48	^{(l):} 48	^{(q):} 48				
Total (Watts):	^{(c):} 78	^{(h):} 78	^(m) 78	^{(r):} 78				
Solar Array (Watts):	^{(d):} 150	^{(i):} 143	^{(n):} 140	^{(s):} 133				
Depth of Battery Discharge (%):	^(e) 35 %	^(j) 35 %	⁽⁰⁾ 35 %	^(t) 35 %				

S17. CERTIFICATIONS:

a. Are the power flux density limits of § 25.208 met?:		YES	#	NO	#	N/A
b. Are the appropriate service area coverage requirements of § 25.143(b)(ii) and (iii), or § 25.145(c)(1) and (2) me	t?	YES	#	NO	#	N/A
c. Are the frequency tolerances of § 25.202(e) and the out-of-band emission limits of § 25.202(f)(1), (2) and (3) more	et?	YES	#	NO	#	N/A
In addition to the information varyingd in this Form the appearation applicant is required to provide all the information applied in Section 2F 444 of the						

In addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the Commission's rules, 47 C.F.R § 25.114.

FCC NOTICE REQUIRED BY THE PAPERWORK REDUCTION ACT

The public reporting estimate for this collection of information includes the time for reviewing instructions, searching existing data sources, gathering and maintaining the required data, and completing and reviewing the collection of information. If you have any comments on this burden estimate, or how we can improve the collection and reduce the burden it causes you, please write to the Federal Communications Commission, AMD-PERM, Paperwork Reduction Project (3060-0678), Washington, DC 20554. We will also accept your comments regarding the Paperwork Reduction Act aspects of this collection via the Internet if you send them to PERM@fcc.gov. PLEASE DO NOT SEND COMPLETED FORMS TO THIS ADDRESS.

Remember - You are not required to respond to a collection of information sponsored by the Federal government, and the government may not conduct or sponsor this collection, unless it displays a currently valid OMB control number or if we fail to provide you with this notice. This collection has been assigned an OMB control number of 3060-0678.

THE FOREGOING NOTICE IS REQUIRED BY THE PAPERWORK REDUCTION ACT OF 1995, PUBLIC LAW 104-13, OCTOBER 1, 1995, 44 U.S.C. SECTION 3507.