FREQUENCY COORDINATION AND INTERFERENCE ANALYSIS REPORT

Prepared for
Newcom International
MIAMI, FL
(9 Meter)
Satellite Earth Station

Prepared By:
COMSEARCH
19700 Janelia Farm Boulevard
Ashburn, VA 20147
June 14, 2004

TABLE OF CONTENTS

1. CONCLUSIONS 3
2. SUMMARY OF RESULTS 4
3. SUPPLEMENTAL SHOWING 5
4. EARTH STATION COORDINATION DATA 6
5. CERTIFICATION 10

1. CONCLUSIONS

An interference study considering all existing, proposed and prior coordinated microwave facilities within the coordination contours of the proposed earth station demonstrates that this site will operate satisfactorily with the common carrier microwave environment. Further, there will be no restrictions of its operation due to interference considerations.

2. SUMMARY OF RESULTS

A number of great circle interference cases were identified during the interference study of the proposed earth station. Each of the cases, which exceeded the interference objective on a line-of-sight basis, was profiled and the propagation losses estimated using NBS TN101 (Revised) techniques. The losses were found to be sufficient to reduce the signal levels to acceptable magnitudes in every case.

The following companies reported potential great circle interference conflicts that did not meet the objectives on a line-of-sight basis. When over-the-horizon losses are considered on the interfering paths, sufficient blockage exists to negate harmful interference from occurring with the proposed transmit-receive earth station.

Company

Cingular Wireless, LLC - South FL Rgn
Florida Cellular Service, LLC
Sprint Florida, Inc.
PALM BEACH COUNTY FAC DEV & OP
South Florida Water Management District
AT&T Wireless Services of FL Inc. - FL

No other carriers reported potential interference cases.

3. SUPPLEMENTAL SHOWING

Pursuant to Part 25.203(c) of the FCC Rules and Regulations, the satellite earth station proposed in this application was coordinated by Comsearch using computer techniques and in accordance with Part 25 of the FCC Rules and Regulations.

Coordination data for this earth station was sent to the below listed carriers with a letter dated 05/21/2004.

Company
ACME TELEVISION LICENSES OF FLORIDA LLC
ALLTEL Wireless Holdings, LLC.
AT&T Wireless Services of FL Inc - FL
Central Florida Cellular Telephone Co
Cingular Wireless, LLC - South FL Rgn
FLORIDA POWER AND LIGHT COMPANY
Florida Cellular Service, LLC
LEE COUNTY FLORIDA
M/A COM, INC.
PALM BEACH COUNTY FAC DEV & OP
South Florida Water Management District
Sprint Florida, Inc.
Verizon Personal Communications,L.P.(FL)
Wireless One Holding Company LP

4. EARTH STATION COORDINATION DATA

This section presents the data pertinent to frequency coordination of the proposed earth station that was circulated to all carriers within its coordination contours.

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 http://www.comsearch.com

Date: 06/14/2004
Job Number: 040521COMSGE05

Administrative Information

Status	ENGINEER PROPOSAL
Call Sign	
Licensee Code	NCOMIN
Licensee Name	Newcom International

Site Information — MIAMI, FL

Venue Name	
Latitude (NAD 83)	25° 54' 59.3" N
Longitude (NAD 83)	80° 13' 29.2" W
Climate Zone	B
Rain Zone	1
Ground Elevation (AMSL)	1.83 m / 6.0 ft

Link Information

Satellite Type	Geostationary
Mode	TR - Transmit-Receive
Modulation	Digital
Satellite Arc	15° W to 143° West Longitude
Azimuth Range	101.4° to 257.3°
Corresponding Elevation Angles	13.7° / 15.9°
Antenna Centerline (AGL)	5.49 m / 18.0 ft

Antenna Information		Receive - FCC32	Transmit - FCC32
Manufacturer		Vertex	Vertex
Model		9 KPC	9 KPC
Gain / Diameter		49.9 dBi / 9.0 m	53.7 dBi / 9.0 m
3-dB / 15-dB Beamwidth		0.54° / 1.13°	0.35° / 0.74°
Max Available RF Power	(dBW/4 kHz)		(1) -2.7 (2) -16.3
	(dBW/MHz)		21.3 7.7
Maximum EIRP	(dBW/4 kHz)		51.0 37.40
	(dBW/MHz)		75.0 61.40
Interference Objectives:	Long Term	-156.0 dBW/MHz 20%	-154.0 dBW/4 kHz 20%
	Short Term	-146.0 dBW/MHz 0.01%	-131.0 dBW/4 kHz 0.0025%

Frequency Information	Receive 4.0 GHz	Transmit 6.1 GHz
Emission / Frequency Range (MHz)	128KG7D - 45M0G7W / 3700.0 - 4200.0	(1) 128KG7D - 45M0G7W / 5925.0 - 5929.0, 5961.0 – 5988.0, 6020.0 – 6047.0, 6079.0 – 6107.0, 6168.0 – 6240.0, 6331.0 – 6359.0, 6391.0 – 6425.0
		(2) 128KG7D – 45M0G7W / 5925.0 – 6425.0

Frequency Information	Receive 4.0 GHz	Transmit 6.1 GHz
Emission / Frequency Range (MHz)	128KG7D - 45M0G7W / 3700.0 - 4200.0	(1) 128KG7D - 45M0G7W / 5925.0 - 5929.0 128KG7D - 45M0G7W / 5961.0 - 5988.0 128KG7D - 45M0G7W / 6020.0 - 6047.0 128KG7D - 45M0G7W / 6079.0 - 6107.0 128KG7D - 45M0G7W / 6168.0 - 6240.0 128KG7D - 45M0G7W / 6331.0 - 6359.0 128KG7D - 45M0G7W / 6391.0 - 6425.0 (2) 128KG7D – 45M0G7W / 5925.0 – 6425.0
Max Great Circle Coordination Distance	618.3 km / 384.1 mi	289.4 km / 179.8 mi
Precipitation Scatter Contour Radius	605.3 km / 376.1 mi	134.3 km / 83.5 mi

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 http://www.comsearch.com

Coordination Values	**MIAMI, FL**			
Licensee Name	Newcom International			
Latitude (NAD 83)	25° 54' 59.3" N			
Longitude (NAD 83)	80° 13' 29.2" W			
Ground Elevation (AMSL)	1.83 m / 6.0 ft			
Antenna Centerline (AGL)	5.49 m / 18.0 ft			
Antenna Model	Vertex 9 Meter			
Antenna Mode	Receive 4.0 GHz		Transmit 6.1 GHz	
Interference Objectives: Long Term	-156.0 dBW/MHz	20%	-154.0 dBW/4 kHz	20%
Short Term	-146.0 dBW/MHz	0.01%	-131.0 dBW/4 kHz	0.0025%
Max Available RF Power			-2.7 (dBW/4 kHz)	

			Receive 4.0 GHz		Transmit 6.1 GHz	
Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	0.00	101.08	-10.00	412.20	-10.00	200.77
5	0.00	96.22	-10.00	412.20	-10.00	200.77
10	0.00	91.37	-10.00	412.20	-10.00	200.77
15	0.00	86.51	-10.00	412.20	-10.00	200.77
20	0.00	81.65	-10.00	412.20	-10.00	200.77
25	0.00	76.80	-10.00	412.20	-10.00	200.77
30	0.00	71.95	-10.00	412.20	-10.00	200.77
35	0.00	67.12	-10.00	412.20	-10.00	200.77
40	0.00	62.29	-10.00	412.20	-10.00	200.77
45	0.00	57.48	-10.00	412.20	-10.00	200.77
50	0.00	52.70	-10.00	412.20	-10.00	200.77
55	0.00	47.94	-10.00	412.20	-10.00	200.77
60	0.00	43.22	-8.89	426.18	-8.89	207.17
65	0.00	38.56	-7.65	442.40	-7.65	214.51
70	0.00	33.98	-6.28	461.09	-6.28	222.88
75	0.00	29.52	-4.75	482.19	-4.75	232.48
80	0.00	25.24	-3.05	507.62	-3.05	243.53
85	0.00	21.25	-1.18	537.03	-1.18	256.09
90	0.00	17.75	0.77	569.45	0.77	268.24
95	0.00	15.09	2.53	600.19	2.53	281.51
100	0.00	13.76	3.53	618.25	3.53	289.40
105	0.00	14.15	3.23	612.81	3.23	287.01
110	0.00	16.12	1.81	587.51	1.81	276.01
115	0.00	19.20	-0.08	555.07	-0.08	262.10
120	0.00	22.95	-2.02	523.69	-2.02	250.42
125	0.00	27.08	-3.82	496.01	-3.82	238.51
130	0.00	31.32	-5.39	472.94	-5.39	228.41
135	0.00	35.46	-6.74	454.70	-6.74	220.03
140	0.00	39.48	-7.91	438.99	-7.91	212.97
145	0.00	43.35	-8.92	425.76	-8.92	206.98
150	0.00	47.01	-9.81	414.62	-9.81	201.88
155	0.00	50.41	-10.00	412.20	-10.00	200.77
160	0.00	53.45	-10.00	412.20	-10.00	200.77
165	0.00	56.03	-10.00	412.20	-10.00	200.77
170	0.00	58.02	-10.00	412.20	-10.00	200.77
175	0.00	59.28	-10.00	412.20	-10.00	200.77
180	0.00	59.71	-10.00	412.20	-10.00	200.77
185	0.00	59.28	-10.00	412.20	-10.00	200.77

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 http://www.comsearch.com

Coordination Values	**MIAMI, FL**			
Licensee Name	Newcom International			
Latitude (NAD 83)	25° 54' 59.3" N			
Longitude (NAD 83)	80° 13' 29.2" W			
Ground Elevation (AMSL)	1.83 m / 6.0 ft			
Antenna Centerline (AGL)	5.49 m / 18.0 ft			
Antenna Model	Vertex 9 Meter			
Antenna Mode	Receive 4.0 GHz		Transmit 6.1 GHz	
Interference Objectives: Long Term	-156.0 dBW/MHz	20%	-154.0 dBW/4 kHz	20%
Short Term	-146.0 dBW/MHz	0.01%	-131.0 dBW/4 kHz	0.0025%
Max Available RF Power			-2.7 (dBW/4 kHz)	

			Receive 4.0 GHz		Transmit 6.1 GHz	
Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
190	0.00	58.01	-10.00	412.20	-10.00	200.77
195	0.00	56.03	-10.00	412.20	-10.00	200.77
200	0.00	53.45	-10.00	412.20	-10.00	200.77
205	0.00	50.41	-10.00	412.20	-10.00	200.77
210	0.00	47.02	-9.81	414.61	-9.81	201.88
215	0.00	43.35	-8.92	425.76	-8.92	206.98
220	0.00	39.48	-7.91	438.98	-7.91	212.97
225	0.00	35.46	-6.74	454.71	-6.74	220.03
230	0.00	31.32	-5.40	472.93	-5.40	228.40
235	0.00	27.19	-3.86	495.36	-3.86	238.22
240	0.00	23.37	-2.22	520.54	-2.22	249.08
245	0.00	20.05	-0.55	547.33	-0.55	258.82
250	0.00	17.50	0.92	572.11	0.92	269.38
255	0.00	16.10	1.83	587.77	1.83	276.12
260	0.00	16.15	1.79	587.15	1.79	275.86
265	0.00	17.64	0.83	570.57	0.83	268.72
270	0.00	20.26	-0.67	545.46	-0.67	258.03
275	0.00	23.63	-2.33	518.71	-2.33	248.29
280	0.00	27.47	-3.97	493.70	-3.97	237.50
285	0.00	31.62	-5.50	471.46	-5.50	227.75
290	0.00	35.96	-6.90	452.61	-6.90	219.09
295	0.00	40.44	-8.17	435.56	-8.17	211.42
300	0.00	45.01	-9.33	420.56	-9.33	204.60
305	0.00	49.65	-10.00	412.20	-10.00	200.77
310	0.00	54.34	-10.00	412.20	-10.00	200.77
315	0.00	59.06	-10.00	412.20	-10.00	200.77
320	0.00	63.81	-10.00	412.20	-10.00	200.77
325	0.00	68.58	-10.00	412.20	-10.00	200.77
330	0.00	73.36	-10.00	412.20	-10.00	200.77
335	0.00	78.16	-10.00	412.20	-10.00	200.77
340	0.00	82.96	-10.00	412.20	-10.00	200.77
345	0.00	87.76	-10.00	412.20	-10.00	200.77
350	0.00	92.57	-10.00	412.20	-10.00	200.77
355	0.00	97.38	-10.00	412.20	-10.00	200.77

5. CERTIFICATION

I HEREBY CERTIFY THAT I AM THE TECHNICALLY QUALIFIED PERSON RESPONSIBLE FOR THE PREPARATION OF THE FREQUENCY COORDINATION DATA CONTAINED IN THIS APPLICATION, THAT I AM FAMILIAR WITH PARTS 101 AND 25 OF THE FCC RULES AND REGULATIONS, THAT I HAVE EITHER PREPARED OR REVIEWED THE FREQUENCY COORDINATION DATA SUBMITTED WITH THIS APPLICATION, AND THAT IT IS COMPLETE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

BY: _ 

Gary K. Edwards
Senior Manager
COMSEARCH
19700 Janelia Farm Boulevard
Ashburn, VA 20147

DATED: June 14, 2004