

FCC OET-65 RF Exposure Study - Satellite Uplink Facility

NBC HD-2A (has no current FCC License)

Antenna Vendor: AVL Technologies
Antenna Size: 2.4 m.
Amplifier Make/Model: ETM-400
Amplifier Max Power: 400 w.

FCC Maximum Permissible Exposure Levels	Source	Units	Notes
Public/uncontrolled area exposure limit	47CFR §1.1310	1 mW/cm ²	
Occupational/controlled area exposure limit	47CFR §1.1310	5 mW/cm ²	

Input Data

Antenna Diameter	datasheet	240.0 cm	
Antenna surface area	calculated	45239 cm ²	
Feed flange diameter	measured	6.350 cm	WR-75
Feed flange area	calculated	32 cm ²	
Frequency	(entry)	14125 MHz	
Wavelength (speed of light = 299,792,458 m/s)	calculated	2.122 cm	
Transmit power at flange	datasheet	350000 milliwatts	
Antenna gain	datasheet	49 dBi	
Antenna gain factor	calculated	79433	
Height of base of antenna above ground	measured	4.145 m	
Height of center of antenna above ground	measured	5.345 m	
Minimum Elevation Angle	(entry)	5 degrees	
Minimum Elevation Angle	calculated	0.08727 radians	

FCC Maximum Permissible Exposure (MPE)

Results calculated using FCC Bulletin OET-65 (Edition 97-01 August 1997)			FCC Maximum Permissible Exposure (MPE)	
			Uncontrolled	Controlled
Maximum power density at antenna surface	Eq. 11 Pg 27	30.94679449 mW/cm ²	Potential Hazard	Potential Hazard
Power density at feed flange	Eq. 11 Pg 27	44206.96541 mW/cm ²	Potential Hazard	Potential Hazard
Extent of near-field	Eq. 12 Pg 27	6785 cm		
Maximum new-field power density	Eq. 13 Pg 28	19.47860878 mW/cm ²	Potential Hazard	Potential Hazard
Aperture efficiency	Eq. 14 Pg 28	0.629422501		
Distance to beginning of far-field	Eq. 16 Pg 29	16283.26487 cm		
Power density at end of the transition region	Eq. 17 Pg 29	8.11608699 mW/cm ²	Potential Hazard	Potential Hazard
Maximum far-field power density	Eq. 18 Pg 29	8.344 mW/cm ²	Potential Hazard	Potential Hazard

Main Beam Far-field region safe exposure distances

Minimum distance for public/uncontrolled exposure	Eq. 18 Pg 29	470.3586012 meters
Height at minimum antenna elevation angle	calculated	46.33945325 meters
Horizontal distance	calculated	468.5687447 meters
Minimum distance for occupational/controlled exposure	Eq. 18 Pg 29	210.3507612 meters
Height at minimum antenna elevation angle	calculated	23.67827683 meters
Horizontal distance	calculated	209.5503131 meters

Off-Axis Near Field/Transition Region safe exposure distances from antenna

(20 dB reduction in power density at distances greater than one antenna diameter from the main beam center.)	OET-65 Pg 30			
Maximum off-axis near field power density	Eq. 13 Pg 28	0.1948 mW/cm ²	Below FCC MPE	Below FCC MPE
Public/uncontrolled exposure off-axis distance	Diam/or Eq 17	2.4 meters		
Occupational/controlled exposure off-axis distance	Diam/or Eq 17	2.4 meters		

Off-Axis Far Field safe exposure distances from the antenna

(Based on side lobe attenuation required by FCC 25.209(a)(2))			
Angle off main beam axis (1 to 48 degrees)	(entry)	5 degree(s)	
Off-axis antenna gain factor	OET-65 Pg 30*	28	
Minimum distance for public/uncontrolled exposure	Eq. 18 Pg 29**	162.8326487 meters	

* Gain converted from dBi to linear multiple

** If calculated distance is less than the start of the far field region, the distance to the start of the far field region is shown.