

# FCC OET-65 RF Exposure Study - Satellite Uplink Facility

## NBC HD-2B (has no current FCC License)

**Antenna Vendor:** AVL MVS1200  
**Antenna Size:** 1.2 m.  
**Amplifier Make/Model:** Anacom KU-Band SSPA  
**Amplifier Max Power:** 25 w.

FCC Maximum Permissible Exposure Levels	Source	Units	Notes
Public/uncontrolled area exposure limit	47CFR §1.1310	1 mW/cm <sup>2</sup>	
Occupational/controlled area exposure limit	47CFR §1.1310	5 mW/cm <sup>2</sup>	

### Input Data

Antenna Diameter	datasheet	120.0 cm	
Antenna surface area	calculated	11310 cm <sup>2</sup>	
Feed flange diameter	measured	6.350 cm	WR-75
Feed flange area	calculated	32 cm <sup>2</sup>	
Frequency	(entry)	14125 MHz	
Wavelength (speed of light = 299,792,458 m/s)	calculated	2.122 cm	
Transmit power at flange	datasheet	25000 milliwatts	
Antenna gain	datasheet	43.5 dBi	
Antenna gain factor	calculated	22387	
Height of base of antenna above ground	measured	4.145 m	
Height of center of antenna above ground	measured	4.745 m	
Minimum Elevation Angle	(entry)	5 degrees	
Minimum Elevation Angle	calculated	0.08727 radians	

### FCC Maximum Permissible Exposure (MPE)

Results calculated using FCC Bulletin OET-65 (Edition 97-01 August 1997)			FCC Maximum Permissible Exposure (MPE)	
			Uncontrolled	Controlled
Maximum power density at antenna surface	Eq. 11 Pg 27	8.841941283 mW/cm <sup>2</sup>	Potential Hazard	Potential Hazard
Power density at feed flange	Eq. 11 Pg 27	3157.640386 mW/cm <sup>2</sup>	Potential Hazard	Potential Hazard
Extent of near-field	Eq. 12 Pg 27	1696 cm		
Maximum new-field power density	Eq. 13 Pg 28	6.274077543 mW/cm <sup>2</sup>	Potential Hazard	Potential Hazard
Aperture efficiency	Eq. 14 Pg 28	0.709581453		
Distance to beginning of far-field	Eq. 16 Pg 29	4070.816218 cm		
Power density at end of the transition region	Eq. 17 Pg 29	2.614198976 mW/cm <sup>2</sup>	Potential Hazard	Below FCC MPE
Maximum far-field power density	Eq. 18 Pg 29	2.688 mW/cm <sup>2</sup>	Potential Hazard	Below FCC MPE

### Main Beam Far-field region safe exposure distances

Minimum distance for public/uncontrolled exposure	Eq. 18 Pg 29	66.73675294 meters
Height at minimum antenna elevation angle	calculated	10.56149127 meters
Horizontal distance	calculated	66.48279944 meters
Minimum distance for occupational/controlled exposure	Eq. 18 Pg 29	29.84558323 meters
Height at minimum antenna elevation angle	calculated	7.346213974 meters
Horizontal distance	calculated	29.73201178 meters

### Off-Axis Near Field/Transition Region safe exposure distances from antenna

(20 dB reduction in power density at distances greater than one antenna diameter from the main beam center.)	OET-65 Pg 30			
Maximum off-axis near field power density	Eq. 13 Pg 28	0.0627 mW/cm <sup>2</sup>	Below FCC MPE	Below FCC MPE
Public/uncontrolled exposure off-axis distance	Diam/or Eq 17	1.2 meters		
Occupational/controlled exposure off-axis distance	Diam/or Eq 17	1.2 meters		

### Off-Axis Far Field safe exposure distances from the antenna

(Based on side lobe attenuation required by FCC 25.209(a)(2))			
Angle off main beam axis (1 to 48 degrees)	(entry)	5 degree(s)	
Off-axis antenna gain factor	OET-65 Pg 30*	28	
Minimum distance for public/uncontrolled exposure	Eq. 18 Pg 29 **	40.70816218 meters	

\* Gain converted from dBi to linear multiple

\*\* If calculated distance is less than the start of the far field region, the distance to the start of the far field region is shown.