

FREQUENCY COORDINATION AND INTERFERENCE ANALYSIS REPORT

Prepared for
GCI Communication Corporation
PORT LIONS, AK
Satellite Earth Station

Prepared By:
COMSEARCH
19700 Janelia Farm Boulevard
Ashburn, VA 20147
September 19, 2011

TABLE OF CONTENTS

| | |
|---|----|
| 1. CONCLUSIONS | 3 |
| 2. SUMMARY OF RESULTS | 4 |
| 3. SUPPLEMENTAL SHOWING | 5 |
| 4. EARTH STATION COORDINATION DATA..... | 6 |
| 5. CERTIFICATION..... | 10 |

1. CONCLUSIONS

An interference study considering all existing, proposed and prior coordinated microwave facilities within the coordination contours of the proposed earth station demonstrates that this site will operate satisfactorily with the common carrier microwave environment. Further, there will be no restrictions of its operation due to interference considerations.

2. SUMMARY OF RESULTS

There were no great circle interference cases which exceeded the interference objective on a line-of-sight basis identified during the interference study of the proposed earth station.

No carriers reported potential interference cases.

3. SUPPLEMENTAL SHOWING

Pursuant to Part 25.203(c) of the FCC Rules and Regulations, the satellite earth station proposed in this application was coordinated by Comsearch using computer techniques and in accordance with Part 25 of the FCC Rules and Regulations.

Coordination data for this earth station was sent to the below listed carriers.

Company

GCI Communication Corporation

4. EARTH STATION COORDINATION DATA

This section presents the data pertinent to frequency coordination of the proposed earth station that was circulated to all carriers within its coordination contours.

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Date: 09/19/2011
Job Number: 110919COMSTC02

Administrative Information

Licensee Code P3203
Licensee Name GCI Communication Corporation

Site Information

PORT LIONS, AK

Latitude (NAD 83) 57° 52' 5.4" N
Longitude (NAD 83) 152° 53' 29.4" W
Climate Zone A
Rain Zone 2
Ground Elevation (AMSL) 71.93 m / 236.0 ft

Link Information

Satellite Type Geostationary
Mode TR - Transmit-Receive
Modulation Digital
Satellite Arc 91°W to 194° West Longitude
Azimuth Range 114.3° to 225.9°
Corresponding Elevation Angles 5.9° / 15.2°
Antenna Centerline (AGL) 2.13 m / 7.0 ft

Antenna Information

Receive

Transmit

| | | |
|------------------------------------|----------------------|--------------------------|
| Manufacturer | Patriot | Patriot |
| Model | 380AZ | 380AZ |
| Gain / Diameter | 42.3 dBi / 3.8 m | 46.3 dBi / 3.8 m |
| 3-dB / 15-dB Beamwidth | 1.20° / 2.40° | 0.60° / 1.20° |
| | | 6K72G7W - 36M0G7W |
| | | <u>6K72D7W - 36M0D7W</u> |
| Max Available RF Power (dBW/4 kHz) | | -2.7 -16.53 |
| (dBW/MHz) | | -0.45 7.47 |
| Maximum EIRP (dBW/4 kHz) | | 43.6 29.77 |
| (dBW/MHz) | | 45.85 53.77 |
| (dBW) | | 45.85 69.31 |
| Interference Objectives: Long Term | -156.0 dBW/MHz 20% | -154.0 dBW/4 kHz 20% |
| Short Term | -146.0 dBW/MHz 0.01% | -131.0 dBW/4 kHz 0.0025% |

Frequency Information

Receive 4.0 GHz

Transmit 6.1 GHz

| | | |
|--|-------------------------------------|-------------------------------------|
| Emission / Frequency Range (MHz) | 6K72G7W - 36M0G7W / 3700.0 - 4200.0 | 6K72G7W - 36M0G7W / 5925.0 - 6425.0 |
| | 6K72D7W - 36M0D7W / 3700.0 - 4200.0 | 6K72D7W - 36M0D7W / 5925.0 - 6425.0 |
| Max Great Circle Coordination Distance | 529.0 km / 328.6 mi | 302.1 km / 187.7 mi |
| Precipitation Scatter Contour Radius | 601.8 km / 373.9 mi | 101.0 km / 62.7 mi |

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Coordination Values

PORT LIONS, AK

Licensee Name GCI Communication Corporation
Latitude (NAD 83) 57° 52' 5.4" N
Longitude (NAD 83) 152° 53' 29.4" W
Ground Elevation (AMSL) 71.93 m / 236.0 ft
Antenna Centerline (AGL) 2.13 m / 7.0 ft
Antenna Mode Receive 4.0 GHz Transmit 6.1 GHz
Interference Objectives: Long Term -156.0 dBW/MHz 20% -154.0 dBW/4 kHz 20%
Short Term -146.0 dBW/MHz 0.01% -131.0 dBW/4 kHz 0.0025%
Max Available RF Power -2.7 (dBW/4 kHz)

| Azimuth (°) | Horizon Elevation (°) | Antenna Discrimination (°) | Receive 4.0 GHz | | Transmit 6.1 GHz | |
|-------------|-----------------------|----------------------------|--------------------|----------------------------|--------------------|----------------------------|
| | | | Horizon Gain (dBi) | Coordination Distance (km) | Horizon Gain (dBi) | Coordination Distance (km) |
| 0 | 0.00 | 114.21 | -10.00 | 285.28 | -10.00 | 170.66 |
| 5 | 0.00 | 109.24 | -10.00 | 285.28 | -10.00 | 170.66 |
| 10 | 0.00 | 104.26 | -10.00 | 285.28 | -10.00 | 170.66 |
| 15 | 0.00 | 99.29 | -10.00 | 285.28 | -10.00 | 170.66 |
| 20 | 0.00 | 94.32 | -10.00 | 285.28 | -10.00 | 170.66 |
| 25 | 0.00 | 89.34 | -10.00 | 285.28 | -10.00 | 170.66 |
| 30 | 0.00 | 84.37 | -10.00 | 285.28 | -10.00 | 170.66 |
| 35 | 0.00 | 79.40 | -10.00 | 285.28 | -10.00 | 170.66 |
| 40 | 0.00 | 74.42 | -10.00 | 285.28 | -10.00 | 170.66 |
| 45 | 0.00 | 69.45 | -10.00 | 285.28 | -10.00 | 170.66 |
| 50 | 0.00 | 64.48 | -10.00 | 285.28 | -10.00 | 170.66 |
| 55 | 0.00 | 59.52 | -10.00 | 285.28 | -10.00 | 170.66 |
| 60 | 0.00 | 54.56 | -10.00 | 285.28 | -10.00 | 170.66 |
| 65 | 0.00 | 49.60 | -10.00 | 285.28 | -10.00 | 170.66 |
| 70 | 0.00 | 44.65 | -9.24 | 290.13 | -9.24 | 173.59 |
| 75 | 0.00 | 39.70 | -7.97 | 298.51 | -7.97 | 178.53 |
| 80 | 0.00 | 34.78 | -6.53 | 308.30 | -6.53 | 184.09 |
| 85 | 0.00 | 29.87 | -4.88 | 320.53 | -4.88 | 190.45 |
| 90 | 0.00 | 24.99 | -2.95 | 334.52 | -2.95 | 197.86 |
| 95 | 0.00 | 20.18 | -0.62 | 351.87 | -0.62 | 205.10 |
| 100 | 0.00 | 15.47 | 2.26 | 374.23 | 2.26 | 216.61 |
| 105 | 0.00 | 11.01 | 5.95 | 403.62 | 5.95 | 232.80 |
| 110 | 0.00 | 7.29 | 10.44 | 442.94 | 10.44 | 254.07 |
| 115 | 0.00 | 5.90 | 12.74 | 528.97 | 12.74 | 302.10 |
| 120 | 0.00 | 7.84 | 9.64 | 462.73 | 9.64 | 259.94 |
| 125 | 0.00 | 10.14 | 6.85 | 416.90 | 6.85 | 238.13 |
| 130 | 0.00 | 12.32 | 4.73 | 393.47 | 4.73 | 227.26 |
| 135 | 0.00 | 14.38 | 3.05 | 380.51 | 3.05 | 219.94 |
| 140 | 0.00 | 16.30 | 1.69 | 369.74 | 1.69 | 214.26 |
| 145 | 0.00 | 18.05 | 0.59 | 361.15 | 0.59 | 209.81 |
| 150 | 0.00 | 19.61 | -0.31 | 354.23 | -0.31 | 206.29 |
| 155 | 0.00 | 20.97 | -1.04 | 348.70 | -1.04 | 205.13 |
| 160 | 0.00 | 22.11 | -1.62 | 344.37 | -1.62 | 202.94 |
| 165 | 0.00 | 23.01 | -2.05 | 341.13 | -2.05 | 201.28 |
| 170 | 0.00 | 23.67 | -2.36 | 338.87 | -2.36 | 200.12 |
| 175 | 0.00 | 24.08 | -2.54 | 337.51 | -2.54 | 199.42 |
| 180 | 0.00 | 24.20 | -2.60 | 337.08 | -2.60 | 199.20 |
| 185 | 0.00 | 24.07 | -2.54 | 337.52 | -2.54 | 199.42 |

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Coordination Values


PORT LIONS, AK

Licensee Name GCI Communication Corporation
Latitude (NAD 83) 57° 52' 5.4" N
Longitude (NAD 83) 152° 53' 29.4" W
Ground Elevation (AMSL) 71.93 m / 236.0 ft
Antenna Centerline (AGL) 2.13 m / 7.0 ft
Antenna Mode Receive 4.0 GHz Transmit 6.1 GHz
Interference Objectives: Long Term -156.0 dBW/MHz 20% -154.0 dBW/4 kHz 20%
Short Term -146.0 dBW/MHz 0.01% -131.0 dBW/4 kHz 0.0025%
Max Available RF Power -2.7 (dBW/4 kHz)

| Azimuth (°) | Horizon Elevation (°) | Antenna Discrimination (°) | Receive 4.0 GHz | | Transmit 6.1 GHz | |
|-------------|-----------------------|----------------------------|--------------------|----------------------------|--------------------|----------------------------|
| | | | Horizon Gain (dBi) | Coordination Distance (km) | Horizon Gain (dBi) | Coordination Distance (km) |
| 190 | 0.00 | 23.67 | -2.36 | 338.86 | -2.36 | 200.11 |
| 195 | 0.00 | 23.01 | -2.05 | 341.13 | -2.05 | 201.28 |
| 200 | 0.00 | 22.11 | -1.61 | 344.38 | -1.61 | 202.94 |
| 205 | 0.00 | 20.97 | -1.04 | 348.70 | -1.04 | 205.13 |
| 210 | 0.00 | 19.61 | -0.31 | 354.22 | -0.31 | 206.28 |
| 215 | 0.00 | 18.05 | 0.59 | 361.14 | 0.59 | 209.81 |
| 220 | 0.00 | 16.30 | 1.70 | 369.77 | 1.70 | 214.28 |
| 225 | 0.00 | 15.26 | 2.41 | 375.41 | 2.41 | 217.24 |
| 230 | 0.00 | 15.77 | 2.05 | 372.55 | 2.05 | 215.73 |
| 235 | 0.00 | 17.71 | 0.79 | 362.72 | 0.79 | 210.62 |
| 240 | 0.00 | 20.67 | -0.88 | 349.87 | -0.88 | 205.72 |
| 245 | 0.00 | 24.29 | -2.63 | 336.81 | -2.63 | 199.06 |
| 250 | 0.00 | 28.30 | -4.30 | 324.72 | -4.30 | 192.70 |
| 255 | 0.00 | 32.57 | -5.82 | 313.88 | -5.82 | 186.83 |
| 260 | 0.00 | 37.01 | -7.21 | 303.67 | -7.21 | 181.49 |
| 265 | 0.00 | 41.56 | -8.47 | 295.23 | -8.47 | 176.62 |
| 270 | 0.00 | 46.18 | -9.61 | 287.76 | -9.61 | 172.17 |
| 275 | 0.00 | 50.86 | -10.00 | 285.28 | -10.00 | 170.66 |
| 280 | 0.00 | 55.59 | -10.00 | 285.28 | -10.00 | 170.66 |
| 285 | 0.00 | 60.34 | -10.00 | 285.28 | -10.00 | 170.66 |
| 290 | 0.00 | 65.12 | -10.00 | 285.28 | -10.00 | 170.66 |
| 295 | 0.00 | 69.91 | -10.00 | 285.28 | -10.00 | 170.66 |
| 300 | 0.00 | 74.71 | -10.00 | 285.28 | -10.00 | 170.66 |
| 305 | 0.00 | 79.53 | -10.00 | 285.28 | -10.00 | 170.66 |
| 310 | 0.00 | 84.35 | -10.00 | 285.28 | -10.00 | 170.66 |
| 315 | 0.00 | 89.17 | -10.00 | 285.28 | -10.00 | 170.66 |
| 320 | 0.00 | 94.00 | -10.00 | 285.28 | -10.00 | 170.66 |
| 325 | 0.00 | 98.82 | -10.00 | 285.28 | -10.00 | 170.66 |
| 330 | 0.00 | 103.64 | -10.00 | 285.28 | -10.00 | 170.66 |
| 335 | 0.00 | 108.45 | -10.00 | 285.28 | -10.00 | 170.66 |
| 340 | 0.00 | 113.24 | -10.00 | 285.28 | -10.00 | 170.66 |
| 345 | 0.00 | 118.03 | -10.00 | 285.28 | -10.00 | 170.66 |
| 350 | 0.00 | 122.79 | -10.00 | 285.28 | -10.00 | 170.66 |
| 355 | 0.00 | 119.17 | -10.00 | 285.28 | -10.00 | 170.66 |

5. CERTIFICATION

I HEREBY CERTIFY THAT I AM THE TECHNICALLY QUALIFIED PERSON RESPONSIBLE FOR THE PREPARATION OF THE FREQUENCY COORDINATION DATA CONTAINED IN THIS APPLICATION, THAT I AM FAMILIAR WITH PARTS 101 AND 25 OF THE FCC RULES AND REGULATIONS, THAT I HAVE EITHER PREPARED OR REVIEWED THE FREQUENCY COORDINATION DATA SUBMITTED WITH THIS APPLICATION, AND THAT IT IS COMPLETE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.



Timothy O. Crutcher
Frequency Planner
COMSEARCH
19700 Janelia Farm Boulevard
Ashburn, VA 20147

DATED: September 19 2011