

Micronet Communications, Inc.

720 F Avenue, Suite 100
Plano, Texas 75074
972-422-7200

SUPPLEMENTAL SHOWING PART 101.103(D)

File Number: M1125708
Licensee: Globe Wireless LLC

5.93 GHz

Page 1

Pursuant to Parts 25.203 and 101.103(d) of the FCC Rules and Regulations, a frequency coordination study was conducted by Micronet Communications, Inc. for the following proposed earth station:

Palm Bay, FL

The results of the study indicate that no unacceptable interference will result with existing, proposed or prior coordinated radio facilities.

Coordination was performed with existing, proposed and prior coordinated carriers within coordination range on the following dates:

10/18/2011 Original PCN (Expedited response requested by 11/01/2011)
There were no unresolved interference objections.

The attached coordination data was forwarded on the latest date to the following parties within coordination range or their authorized coordination agents:

ALLTEL COMMUNICATIONS LLC - S FLORIDA
AT&T COMMUNICATIONS OF THE SOUTH CENTRAL STATES INC
COMSEARCH INC
EMBARQ FLORIDA INC
FLORIDA POWER AND LIGHT COMPANY
FLORIDA RSA #2B (INDIAN RIVER) L P
HARRIS CORPORATION
METROPOLITAN AREA NETWORKS INC
MICRONET COMMUNICATIONS INC
NEW CINGULAR WIRELESS PCS LLC
NEW CINGULAR WIRELESS SERVICES OF FL-FL
POLK COUNTY OF
RADIO DYNAMICS
SOUTH FLORIDA WATER MANAGEMENT DISTRICT
ST LUCIE COUNTY GOVERNMENT
T-MOBILE LICENSE LLC
VERIZON WIRELESS PERSONAL COMMUNICATIONS LP

Respectfully Submitted,

Brad Youngblood
Systems Engineer

Attached: 1 data sheet

Micronet Communications, Inc.
 720 F Avenue, Suite 100
 Plano, Texas 75074
 972-422-7200

File: M1125708

=====

TECHNICAL CHARACTERISTICS OF TRANSMIT RECEIVE EARTH STATION

=====

Company:	Globe Wireless LLC		
Site Name, State:	Palm Bay, FL		
Call Sign:			
Latitude	(NAD83)	28 2	16.5 N
Longitude	(NAD83)	80 35	47.3 W
Elevation AMSL	(ft/m)	19.00	5.79
Receive Frequency Range	(MHz)	3700-4200	
Transmit Frequency Range	(MHz)	5925-6425	
Range of Satellite Orbital Long.	(deg W)	50.00	140.00
Range of Azimuths from North	(deg)	128.48	254.47
Antenna Centerline	(ft/m)	6.00	1.83
Antenna Elevation Angles	(deg)	43.12	18.46

Equipment Parameters		Receive	Transmit
Antenna Gain, Main Beam	(dbI)	38.00	42.00
15 DB Half Beamwidth	(deg)	1.50	0.00
Antennas	Receive: PRODELIN 1244 (2.4M) Transmit: PRODELIN 1244 (2.4M)		
Max Transmitter Power	(dbW/4KHz)		-22.06
Max EIRP Main Beam	(dbW/4KHz)		19.94
Modulation / Emission Designator	DIGITAL 36M0G7W		

Coordination Parameters		Receive	Transmit
Max Greater Circle Distances	(km)	312.26	136.86
Max Rain Scatter Distances	(km)	522.57	100.00
Max Interference Power Long Term	(dbW)	-140.60	-151.80
Max Interference Power Short Term	(dbW)	-118.40	-130.80
Rain Zone / Radio Zone		1	A