

**Exhibit B – Declaration of Peter Blaney, Chief
Engineer of Cobham SATCOM, Sea Tel Inc.**

COBHAM


Cobham SATCOM
Marine Systems
Sea Tel Products
4030 Nelson Ave., Concord
California, 94520, USA
T: +1 (925) 798-7979
F: +1 (925) 798-7986

Declaration of Cobham SATCOM, Sea Tel, Inc.

1. Cobham SATCOM - Marine Systems, Sea Tel Products designs, develops, manufactures and services marine stabilized antenna systems for satellite communication at sea. These products are in turn used by our customers as part of their Ku-band Earth Station on Vessels (ESV) networks.
2. FCC regulation 47 C.F.R. § 25.222 defines the provisions for blanket licensing of ESV antennas operating in the Ku Band. This declaration covers the requirements for meeting § 25.222 (a)(1) by the demonstrations outlined in paragraphs (b)(1)(i) and (b)(1)(iii). The requirements for meeting § 25.222 (a)(3)-(a)(7) are left to the applicant. The paragraph numbers in this declaration refer to the 2009 version of FCC 47 C.F.R. § 25.222.
3. Sea Tel hereby declares that the antennas listed below will meet the off-axis EIRP spectral density requirements of § 25.222 (a)(1)(i) with an N value of 1, when the following Input Power spectral density limitations are met:

0.6 Meter Ku Band, Models 2406 and USAT-24 are limited to	-21.6 dBW/4kHz
0.75 Meter Ku Band, Model USAT-30 is limited to	-21.6 dBW/4kHz
1.0 Meter Ku Band, Models 4003/4006/4009/4010 are limited to	-16.3 dBW/4kHz
1.2 Meter Ku Band, Models 4996/5009/5010 are limited to	-14.0 dBW/4kHz
1.5 Meter Ku Band, Models 6006/6009 are limited to	-14.0 dBW/4kHz
2.4 Meter Ku Band, Model 9797 is limited to	-14.0 dBW/4kHz
4. Sea Tel hereby declares that the antennas referenced in paragraph 3 above, will maintain a stabilization pointing accuracy of better than 0.2 degrees under specified ship motion conditions, thus meeting the requirements of § 25.222 (a)(1)(ii).
5. Sea Tel hereby declares that the antennas referenced in paragraph 3 above, will automatically cease transmission within 100 milliseconds if the pointing error should exceed 0.5 degrees and will not resume transmission until the error drops below 0.2 degrees, thus meeting the requirements of § 25.222 (a)(1)(iii).
6. Sea Tel maintains all relevant test data, which is available upon request, to verify these declarations.

Executed on: 7/28/10

By: 
Peter G. Blaney
Chief Engineer, Sea Tel Products
Cobham SATCOM, Marine Systems