

General:	Units	Clear Sky
Emission Designator		25K0N0N
Data Rate	Mbit/s	0
Modulation		N/A
Coding Rate		N/A
Noise Bandwidth	dB-Hz	N/A
Uplink Frequency	GHz	28.5
Downlink Frequency	GHz	18.7
Uplink Site		Hawaii
Downlink Site		Japan
Uplink:		
Tx E/S Antenna Diameter	m	1.2
Tx E/S Power to Antenna	W	0.087
Tx E/S Antenna Gain	dBi	48.4
Tx E/S EIRP per Carrier	dBW	37.8
Tx E/S Antenna Pointing Loss	dB	0.5
Atmospheric and Rain Losses	dB	0.5
Free Space Loss	dB	213.5
G/T	dB/K	9.7
Downlink:		
EIRP per Carrier towards Rx E/S	dBW	38.8
Atmospheric and Rain Losses	dB	0.4
Free Space Loss	dB	209.1
Rx E/S Antenna Pointing Loss	dB	0.5
Rx E/S Antenna Diameter	m	1.2
Rx E/S Antenna Gain	dBi	44.5
Rx E/S G/T	dB/K	19.5
End-to-End:		
C/N - Thermal Uplink	dB	17.6
C/I Up - ASI	dB	27.8
C/N - Thermal Downlink	dB	32.9
C/I Down - ASI	dB	35.7
C/(N+I) - Total Actual	dB	17.0
C/N - Required	dB	12.0
Excess Margin	dB	5.0