

General:	Units	Clear Sky
Emission Designator		26M7G7W
Data Rate	Mbit/s	24.992
Modulation		QPSK
Coding Rate		0.67
Noise Bandwidth	dB-Hz	72.8
Uplink Frequency	GHz	28.5
Downlink Frequency	GHz	18.7
Uplink Site		Hawaii
Downlink Site		Japan
Uplink:		
Tx E/S Antenna Diameter	m	1.2
Tx E/S Power to Antenna	W	25.7
Tx E/S Antenna Gain	dBi	48.4
Tx E/S EIRP per Carrier	dBW	62.5
Tx E/S Antenna Pointing Loss	dB	0.5
Atmospheric and Rain Losses	dB	0.5
Free Space Loss	dB	213.5
G/T	dB/K	9.7
Downlink:		
EIRP per Carrier towards Rx E/S	dBW	58.3
Atmospheric and Rain Losses	dB	0.4
Free Space Loss	dB	209.1
Rx E/S Antenna Pointing Loss	dB	0.5
Rx E/S Antenna Diameter	m	1.2
Rx E/S Antenna Gain	dBi	44.5
Rx E/S G/T	dB/K	19.5
End-to-End:		
C/N - Thermal Uplink	dB	13.5
C/I Up - ASI	dB	23.7
C/N - Thermal Downlink	dB	23.6
C/I Down - ASI	dB	26.4
C/(N+I) - Total Actual	dB	12.5
C/N - Required	dB	9.0
Excess Margin	dB	3.5